

FCC RF Exposure Report

FCC ID : AK8DHUKSY22

Equipment : WLAN/BT Module

Model No. : DHUK-SY22

Brand Name : Wistron NeWeb Corporation

Applicant: Sony Corporation

Address : 1-7-1 Konan Minato-ku, Tokyo ,108-0075 Japan

Standard : 47 CFR FCC Part 2.1091

Received Date : Jul. 26, 2019

Tested Date : Aug. 12 ~ Oct. 02, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen Assistant Manager Gary Chang / Manager

A THE

Testing Laboratory

2732

Report Version: Rev. 01

Report No.: FA972601 Page: 1 of 6



Table of Contents

1	MPE EVALUATION OF MOBILE DEVICES	4
1.1	LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE	
1.1	MPE EVALUATION FORMULA	
1.2	DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE	
1.3 1.4	MEASUREMENT UNCERTAINTY	
1.4	MPE EVALUATION RESULTS	
1.6	MPE EVALUATION OF SIMULTANEOUS TRANSMISSION	
1.0	WIFE EVALUATION OF SIMULTANEOUS TRANSMISSION	
2	TEST LABORATORY INFORMATION	ε

Report No.: FA972601

Page : 2 of 6



Release Record

Report No.	Version	Description	Issued Date
FA972601	Rev. 01	Initial issue	Oct. 22, 2019

Report No.: FA972601 Page: 3 of 6



1 MPE EVALUATION OF MOBILE DEVICES

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

1.1 LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE

Frequency Range (MHz)	Power Density (mW /cm ²)	Averaging Time (minutes)
300~1500	F/1500	30
1500~100000	1.0	30

1.2 MPE EVALUATION FORMULA

$$Pd = \frac{Pt}{4 * Pi * R^2}$$

Where

Pd= Power density in mW/cm²

Pt= EIRP in mW Pi= 3.1416

R= Measurement distance

1.3 DEVIATION FROM TEST STANDARD AND MEASUREMENT PROCEDURE

None

1.4 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Parameters	Uncertainty		
Conducted power	±0.808 dB		

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FA972601 Page: 4 of 6



1.5 MPE EVALUATION RESULTS

Frequency Range (MHz)	Maximum Conducted Power (dBm)	Rated Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm²)	Ratio*	Pass / Fail
2412~2462 (Wi-Fi)	23.01	23.50	2.82	20	0.085	1	0.085	Pass
5150~5250 (Wi-Fi)	12.08	12.50	3.96	20	0.009	1	0.009	Pass
5250~5350 (Wi-Fi)	19.01	19.50	4.24	20	0.047	1	0.047	Pass
5470~5725 (Wi-Fi)	19.57	20.00	4.21	20	0.052	1	0.052	Pass
5725~5850 (Wi-Fi)	19.16	19.50	3.74	20	0.042	1	0.042	Pass
2402-2480 (BT)	5.46	5.50	-0.26	20	0.001	1	0.001	Pass

^{*}Ratio = Power density / Limit.

1.6 MPE EVALUATION OF SIMULTANEOUS TRANSMISSION

Mode	Max Ratio of Each Mode
Wi-Fi 2.4 GHz	0.085
Wi-Fi 5 GHz	0.052
BT EDR	0.001
Sum (Wi-Fi 2.4 GHz+ BT)	0.086
Sum (Wi-Fi 5 GHz+ BT)	0.053
Limit	1
Pass / Fail	Pass

Report No.: FA972601 Page: 5 of 6



2 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City, Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan

City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END===

Report No.: FA972601 Page: 6 of 6