



SAR TEST REPORT

Test Report No.: 32BE0317-SH-02-C

Applicant : Sony Corporation
Type of Equipment : Digital Still Camera
Model No. : DSC-HX30V
FCC ID : AK8DSCHX30V
Test Standard : FCC 47CFR §2.1093,
Supplement C (Edition 01-01) to OET Bulletin 65

Test Result : Complied

*.Maximum SAR(1g) Value: **0.29 W/kg** (DTS, 2412MHz, IEEE 802.11b, (1Mbps, DBPSK/DSSS))

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by any agency of the Federal Government.
6. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.

Date of test: November 16, 2011

Test engineer: *H. Naka*

Hiroshi Naka
Engineer of WiSE Japan, UL Verification Service

Approved by: *T. Imamura*

Toyokazu Imamura
Leader of WiSE Japan, UL Verification Service



- The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
 There is no testing item of "Non-accreditation".

CONTENTS	PAGE
SECTION 1: Customer information	3
SECTION 2: Equipment under test (EUT).....	3
SECTION 3: Test specification, procedures and results.....	4
3.1 Test specification	4
3.2 Exposure limit	4
3.3 Procedure and result.....	4
3.4 Test location	4
3.5 Confirmation before SAR testing	5
3.6 Confirmation after SAR testing.....	5
3.7 Measurement procedure	6
3.8 Test setup of EUT	6
SECTION 4: Operation of EUT during testing.....	6
4.1 Operating modes for SAR testing.....	6
SECTION 5: Uncertainty assessment (SAR measurement).....	7
SECTION 6: Confirmation before testing	8
6.1 Assessment for the conducted power of EUT	8
SECTION 7: Measurement results.....	9
7.1 SAR (Body touch).....	9
 Contents of annexes	
APPENDIX 1: Photographs of test setup	10
Appendix 1-1 Photograph of EUT and antenna position	10
Appendix 1-2 EUT and support equipment.....	11
Appendix 1-3 Photograph of test setup	11
APPENDIX 2: SAR Measurement data	13
Appendix 2-1 Evaluation procedure	13
Appendix 2-2 Measurement data.....	14
APPENDIX 3: Test instruments	20
Appendix 3-1 Equipment used	20
Appendix 3-2 Dosimetry assessment setup	21
Appendix 3-3 Configuration and peripherals.....	21
Appendix 3-4 System components.....	22
Appendix 3-5 Test system specification.....	23
Appendix 3-6 Simulated tissues composition	23
Appendix 3-7 Simulated tissues parameter confirmation	24
Appendix 3-8 System check data	24
Appendix 3-9 System check measurement data	25
Appendix 3-10 System check uncertainty.....	25
Appendix 3-11 Calibration certificate: Dipole (D2450V2).....	26
Appendix 3-12 Calibration certificate: E-Field Probe (EX3DV4)	35
Appendix 3-13 References.....	46

SECTION 1: Customer information

Company Name	Sony Corporation
Brand Name	SONY
Address	Shinagawa INTERCITY C tower, 2-15-3 Konan Minato-ku, Tokyo, 108-6201 Japan
Telephone Number	+81-3-5769-5640
Facsimile Number	+81-3-5769-5996
Contact Person	Keizo Tsuneki

SECTION 2: Equipment under test (EUT)**2.1 Identification of EUT**

Type of Equipment	Digital Still Camera
Model Number	DSC-HX30V
Serial Number	17
Condition of EUT	Engineering prototype (*. Not for sale: This sample is equivalent to mass-produced items.)
Receipt Date of Sample	October 21, 2011 (for antenna terminal conducted power measurement) November 15, 2011 (for SAR measurement) *. No modification by the Lab.
Country of Mass-production	Thailand or Japan
Category Identified	Portable device *. This EUT is hand-held and hand-operated device with output power <math><645\text{mW}(1000 \times [2.4\text{GHz}]^{-0.5})</math>. Therefore, the hand-SAR is not required (KDB447498). This EUT may contact a human body. *. This EUT may contact a human body.
Rating	DC3.6V *. The EUT operates with a specified re-chargeable Li-ion battery. Therefore, the EUT operated with a full-charged battery for each SAR test.
Feature of EUT	The EUT is a digital still camera with Wi-Fi (IEEE 802.11b/g/n(20HT)) specification.
Accessory of EUT	Any accessory of body-worn application was not supplied for the EUT. Therefore, the SAR test was applied with touch conditions (0mm for separation distance).

2.2 Product Description (Wireless module: WM217)

Equipment type	Transceiver
Frequency of operation channel	2412-2462 MHz
Channel spacing	5MHz
Bandwidth	20MHz
ITU code	G1D(11b), D1D(11g,11n(20HT))
Type of modulation	DSSS(11b), OFDM(11g,11n(20HT))
Q'ty of Antenna	1 pc.
Antenna type	Chip antenna
Antenna gain (peak)	-4.93dBi (peak)
Transmit power	*. Refers to section 6 in this report.
Power supply	DC 3.3V, DC1.8V (*. with constantly voltage circuit operation.)
Operation temperature range	0 to +40 deg.C.

*. The EUT do not use the special transmitting technique such as "beam-forming" and "time-space code diversity."

SECTION 3: Test specification, procedures and results

3.1 Requirements for compliance testing defined by the FCC / Test specification

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

- Specific Absorption Rate (SAR) is a measure of the rate of energy absorption due to exposure to an RF transmitting source (wireless portable device).
- IEEE/ANSI Std. C95.1-1992 limits are used to determine compliance with FCC ET Docket 93-62.

Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01):

Supplement C (Edition 01-01) - Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions

OET Bulletin 65 (Edition 97-01) - Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

IEEE Std. 1528-2003:

IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques Supplement C

In additions;

KDB 447498 D01(v04)(Nov.13, 2009): Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies

KDB 248227 (rev.1.2)(May 29, 2007): SAR Measurement Procedures for 802.11a/b/g Transmitters

3.2 Exposure limit

(A) Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
0.4	8.0	20.0

(B) Limits for General population/Uncontrolled Exposure (W/kg)

Whole-Body (averaged over the entire body)	Partial-Body (averaged over any 1g of tissue)	Hands, Wrists, Feet and Ankles (averaged over any 10g of tissue)
0.08	1.6	4.0

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments: are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

The limit applied in this test report is;

General population / Uncontrolled exposure, Partial-Body (averaged over any 1g of tissue) limit: 1.6 W/kg

3.3 Procedures and Results

Item	Test Procedure	Limit	Exclusion	Remarks	Result
Human exposure	FCC OET Bulletin 65, Supplement C	SAR(1g): 1.6 W/kg (FCC 47CFR §2.1093)	none	SAR measurement	Complied (*1)

Note: UL Japan's SAR Work Procedures No.13-EM-W0429 and 13-EM-W0430. Other than above, no addition, deviation nor exclusion has been made from standards

*1. The worst SAR(1g) was as follows;

0.29 W/kg (2412MHz, IEEE 802.11b, (1Mbps, DBPSK/DSSS))(DTS)

3.4 Test Location

No.7 shielded room (2.76(Width) × 3.76m(Depth) × 2.4m(Height)) for SAR testing.

UL Japan, Inc., Shonan EMC Lab.

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken 259-1220 JAPAN

Telephone number: +81 463 50 6400 / Facsimile number: +81 463 50 6401

3.5 Confirmation before SAR testing

3.5.1 Correlation of Output Power between EMC and SAR tests

It was checked that the antenna port power was correlated within 0~+5% (FCC requirements). The result is shown in Section 6.

*. **Output power at SAR test:** SAR power was measured before SAR testing (serial number: 17).

Before SAR test, the RF wiring for the sample that was actually used for the SAR test, had been switched to the antenna conducted power measurement line from the antenna line, and the average power was measured.

The antenna terminal conducted output power was measured by the calibrated power sensor and power meter (65MHz measurement bandwidth). The average and the peak power of 11b mode were measured at default channel.

After power measurement, the RF wiring was changed to the antenna line from the antenna conducted power measurement line for the SAR test.

*. **Output power at EMC radio test:** EMC power was measured during EMC testing. (serial number:17).

For the EMC test, the antenna terminal conducted average output power was measured at 11b, 11g and 11n(20HT).

3.5.2 Average power for SAR tests

Step.1 Data rate check

For the SAR test, the average and peak power related with the data rate was measured on one of the channel for 11b mode, because the average power of 11g and 11n(20HT) modes was lower than the corresponded 11b power when the EMC test was applied.

11b		11g		11n(20HT)		
Modulation	Data rate [Mbps]	Modulation	Data rate [Mbps]	MCS Index	Spatial Stream	Modulation
DBPSK/DSSS	1	BPSK/OFDM	6	MCS0	1	BPSK/OFDM
DQPSK/DSSS	2	BPSK/OFDM	9	MCS1	1	QPSK/OFDM
CCK/DSSS	5.5	QPSK/OFDM	12	MCS2	1	QPSK/OFDM
CCK/DSSS	11	QPSK/OFDM	18	MCS3	1	16QAM/OFDM
		16QAM/OFDM	24	MCS4	1	16QAM/OFDM
		16QAM/OFDM	36	MCS5	1	64QAM/OFDM
		64QAM/OFDM	48	MCS6	1	64QAM/OFDM
		64QAM/OFDM	54	MCS7	1	64QAM/OFDM

Step.2 Decision of SAR test channel

For the SAR test reference, the average power was measured on default channels of 11b.

Mode	GHz	Channel	"Default Test Channel"	
			FCC 15.247	
			802.11b	802.11g
802.11 b/g	2.412	1#	√	Δ
	2.437	6	√	Δ
	2.462	11#	√	Δ

√ = "default test channels" in KDB248227.

Δ = Possible 802.11g channels with maximum average output 1/4 dB ≥ the "default test channels"

#. Any output power was reduced for channel 1 and 11 to meet restricted band requirements. Therefore channel 1 and 11 was selected for the default channels and SAR test was applied.

3.6 Confirmation after SAR testing

It was checked that the power drift [W] is within ±5% in the evaluation procedure of SAR testing. The verification of power drift during the SAR test is that DASY4 system calculates the power drift by measuring the e-filed at the same location at beginning and the end of the scan measurement for each test position.

The result is shown in APPENDIX 2.

*. DASY4 system calculation Power drift value[dB] = 20log(Ea)/(Eb) (where, Before SAR testing: Eb[V/m] / After SAR testing: Ea[V/m])

Limit of power drift[W] = ±5%

Power drift limit (X) [dB] = 10log(P_drift) = 10log(1.05/1) = 10log(1.05) - 10log(1) = 0.21dB
from E-filed relations with power.

$S = E \times H = E^2 / \eta = P / (4 \times \pi \times r^2)$ (η : Space impedance) → $P = (E^2 \times 4 \times \pi \times r^2) / \eta$

Therefore, The correlation of power and the E-filed

Power drift limit (X) dB = 10log(P_drift) = 10log(E_drift)^2 = 20log(E_drift)

From the above mentioned, the calculated power drift of DASY4 system must be the less than ±0.21dB.

3.7 Measurement procedure

Step 1	Worst position search.
Step 2	Change the channels.

*. During SAR test, the radiated power is always monitored by Spectrum Analyzer.

3.8 Test setup of EUT

Setup	Explanation	Antenna to User	SAR test
Rear-touch	The rear surface of EUT (LCD side) was touched to the Flat phantom. This section is the closest to an antenna.	3mm	applied
Right-touch	The right surface of EUT was touched to the Flat phantom.	6mm	applied
Right-rear-touch	The right-rear edge section of EUT that was near the antenna was touched to the Flat phantom.	approx. 5mm	applied
Front-touch	The front surface of EUT (Lens side) was touched to the Flat phantom.	32mm	applied
Top-touch	The part of top section of EUT was touched to the Flat phantom.	20mm	applied
Bottom-touch	The bottom surface of EUT was touched to the Flat phantom.	32mm	applied
Left-touch	This left surface of EUT was more than approx. 95mm far from the antenna.	approx. 100mm	not applied

*. The SAR test was not applied, because the antenna-to-user distance was approx.. 100mm.

SECTION 4: Operation of EUT during testing

4.1 Operating modes for SAR testing

This EUT has IEEE.802.11b, 11g and 11n(20HT) continuous transmitting modes.

The operation mode, frequency and the modulation used in the SAR testing are shown as a following.

Operation mode	11b (*1)
Tx frequency band	2412-2462MHz
Tested frequency	2412, 2437, 2462MHz (*2)
Modulation	DBPSK/DSSS
Data rate	1Mbps (*3)
Crest factor	1.0 (100% duty cycle)
Controlled software	The WLAN TEST (AdjustCmdExe) software that installed into the EUT was used for both the antenna power measurement and the SAR test. (*4)

*1. The average power of 11g and 11n(20HT) were lower than the corresponded 11b power. According to KDB248227; SAR test was not applied to the 11g and 11n(20HT) mode. (For the antenna terminal conducted power, refer to section 6 in this report)

*2. Decision of SAR tested channels are described in the below the "SAR test applied channel list".

[SAR test applied channels list]

Mode	MHz	Channel	default	SAR tested channel			Remarks
			11b/g/n(20HT)	11b	11g	11n(20HT)	
802.11 b/g/n	2412	1	√	#	n/a (*1)	n/a (*1)	default channel of 11b.
	2437	6	√	#	n/a (*1)	n/a (*1)	default channel of 11b.
	2462	11	√	#	n/a (*1)	n/a (*1)	default channel of 11b.

√ = "default test channels of requested by KDB248227", n/a: SAR test was not applied, # = SAR test was applied.

*3. It was lowest data rate. According to KDB248227; SAR is not required for higher data rate when the maximum average output power is less than 1/4 dB higher than the lowest data rate. (For the antenna terminal conducted power, refer to section 6 in this report)

*4. The calibrated transmit power was transmitted continuously at selected channel and selected data rate (operation mode) by this software.

The example of a software screen refers at the following photograph.



SECTION 5: Uncertainty Assessment (SAR measurement)

Uncertainty of SAR measurement system	Under 3GHz	
	1g SAR	10g SAR
combined measurement uncertainty of the measurement system (k=1)	± 11.7%	± 11.4%
expanded uncertainty (k=2)	± 23.3%	± 22.8%

	Error Description	Uncertainty Value	Probability distribution	Divisor	ci (1g)	ci (10g)	ui (1g) (std. uncertainty)	ui (10g) (std. uncertainty)	V _i , v _{eff}
A	Measurement System								
1	Probe calibration	±5.9 %	Normal	1	1	1	±5.9 %	±5.9 %	∞
2	Axial isotropy	±4.7 %	Rectangular	√3	0.7	0.7	±1.9 %	±1.9 %	∞
3	Hemispherical isotropy (*flat phantom, <5°)	±2.6 %	Rectangular	√3	0.7	0.7	±1.1 %	±1.1 %	∞
4	Boundary effects	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
5	Probe linearity	±4.7 %	Rectangular	√3	1	1	±2.7 %	±2.7 %	∞
6	System detection limit	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
7	System readout electronics	±0.3 %	Normal	1	1	1	±0.3 %	±0.3 %	∞
8	Response time	±0.8 %	Rectangular	√3	1	1	±0.5 %	±0.5 %	∞
9	Integration time	±2.6 %	Rectangular	√3	1	1	±1.5 %	±1.5 %	∞
10	RF ambient – noise	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
11	RF ambient – reflections	±3.0 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
12	Probe positioner mechanical tolerance	±0.4 %	Rectangular	√3	1	1	±0.2 %	±0.2 %	∞
13	Probe positioning with respect to phantom shell	±2.9 %	Rectangular	√3	1	1	±1.7 %	±1.7 %	∞
14	Max.SAR evaluation	±1.0 %	Rectangular	√3	1	1	±0.6 %	±0.6 %	∞
B	Test Sample Related								
15	Device positioning	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	5
16	Device holder uncertainty	±5.0 %	Normal	1	1	1	±5.0 %	±5.0 %	5
17	Power drift	±5.0 %	Rectangular	√3	1	1	±2.9 %	±2.9 %	∞
C	Phantom and Setup								
18	Phantom uncertainty	±4.0 %	Rectangular	√3	1	1	±2.3 %	±2.3 %	∞
19	Liquid conductivity (target)	±5.0 %	Rectangular	√3	0.64	0.43	±1.8 %	±1.2 %	∞
20	Liquid conductivity (meas.)	±2.9 %	Normal	1	0.64	0.43	±1.9 %	±1.2 %	3
21	Liquid permittivity (target)	±5.0 %	Rectangular	√3	0.6	0.49	±1.7 %	±1.4 %	∞
22	Liquid permittivity (meas.)	±2.9 %	Normal	1	0.6	0.49	±1.7 %	±1.4 %	3
	Combined Standard Uncertainty						±11.7 %	±11.4 %	59
	Expanded Uncertainty (k=2)						±23.3 %	±22.8 %	

*. This measurement uncertainty budget is suggested by IEEE 1528 and determined by Schmid & Partner Engineering AG (DASY4 Uncertainty Budget). [6]

SECTION 6: Confirmation before testing

6.1 Assessment for the conducted power of EUT

**6.1.1 Worst data rate & worst channel determination of SAR (EUT serial number: 17)
/ Correction of the power at SAR test and at EMC test (EUT serial number: 17)**

Ch.	Freq. [MHz]	D/R	Ant. No.	Max.Ave. pwr.[o]	Modulation	Tx mode: 11b				SAR test reference power				*PAR=Peak(dB)-Ave(dB)[dB] Power at EMC test				
						P/M Reading		Cable Loss [dB]	Attenuator [dB]	duty factor [dB]	Power Reading Results				Δworst ave.[dB]	PAR [dB]	Ave. [dB]	Δ(sar- emc)
						Ave.[dBm]	Pk[dB]				Ave[dBm]	Pk[dBm]	Ave[mW]	Pk[mW]				
1	2412	1	1		DBPSK DSSS	-4.22	-1.47	0.50	10.02	0.01	6.31	9.06	4.28	8.05	0.00	2.75		
6	2437	1	1		DBPSK DSSS	-4.22	-1.67	0.50	10.02	0.01	6.31	8.86	4.28	7.69	0.00	2.55		
11	2462	1	1	o	DBPSK DSSS	-3.88	-1.38	0.50	10.02	0.01	6.65	9.15	4.62	8.22	0.34	2.50		
1	2412	5.5	1		OOK/PECK DSSS	-4.20	-1.39	0.50	10.02	0.03	6.35	9.16	4.32	8.24	0.03	2.81	6.16	0.19
6	2437	5.5	1		OOK/PECK DSSS	-4.23	-1.62	0.50	10.02	0.03	6.32	8.93	4.29	7.82	0.00	2.61	6.30	0.02
11	2462	5.5	1	o	OOK/PECK DSSS	-3.86	-1.37	0.50	10.02	0.03	6.69	9.18	4.67	8.28	0.37	2.49	6.50	0.19
6	2437	1	1		DBPSK DSSS	-4.22	-1.67	0.50	10.02	0.01	6.31	8.86	4.28	7.69	0.00	2.55	6.18	0.13
6	2437	2	1		DQPSK DSSS	-4.22	-1.62	0.50	10.02	0.03	6.33	8.93	4.30	7.82	0.02	2.60	6.28	0.05
6	2437	5.5	1	o	OOK/PECK DSSS	-4.23	-1.57	0.50	10.02	0.03	6.32	8.98	4.29	7.91	0.01	2.66	6.30	0.02
6	2437	11	1		OOK/PECK DSSS	-4.27	-1.56	0.50	10.02	0.06	6.31	9.02	4.28	7.98	0.00	2.71	6.17	0.14

- *. Calculating formula: Results = (P/M Reading) + (Cable loss) + (Attenuator) + (duty factor)
- *. Date tested: November 2, 2011 / By: Hiroshi Naka / Place: preparation room of No. 7 shielded room. (25 deg.C, 55%RH)
- *. The difference between the SAR reference power and the power of EMC test was not less than 0dB and not higher than 0.21dB.
- *. The average power of higher data rate was less than 0.25dB higher than the lowest data rate. Therefore, SAR test was only applied to the lowest data rate.
- *. The average power of 11g and 11n(20HT) was lower than the corresponded 11b power. Therefore, SAR test was not applied. (refer to table 1, in below)

[Table 1: Average power at EMC test]

Freq. [MHz]	ch.	Average Power at EMC test					
		11b		11g		11n(20HT)	
		Data rate	Average power [dBm]	Data rate	Average power [dBm]	Data rate	Average power [dBm]
2437	6	1 Mbps	6.18	6	6.11	MCS0	6.08
		2 Mbps	6.28	9	6.03	MCS1	6.07
		5.5 Mbps	6.30	12	6.06	MCS2	6.07
		11 Mbps	6.17	18	6.03	MCS3	6.05
				24	6.04	MCS4	6.06
				36	6.14	MCS5	6.04
				48	6.18	MCS6	6.01
				54	6.11	MCS7	6.01
2412	1	5.5	6.16	24	6.24	MCS6	6.11
2437	6	5.5	6.30	24	6.18	MCS6	6.08
2462	11	5.5	6.50	24	6.31	MCS6	6.23

6.1.2 Duty cycle (Crest factor) (at EMC test)

Mode	Data rate	Freq. [MHz]	On time [ms]	1 cycle [ms]	Duty [%]	Crest factor (DASY4)
802. 11b	1Mbps	2437	12.180	12.220	99.7	1.0 (1.00)
	2Mbps	2437	6.179	6.216	99.4	(1.01)(*1)
	5.5Mbps	2437	6.1830	6.2200	99.4	(1.01)(*1)
	11Mbps	2437	2.3670	2.3980	98.7	(1.01)(*1)
802. 11g	6Mbps	2437	2.0130	2.0560	97.9	(1.02)(*1)
	9Mbps	2437	1.3550	1.3880	97.6	(1.02)(*1)
	12Mbps	2437	1.0220	1.0560	96.8	(1.03)(*1)
	18Mbps	2437	0.6880	0.7200	95.6	(1.05)(*1)
	24Mbps	2437	0.5234	0.5561	94.1	(1.06)(*1)
	36Mbps	2437	0.3545	0.3882	91.3	(1.10)(*1)
	48Mbps	2437	0.2712	0.3041	89.2	(1.12)(*1)
	54Mbps	2437	0.2429	0.2760	88.0	(1.14)(*1)
802. 11n (20HT)	MCS0	2437	1.8730	1.9210	97.5	(1.03)(*1)
	MCS1	2437	0.9630	1.0040	95.9	(1.04)(*1)
	MCS2	2437	0.6530	0.6880	94.9	(1.05)(*1)
	MCS3	2437	0.4995	0.5324	93.8	(1.07)(*1)
	MCS4	2437	0.3480	0.3801	91.6	(1.09)(*1)
	MCS5	2437	0.2674	0.2999	89.2	(1.12)(*1)
	MCS6	2437	0.2437	0.2762	88.2	(1.13)(*1)

- *. Calculating formula: Duty[%] = {(On time) / (1 cycle)} x 100, Crest factor[-] = 1 / {(On time) / (1 cycle)}
- *1. SAR test was not applied.
- *. "Power of EMC test" and "Duty cycle (duty factor)"; these reference are described in the test report of 32BE0317-SH-02-A.

SECTION 7: Measurement results**7.1 SAR (Body touch)**

Measurement date: November 16, 2011

Measurement by: Hiroshi Naka

[Liquid measurement (Body)]

Used Target Frequency [MHz]	Target Body Tissue		Measured Body Tissue			Environment			Measured Date
	Permittivity [-]	Conductivity [S/m]	Permittivity (ϵ_r) [-]	Conductivity (σ) [S/m]	Temp. [deg.C.]	Depth [mm]	Temp. [deg.C.]	Humidity [%RH]	
2450	52.7	1.95	50.76 (-3.7%)	1.976 (+1.3%)	22.7	152	23	40	Nov. 16, 2011, before SAR test.
2412	52.75	1.914	50.82 (-3.7%)	1.936 (+1.2%)					
2437	52.72	1.938	50.69 (-3.8%)	1.970 (+1.7%)					
2462	52.68	1.967	50.63 (-3.9%)	2.003 (+1.8%)					

*. The target value is a parameter defined in OET65 Supplement C. In the current standards (e.g., IEEE 1528, OET 65 Supplement C), the dielectric parameters suggested for head and body tissue simulating liquid are given at 2450MHz. As an intermediate solution, dielectric parameters for the frequencies between 2000 to 2450 MHz and 2450 to 3000MHz were obtained using linear interpolation. (Refer to Appendix 3-7 in this report)

[SAR measurement results (Body)]

SAR measurement results											
Mode	Frequency		Modulation / Data rate [Mbps] / crest factor	EUT setup conditions			Liquid temp. [deg.C.]		Power drift [dB]	SAR(1g) [W/kg] maximum value of multi-peak	Remarks
	Ch.	[MHz]		Position	Distance [mm]	Battery	Before	After			
Step 1: Worst position search											
11b	11	2462	DBPSK&DSSS / 1Mbps / 1.0	Right-touch	0	#1	22.5	22.5	0.20	<0.10	-
	11	2462	DBPSK&DSSS / 1Mbps / 1.0	Right-rear-touch	0	#3	22.2	22.2	-0.199	<0.10	-
	11	2462	DBPSK&DSSS / 1Mbps / 1.0	Rear-touch	0	#1	22.2	22.2	-0.180	0.14	-
	11	2462	DBPSK&DSSS / 1Mbps / 1.0	Front-touch	0	#3	22.4	22.4	-	n/a	(*1)
	11	2462	DBPSK&DSSS / 1Mbps / 1.0	Top-touch	0	#1	22.3	22.2	-	n/a	(*1)
	11	2462	DBPSK&DSSS / 1Mbps / 1.0	Bottom-touch	0	#2	22.2	22.2	-	n/a	(*1)
Step 2: Change the channels											
11b	6	2437	DBPSK&DSSS / 1Mbps / 1.0	Rear-touch	0	#3	22.1	22.1	-0.001	0.22	-
	1	2412	DBPSK&DSSS / 1Mbps / 1.0	Rear-touch	0	#2	22.2	22.1	-0.143	0.29	→ Worst SAR. * peak-sar (extrapolated): 1.16W/kg
	1	2412	DBPSK&DSSS / 1Mbps / 1.0	Rear (with separation distance=5mm)	5	#1	22.1	22.1	-0.189	0.11	* peak-sar (extrapolated): 0.30W/kg (*2)

Notes:

- *. During test, the EUT was operated with full-charged battery and without all signal interface cables.
- *. Bty.: Battery, Battery No.#1, #2 and #3 were same model.; Refer to Appendix 1.
- *. The SAR test was not applied to 11g and 11n(20HT) mode. According to KDB248227; SAR is not required for 11g and 11n(HT20) channels when the maximum average output power is less than 1/4 dB higher than that measured on the corresponding 802.11b channels.
- *. Calibration frequency of the SAR measurement probe (and used conversion factors)

SAR test frequency [MHz]	Probe calibration frequency [MHz]	Validity [MHz]	Used conversion factor	Uncertainty
2412	2450	-38MHz, within ± 50 of cal.frequency	7.34	$\pm 12.0\%$
2437	2450	-13MHz, within ± 50 of cal.frequency	7.34	$\pm 12.0\%$
2462	2450	+12MHz, within ± 50 of cal.frequency	7.34	$\pm 12.0\%$

*. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

- *1. The interpolated SAR value of area scan result was very small (<0.01mW/g), therefore the zoom scan was not applied for these conditions.
- *2. Additional SAR evaluation was applied to verify the enhanced energy coupling at increased separation distances (0mm->5mm).