

SAR TEST REPORT

Project No. : JB-Z0436-B
 Client : Sony Corporation
 Address : 1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan
 Type of Equipment : Communication Module
 Model No. : FLE01WBM (* installed in Head Mounted Display FL-E01)
 FCC-ID : AK8FLE01WBM
 Regulation Applied : FCC 47 CFR 2.1093

SAR Limits :

Exposure Characteristics	Spatial Peak SAR (Head and Trunk) averaged over any 1 g of tissue	Spatial Peak SAR (Extremities: Hands/Wrists/Feet/Ankles) averaged over any 10 g of tissue
General Public Exposure	1.6 W/kg	4.0 W/kg

The Highest Reported SAR:

RF Exposure Conditions	Wi-Fi 2.4 GHz	Wi-Fi 5 GHz	Bluetooth	Note()
Head	0.036 W/kg	0.065 W/kg	N/A	
Extremity (Hand)	0.333 W/kg	0.535 W/kg	N/A	

Test Result : **Complied**

Sample Receipt : May 14, 2018
 Testing : May 14, 2018 - June 20, 2018
 Reported : August 23, 2018

Reported by :

Approved Signatory :




Yuji Kajihara
 Technical Manager
 EMC/ RF Test Laboratory Main Lab.
 Design Technology Division
 Sony Global Manufacturing & Operations Corporation

Teruki Kurihara
 Technical Manager
 EMC/ RF Test Laboratory Main Lab.
 Design Technology Division
 Sony Global Manufacturing & Operations Corporation

Notice

- * These test results relate only to the items (combination equipment, test configuration, operation condition etc.) tested.
- * This report shall not be reproduced except in full, without written approval of the laboratory.
- * This report must not be used by the client to claim product endorsement by A2LA or any agency of the U.S. Government.
- * All test results are traceable to the national and / or international standards.
- * The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory.



Sony Global Manufacturing & Operations Corporation EMC/RF Test Laboratory, Main Lab.

A2LA Cert. #3203.01
 Kisarazu Site 8-4 Shiomi Kisarazu-shi, Chiba, 292-0834 Japan
 PHONE +81-(438) 37-2750 FAX +81-(438) 37-1021

REVISION HISTORY

Project No.	Revision	Page	Description	Issued date
JB-Z0436	Original	-	-	August 1, 2018
JB-Z0436-A	1	5, 6, 7, 8, 31, 32, 33, 34, 37, 39	Replaced the Max possible power for Wi-Fi 2.4 GHz, Wi-Fi 5 GHz and Bluetooth; updated related items.	August 21, 2018
		1	Updated the Highest Reported SAR value for Wi-Fi 2.4GHz.	
JB-Z0436-B	2	4	Corrected the note of the Radio Specification.	August 23, 2018

TABLE OF CONTENTS

1. General Information	4
1.1. Description of Device Under Test (DUT).....	4
1.2. Antenna Placement	4
1.3. Simultaneous Transmission Conditions.....	5
1.4. Nominal and Maximum Possible Power (Maximum Tune-up Tolerance Limit)	5
1.5. RF Exposure Conditions	6
1.6. RF Exposure Limits.....	6
1.7. SAR Test Exclusion	7
1.8. Test Specification, Methods and Procedures.....	9
1.9. Test Facilities and Accreditation	10
2. Test Set-up.....	11
2.1. Test Equipment and Measurement Software Lists.....	11
2.2. Measurement System Description	13
2.3. Measurement System Main Components.....	14
2.4. Tissue Simulating Liquids.....	17
2.5. SAR Measurement	19
2.6. Measurement Uncertainty	20
2.7. Dielectric Parameter Measurement of Tissue Simulating Liquids	24
2.8. System Check Measurement	27
3. Conducted Power Measurements	30
3.1. Conducted Power Measurement Results	31
4. SAR Measurements	35
4.1. SAR Measurement Results	37
4.2. SAR Measurement Variability.....	41
Appendix A. Plots of SAR Measurement.....	42
Appendix B. Plots of System Check.....	51
Appendix C. Calibration Certificate	60
Appendix D. Photographs.....	99

1. General Information

1.1. Description of Device Under Test (DUT)

DUT and Host Platform Descriptions

	DUT	Host Platform *The DUT is installed in this host.
Type of Equipment	Communication Module	Head Mounted Display
Model No.	FLE01WBM	FL-E01
FCC-ID	AK8FLE01WBM	
Test Sample Condition	<input checked="" type="checkbox"/> Prototype <input type="checkbox"/> Pre-production <input type="checkbox"/> Mass-production * Not for sale: The sample is equivalent to mass-production items. * No modification by the test lab.	<input checked="" type="checkbox"/> Prototype <input type="checkbox"/> Pre-production <input type="checkbox"/> Mass-production
Serial No.	1	90001
Rating	DC 3.3 V (VDD33) DC 3.3 V (VIO)	Li-ion Battery DC 3.3 V/ 1240 mAh <input type="checkbox"/> Not user accessible. *During the SAR tests, power was supplied from an external power supply.
Head/Body-Worn Accessories (supplied with the device)	n/a	n/a
Device Dimension (W x H x D)	12.6 mm x 8.9 mm x 1.9 mm	See Appendix D
Device Category	Portable	
Exposure Category	General population/ Uncontrolled environment	

Wireless Technologies

Wireless Technologies	Frequency Bands	Operating Mode
Wi-Fi	2.4 GHz	802.11b 802.11g 802.11n (HT20/HT40)
	5GHz	802.11a 802.11n (HT20/HT40) 802.11ac (VHT20/VHT40/VHT80)
Bluetooth	2.4 GHz	Version 4.2 (BR/EDR/LE)

Radio Specification

	DUT	Host Platform
Antenna Type	Inverted-F antenna	Inverted-F antenna
Antenna Gain	+ 1.1 dBi (2.4GHz) 0.0 dBi (5GHz)	- 1.9 dBi (2.4GHz) - 1.6 dBi (5GHz)
Note(s):	* The antenna is of the same and lower gain than in the DUT.	

1.2. Antenna Placement

Antenna	Minimum Distance from Edges or Sides of Host Platform (mm)							
	Front	Top	Top-Right	Top-Left	Front of Face	Right	Left	Bottom
Wi-Fi/Bluetooth	36.0	0.9	≈ 0.9	≈ 0.9	7.0	50.0	50.0	81.0

* Please refer to Appendix D for more details.

1.3. Simultaneous Transmission Conditions

Wi-Fi 2.4 GHz, Wi-Fi 5 GHz and/or Bluetooth cannot transmit simultaneously.

1.4. Nominal and Maximum Possible Power (Maximum Tune-up Tolerance Limit)

Wireless Technologies	Mode	Band	Frequency Range (MHz)		Channel	Data Rate /MCS	Full Power (Burst Averaged)			
			Lower	Higher			Nominal (dBm)	Tolerance (dB)	Max. Tune-up Limit (dBm)	
Wi-Fi	802.11b	2.4 GHz	2412	2462	All	All	11.5	-2.0	+2.0	13.5
	802.11g		2412	2462	All	All	11.5	-2.0	+2.0	13.5
	802.11n (HT20)		2412	2462	All	All	11.5	-2.0	+2.0	13.5
	802.11n (HT40)		2412	2462	All	All	11.0	-2.0	+2.0	13.0
	802.11a	W52	5180	5240	All	All	12.0	-2.0	+2.0	14.0
		W53	5260	5320	All	All	12.0	-2.0	+2.0	14.0
		W56	5500	5700	All	All	12.0	-2.0	+2.0	14.0
		W58	5745	5825	All	All	12.0	-2.0	+2.0	14.0
	802.11n (HT20)	W52	5180	5240	All	All	12.0	-2.0	+2.0	14.0
		W53	5260	5320	All	All	12.0	-2.0	+2.0	14.0
		W56	5500	5700	All	All	12.0	-2.0	+2.0	14.0
		W58	5745	5825	All	All	12.0	-2.0	+2.0	14.0
	802.11n (HT40)	W52	5190	5230	All	All	9.5	-2.0	+2.0	11.5
		W53	5270	5310	All	All	9.5	-2.0	+2.0	11.5
		W56	5510	5670	All	All	9.5	-2.0	+2.0	11.5
		W58	5755	5795	All	All	9.5	-2.0	+2.0	11.5
	802.11ac (VHT20)	W52	5180	5240	All	All	8.0	-2.0	+2.0	10.0
		W53	5260	5320	All	All	8.0	-2.0	+2.0	10.0
		W56	5510	5710	All	All	8.0	-2.0	+2.0	10.0
		W58	5745	5825	All	All	8.0	-2.0	+2.0	10.0
	802.11ac (VHT40)	W52	5190	5230	All	All	8.0	-2.0	+2.0	10.0
		W53	5270	5310	All	All	8.0	-2.0	+2.0	10.0
		W56	5510	5710	All	All	8.0	-2.0	+2.0	10.0
		W58	5755	5795	All	All	8.0	-2.0	+2.0	10.0
802.11ac (VHT80)	W52	5210		All	All	5.0	-2.0	+2.0	7.0	
	W53	5290		All	All	5.0	-2.0	+2.0	7.0	
	W56	5530	5690	All	All	5.0	-2.0	+2.0	7.0	
	W58	5775		All	All	5.0	-2.0	+2.0	7.0	

Wireless Technologies	Mode	Packet Type	Frequency Range (MHz)		Channel	Full Power (Burst Averaged)			
			Lower	Higher		Nominal (dBm)	Tolerance (dB)		Max. Tune-up Limit (dBm)
Bluetooth	BR	DH1	2402	2480	All	0.0	-6.0	+0.8	0.8
		DH3	2402	2480	All	0.0	-6.0	+0.8	0.8
		DH5	2402	2480	All	0.0	-6.0	+0.8	0.8
	EDR	2DH1	2402	2480	All	0.0	-6.0	+0.8	0.8
		2DH3	2402	2480	All	0.0	-6.0	+0.8	0.8
		2DH5	2402	2480	All	0.0	-6.0	+0.8	0.8
		3DH1	2402	2480	All	0.0	-6.0	+0.8	0.8
		3DH3	2402	2480	All	0.0	-6.0	+0.8	0.8
		3DH5	2402	2480	All	0.0	-6.0	+0.8	0.8
		LE	-	2402	2480	All	0.0	-6.0	+0.8

1.5. RF Exposure Conditions

Wireless Technologies	RF Exposure Conditions	User-to-Host Distance (mm)	Test Position	Host-to-Ant. Distance (mm)	SAR Required	Note(s)
Wi-Fi Bluetooth	Head	0	Front of Face	7.0	Yes	
	Extremity (Hand)	0	Front	36.0	Yes	
			Top	0.9	Yes	
			Top-Right	≈ 0.9	Yes	
			Top-Left	≈ 0.9	Yes	
			Front of Face	7.0	N/A	1
			Right	50.0	Yes	
			Left	50.0	Yes	
Bottom	81.0	Yes				

Note(s):

- According to the intended use as specified by the host platform manufacturer, SAR test for "Front of Face" was not applied to the extremity conditions.

1.6. RF Exposure Limits

Human Exposure	General Population/ Uncontrolled Exposure	Occupational/ Controlled Exposure
Spatial Peak SAR (Head and Trunk) averaged over any 1 g of tissue	1.6 W/kg*	8 W/kg
Spatial Average SAR (Whole Body) averaged over the whole body	0.08 W/kg	0.4 W/kg
Spatial Peak SAR (Extremities: Hands/Wrists/Feet/Ankles) averaged over any 10 g of tissue	4 W/kg*	20 W/kg

* The limit(s) applied in this report.

1.7. SAR Test Exclusion

SAR test exclusion is applied according to KDB 447498 D01.

- a) The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- * f(GHz) is the RF channel transmit frequency in GHz
- * Power and distance are rounded to the nearest mW and mm before calculation
- * The result is rounded to one decimal place for comparison
- * When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

Head SAR (1-g SAR) Test Exclusion as per KDB 447498 D01

Freq. Band	Freq. (MHz)	Test Position	User-to-Host Distance (mm)	Host-to-Ant Distance (mm)	User-to-Ant Distance (mm)	Min. Test Sep. Distance (mm)	Max. Possible Power			Exclusion Threshold	SAR Required (> 3.0)
							(dBm)	(mW)	rounded (mW)		
Wi-Fi 2.4GHz	2450	Front of Face	0	7.0	7.0	7	13.5	22.4	22	4.9	Yes
Wi-Fi 5GHz	5800	Front of Face	0	7.0	7.0	7	14.0	25.1	25	8.6	Yes
Bluetooth	2450	Front of Face	0	7.0	7.0	7	0.8	1.2	1	0.2	No

Extremity SAR (10-g SAR) Test Exclusion as per KDB 447498 D01

Freq. Band	Freq. (MHz)	Test Position	User-to-Host Distance (mm)	Host-to-Ant Distance (mm)	User-to-Ant Distance (mm)	Min. Test Sep. Distance (mm)	Max. Possible Power			Exclusion Threshold	SAR Required (> 7.5)
							(dBm)	(mW)	rounded (mW)		
Wi-Fi 2.4GHz	2450	Front	0	36.0	36.0	36	13.5	22.4	22	1.0	No
	2450	Top	0	0.9	0.9	5	13.5	22.4	22	6.9	Yes
	2450	Top-Right	0	0.9	0.9	5	13.5	22.4	22	6.9	Yes
	2450	Top-Left	0	0.9	0.9	5	13.5	22.4	22	6.9	Yes
	2450	Right	0	50.0	50.0	50	13.5	22.4	22	0.7	No
	2450	Left	0	50.0	50.0	50	13.5	22.4	22	0.7	No
	2450	Bottom	0	81.0	81.0	81	13.5	22.4	22	N/A	N/A
Wi-Fi 5GHz	5800	Front	0	36.0	36.0	36	14.0	25.1	25	1.7	No
	5800	Top	0	0.9	0.9	5	14.0	25.1	25	12.0	Yes
	5800	Top-Right	0	0.9	0.9	5	14.0	25.1	25	12.0	Yes
	5800	Top-Left	0	0.9	0.9	5	14.0	25.1	25	12.0	Yes
	5800	Right	0	50.0	50.0	50	14.0	25.1	25	1.2	No
	5800	Left	0	50.0	50.0	50	14.0	25.1	25	1.2	No
	5800	Bottom	0	81.0	81.0	81	14.0	25.1	25	N/A	N/A
Bluetooth	2450	Front	0	36.0	36.0	36	0.8	1.2	1	0.0	No
	2450	Top	0	0.9	0.9	5	0.8	1.2	1	0.3	No
	2450	Top-Right	0	0.9	0.9	5	0.8	1.2	1	0.3	No
	2450	Top-Left	0	0.9	0.9	5	0.8	1.2	1	0.3	No
	2450	Right	0	50.0	50.0	50	0.8	1.2	1	0.0	No
	2450	Left	0	50.0	50.0	50	0.8	1.2	1	0.0	No
	2450	Bottom	0	81.0	81.0	81	0.8	1.2	1	N/A	N/A

- b) For 100 MHz to 6 GHz and test separation distances > 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:
- 1) $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$ mW, for 100 MHz to 1500 MHz
 - 2) $\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$ mW, for > 1500 MHz and ≤ 6 GHz

Extremity SAR (10-g SAR) Test Exclusion as per KDB 447498 D01

Freq. Band	Freq. (MHz)	Test Position	User-to-Host Distance (mm)	Host-to-Ant Distance (mm)	User-to-Ant Distance (mm)	Min. Test Sep. Distance (mm)	Max. Possible Power			Exclusion Threshold (mW)	SAR Required
							(dBm)	(mW)	rounded (mW)		
Wi-Fi 2.4GHz	2450	Front	0	36.0	36.0	36	13.5	22.4	22	N/A	N/A
	2450	Top	0	0.9	0.9	5	13.5	22.4	22	N/A	N/A
	2450	Top-Right	0	0.9	0.9	5	13.5	22.4	22	N/A	N/A
	2450	Top-Left	0	0.9	0.9	5	13.5	22.4	22	N/A	N/A
	2450	Right	0	50.0	50.0	50	13.5	22.4	22	N/A	N/A
	2450	Left	0	50.0	50.0	50	13.5	22.4	22	N/A	N/A
	2450	Bottom	0	81.0	81.0	81	13.5	22.4	22	406	No
Wi-Fi 5GHz	5800	Front	0	36.0	36.0	36	14.0	25.1	25	N/A	N/A
	5800	Top	0	0.9	0.9	5	14.0	25.1	25	N/A	N/A
	5800	Top-Right	0	0.9	0.9	5	14.0	25.1	25	N/A	N/A
	5800	Top-Left	0	0.9	0.9	5	14.0	25.1	25	N/A	N/A
	5800	Right	0	50.0	50.0	50	14.0	25.1	25	N/A	N/A
	5800	Left	0	50.0	50.0	50	14.0	25.1	25	N/A	N/A
	5800	Bottom	0	81.0	81.0	81	14.0	25.1	25	372	No
Bluetooth	2450	Front	0	36.0	36.0	36	0.8	1.2	1	N/A	N/A
	2450	Top	0	0.9	0.9	5	0.8	1.2	1	N/A	N/A
	2450	Top-Right	0	0.9	0.9	5	0.8	1.2	1	N/A	N/A
	2450	Top-Left	0	0.9	0.9	5	0.8	1.2	1	N/A	N/A
	2450	Right	0	50.0	50.0	50	0.8	1.2	1	N/A	N/A
	2450	Left	0	50.0	50.0	50	0.8	1.2	1	N/A	N/A
	2450	Bottom	0	81.0	81.0	81	0.8	1.2	1	406	No

1.8. Test Specification, Methods and Procedures

Test Specification

FCC 47 CFR 2.1093 Radiofrequency radiation exposure evaluation: portable devices

Test Methods

- IEEE Std 1528-2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
- KDB 248227 D01 v02r02 SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters
- KDB 447498 D01 v06 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies
- KDB 447498 D02 v02r01 SAR Measurement Procedures for USB Dongle Transmitters
- KDB 615223 D01 v01r01 802.16e/WiMax SAR Measurement Guidance
- KDB 616217 D04 v01r02 SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers
- KDB 643646 D01 v01r03 SAR Test Reduction Considerations for Occupational PTT Radios
- KDB 648474 D03 v01r04 Evaluation and Approval Considerations for Handsets with Specific Wireless Charging Battery Covers
- KDB 648474 D04 v01r03 SAR Evaluation Considerations for Wireless Handsets
- KDB 865664 D01 v01r04 SAR Measurement Requirements for 100 MHz to 6 GHz
- KDB 941225 D01 v03r01 3G SAR Measurement Procedures
- KDB 941225 D05 v02r05 SAR Evaluation Considerations for LTE Devices
- KDB 941225 D06 v02r01 SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities
- KDB 941225 D07 v01r02 SAR Evaluation Procedures for UMPC Mini-Tablet Devices

Test Procedures

The SAR tests were performed according to the procedures of Sony Global Manufacturing & Operations Corporation EMC/RF Test Laboratory, the Document No. NV3-2 and NV3-16, available upon request.

- No deviation from the procedures
- Deviation from the procedures
- _____

Additional Guidance: KDB inquiry

Due to the form factor of the host platform, a KDB inquiry was made to the FCC to determine the acceptable SAR test procedures.

Consequently, the SAM phantom was used for SAR testing instead of the flat phantom.

Please refer to Appendix D for details.

References

- [1] ICNIRP. Guidelines for limiting exposure to time-varying electric, magnetic, and electromagnetic fields (up to 300 GHz). Health Physics 74(4): 494-522, 1998.
- [2] American National Standards Institute (ANSI), "Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz," ANSI/IEEE C95.1-1992.
- [3] Health Canada, "Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3 kHz to 300 GHz," Safety Code 6 (2009).
- [4] European Council Recommendation 1999/519/EC of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz) (Official Journal L 199 of 30 July 1999).
- [5] REDCA Technical Guidance Note 20 (TGN 20), SAR Testing and Assessment Guidance, Version 5.0, July 2017.
- [6] Australian Communications and Media Authority (ACMA), Radiocommunications (Electromagnetic Radiation - Human Exposure) Standard 2014.
- [7] Schmid & Partner Engineering AG (SPEAG), DASY52 System Handbook, April 2014.
- [8] Schmid & Partner Engineering AG (SPEAG), Safety Data Sheet, Doc No 772-SLAAx0yy-J, June 14, 2013.
- [9] Schmid & Partner Engineering AG (SPEAG), Safety Data Sheet, Doc No 772-SLAAx1yy-I, October 18, 2013.
- [10] Schmid & Partner Engineering AG (SPEAG), Safety Data Sheet, Doc No 772-SLAAx6yy-H, September 26, 2013.
- [11] Schmid & Partner Engineering AG (SPEAG), Material Safety Data Sheet, Doc No 772-SLAAH502A-D, August 9, 2013.
- [12] Schmid & Partner Engineering AG (SPEAG), Material Safety Data Sheet, Doc No 772-SLAAx4yy-J, August 9, 2013.
- [13] Schmid & Partner Engineering AG (SPEAG), Material Safety Data Sheet, Doc No 772-SLAAHxU16B-C, June 9, 2015.

1.9. Test Facilities and Accreditation

Test Facilities

Test Facility Name : Sony Global Manufacturing & Operations Corporation
EMC/RF Test Laboratory, Main Lab.
Address : Kisarazu Site 8-4 Shiomi Kisarazu-shi, Chiba, 292-0834 Japan
Shielded Room Used : 4th Site Shielded Room 2 4th Site Shielded Room 3

A2LA Accreditation

Certificate No. : 3203.01
Expiration : October 31, 2019

2. Test Set-up

2.1. Test Equipment and Measurement Software Lists

Table 2-1 Test Equipment List

Used	Control No.	Equipment Description	Model No.	Serial No.	Manufacturer	Cal. Int.	Last Cal.	Note(s)
<input checked="" type="checkbox"/>	W0128	Robot	TX60 L	F14/5VR2B1/A/01	Staubli	N/A	N/A *1	
<input type="checkbox"/>	W0124	Robot	RX60B L	F04/5Z71A1/A/03	Staubli	N/A	N/A *1	
<input checked="" type="checkbox"/>	WA0002	E-Field Probe	EX3DV4	3921	SPEAG	1Y	17.10.23	
<input type="checkbox"/>	WA0052	E-Field Probe	EX3DV4	7452	SPEAG	1Y	18.03.12	
<input type="checkbox"/>	W0095	Data Acquisition Electronics	DAE4	482	SPEAG	1Y	17.09.15	
<input checked="" type="checkbox"/>	W0096	Data Acquisition Electronics	DAE4	610	SPEAG	1Y	18.01.10	
<input type="checkbox"/>	W0081	Twin SAM Phantom	Twin SAM	TP-1441	SPEAG	N/A	N/A *1	
<input type="checkbox"/>	W0082	Twin SAM Phantom	Twin SAM	TP-1325	SPEAG	N/A	N/A *1	
<input type="checkbox"/>	W0126	Twin SAM Phantom	Twin SAM	TP-1851	SPEAG	N/A	N/A *1	
<input checked="" type="checkbox"/>	W0127	Twin SAM Phantom	Twin SAM	TP-1852	SPEAG	N/A	N/A *1	
<input type="checkbox"/>	W0119	ELI Phantom	ELI V5.0	1259	SPEAG	N/A	N/A *1	
<input checked="" type="checkbox"/>	WA0041	System Validation Dipole	D2450V2	765	SPEAG	1Y	18.05.16	
<input checked="" type="checkbox"/>	WA0042	System Validation Dipole	D5GHzV2	1039	SPEAG	1Y	18.04.17	
<input checked="" type="checkbox"/>	RM051	Vector Reflectometer	DAKS_VNA R140	0110614	Copper Mountain Technologies	1Y	18.02.19	
<input checked="" type="checkbox"/>	WA0044	Dielectric Probe	DAKS-3.5	1058	SPEAG	1Y	18.05.16	
<input checked="" type="checkbox"/>	W0009	Signal Generator	E4438C	US41461247	Agilent	1Y	17.11.02	
<input checked="" type="checkbox"/>	W0122	Power Amp	CGA020M60 2-2633R	B40550	R&K	N/A	N/A *1	
<input checked="" type="checkbox"/>	W0104	Power Sensor	U2021XA	MY54040006	Agilent	1Y	17.11.02	
<input checked="" type="checkbox"/>	W0105	Power Sensor	U2021XA	MY54080005	Agilent	1Y	17.11.02	
<input checked="" type="checkbox"/>	W0120	Directional Coupler	4226-20	-	narda	1Y	17.11.02	
<input checked="" type="checkbox"/>	W0117	Attenuator	8493B 3 dB	MY39260857	Agilent	1Y	17.11.02	
<input checked="" type="checkbox"/>	W0118	Attenuator	AT-110 10 dB	932968	Hirose	1Y	17.11.02	
<input checked="" type="checkbox"/>	W0148	Attenuator	AT-103 3 dB	980711	Hirose	1Y	17.11.02	
<input type="checkbox"/>	WC0022	RF Cable	SUCOFLEX 106	503094/6	HUBER+SUHNER	1Y	17.11.02	
<input checked="" type="checkbox"/>	WC0023	RF Cable	SUCOFLEX 104	MY36443/4	HUBER+SUHNER	1Y	17.11.02	
<input checked="" type="checkbox"/>	WC0024	RF Cable	SUCOFLEX 126E	MY1150/26E	HUBER+SUHNER	1Y	17.11.02	
<input checked="" type="checkbox"/>	WC0025	RF Cable	SUCOFLEX 104	MY37246/4	HUBER+SUHNER	1Y	17.11.02	
<input checked="" type="checkbox"/>	WC0026	RF Cable	SUCOFLEX 126E	MY1558/26E	HUBER+SUHNER	1Y	17.11.02	
<input checked="" type="checkbox"/>	M1048	Thermometer	0560 6220	39512479/703	testo	1Y	17.07.10	
<input checked="" type="checkbox"/>	M1049	Thermometer	0560 6220	39512571/703	testo	1Y	18.06.01	
<input type="checkbox"/>	W0112	Water Thermometer	735-1	02736130	testo	1Y	17.07.13	
<input checked="" type="checkbox"/>	W0113	Water Thermometer	735-1	02788580	testo	1Y	18.05.30	
<input type="checkbox"/>	W0114	Water Thermometer	735-1	02788582	testo	1Y	17.06.26	
<input type="checkbox"/>	W0115	Water Thermometer	735-1	02788585	testo	1Y	17.06.26	
<input type="checkbox"/>	W0116	Water Thermometer	735-1	02788596	testo	1Y	Under Calibration	

Note(s):
*1 In-house verification is conducted periodically.

Table 2-2 Measurement Software List

Used	Control No.	Software Description	Model No.	Ver.	Manufacturer
<input type="checkbox"/>	SW-0401	SAR measurement software	DASY52	52.8.8.1222	SPEAG
<input type="checkbox"/>	SW-0402	SAR post-processing software	SEMCAD X	14.6.10 (7331)	SPEAG
<input checked="" type="checkbox"/>	SW-0403	Dielectric measurement software	DAK	2.4.0.638	SPEAG
<input checked="" type="checkbox"/>	SW-0404	SAR measurement software	DASY52	52.8.8.1222	SPEAG
<input checked="" type="checkbox"/>	SW-0405	SAR post-processing software	SEMCAD X	14.6.10 (7331)	SPEAG
<input type="checkbox"/>	SW-0406	SAR measurement spreadsheet	-	1.00	Main Lab.
<input checked="" type="checkbox"/>	SW-0314	Power measurement software	N1918A	R03.09.00	Agilent

2.2. Measurement System Description

The DASY5 system for performing compliance tests consists of the following items:




Figure 2-1 Measurement System Description

- A standard high precision 6-axis robot (Staubli TX/RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantoms (the Twin SAM and/or ELI phantoms) enabling the testing of handheld (left-hand and right-hand) and/or body-mounted usage.
- The device holders for handheld mobile phones and/or larger devices (e.g., laptops, cameras, etc.).
- Tissue simulating liquid (TSL) mixed according to the given recipes.
- System Validation Dipole Kits allowing to validate the proper functioning of the system.

2.3. Measurement System Main Components

Robot (Positioner)

	Shielded Room 2	Shielded Room 3
Manufacturer	Staubli SA	
Model No.	TX60L	RX60BL
Number of Axis	6	
Reach at Wrist	920 mm	865 mm
Repeatability	+/- 0.03 mm	+/- 0.033 mm
Nominal Load Capacity	2 kg	1.5 kg
Maximum Load Capacity	5 kg	2.5 kg
Control Unit	CS8c	CS7m
Weight	52.2 kg	45 kg

E-Field Probe

Manufacturer	Schmid & Partner Engineering AG (SPEAG)
Model No.	EX3DV4
Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Frequency	10 MHz to > 6 GHz Linearity: ± 0.2 dB (30 MHz to 6 GHz)
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)
Dynamic Range	10 μ W/g to > 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)
Dimensions	Overall length: 337 mm (Tip length: 20 mm) Tip diameter: 2.5 mm (Body diameter: 12 mm) Typical distance from probe tip to dipole centers: 1 mm

Data Acquisition Electronics (DAE)

Manufacturer	Schmid & Partner Engineering AG (SPEAG)
Model No.	DAE4
Construction	Signal amplifier, multiplexer, A/D converter, and control logic Serial optical link for communication with DASY4/5 embedded system (fully remote controlled) Two-step probe touch detector for mechanical surFace detection and emergency robot stop
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4 mV, 400 mV)
Input Offset Voltage	< 5 μ V (with auto zero)
Input Resistance	200 M Ω
Input Bias Current	< 50 fA
Battery Power	> 10 hours of operation (with two 9.6 V NiMH accus)
Dimensions (L x W x H)	60 x 60 x 68 mm

DASY5 Measurement Server

Manufacturer	Schmid & Partner Engineering AG (SPEAG)
Model No.	DASY5 Measurement Server
CPU	Intel ULV Celeron 400 MHz
Chip-Disk	128 MB
RAM	128 MB
Construction	16 Bit A/D converter for surFace detection system Vacuum Fluorescent Display
I/O InterFace	Robot InterFace / Serial link to DAE (with watchdog supervision) / Door contact port / Emergency stop port (to connect the remote control) / Signal lamps port / Light beam port / Three Ethernet connection ports (for PC, Control Unit, and future applications) / Two USB 2.0 ports (for installation and advanced troubleshooting by SPEAG) / Two serial links (for future applications) / Expansion port (for future applications)
Dimensions (L x W x H)	440 x 241 x 89 mm

Phantoms (Twin SAM Phantom)

Manufacturer	Schmid & Partner Engineering AG (SPEAG)
Model No.	Twin SAM
Description	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot. Twin SAM V5.0 has the same shell geometry and is manufactured from the same material as Twin SAM V4.0, but has reinforced top structure.
Material	Vynlester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet
Filling Volume	Approx. 25 liters
Wooden Support	SPEAG standard phantom table

Phantoms (ELI Phantom)

Manufacturer	Schmid & Partner Engineering AG (SPEAG)
Model No.	ELI V5.0
Description	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles. ELI V5.0 has the same shell geometry and is manufactured from the same material as ELI4, but has reinforced top structure.
Material	Vynlester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	Approx. 30 liters
Wooden Support	SPEAG standard phantom table

Device Holder (Mounting Device for Hand-Held Transmitters)

Manufacturer	Schmid & Partner Engineering AG (SPEAG)
Model No.	MD4HHTV5
Description	In combination with the Twin SAM or ELI Phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).
Material	Polyoxymethylene (POM)

Device Holder (Mounting Device Adaptor for Ultra Wide Transmitters)

Manufacturer	Schmid & Partner Engineering AG (SPEAG)
Model No.	MDA4WTV5
Description	An upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140mm.
Material	Polyoxymethylene (POM)

Device Holder (Mounting Device Adaptor for Laptops)

Manufacturer	Schmid & Partner Engineering AG (SPEAG)
Model No.	MDA4LAP
Description	A simple but effective and easy-to-use extension for the Mounting Device; facilitates testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.); lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin SAM, ELI Phantoms.
Material	Polyoxymethylene (POM), PET-G, Foam

System Validation Dipole Kits


Manufacturer	Schmid & Partner Engineering AG (SPEAG)		
Model No.	D-Series		
Construction	Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with tissue simulating solutions		
Frequency	2450, 5100 to 5800 MHz		
Return Loss	> 20 dB at specified validation position		
Power Capability	> 100 W (f < 1 GHz); > 40 W (f > 1 GHz)		
Accessories	Distance holder, tripod adaptor, tripod		
Dimensions	Product	Dipole length	Overall height
	D2450V2	52.0 mm	290.0 mm
	D5GHzV2	20.6 mm	300.0 mm

2.4. Tissue Simulating Liquids


Recipes for tissue simulating liquids manufactured by SPEAG

Ingredients (% by weight)	Frequency (MHz)					
	1900 to 3800		3500 to 5800		600 to 6000	
Used	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Tissue Simulating Liquids	HBBL 1900- 3800 V3	MBBL 1900- 3800 V3	HBBL 3500- 5800 V5	MBBL 3500- 5800 V5	HBBL 600- 6000 V6	MBBL 600- 6000 V6
Tissue Type	Head	Body	Head	Body	Head	Body
H ₂ O	50 – 73 %		50 – 65 %	60 – 80 %	–	
Non-ionic detergents	25 – 50 %		–	–	–	
NaCl	0 – 2 %		0 – 1.5 %	0 – 1.5 %	–	
Preventol-D7	0.05 – 0.1 %		–	–	–	
Ethanediol	–		–	–	1.0 – 4.9 %	
Sodium Petroleum Sulfonate	–		–	–	< 2.9 %	
Hexylene Glycol	–		–	–	< 2.9 %	
Alkoxyated Alcohol	–		–	–	< 2.0 %	
Mineral Oil	–		10 – 30 %	–	< 20 %	
Emulsifiers	–		8 – 25 %	20 – 40 %	–	

For the SAR measurement, the phantom must be filled with tissue simulating liquid to a depth of at least 15 cm.




HBBL 600-6000 V6




MBBL 600-6000 V6

Figure 2-2 Photos: Liquid Depth (at the ERP location of the SAM phantom)



HBBL 600-6000 V6



MBBL 600-6000 V6

Figure 2-3 Photos: Liquid Depth (at the center of the flat phantom)

2.5. SAR Measurement

Step 1: Power Reference Measurement

Before an area scan and after the zoom scan, single point SAR measurements are performed at defined locations to estimate the SAR measurement drift due to device output power variations.

Step 2: Area Scan

An area scan is performed according to the requirements in Table 2-3.

Step 3: Zoom Scan

A zoom scan is performed according to the requirements in Table 2-3.

Step 4: Power Drift Measurement

Before an area scan and after the zoom scan, single point SAR measurements are performed at defined locations to estimate the SAR measurement drift due to device output power variations.

Table 2-3 Area Scan and Zoom Scan Parameters

		DUT Transmit Frequency being Tested		
		≤ 3 GHz	> 3 GHz	
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surFace		5 ± 1 mm	½ δ ln(2) ± 0.5 mm	
Maximum probe angle from probe axis to phantom surFace normal at the measurement location		30° ± 1°	20° ± 1°	
Maximum area scan spatial resolution: Δx _{Area} , Δy _{Area}		≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm	
		When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.		
Maximum zoom scan spatial resolution: Δx _{Zoom} , Δy _{Zoom}		≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm	3 – 4 GHz: ≤ 5 mm 4 – 6 GHz: ≤ 4 mm	
Maximum zoom scan spatial resolution, normal to phantom surFace	uniform grid: Δz _{Zoom} (n)	≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm	
	graded grid	Δz _{Zoom} (1): between 1st two points closest to phantom surFace	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		Δz _{Zoom} (n>1): between subsequent points	≤ 1.5 · Δz _{Zoom} (n-1)	
Minimum zoom scan volume	x, y, z	≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm	

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium.

2.6. Measurement Uncertainty

☒ Table 2-4 DASY5 Uncertainty Budget for SAR Tests

According to IEEE Std 1528-2013 (0.3GHz to 3GHz range)								
Input quantity	Uncertainty of Xi			Ci		Ciu(Xi)		Vi Veff
	Xi	Prob. Dist.	Div.	1g [-]	10g [-]	1g	10g	
Measurement System								
Probe Calibration (k=1)	±6.0%	N	1.00	1.00	1.00	±6.0%	±6.0%	∞
Axial Isotropy	±4.7%	R	1.73	0.70	0.70	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.7%	R	1.73	0.70	0.70	±3.9%	±3.9%	∞
Boundary Effects	±1.0%	R	1.73	1.00	1.00	±0.6%	±0.6%	∞
Linearity	±4.7%	R	1.73	1.00	1.00	±2.7%	±2.7%	∞
System Detection Limits	±0.3%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
Modulation Response	±2.4%	R	1.73	1.00	1.00	±1.4%	±1.4%	∞
Readout Electronics	±0.3%	N	1.00	1.00	1.00	±0.3%	±0.3%	∞
Response Time	±0.8%	R	1.73	1.00	1.00	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	1.73	1.00	1.00	±1.5%	±1.5%	∞
RF Ambient Noise	±0.2%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
RF Ambient Reflections	±0.3%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
Probe Positioner	±0.4%	R	1.73	1.00	1.00	±0.2%	±0.2%	∞
Probe Positioning	±2.9%	R	1.73	1.00	1.00	±1.7%	±1.7%	∞
Max. SAR Eval.	±2.0%	R	1.73	1.00	1.00	±1.2%	±1.2%	∞
Test Sample Related								
Device Positioning	±1.8%	N	1.00	1.00	1.00	±1.8%	±1.8%	14
Device Holder	±3.6%	N	1.00	1.00	1.00	±3.6%	±3.6%	5
Power Drift	±5.0%	R	1.73	1.00	1.00	±2.9%	±2.9%	∞
Power Scaling	±0.0%	R	1.73	1.00	1.00	±0.0%	±0.0%	∞
Phantom and Setup								
Phantom Uncertainty	±7.2%	R	1.73	1.00	1.00	±4.2%	±4.2%	∞
SAR Correction	±1.9%	R	1.73	1.00	0.84	±1.1%	±0.9%	∞
Liquid Conductivity (mea.)	±2.5%	R	1.73	0.78	0.71	±1.1%	±1.0%	∞
Liquid Permittivity (mea.)	±2.5%	R	1.73	0.23	0.26	±0.3%	±0.4%	∞
Temp. Unc. - Conductivity	±3.4%	R	1.73	0.78	0.71	±1.5%	±1.4%	∞
Temp. Unc. - Permittivity	±0.4%	R	1.73	0.23	0.26	±0.1%	±0.1%	∞
Combined Standard Uncertainty						±10.9%	±10.8%	406
Expanded Uncertainty (95% conf. interval)			k=2			±21.7%	±21.6%	

☒ Table 2-5 DASY5 Uncertainty Budget for SAR Tests

According to IEEE Std 1528-2013 (3GHz to 6GHz range)								
Input quantity	Uncertainty of Xi			Ci		Ciu(Xi)		Vi Veff
	Xi	Prob. Dist.	Div.	1g [-]	10g [-]	1g	10g	
Measurement System								
Probe Calibration (k=1)	±6.55%	N	1.00	1.00	1.00	±6.6%	±6.6%	∞
Axial Isotropy	±4.7%	R	1.73	0.70	0.70	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.7%	R	1.73	0.70	0.70	±3.9%	±3.9%	∞
Boundary Effects	±2.0%	R	1.73	1.00	1.00	±1.2%	±1.2%	∞
Linearity	±4.7%	R	1.73	1.00	1.00	±2.7%	±2.7%	∞
System Detection Limits	±0.3%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
Modulation Response	±2.4%	R	1.73	1.00	1.00	±1.4%	±1.4%	∞
Readout Electronics	±0.3%	N	1.00	1.00	1.00	±0.3%	±0.3%	∞
Response Time	±0.8%	R	1.73	1.00	1.00	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	1.73	1.00	1.00	±1.5%	±1.5%	∞
RF Ambient Noise	±0.2%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
RF Ambient Reflections	±0.3%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
Probe Positioner	±0.8%	R	1.73	1.00	1.00	±0.5%	±0.5%	∞
Probe Positioning	±6.7%	R	1.73	1.00	1.00	±3.9%	±3.9%	∞
Max. SAR Eval.	±4.0%	R	1.73	1.00	1.00	±2.3%	±2.3%	∞
Test Sample Related								
Device Positioning	±1.8%	N	1.00	1.00	1.00	±1.8%	±1.8%	14
Device Holder	±3.6%	N	1.00	1.00	1.00	±3.6%	±3.6%	5
Power Drift	±5.0%	R	1.73	1.00	1.00	±2.9%	±2.9%	∞
Power Scaling	±0.0%	R	1.73	1.00	1.00	±0.0%	±0.0%	∞
Phantom and Setup								
Phantom Uncertainty	±7.6%	R	1.73	1.00	1.00	±4.4%	±4.4%	∞
SAR Correction	±1.9%	R	1.73	1.00	0.84	±1.1%	±0.9%	∞
Liquid Conductivity (mea.)	±2.5%	R	1.73	0.78	0.71	±1.1%	±1.0%	∞
Liquid Permittivity (mea.)	±2.5%	R	1.73	0.23	0.26	±0.3%	±0.4%	∞
Temp. Unc. - Conductivity	±3.4%	R	1.73	0.78	0.71	±1.5%	±1.4%	∞
Temp. Unc. - Permittivity	±0.4%	R	1.73	0.23	0.26	±0.1%	±0.1%	∞
Combined Standard Uncertainty						±12.0%	±12.0%	606
Expanded Uncertainty (95% conf. interval)			k=2			±24.0%	±23.9%	

□ Table 2-6 DASY5 Uncertainty Budget for SAR Tests


According to IEC 62209-2/2010 (0.03GHz to 6GHz range)								
Input quantity	Uncertainty of Xi			Ci		Ciu(Xi)		Vi Veff
	Xi	Prob. Dist.	Div.	1g [-]	10g [-]	1g	10g	
Measurement System								
Probe Calibration (k=1)	±6.55%	N	1.00	1.00	1.00	±6.6%	±6.6%	∞
Axial Isotropy	±4.7%	R	1.73	0.70	0.70	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.7%	R	1.73	0.70	0.70	±3.9%	±3.9%	∞
Boundary Effects	±2.0%	R	1.73	1.00	1.00	±1.2%	±1.2%	∞
Linearity	±4.7%	R	1.73	1.00	1.00	±2.7%	±2.7%	∞
System Detection Limits	±0.3%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
Modulation Response	±2.4%	R	1.73	1.00	1.00	±1.4%	±1.4%	∞
Readout Electronics	±0.3%	N	1.00	1.00	1.00	±0.3%	±0.3%	∞
Response Time	±0.8%	R	1.73	1.00	1.00	±0.5%	±0.5%	∞
Integration Time	±2.6%	R	1.73	1.00	1.00	±1.5%	±1.5%	∞
RF Ambient Noise	±0.2%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
RF Ambient Reflections	±0.3%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
Probe Positioner	±0.8%	R	1.73	1.00	1.00	±0.5%	±0.5%	∞
Probe Positioning	±6.7%	R	1.73	1.00	1.00	±3.9%	±3.9%	∞
Post-Processing	±4.0%	R	1.73	1.00	1.00	±2.3%	±2.3%	∞
Test Sample Related								
Test Sample Positioning	±1.8%	N	1.00	1.00	1.00	±1.8%	±1.8%	14
Device Holder	±3.6%	N	1.00	1.00	1.00	±3.6%	±3.6%	5
Power Drift	±5.0%	R	1.73	1.00	1.00	±2.9%	±2.9%	∞
Power Scaling	±0.0%	R	1.73	1.00	1.00	±0.0%	±0.0%	∞
Phantom and Setup								
Phantom Uncertainty	±7.6%	R	1.73	1.00	1.00	±4.4%	±4.4%	∞
SAR Correction	±1.9%	R	1.73	1.00	0.84	±1.1%	±0.9%	∞
Liquid Conductivity (mea.)	±2.5%	R	1.73	0.78	0.71	±1.1%	±1.0%	∞
Liquid Permittivity (mea.)	±2.5%	R	1.73	0.23	0.26	±0.3%	±0.4%	∞
Temp. Unc. - Conductivity	±3.4%	R	1.73	0.78	0.71	±1.5%	±1.4%	∞
Temp. Unc. - Permittivity	±0.4%	R	1.73	0.23	0.26	±0.1%	±0.1%	∞
Combined Standard Uncertainty						±12.0%	±12.0%	606
Expanded Uncertainty (95% conf. interval)			k=2			±24.0%	±23.9%	

☒ Table 2-7 DASYS5 Uncertainty Budget for SAR System Check


According to IEEE Std 1528-2013, IEC 62209-2/2010 (0.3GHz to 6GHz range)								
Input quantity	Uncertainty of Xi			Ci		Ciu(Xi)		Vi Veff
	Xi	Prob. Dist.	Div.	1g [-]	10g [-]	1g	10g	
Measurement System								
Probe Calibration (k=1)	±6.55%	N	1.00	1.00	1.00	±6.6%	±6.6%	∞
Axial Isotropy	±4.7%	R	1.73	0.70	0.70	±1.9%	±1.9%	∞
Hemispherical Isotropy	±9.7%	R	1.73	0.70	0.70	±3.9%	±3.9%	∞
Boundary Effects	±2.0%	R	1.73	1.00	1.00	±1.2%	±1.2%	∞
Linearity	±4.7%	R	1.73	1.00	1.00	±2.7%	±2.7%	∞
System Detection Limits	±0.3%	R	1.73	1.00	1.00	±0.1%	±0.1%	∞
Modulation Response	±0.0%	R	1.73	1.00	1.00	±0.0%	±0.0%	∞
Readout Electronics	±0.3%	N	1.00	1.00	1.00	±0.3%	±0.3%	∞
Response Time	±0.0%	R	1.73	1.00	1.00	±0.0%	±0.0%	∞
Integration Time	±0.0%	R	1.73	1.00	1.00	±0.0%	±0.0%	∞
RF Ambient Noise	±1.0%	R	1.73	1.00	1.00	±0.6%	±0.6%	∞
RF Ambient Reflections	±1.0%	R	1.73	1.00	1.00	±0.6%	±0.6%	∞
Probe Positioner	±0.8%	R	1.73	1.00	1.00	±0.5%	±0.5%	∞
Probe Positioning	±6.7%	R	1.73	1.00	1.00	±3.9%	±3.9%	∞
Max. SAR Eval.	±4.0%	R	1.73	1.00	1.00	±2.3%	±2.3%	∞
Dipole Related								
Deviation of exp. Dipole	±5.5%	R	1.73	1.00	1.00	±3.2%	±3.2%	∞
Dipole Axis to Liquid Dist.	±2.0%	R	1.73	1.00	1.00	±1.2%	±1.2%	∞
Inoput Power & SAR Drift	±3.4%	R	1.73	1.00	1.00	±2.0%	±2.0%	∞
Phantom and Setup								
Phantom Uncertainty	±7.6%	R	1.73	1.00	1.00	±4.4%	±4.4%	∞
SAR Correction	±1.9%	R	1.73	1.00	0.84	±1.1%	±0.9%	∞
Liquid Conductivity (mea.)	±2.5%	N	1.00	0.78	0.71	±2.0%	±1.8%	∞
Liquid Permittivity (mea.)	±2.5%	N	1.00	0.23	0.26	±0.6%	±0.7%	∞
Temp. Unc. - Conductivity	±3.4%	R	1.73	0.78	0.71	±1.5%	±1.4%	∞
Temp. Unc. - Permittivity	±0.4%	R	1.73	0.23	0.26	±0.1%	±0.1%	∞
Combined Standard Uncertainty						±11.6%	±11.5%	
Expanded Uncertainty (95% conf. interval)			k=2			±23.1%	±23.0%	

2.7. Dielectric Parameter Measurement of Tissue Simulating Liquids

The dielectric properties of the tissue simulating liquids used were verified within 24 hours before the SAR measurement.



(a) Dielectric Parameter Measurement System



(b) Example Photo: Dielectric Parameter Measurement

Figure 2-4 Dielectric Parameter Measurement Set-up

*1 Target values are linearly interpolated between the values defined in KDB 865664 D01, when necessary.

*2 The deviation of measured values from target values must be within +/-5 %.

4th Site Shielded Room 2 (Head TSL)

TSL	Freq. (MHz)	Param.	Target *1	Meas.	Dev. (%) *2	Date	Amb. Temp. (deg. C)	Rel. Hum. (%RH)	Liquid Temp. (deg. C)	Note(s)
HBBL 600-6000V6	2412	ϵ_r	39.27	39.43	0.41	2018/06/19	22.1	58.0	22.2	
		σ (S/m)	1.77	1.82	2.82					
	2437	ϵ_r	39.22	39.39	0.43					
		σ (S/m)	1.79	1.83	2.23					
	2462	ϵ_r	39.18	39.35	0.43					
		σ (S/m)	1.81	1.85	2.21					
	5260	ϵ_r	35.92	35.78	-0.39	2018/06/20	21.1	63.0	21.1	
		σ (S/m)	4.72	4.63	-1.91					
	5280	ϵ_r	35.89	35.75	-0.39					
		σ (S/m)	4.74	4.65	-1.90					
	5300	ϵ_r	35.87	35.72	-0.42					
		σ (S/m)	4.76	4.68	-1.68					
	5320	ϵ_r	35.85	35.69	-0.45					
		σ (S/m)	4.78	4.70	-1.67					
	5500	ϵ_r	35.64	34.62	-2.86					
		σ (S/m)	4.96	4.90	-1.21					
	5600	ϵ_r	35.53	34.46	-3.01					
		σ (S/m)	5.07	5.00	-1.38					
	5700	ϵ_r	35.41	34.28	-3.19					
		σ (S/m)	5.17	5.10	-1.35					
5745	ϵ_r	35.36	34.19	-3.31						
	σ (S/m)	5.21	5.16	-0.96						
5785	ϵ_r	35.32	34.13	-3.37						
	σ (S/m)	5.25	5.21	-0.76						
5825	ϵ_r	35.27	34.06	-3.43						
	σ (S/m)	5.30	5.26	-0.75						

4th Site Shielded Room 2 (Body TSL)

TSL	Freq. (MHz)	Param.	Target *1	Meas.	Dev. (%) *2	Date	Amb. Temp. (deg. C)	Rel. Hum. (%RH)	Liquid Temp. (deg. C)	Note(s)
MBBL 600-6000V6	2412	ϵ_r	52.75	52.04	-1.35	2018/06/15	24.4	60.0	23.3	
		σ (S/m)	1.91	1.99	4.19					
	2437	ϵ_r	52.72	52.01	-1.35					
		σ (S/m)	1.94	2.02	4.12					
	2462	ϵ_r	52.68	51.97	-1.35					
		σ (S/m)	1.97	2.04	3.55					
	5260	ϵ_r	48.93	47.89	-2.13	2018/06/17	24.7	57.0	22.6	
		σ (S/m)	5.37	5.56	3.54					
	5280	ϵ_r	48.91	47.86	-2.15					
		σ (S/m)	5.39	5.58	3.53					
	5300	ϵ_r	48.88	47.82	-2.17					
		σ (S/m)	5.42	5.61	3.51					
	5320	ϵ_r	48.85	47.79	-2.17					
		σ (S/m)	5.44	5.64	3.68					
	5500	ϵ_r	48.61	47.78	-1.71	2018/06/18	24.3	51.0	23.6	
		σ (S/m)	5.65	5.71	1.06					
	5600	ϵ_r	48.47	47.62	-1.75					
		σ (S/m)	5.77	5.85	1.39					
5700	ϵ_r	48.34	47.45	-1.84						
	σ (S/m)	5.88	5.98	1.70						
5745	ϵ_r	48.27	47.37	-1.86						
	σ (S/m)	5.94	6.05	1.85						
5785	ϵ_r	48.22	47.29	-1.93						
	σ (S/m)	5.98	6.11	2.17						
5825	ϵ_r	48.17	47.21	-1.99						
	σ (S/m)	6.03	6.18	2.49						

2.8. System Check Measurement

The system check was performed before each series of SAR measurements using the same probe calibration point and tissue-equivalent medium.




Figure 2-5 System Check Measurement Set-up



D2450V2



D5GHzV2

(c) Photo: System Validation Dipole Placement

Figure 2-5 System Check Measurement Set-up (continued)

*1 The normalized values (1 W) were calculated by normalizing the measured values to 1-W forward input power.

*2 The target values (1 W) are defined in IEEE Std 1528 and/or the calibration certificate of system validation dipoles used.

*3 The deviation of normalized values from target values must be within +/-10 %.

4th Site Shielded Room 2 (Head TSL)

System Validation Dipole	Freq. (MHz)	Param.	250 mW-Meas. (W/kg)	1 W-Norm. (W/kg) *1	1 W-Target (W/kg) *2	Dev. (%) *3	Date	Amb. Temp. (deg. C)	Rel. Hum. (%RH)	Liquid Temp. (deg. C)	Note(s)
D2450V2	2450	1-g SAR	13.60	54.40	51.40	5.84	2018/06/19	21.9	61.0	22.1	
		10-g SAR	6.27	25.08	23.90	4.94					
System Validation Dipole	Freq. (MHz)	Param.	100 mW-Meas. (W/kg)	1 W-Norm. (W/kg) *1	1 W-Target (W/kg) *2	Dev. (%) *3	Date	Amb. Temp. (deg. C)	Rel. Hum. (%RH)	Liquid Temp. (deg. C)	Note(s)
D5GHzV2	5300	1-g SAR	7.79	77.90	83.80	-7.04	2018/06/20	21.0	60.0	21.0	
		10-g SAR	2.19	21.90	24.10	-9.13					
D5GHzV2	5600	1-g SAR	7.96	79.60	86.80	-8.29		22.0	55.9	20.6	
		10-g SAR	2.25	22.50	24.80	-9.27					
D5GHzV2	5800	1-g SAR	7.63	76.30	83.00	-8.07		22.5	62.9	20.7	
		10-g SAR	2.15	21.50	23.70	-9.28					

4th Site Shielded Room 2 (Body TSL)

System Validation Dipole	Freq. (MHz)	Param.	250 mW-Meas. (W/kg)	1 W-Norm. (W/kg) *1	1 W-Target (W/kg) *2	Dev. (%) *3	Date	Amb. Temp. (deg. C)	Rel. Hum. (%RH)	Liquid Temp. (deg. C)	Note(s)
D2450V2	2450	1-g SAR	13.10	52.40	49.80	5.22	2018/06/15	24.3	63.0	23.1	
		10-g SAR	6.11	24.44	23.20	5.34					
System Validation Dipole	Freq. (MHz)	Param.	100 mW-Meas. (W/kg)	1 W-Norm. (W/kg) *1	1 W-Target (W/kg) *2	Dev. (%) *3	Date	Amb. Temp. (deg. C)	Rel. Hum. (%RH)	Liquid Temp. (deg. C)	Note(s)
D5GHzV2	5300	1-g SAR	8.10	81.00	76.80	5.47	2018/06/17	24.5	57.0	22.8	
		10-g SAR	2.30	23.00	21.60	6.48					
D5GHzV2	5600	1-g SAR	8.34	83.40	79.90	4.38	2018/06/18	24.5	54.6	24.1	
		10-g SAR	2.38	23.80	22.40	6.25					
D5GHzV2	5800	1-g SAR	7.61	76.10	75.80	0.40		24.4	53.0	23.5	
		10-g SAR	2.15	21.50	21.20	1.42					

3. Conducted Power Measurements

☒ <The Initial Test Configuration Procedures for Wi-Fi>

According to KDB 248227 D01,

the initial test configuration is determined by the 802.11 configuration with the highest maximum output power specified for production units, including tune-up tolerance, in each standalone and aggregated frequency band.

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is determined by applying the following steps sequentially.

- 1) The largest channel bandwidth configuration is selected among the multiple configurations in a frequency band with the same specified maximum output power.
- 2) If multiple configurations have the same specified maximum output power and largest channel bandwidth, the lowest order modulation among the largest channel bandwidth configurations is selected.
- 3) If multiple configurations have the same specified maximum output power, largest channel bandwidth and lowest order modulation, the lowest data rate configuration among these configurations is selected.
- 4) When multiple transmission modes (802.11a/g/n/ac) have the same specified maximum output power, largest channel bandwidth, lowest order modulation and lowest data rate, the lowest order 802.11 mode is selected; i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n.

3.1. Conducted Power Measurement Results

Wi-Fi 2.4 GHz

Date : 2018/05/14 Measured by : M. Kouga
 Amb. Temp. : 21.0 deg. C Rel. hum. : 45.0 %RH

IEEE 802.11b

Ch.	Freq. (MHz)	Data Rate (Mbps)	Meas. Frame Averaged Power (dBm)	Meas. Burst Averaged Power (dBm) *1	Max. Poss. Power (dBm)	Within 2 dB of Max. Poss. Power	SAR Tested	Note(s)
1	2412	1.0	13.37	13.38	13.5	Yes	Yes	Worst Ch
6	2437	1.0	13.17	13.18	13.5	Yes	Yes	
11	2462	1.0	13.18	13.19	13.5	Yes	Yes	

IEEE 802.11g (*2)

Ch.	Freq. (MHz)	Data Rate (Mbps)	Meas. Frame Averaged Power (dBm)	Meas. Burst Averaged Power (dBm) *1	Max. Poss. Power (dBm)	Within 2 dB of Max. Poss. Power	SAR Tested	Note(s)
1	2412	6.0	12.68	12.75	13.5	Yes	-	
6	2437	6.0	12.79	12.86	13.5	Yes	-	Worst Ch
11	2462	6.0	12.47	12.54	13.5	Yes	-	

IEEE 802.11n (HT20) (*2)

Ch.	Freq. (MHz)	MCS	Meas. Frame Averaged Power (dBm)	Meas. Burst Averaged Power (dBm) *1	Max. Poss. Power (dBm)	Within 2 dB of Max. Poss. Power	SAR Tested	Note(s)
1	2412	0	12.52	12.59	13.5	Yes	-	
6	2437	0	12.66	12.73	13.5	Yes	-	Worst Ch
11	2462	0	12.50	12.57	13.5	Yes	-	

IEEE 802.11n (HT40) (*2)

Ch.	Freq. (MHz)	MCS	Meas. Frame Averaged Power (dBm)	Meas. Burst Averaged Power (dBm) *1	Max. Poss. Power (dBm)	Within 2 dB of Max. Poss. Power	SAR Tested	Note(s)
1	2422	0	12.48	12.56	13.0	Yes	-	
6	2437	0	12.49	12.57	13.0	Yes	-	Worst Ch
11	2452	0	12.21	12.29	13.0	Yes	-	

*1 Used for confirmation that the DUT's output power is within +0/-2 dB of the maximum tune-up tolerance limits (max. poss. power), since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 SAR is not required for 802.11g/n channels when the highest reported SAR for DSSS (802.11b) is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg or 3 W/kg (1-g or 10-g respectively), according to KDB 248227 D01.

Wi-Fi 5 GHz (W52: U-NII-1 and W53: U-NII-2A Bands)

Date : 2018/6/12 Measured by : M. Kouga
 Amb. Temp. : 24.5 deg. C Rel. hum. : 56.3 %RH

The Initial Test Configuration (ITC) : IEEE 802.11a in W53 (*3)(*4)

Mode	Freq. Band	Ch.	Freq. (MHz)	Data Rate /MCS	Meas. Frame Averaged Power (dBm)	Meas. Burst Averaged Power (dBm) *1	Max. Poss. Power (dBm)	Within 2 dB of Max. Poss. Power	SAR Tested	Note(s)
802.11a	W52	36	5180	6.0 Mbps	13.78	13.85	14.0	Yes	-	
		40	5200	6.0 Mbps	13.52	13.59	14.0	Yes	-	
		44	5220	6.0 Mbps	13.84	13.91	14.0	Yes	-	
		48	5240	6.0 Mbps	13.82	13.89	14.0	Yes	-	
	W53	52	5260	6.0 Mbps	13.72	13.79	14.0	Yes	Yes	ITC
		56	5280	6.0 Mbps	13.30	13.37	14.0	Yes	Yes	
		60	5300	6.0 Mbps	13.65	13.72	14.0	Yes	Yes	
		64	5320	6.0 Mbps	13.59	13.66	14.0	Yes	Yes	
802.11n (HT20)	W52	36	5180	MCS-0	13.75	13.82	14.0	Yes	-	
		40	5200	MCS-0	13.62	13.69	14.0	Yes	-	
		44	5220	MCS-0	13.37	13.44	14.0	Yes	-	
		48	5240	MCS-0	13.61	13.68	14.0	Yes	-	
	W53	52	5260	MCS-0	13.51	13.58	14.0	Yes	-	
		56	5280	MCS-0	13.41	13.48	14.0	Yes	-	
		60	5300	MCS-0	13.46	13.53	14.0	Yes	-	
		64	5320	MCS-0	13.52	13.59	14.0	Yes	-	
802.11n (HT40)	W52	38	5190	MCS-0	11.34	11.42	11.5	Yes	-	
		46	5230	MCS-0	11.35	11.43	11.5	Yes	-	
	W53	54	5270	MCS-0	11.38	11.46	11.5	Yes	-	
		62	5310	MCS-0	11.41	11.49	11.5	Yes	-	
802.11ac (VHT20)	W52	36	5180	MCS-0	9.48	9.55	10.0	Yes	-	
		40	5200	MCS-0	9.18	9.25	10.0	Yes	-	
		44	5220	MCS-0	9.26	9.33	10.0	Yes	-	
		48	5240	MCS-0	9.39	9.46	10.0	Yes	-	
	W53	52	5260	MCS-0	8.97	9.04	10.0	Yes	-	
		56	5280	MCS-0	9.08	9.15	10.0	Yes	-	
		60	5300	MCS-0	8.97	9.04	10.0	Yes	-	
		64	5320	MCS-0	9.11	9.18	10.0	Yes	-	
802.11ac (VHT40)	W52	38	5190	MCS-0	9.49	9.56	10.0	Yes	-	
		46	5230	MCS-0	9.23	9.30	10.0	Yes	-	
	W53	54	5270	MCS-0	9.23	9.30	10.0	Yes	-	
		62	5310	MCS-0	9.38	9.45	10.0	Yes	-	
802.11ac (VHT80)	W52	42	5210	MCS-0	6.71	6.78	7.0	Yes	-	
	W53	58	5290	MCS-0	6.50	6.57	7.0	Yes	-	

*1 Used for confirmation that the DUT's output power is within +0/-2 dB of the maximum tune-up tolerance limits (max. poss. power), since the maximum tune-up tolerance limits are defined as burst averaged values.

*3 When the same maximum output power is specified for U-NII-1 and U-NII-2A bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg or 3 W/kg (1-g or 10-g respectively), SAR is not required for U-NII-1 band for that configuration.

*4 SAR is not required for the remaining 802.11 transmission configurations (802.11 n-HT20/n-HT40/ac-VHT20/ac-VHT40/ac-VHT80) when the highest reported SAR for the initial test configuration (802.11 a) is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg or 3 W/kg (1-g or 10-g respectively), according to KDB 248227 D01.

Wi-Fi 5 GHz (W56: U-NII-2C Band)

Date : 2018/6/12 Measured by : M. Kouga
 Amb. Temp. : 24.5 deg. C Rel. hum. : 56.3 %RH

The Initial Test Configuration (ITC) : IEEE 802.11a (*4)

Mode	Freq. Band	Ch.	Freq. (MHz)	Data Rate /MCS	Meas. Frame Averaged Power (dBm)	Meas. Burst Averaged Power (dBm) *1	Max. Poss. Power (dBm)	Within 2 dB of Max. Poss. Power	SAR Tested	Note(s)
802.11a	W56	100	5500	6.0 Mbps	13.58	13.65	14.0	Yes	Yes	ITC
		120	5600	6.0 Mbps	13.28	13.35	14.0	Yes	Yes	
		140	5700	6.0 Mbps	12.58	12.65	14.0	Yes	Yes	
802.11n (HT20)	W56	100	5500	MCS-0	13.33	13.40	14.0	Yes	-	
		116	5600	MCS-0	13.27	13.34	14.0	Yes	-	
		140	5700	MCS-0	12.28	12.35	14.0	Yes	-	
802.11n (HT40)	W56	102	5510	MCS-0	11.38	11.46	11.5	Yes	-	
		118	5590	MCS-0	11.16	11.24	11.5	Yes	-	
		134	5670	MCS-0	10.62	10.70	11.5	Yes	-	
802.11ac (VHT20)	W56	100	5500	MCS-0	9.43	9.50	10.0	Yes	-	
		116	5600	MCS-0	8.98	9.05	10.0	Yes	-	
		140	5620	MCS-0	9.13	9.20	10.0	Yes	-	
		144	5720	MCS-0	8.32	8.39	10.0	Yes	-	
802.11ac (VHT40)	W56	102	5510	MCS-0	9.38	9.45	10.0	Yes	-	
		118	5590	MCS-0	9.06	9.13	10.0	Yes	-	
		134	5630	MCS-0	9.04	9.11	10.0	Yes	-	
		142	5720	MCS-0	8.43	8.50	10.0	Yes	-	
802.11ac (VHT80)	W56	106	5530	MCS-0	6.56	6.63	7.0	Yes	-	
		122	5610	MCS-0	6.29	6.36	7.0	Yes	-	
		138	5690	MCS-0	6.04	6.11	7.0	Yes	-	

*1 Used for confirmation that the DUT's output power is within +0/-2 dB of the maximum tune-up tolerance limits (max. poss. power), since the maximum tune-up tolerance limits are defined as burst averaged values.

*4 SAR is not required for the remaining 802.11 transmission configurations (802.11 n-HT20/n-HT40/ac-VHT20/ac-VHT40/ac-VHT80) when the highest reported SAR for the initial test configuration (802.11 a) is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg or 3 W/kg (1-g or 10-g respectively), according to KDB 248227 D01.

Wi-Fi 5 GHz (W58: U-NII-3 Band)

Date : 2018/6/12 Measured by : M. Kouga
 Amb. Temp. : 24.5 deg. C Rel. hum. : 56.3 %RH

The Initial Test Configuration (ITC) : IEEE 802.11a (*4)

Mode	Freq. Band	Ch.	Freq. (MHz)	Data Rate /MCS	Meas. Frame Averaged Power (dBm)	Meas. Burst Averaged Power (dBm) *1	Max. Poss. Power (dBm)	Within 2 dB of Max. Poss. Power	SAR Tested	Note(s)
802.11a	W58	149	5745	6.0 Mbps	13.15	13.22	14.0	Yes	Yes	ITC
		157	5785	6.0 Mbps	12.99	13.06	14.0	Yes	Yes	
		165	5825	6.0 Mbps	12.75	12.82	14.0	Yes	Yes	
802.11n (HT20)	W58	149	5745	MCS-0	13.36	13.43	14.0	Yes	-	
		157	5785	MCS-0	13.16	13.23	14.0	Yes	-	
		165	5825	MCS-0	12.53	12.60	14.0	Yes	-	
802.11n (HT40)	W58	151	5755	MCS-0	11.12	11.20	11.5	Yes	-	
		159	5795	MCS-0	11.00	11.08	11.5	Yes	-	
802.11ac (VHT20)	W58	149	5745	MCS-0	8.99	9.06	10.0	Yes	-	
		157	5785	MCS-0	8.83	8.90	10.0	Yes	-	
		165	5825	MCS-0	8.94	9.01	10.0	Yes	-	
802.11ac (VHT40)	W58	151	5755	MCS-0	9.18	9.25	10.0	Yes	-	
		159	5795	MCS-0	8.99	9.06	10.0	Yes	-	
802.11ac (VHT80)	W58	155	5775	MCS-0	6.32	6.39	7.0	Yes	-	

*1 Used for confirmation that the DUT's output power is within +/-2 dB of the maximum tune-up tolerance limits (max. poss. power), since the maximum tune-up tolerance limits are defined as burst averaged values.

*4 SAR is not required for the remaining 802.11 transmission configurations (802.11 n-HT20/n-HT40/ac-VHT20/ac-VHT40/ac-VHT80) when the highest reported SAR for the initial test configuration (802.11 a) is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg or 3 W/kg (1-g or 10-g respectively), according to KDB 248227 D01.

4. SAR Measurements

<SAR Correction/Scaling>

According to KDB 865664 D01, the maximum SAR values are determined by taking account of the following correction or scaling factors.

The maximum 1-g SAR and/or 10-g SAR values (reported SAR) are calculated by applying the Δ SAR positive correction for deviations of the tissue-equivalent liquid and the power scaling for the maximum duty factor and maximum possible power levels (maximum tune-up tolerance limit) to each measured 1-g SAR and/or 10-g SAR value:

$$\text{Reported SAR (W/kg)} = \text{Measured SAR (W/kg)} * \Delta\text{SAR positive correction factor} * \text{Duty cycle scaling factor} * \text{Tune-up scaling factor}$$

where:

$$\Delta\text{SAR positive correction factor} = (100 - \Delta\text{SAR}^{*1}) / 100$$

$$\text{Duty cycle scaling factor} = \text{Max. possible duty cycle} / \text{Measured duty cycle used for the SAR measurement}$$

$$\text{Tune-up scaling factor} = \text{Max. possible power (mW)} / \text{Measured power used for the SAR measurement (mW)}$$

$$*1 \quad \Delta\text{SAR} (\%) = c_e * \Delta\epsilon_r + c_o * \Delta\sigma$$

<For 1-g SAR>

$$c_e = -7.854 * 10^{-4} f^3 + 9.402 * 10^{-3} f^2 - 2.742 * 10^{-2} f - 0.2026$$

$$c_o = 9.804 * 10^{-3} f^3 - 8.661 * 10^{-2} f^2 + 2.981 * 10^{-2} f + 0.7829$$

<For 10-g SAR>

$$c_e = 3.456 * 10^{-3} f^3 - 3.531 * 10^{-2} f^2 + 7.675 * 10^{-2} f - 0.1860$$

$$c_o = 4.479 * 10^{-3} f^3 - 1.586 * 10^{-2} f^2 - 0.1972 f + 0.7717$$

where:

c_e coefficient representing the sensitivity of SAR to permittivity

$\Delta\epsilon_r$ percent change in permittivity

c_o coefficient representing the sensitivity of SAR to conductivity

$\Delta\sigma$ percent change in conductivity

f frequency in GHz

A negative Δ SAR would translate to a lower measured SAR value than what would be measured if using dielectric properties equal to the target values.

A positive Δ SAR would translate to a higher measured SAR value than what would be measured if using dielectric properties equal to the target values.

SAR correction shall not be made when the Δ SAR has a positive sign to provide a conservative SAR value.

The SAR is only corrected when Δ SAR has a negative sign.

<SAR Test Reduction for Wi-Fi>

SAR test reduction for Wi-Fi is applied according to KDB 248227 D01.

For 2.4 GHz 802.11g/n OFDM configurations

SAR is not required for the following 2.4 GHz OFDM conditions.

- 1) When KDB Publication 447498 SAR test exclusion applies to the OFDM configuration.
- 2) When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg or 3 W/kg (1-g or 10-g respectively).

For U-NII-1 (W52) and U-NII-2A (W53) Bands

When the same transmitter and antenna(s) are used for U-NII-1 and U-NII-2A bands, additional SAR test reduction applies.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg or 3 W/kg (1-g or 10-g respectively), SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition); otherwise, each band is tested independently for SAR.
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg or 3 W/kg (1-g or 10-g respectively), SAR is not required for the band with lower maximum output power in that test configuration; otherwise, each band is tested independently for SAR.

4.1. SAR Measurement Results

<Head SAR>

Wi-Fi 2.4 GHz

Date : 2018/06/19 Measured by : S. Fukushima
 Amb. Temp. : 21.5 deg. C Rel. hum. : 58.0 %RH

Mode	Ch.	Freq. (MHz)	Pos.	Dis. (mm)	Max. Poss. Power (dBm)	Meas. Power (dBm)	Max. Duty Cycle (%)	Meas. Duty Cycle (%)	Meas. 1-g SAR (W/kg)	Reported 1-g SAR (W/kg)	Liquid Temp. (deg. C)	Plot No.
802.11b	1	2412	Front of Face	0	13.50	13.38	100.00	99.69	0.035	0.036	22.0	1
	6	2437			13.50	13.18	100.00	99.69	0.026	0.028	22.0	
	11	2462			13.50	13.19	100.00	99.69	0.022	0.024	22.1	

*1 The burst averaged power values are used for power scaling since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 Reported SAR (W/kg) = Measured SAR (W/kg) * Duty cycle scaling factor * Tune-up scaling factor

where:

Duty cycle scaling factor = Max. possible duty cycle (%) / Measured duty cycle used for the SAR measurement (%)

Tune-up scaling factor = Max. possible power (mW) (* equal to 100% duty cycle) / Measured power used for the SAR measurement (mW)

Wi-Fi 5 GHz (W53: U-NII-2A Band)

Date : 2018/06/20 Measured by : S. Fukushima
 Amb. Temp. : 21.2 deg. C Rel. hum. : 65.0 %RH

Mode	Ch.	Freq. (MHz)	Pos.	Dis. (mm)	Max. Poss. Power (dBm)	Meas. Power (dBm)	Max. Duty Cycle (%)	Meas. Duty Cycle (%)	Meas. 1-g SAR (W/kg)	Reported 1-g SAR (W/kg)	Liquid Temp. (deg. C)	Plot No.
802.11a	52	5260	Front of Face	0	14.00	13.79	100.00	98.46	0.055	0.058	21.0	
	56	5280			14.00	13.37	100.00	98.46	0.055	0.065	20.9	2
	60	5300			14.00	13.72	100.00	98.46	0.048	0.052	20.8	
	64	5320			14.00	13.66	100.00	98.46	0.049	0.054	20.7	

*1 The burst averaged power values are used for power scaling since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 Reported SAR (W/kg) = Measured SAR (W/kg) * Duty cycle scaling factor * Tune-up scaling factor

where:

Duty cycle scaling factor = Max. possible duty cycle (%) / Measured duty cycle used for the SAR measurement (%)

Tune-up scaling factor = Max. possible power (mW) (* equal to 100% duty cycle) / Measured power used for the SAR measurement (mW)

Wi-Fi 5 GHz (W56: U-NII-2C Band)

Date : 2018/06/20 Measured by : Y. Kamiko
 Amb. Temp. : 23.1 deg. C Rel. hum. : 57.2 %RH

Mode	Ch.	Freq. (MHz)	Pos.	Dis. (mm)	Max. Poss. Power (dBm)	Meas. Power (dBm)	Max. Duty Cycle (%)	Meas. Duty Cycle (%)	Meas. 1-g SAR (W/kg)	Reported 1-g SAR (W/kg)	Liquid Temp. (deg. C)	Plot No.
802.11a	100	5500	Front of Face	0	14.00	13.65	100.00	98.46	0.051	0.056	20.8	3
	120	5600			14.00	13.35	100.00	98.46	0.040	0.047	21.1	
	140	5700			14.00	12.65	100.00	98.46	0.033	0.045	21.2	

*1 The burst averaged power values are used for power scaling since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 Reported SAR (W/kg) = Measured SAR (W/kg) * Duty cycle scaling factor * Tune-up scaling factor

where;

Duty cycle scaling factor = Max. possible duty cycle (%) / Measured duty cycle used for the SAR measurement (%)

Tune-up scaling factor = Max. possible power (mW) (* equal to 100% duty cycle) / Measured power used for the SAR measurement (mW)

Wi-Fi 5 GHz (W58: U-NII-3 Band)

Date : 2018/06/20 Measured by : Y. Kamiko
 Amb. Temp. : 22.4 deg. C Rel. hum. : 51.7 %RH

Mode	Ch.	Freq. (MHz)	Pos.	Dis. (mm)	Max. Poss. Power (dBm)	Meas. Power (dBm)	Max. Duty Cycle (%)	Meas. Duty Cycle (%)	Meas. 1-g SAR (W/kg)	Reported 1-g SAR (W/kg)	Liquid Temp. (deg. C)	Plot No.
802.11a	149	5745	Front of Face	0	14.00	13.22	100.00	98.46	0.035	0.043	22.4	4
	157	5785			14.00	13.06	100.00	98.46	0.021	0.026	22.1	
	165	5825			14.00	12.82	100.00	98.46	0.026	0.035	22.0	

*1 The burst averaged power values are used for power scaling since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 Reported SAR (W/kg) = Measured SAR (W/kg) * Duty cycle scaling factor * Tune-up scaling factor

where;

Duty cycle scaling factor = Max. possible duty cycle (%) / Measured duty cycle used for the SAR measurement (%)

Tune-up scaling factor = Max. possible power (mW) (* equal to 100% duty cycle) / Measured power used for the SAR measurement (mW)

<Extremity SAR>

Wi-Fi 2.4 GHz

Date : 2018/06/15 Measured by : S. Fukushima
 Amb. Temp. : 24.3 deg. C Rel. hum. : 57.0 %RH

Mode	Ch.	Freq. (MHz)	Pos.	Dis. (mm)	Max. Poss. Power (dBm)	Meas. Power (dBm)	Max. Duty Cycle (%)	Meas. Duty Cycle (%)	Meas. 10-g SAR (W/kg)	Reported 10-g SAR (W/kg)	Liquid Temp. (deg. C)	Plot No.								
Step 1: Worst Position Check																				
802.11b	1	2412	Top	0	13.50	13.38	100.00	99.69	0.262	0.270	23.1									
			Top-Left										13.50	13.38	100.00	99.69	0.199	0.205	23.0	
			Top-Right																	
Step 2: Worst Channel Check (for Step 1)																				
802.11b	1	2437	Top-Right	0	13.50	13.18	100.00	99.69	0.265	0.286	22.9									
	11	2462											13.50	13.19	100.00	99.69	0.254	0.274	22.9	

*1 The burst averaged power values are used for power scaling since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 Reported SAR (W/kg) = Measured SAR (W/kg) * Duty cycle scaling factor * Tune-up scaling factor

where:

Duty cycle scaling factor = Max. possible duty cycle (%) / Measured duty cycle used for the SAR measurement (%)

Tune-up scaling factor = Max. possible power (mW) (* equal to 100% duty cycle) / Measured power used for the SAR measurement (mW)

Wi-Fi 5 GHz (W53: U-NII-2A Band)

Date : 2018/06/17 Measured by : Y. Kamiko
 Amb. Temp. : 24.5 deg. C Rel. hum. : 58.4 %RH

Mode	Ch.	Freq. (MHz)	Pos.	Dis. (mm)	Max. Poss. Power (dBm)	Meas. Power (dBm)	Max. Duty Cycle (%)	Meas. Duty Cycle (%)	Meas. 10-g SAR (W/kg)	Reported 10-g SAR (W/kg)	Liquid Temp. (deg. C)	Plot No.								
Step 1: Worst Position Check																				
802.11a	52	5260	Top	0	14.00	13.79	100.00	98.46	0.399	0.425	22.9									
			Top-Left										14.00	13.79	100.00	98.46	0.285	0.304	23.0	
			Top-Right																	
Step 2: Worst Channel Check (for Step 1)																				
802.11a	56	5280	Top-Right	0	14.00	13.37	100.00	98.46	0.421	0.494	22.9	6								
	60	5300											14.00	13.72	100.00	98.46	0.417	0.452	22.8	
	64	5320											14.00	13.66	100.00	98.46	0.377	0.414	22.8	

*1 The burst averaged power values are used for power scaling since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 Reported SAR (W/kg) = Measured SAR (W/kg) * Duty cycle scaling factor * Tune-up scaling factor

where:

Duty cycle scaling factor = Max. possible duty cycle (%) / Measured duty cycle used for the SAR measurement (%)

Tune-up scaling factor = Max. possible power (mW) (* equal to 100% duty cycle) / Measured power used for the SAR measurement (mW)

Wi-Fi 5 GHz (W56: U-NII-2C Band)

Date : 2018/06/18 Measured by : S. Fukushima
 Amb. Temp. : 24.5 deg. C Rel. hum. : 58.4 %RH

Mode	Ch.	Freq. (MHz)	Pos.	Dis. (mm)	Max. Poss. Power (dBm)	Meas. Power (dBm)	Max. Duty Cycle (%)	Meas. Duty Cycle (%)	Meas. 10-g SAR (W/kg)	Reported 10-g SAR (W/kg)	Liquid Temp. (deg. C)	Plot No.
Step 1: Worst Position Check												
802.11a	100	5500	Top	0	14.00	13.65	100.00	98.46	0.389	0.428	23.9	
			Top-Left		14.00	13.65	100.00	98.46	0.289	0.318	23.8	
			Top-Right		14.00	13.65	100.00	98.46	0.486	0.535	24.1	7
Step 2: Worst Channel Check (for Step 1)												
802.11a	120	5600	Top-Right	0	14.00	13.35	100.00	98.46	0.305	0.360	23.9	
	140	5700			14.00	12.65	100.00	98.46	0.291	0.403	23.9	

*1 The burst averaged power values are used for power scaling since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 Reported SAR (W/kg) = Measured SAR (W/kg) * Duty cycle scaling factor * Tune-up scaling factor

where:

Duty cycle scaling factor = Max. possible duty cycle (%) / Measured duty cycle used for the SAR measurement (%)

Tune-up scaling factor = Max. possible power (mW) (* equal to 100% duty cycle) / Measured power used for the SAR measurement (mW)

Wi-Fi 5 GHz (W58: U-NII-3 Band)

Date : 2018/06/18 Measured by : S. Fukushima
 Amb. Temp. : 24.6 deg. C Rel. hum. : 62.0 %RH

Mode	Ch.	Freq. (MHz)	Pos.	Dis. (mm)	Max. Poss. Power (dBm)	Meas. Power (dBm)	Max. Duty Cycle (%)	Meas. Duty Cycle (%)	Meas. 10-g SAR (W/kg)	Reported 10-g SAR (W/kg)	Liquid Temp. (deg. C)	Plot No.
Step 1: Worst Position Check												
802.11a	149	5745	Top	0	14.00	13.22	100.00	98.46	0.247	0.300	23.3	
			Top-Left		14.00	13.22	100.00	98.46	0.237	0.288	23.3	
			Top-Right		14.00	13.22	100.00	98.46	0.257	0.312	23.4	
Step 2: Worst Channel Check (for Step 1)												
802.11a	157	5785	Top-Right	0	14.00	13.06	100.00	98.46	0.257	0.324	23.5	
	165	5825			14.00	12.82	100.00	98.46	0.353	0.470	23.5	8

*1 The burst averaged power values are used for power scaling since the maximum tune-up tolerance limits are defined as burst averaged values.

*2 Reported SAR (W/kg) = Measured SAR (W/kg) * Duty cycle scaling factor * Tune-up scaling factor

where:

Duty cycle scaling factor = Max. possible duty cycle (%) / Measured duty cycle used for the SAR measurement (%)

Tune-up scaling factor = Max. possible power (mW) (* equal to 100% duty cycle) / Measured power used for the SAR measurement (mW)

4.2. SAR Measurement Variability

According to KDB 865664 D01, additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.8 or 2 W/kg (1-g or 10-g respectively); steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.8 or 2 W/kg (1-g or 10-g respectively), repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 or 3.6 W/kg (~ 10% from the 1-g or 10-g respective SAR limit).
- 4) Perform a third repeated measurement only if the original, first, or second repeated measurement is ≥ 1.5 or 3.75 W/kg (1-g or 10-g respectively) and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

Freq. Band (MHz)	RF Exposure Conditions	Position	Highest Meas. SAR (W/kg)		Repeat SAR	Repeated Meas. SAR (W/kg)	Ratio of Largest to Smallest SAR
			1-g SAR	10-g SAR			
Wi-Fi 2.4 GHz	Head	Front of Face	1-g SAR	0.035	No	N/A	N/A
	Extremity	Top-Right	10-g SAR	0.323	No	N/A	N/A
Wi-Fi 5 GHz (W53:U-NII-2A)	Head	Front of Face	1-g SAR	0.055	No	N/A	N/A
	Extremity	Top-Right	10-g SAR	0.424	No	N/A	N/A
Wi-Fi 5 GHz (W56:U-NII-2C)	Head	Front of Face	1-g SAR	0.051	No	N/A	N/A
	Extremity	Top-Right	10-g SAR	0.486	No	N/A	N/A
Wi-Fi 5 GHz (W58:U-NII-3)	Head	Front of Face	1-g SAR	0.035	No	N/A	N/A
	Extremity	Top-Right	10-g SAR	0.353	No	N/A	N/A

Appendix A. Plots of SAR Measurement

Please see the following page(s).

Plot No. 1

Date: 2018/06/19

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Wi-Fi 2.4 GHz (1ch)_Head_Front of Face_0mm

DUT: FLE01WBM (installed in Head Mounted Display FL-E01)

Communication System: UID 0, Wi-Fi_802.11b_1Mbps (0);

Communication System Band: 2.4GHz; Frequency: 2412 MHz;

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.815$ S/m; $\epsilon_r = 39.426$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(7.56, 7.56, 7.56); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Wi-Fi 2.4GHz (1ch)_Head_Front of Face_0mm/

Area Scan (10x16x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.0484 W/kg

Configuration/Wi-Fi 2.4GHz (1ch)_Head_Front of Face_0mm/


Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 5.128 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.0590 W/kg

SAR(1 g) = 0.035 W/kg; SAR(10 g) = 0.021 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 0.0502 W/kg



Plot No. 2

Date: 2018/06/20

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Wi-Fi 5GHz (56ch)_Head_Front of Face_0mm

DUT: FLE01WBM (installed in Head Mounted Display FL-E01)

Communication System: UID 0, Wi-Fi_802.11a_6Mbps (0);

Communication System Band: 5GHz; Frequency: 5280 MHz;

Medium parameters used: $f = 5280$ MHz; $\sigma = 4.653$ S/m; $\epsilon_r = 35.754$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(5.61, 5.61, 5.61); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Wi-Fi 5GHz (56ch)_Head_Front of Face_0mm/

Area Scan (12x19x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.0987 W/kg

Configuration/Wi-Fi 5GHz (56ch)_Head_Front of Face_0mm/


Zoom Scan (10x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 4.620 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.218 W/kg

SAR(1 g) = 0.055 W/kg; SAR(10 g) = 0.020 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 0.122 W/kg



Plot No. 3

Date: 2018/06/20

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Wi-Fi 5GHz (100ch)_Head_Front of Face_0mm

DUT: FLE01WBM (installed in Head Mounted Display FL-E01)

Communication System: UID 0, Wi-Fi_802.11a_6Mbps (0);

Communication System Band: 5GHz; Frequency: 5500 MHz;

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.898$ S/m; $\epsilon_r = 34.617$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(5.06, 5.06, 5.06); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Wi-Fi 5GHz (100ch)_Head_Front of Face_0mm/

Area Scan (12x19x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.118 W/kg

Configuration/Wi-Fi 5GHz (100ch)_Head_Front of Face_0mm/


Zoom Scan (10x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 5.099 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.179 W/kg

SAR(1 g) = 0.0505 W/kg; SAR(10 g) = 0.018 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 0.116 W/kg



Plot No. 4

Date: 2018/06/20

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Wi-Fi 5GHz (149ch)_Head_Front of Face_0mm

DUT: FLE01WBM (installed in Head Mounted Display FL-E01)

Communication System: UID 0, Wi-Fi_802.11a_6Mbps (0);

Communication System Band: 5GHz; Frequency: 5745 MHz;

Medium parameters used: $f = 5745$ MHz; $\sigma = 5.159$ S/m; $\epsilon_r = 34.194$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(5.09, 5.09, 5.09); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Wi-Fi 5GHz (149ch)_Head_Front of Face_0mm/

Area Scan (12x19x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.0778 W/kg

Configuration/Wi-Fi 5GHz (149ch)_Head_Front of Face_0mm/


Zoom Scan (10x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 4.179 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.131 W/kg

SAR(1 g) = 0.035 W/kg; SAR(10 g) = 0.012 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 0.0860 W/kg



Plot No. 5

Date: 2018/06/15

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Wi-Fi 2.4GHz (1ch)_Extremity_Top-Right_0mm

DUT: FLE01WBM (installed in Head Mounted Display FL-E01)

Communication System: UID 0, Wi-Fi_802.11b_1Mbps (0);

Communication System Band: Wi-Fi 2.4GHz; Frequency: 2412 MHz;

Medium parameters used: $f = 2412$ MHz; $\sigma = 1.993$ S/m; $\epsilon_r = 52.042$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(7.78, 7.78, 7.78); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Wi-Fi 2.4GHz (1ch)_Extremity_Top-Right_0mm/

Area Scan (15x9x1): Measurement grid: $dx=12$ mm, $dy=12$ mm

Maximum value of SAR (measured) = 0.791 W/kg

Configuration/Wi-Fi 2.4GHz (1ch)_Extremity_Top-Right_0mm/


Zoom Scan (7x8x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20.63 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 2.44 W/kg

SAR(1 g) = 0.808 W/kg; **SAR(10 g) = 0.323 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 1.75 W/kg



Plot No. 6

Date: 2018/06/17

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Wi-Fi 5GHz (56ch)_Extremity_Top-Right_0mm

DUT: FLE01WBM (installed in Head Mounted Display FL-E01)

Communication System: UID 0, Wi-Fi_802.11a_6Mbps (0);

Communication System Band: 5GHz; Frequency: 5280 MHz;

Medium parameters used: $f = 5280$ MHz; $\sigma = 5.584$ S/m; $\epsilon_r = 47.856$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(5, 5, 5); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Wi-Fi 5GHz (56ch)_Extremity_Top-Right_0mm/

Area Scan (18x11x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 3.72 W/kg

Configuration/Wi-Fi 5GHz (56ch)_Extremity_Top-Right_0mm/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 28.66 V/m; Power Drift = -0.06 dB

Peak SAR (extrapolated) = 10.9 W/kg

SAR(1 g) = 1.7 W/kg; **SAR(10 g) = 0.421 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 4.96 W/kg



Plot No. 7

Date: 2018/06/18

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Wi-Fi 5GHz (100ch)_Extremity_Top-Right_0mm

DUT: FLE01WBM (installed in Head Mounted Display FL-E01)

Communication System: UID 0, Wi-Fi_802.11a_6Mbps (0);

Communication System Band: 5GHz; Frequency: 5500 MHz;

Medium parameters used: $f = 5500$ MHz; $\sigma = 5.711$ S/m; $\epsilon_r = 47.783$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(4.41, 4.41, 4.41); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Wi-Fi 5GHz (100ch)_Extremity_Top-Right_0mm/

Area Scan (18x11x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 3.28 W/kg

Configuration/Wi-Fi 5GHz (100ch)_Extremity_Top-Right_0mm/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 26.47 V/m; Power Drift = 0.18dB

Peak SAR (extrapolated) = 15.2 W/kg

SAR(1 g) = 2.2 W/kg; **SAR(10 g) = 0.486 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 6.90 W/kg



Plot No. 8

Date: 2018/06/18

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Wi-Fi 5GHz (165ch)_Extremity_Top-Right_0mm

DUT: FLE01WBM (installed in Head Mounted Display FL-E01)

Communication System: UID 0, Wi-Fi_802.11a_6Mbps (0);

Communication System Band: 5GHz; Frequency: 5825 MHz;

Medium parameters used: $f = 5825$ MHz; $\sigma = 6.179$ S/m; $\epsilon_r = 47.212$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(4.5, 4.5, 4.5); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Wi-Fi 5GHz (165ch)_Extremity_Top-Right_0mm/

Area Scan (18x11x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 2.94 W/kg

Configuration/Wi-Fi 5GHz (165ch)_Extremity_Top-Right_0mm/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 23.95 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 13.1 W/kg

SAR(1 g) = 1.73 W/kg; **SAR(10 g) = 0.353 W/kg** (SAR corrected for target medium)

Maximum value of SAR (measured) = 5.87 W/kg



Appendix B. Plots of System Check

Please see the following page(s).

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Validation_D2450_HSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 765

Communication System: UID 0, CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.843$ S/m; $\epsilon_r = 39.369$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(7.56, 7.56, 7.56); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

System Performance Check at Frequencies above 2 GHz/Validation D2450 HSL/

Area Scan (8x8x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 17.1 W/kg

System Performance Check at Frequencies above 2 GHz/Validation D2450 HSL/


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 112.4 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 28.6 W/kg

SAR(1 g) = 13.6 W/kg; SAR(10 g) = 6.27 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 22.9 W/kg



Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Validation_D5300_HSL

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: 1039

Communication System: UID 0, CW (0); Frequency: 5300 MHz

Medium parameters used: $f = 5300$ MHz; $\sigma = 4.675$ S/m; $\epsilon_r = 35.723$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(5.61, 5.61, 5.61); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

System Performance Check at Frequencies above 5 GHz/Validation D5300 HSL/

Area Scan (6x7x1): Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 18.2 W/kg

System Performance Check at Frequencies above 5 GHz/Validation D5300 HSL/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value = 68.04 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 34.9 W/kg

SAR(1 g) = 7.79 W/kg; SAR(10 g) = 2.19 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 20.1 W/kg



Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Validation_D5600_HSL

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: 1039

Communication System: UID 0, CW (0); Frequency: 5600 MHz

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.997$ S/m; $\epsilon_r = 34.46$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(4.97, 4.97, 4.97); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

System Performance Check at Frequencies above 5 GHz/Validation D5600 HSL/

Area Scan (6x7x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 17.9 W/kg

System Performance Check at Frequencies above 5 GHz/Validation D5600 HSL/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 68.59 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 36.4 W/kg

SAR(1 g) = 7.96 W/kg; SAR(10 g) = 2.25 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 20.7 W/kg



Date: 2018/06/20

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Validation_D5800_HSL

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: 1039

Communication System: UID 0, CW (0); Frequency: 5800 MHz

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.23$ S/m; $\epsilon_r = 34.102$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(5.09, 5.09, 5.09); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 25.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

System Performance Check at Frequencies above 5 GHz/Validation D5800 HSL/

Area Scan (6x7x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 17.2 W/kg

System Performance Check at Frequencies above 5 GHz/Validation D5800 HSL/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 67.27 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 36.7 W/kg

SAR(1 g) = 7.63 W/kg; SAR(10 g) = 2.15 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 20.2 W/kg



Date: 2018/06/15

Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Validation_D2450_MSL

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 765

Communication System: UID 0, CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.027$ S/m; $\epsilon_r = 51.988$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(7.78, 7.78, 7.78); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

System Performance Check at Frequencies above 2 GHz/Validation D2450 MSL/

Area Scan (8x8x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 15.0 W/kg

System Performance Check at Frequencies above 2 GHz/Validation D2450 MSL/


Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 104.3 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 26.7 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.11 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 21.7 W/kg



Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Validation_D5300_MSL

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: 1039

Communication System: UID 0, CW (0); Frequency: 5300 MHz

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.612$ S/m; $\epsilon_r = 47.822$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(5, 5, 5); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 29.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

System Performance Check at Frequencies above 5 GHz/Validation D5300 MSL/

Area Scan (6x7x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 17.5 W/kg

System Performance Check at Frequencies above 5 GHz/Validation D5300 MSL/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 61.31 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 33.3 W/kg

SAR(1 g) = 8.1 W/kg; SAR(10 g) = 2.3 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 19.3 W/kg



Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Validation_D5600_MSL

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: 1039

Communication System: UID 0, CW (0); Frequency: 5600 MHz

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.847$ S/m; $\epsilon_r = 47.623$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(4.25, 4.25, 4.25); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 29.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

System Performance Check at Frequencies above 5 GHz/Validation D5600 MSL/

Area Scan (6x7x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 18.7 W/kg

System Performance Check at Frequencies above 5 GHz/Validation D5600 MSL/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 61.99 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 35.1 W/kg

SAR(1 g) = 8.34 W/kg; SAR(10 g) = 2.38 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 20.1 W/kg



Test Laboratory: Sony Global Manufacturing & Operations Corporation EMC/ RF Test Laboratory Main Lab. 4th Site Shielded Room 2

Validation_D5800_MSL

DUT: Dipole 5GHz; Type: D5GHzV2; Serial: 1039

Communication System: UID 0, CW (0); Frequency: 5800 MHz

Medium parameters used: $f = 5800$ MHz; $\sigma = 6.138$ S/m; $\epsilon_r = 47.261$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY Configuration:

- Probe: EX3DV4 - SN3921; ConvF(4.5, 4.5, 4.5); Calibrated: 2017/10/23;
- Sensor-SurFace: 1.4mm (Mechanical SurFace Detection), $z = 1.0, 29.0$
- Electronics: DAE4 Sn610; Calibrated: 2018/01/10
- Phantom: SAM (20deg probe tilt) with CRP v5.0 FRONT; Type: QD000P40CD; Serial: TP:1852
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

System Performance Check at Frequencies above 5 GHz/Validation D5800 MSL/

Area Scan (6x7x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 17.0 W/kg

System Performance Check at Frequencies above 5 GHz/Validation D5800 MSL/


Zoom Scan (9x9x6)/Cube 0: Measurement grid: $dx=4$ mm, $dy=4$ mm, $dz=2$ mm

Reference Value = 58.35 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 34.6 W/kg

SAR(1 g) = 7.61 W/kg; SAR(10 g) = 2.15 W/kg (SAR corrected for target medium)

Maximum value of SAR (measured) = 18.7 W/kg



Appendix C. Calibration Certificate

C.1. E-Field Probe EX3DV4 (Serial No. 3921 / Control No. WA0002)

Please see the following pages.

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **SONY Global M&O (Vitec)**

Certificate No: **EX3-3921_Oct17**

CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3921**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-14.v4, QA CAL-23.v5, QA CAL-25.v6
Calibration procedure for dosimetric E-field probes**

Calibration date: **October 23, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02525)	Apr-18
Reference 20 dB Attenuator	SN: S5277 (20x)	07-Apr-17 (No. 217-02528)	Apr-18
Reference Probe ES3DV2	SN: 3013	31-Dec-16 (No. ES3-3013_Dec16)	Dec-17
DAE4	SN: 660	7-Dec-16 (No. DAE4-660_Dec16)	Dec-17
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

Calibrated by:	Name Leif Klysner	Function Laboratory Technician	Signature
Approved by:	Name Katja Pokovic	Function Technical Manager	Signature

Issued: October 25, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Certificate No: EX3-3921_Oct17

Page 1 of 11

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization θ	θ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., θ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- **NORM_{x,y,z}**: Assessed for E-field polarization θ = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- **NORM(f)_{x,y,z} = NORM_{x,y,z} * frequency_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- **DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- **PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- **A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}; A, B, C, D** are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- **ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- **Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- **Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- **Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

EX3DV4 – SN:3921

October 23, 2017

Probe EX3DV4

SN:3921

Manufactured: December 18, 2012
Calibrated: October 23, 2017

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

Certificate No: EX3-3921_Oct17

Page 3 of 11

EX3DV4- SN:3921

October 23, 2017

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3921

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.47	0.42	0.46	± 10.1 %
DCP (mV) ^B	106.7	97.3	102.4	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB√ μV	C	D dB	VR mV	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	144.0	±3.5 %
		Y	0.0	0.0	1.0		139.0	
		Z	0.0	0.0	1.0		142.3	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E²-field uncertainty inside TSL (see Pages 5 and 6).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

EX3DV4- SN:3921

October 23, 2017

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3921

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
750	41.9	0.89	10.70	10.70	10.70	0.37	1.01	± 12.0 %
835	41.5	0.90	10.16	10.16	10.16	0.46	0.80	± 12.0 %
900	41.5	0.97	9.98	9.98	9.98	0.46	0.80	± 12.0 %
1450	40.5	1.20	8.91	8.91	8.91	0.47	0.80	± 12.0 %
1750	40.1	1.37	8.84	8.84	8.84	0.36	0.80	± 12.0 %
1900	40.0	1.40	8.35	8.35	8.35	0.31	0.80	± 12.0 %
1950	40.0	1.40	8.16	8.16	8.16	0.38	0.80	± 12.0 %
2300	39.5	1.67	7.95	7.95	7.95	0.38	0.84	± 12.0 %
2450	39.2	1.80	7.56	7.56	7.56	0.28	0.98	± 12.0 %
2600	39.0	1.96	7.38	7.38	7.38	0.41	0.84	± 12.0 %
3500	37.9	2.91	7.31	7.31	7.31	0.28	1.20	± 13.1 %
5200	36.0	4.66	5.85	5.85	5.85	0.30	1.80	± 13.1 %
5300	35.9	4.76	5.61	5.61	5.61	0.30	1.80	± 13.1 %
5500	35.6	4.96	5.06	5.06	5.06	0.35	1.80	± 13.1 %
5600	35.5	5.07	4.97	4.97	4.97	0.35	1.80	± 13.1 %
5800	35.3	5.27	5.09	5.09	5.09	0.35	1.80	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3921

October 23, 2017

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3921

Calibration Parameter Determined in Body Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc (k=2)
2450	52.7	1.95	7.78	7.78	7.78	0.35	0.90	± 12.0 %
5200	49.0	5.30	5.21	5.21	5.21	0.35	1.90	± 13.1 %
5300	48.9	5.42	5.00	5.00	5.00	0.35	1.90	± 13.1 %
5500	48.6	5.65	4.41	4.41	4.41	0.40	1.90	± 13.1 %
5600	48.5	5.77	4.25	4.25	4.25	0.40	1.90	± 13.1 %
5800	48.2	6.00	4.50	4.50	4.50	0.40	1.90	± 13.1 %

^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

EX3DV4- SN:3921

October 23, 2017

Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)



EX3DV4- SN:3921

October 23, 2017

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM

f=1800 MHz,R22





Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

EX3DV4- SN:3921

October 23, 2017

Dynamic Range f(SAR_{head}) (TEM cell, f_{eval}= 1900 MHz)




Uncertainty of Linearity Assessment: ± 0.6% (k=2)

EX3DV4- SN:3921



October 23, 2017

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ (k=2)

EX3DV4- SN:3921

October 23, 2017

DASY/EASY - Parameters of Probe: EX3DV4 - SN:3921

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	123.1
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

C.2. System Validation Dipole D2450V2 (Serial No. 765 / Control No. WA0041)

Please see the following pages.

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **VGEL**

Certificate No: **D2450V2-765_May18**

CALIBRATION CERTIFICATE

Object: **D2450V2 - SN:765**

Calibration procedure(s): **QA CAL-05.v10
Calibration procedure for dipole validation kits above 700 MHz**

Calibration date: **May 16, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility, environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20K)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Reference Probe EX3DV4	SN: 7349	30-Dec-17 (No. EX3-7349_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: 0837480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: U537292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: U537390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Manu Seltz	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: May 17, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary:

TSL tissue simulating liquid
ConvF sensitivity in TSL / NORM x,y,z
N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.1
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	38.2 ± 6 %	1.85 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.1 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	51.4 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.04 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.9 W/kg ± 16.5 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	52.3 ± 6 %	1.99 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.6 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	49.8 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.84 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.2 W/kg ± 16.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	54.8 Ω + 6.0 jΩ
Return Loss	- 22.7 dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	50.3 Ω + 6.9 jΩ
Return Loss	- 23.2 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.156 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	August 10, 2004

DASY5 Validation Report for Head TSL

Date: 16.05.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:765

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.85$ S/m; $\epsilon_r = 38.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(7.88, 7.88, 7.88) @ 2450 MHz; Calibrated: 30.12.2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 115.3 V/m; Power Drift = -0.02 dB


Peak SAR (extrapolated) = 26.1 W/kg

SAR(1 g) = 13.1 W/kg; SAR(10 g) = 6.04 W/kg

Maximum value of SAR (measured) = 21.6 W/kg



Impedance Measurement Plot for Head TSL



DASY5 Validation Report for Body TSL

Date: 16.05.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:765

Communication System: UID 0 - CW; Frequency: 2450 MHz

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.99$ S/m; $\epsilon_r = 52.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN7349; ConvF(8.01, 8.01, 8.01) @ 2450 MHz; Calibrated: 30.12.2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 107.3 V/m; Power Drift = -0.07 dB

Peak SAR (extrapolated) = 25.2 W/kg

SAR(1 g) = 12.6 W/kg; SAR(10 g) = 5.84 W/kg

Maximum value of SAR (measured) = 20.6 W/kg



C.3. System Validation Dipole D5GHz V2 (Serial No. 1039 / Control No. WA0042)

Please see the following pages.

**Calibration Laboratory of
Schmid & Partner
Engineering AG**
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
S Service suisse d'étalonnage
C Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **VGEL**

Certificate No: **D5GHzV2-1039_Apr18**

CALIBRATION CERTIFICATE

Object **D5GHzV2 - SN:1039**

Calibration procedure(s) **QA CAL-22.v3
Calibration procedure for dipole validation kits between 3-6 GHz**

Calibration date: **April 17, 2018**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Reference Probe EX3DV4	SN: 3503	30-Dec-17 (No. EX3-3503_Dec17)	Dec-18
DAE4	SN: 601	26-Oct-17 (No. DAE4-601_Oct17)	Oct-18
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter EPM-442A	SN: GB37480704	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: US37292783	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
Power sensor HP 8481A	SN: MY41092317	07-Oct-15 (in house check Oct-16)	In house check: Oct-18
RF generator R&S SMT-06	SN: 100972	15-Jun-15 (in house check Oct-16)	In house check: Oct-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: April 18, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

TSL tissue simulating liquid
ConvF sensitivity in TSL / NORM x,y,z
N/A not applicable or not measured

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation:

- e) DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.10.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom V5.0	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy = 4.0 mm, dz = 1.4 mm	Graded Ratio = 1.4 (Z direction)
Frequency	5200 MHz ± 1 MHz 5250 MHz ± 1 MHz 5300 MHz ± 1 MHz 5500 MHz ± 1 MHz 5600 MHz ± 1 MHz 5800 MHz ± 1 MHz	

Head TSL parameters at 5200 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	36.0	4.66 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	36.4 ± 6 %	4.56 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5200 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.04 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.5 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.30 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.0 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.71 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	36.3 ± 6 %	4.61 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5250 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.36 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	83.7 W / kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.41 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.1 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5300 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.76 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	36.2 ± 6 %	4.66 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5300 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.37 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	83.8 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.41 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.1 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.6	4.96 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.9 ± 6 %	4.87 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5500 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.66 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	86.7 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.47 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.7 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.8 ± 6 %	4.98 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.67 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	86.8 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.48 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.8 W/kg ± 19.5 % (k=2)

Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.3	5.27 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	35.5 ± 6 %	5.19 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C	----	----

SAR result with Head TSL at 5800 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	100 mW input power	8.30 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	83.0 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	condition	
SAR measured	100 mW input power	2.37 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.7 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5200 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	49.0	5.30 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.2 ± 6 %	5.44 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5200 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.15 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	71.0 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.01 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	19.9 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5300 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.9	5.42 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	47.0 ± 6 %	5.57 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5300 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.74 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	76.8 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.18 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.6 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.6	5.65 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.7 ± 6 %	5.85 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5500 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	8.07 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	80.2 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.25 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.3 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.5	5.77 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.5 ± 6 %	5.98 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	8.05 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	79.9 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.26 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	22.4 W/kg ± 19.5 % (k=2)

Body TSL parameters at 5800 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	48.2	6.00 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	46.1 ± 6 %	6.26 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C	----	----

SAR result with Body TSL at 5800 MHz

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	100 mW input power	7.63 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	75.8 W/kg ± 19.9 % (k=2)

SAR averaged over 10 cm ³ (10 g) of Body TSL	condition	
SAR measured	100 mW input power	2.14 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.2 W/kg ± 19.5 % (k=2)

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters with Head TSL at 5200 MHz

Impedance, transformed to feed point	49.6 Ω - 9.8 jΩ
Return Loss	- 20.1 dB

Antenna Parameters with Head TSL at 5250 MHz

Impedance, transformed to feed point	51.3 Ω - 7.3 jΩ
Return Loss	- 22.7 dB

Antenna Parameters with Head TSL at 5300 MHz

Impedance, transformed to feed point	51.6 Ω - 3.2 jΩ
Return Loss	- 29.0 dB

Antenna Parameters with Head TSL at 5500 MHz

Impedance, transformed to feed point	49.1 Ω - 2.1 jΩ
Return Loss	- 32.9 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance, transformed to feed point	54.5 Ω - 3.7 jΩ
Return Loss	- 25.1 dB

Antenna Parameters with Head TSL at 5800 MHz

Impedance, transformed to feed point	57.0 Ω + 0.4 jΩ
Return Loss	- 23.7 dB

Antenna Parameters with Body TSL at 5200 MHz

Impedance, transformed to feed point	50.2 Ω - 9.5 jΩ
Return Loss	- 20.5 dB

Antenna Parameters with Body TSL at 5300 MHz

Impedance, transformed to feed point	52.2 Ω - 1.6 jΩ
Return Loss	- 31.3 dB

Antenna Parameters with Body TSL at 5500 MHz

Impedance, transformed to feed point	49.4 Ω - 1.8 jΩ
Return Loss	- 34.5 dB

Antenna Parameters with Body TSL at 5600 MHz

Impedance, transformed to feed point	56.1 Ω - 2.9 jΩ
Return Loss	- 24.0 dB

Antenna Parameters with Body TSL at 5800 MHz

Impedance, transformed to feed point	57.4 Ω + 0.7 jΩ
Return Loss	- 23.2 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.199 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
Manufactured on	December 30, 2005

DASY5 Validation Report for Head TSL

Date: 17.04.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1039

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5250 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200$ MHz; $\sigma = 4.56$ S/m; $\epsilon_r = 36.4$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5250$ MHz; $\sigma = 4.61$ S/m; $\epsilon_r = 36.3$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5300$ MHz; $\sigma = 4.66$ S/m; $\epsilon_r = 36.2$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5500$ MHz; $\sigma = 4.87$ S/m; $\epsilon_r = 35.9$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5600$ MHz; $\sigma = 4.98$ S/m; $\epsilon_r = 35.8$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5800$ MHz; $\sigma = 5.19$ S/m; $\epsilon_r = 35.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.75, 5.75, 5.75); Calibrated: 30.12.2017, ConvF(5.51, 5.51, 5.51); Calibrated: 30.12.2017, ConvF(5.5, 5.5, 5.5); Calibrated: 30.12.2017, ConvF(5.2, 5.2, 5.2); Calibrated: 30.12.2017, ConvF(5.05, 5.05, 5.05); Calibrated: 30.12.2017, ConvF(4.96, 4.96, 4.96); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (front); Type: QD 000 P50 AA; Serial: 1001
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 68.88 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 28.7 W/kg

SAR(1 g) = 8.04 W/kg; SAR(10 g) = 2.3 W/kg

Maximum value of SAR (measured) = 18.2 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5250 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 71.82 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 28.8 W/kg

SAR(1 g) = 8.36 W/kg; SAR(10 g) = 2.41 W/kg


Maximum value of SAR (measured) = 18.7 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5300 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
 Reference Value = 71.35 V/m; Power Drift = -0.03 dB
 Peak SAR (extrapolated) = 30.4 W/kg
 SAR(1 g) = 8.37 W/kg; SAR(10 g) = 2.41 W/kg
 Maximum value of SAR (measured) = 19.1 W/kg


Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
 Reference Value = 70.90 V/m; Power Drift = -0.08 dB
 Peak SAR (extrapolated) = 33.4 W/kg
 SAR(1 g) = 8.66 W/kg; SAR(10 g) = 2.47 W/kg
 Maximum value of SAR (measured) = 20.0 W/kg

Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
 Reference Value = 71.23 V/m; Power Drift = -0.03 dB
 Peak SAR (extrapolated) = 32.8 W/kg
 SAR(1 g) = 8.67 W/kg; SAR(10 g) = 2.48 W/kg
 Maximum value of SAR (measured) = 20.1 W/kg


Dipole Calibration for Head Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan, dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm
 Reference Value = 69.87 V/m; Power Drift = -0.05 dB
 Peak SAR (extrapolated) = 32.5 W/kg
 SAR(1 g) = 8.3 W/kg; SAR(10 g) = 2.37 W/kg
 Maximum value of SAR (measured) = 19.6 W/kg



Impedance Measurement Plot for Head TSL (5200, 5300, 5500, 5600, 5800 MHz)



Impedance Measurement Plot for Head TSL (5250, 5600 MHz)



DASY5 Validation Report for Body TSL

Date: 16.04.2018

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1039

Communication System: UID 0 - CW; Frequency: 5200 MHz, Frequency: 5300 MHz, Frequency: 5500 MHz, Frequency: 5600 MHz, Frequency: 5800 MHz

Medium parameters used: $f = 5200$ MHz; $\sigma = 5.44$ S/m; $\epsilon_r = 47.2$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5300$ MHz; $\sigma = 5.57$ S/m; $\epsilon_r = 47$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5500$ MHz; $\sigma = 5.85$ S/m; $\epsilon_r = 46.7$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5600$ MHz; $\sigma = 5.98$ S/m; $\epsilon_r = 46.5$; $\rho = 1000$ kg/m³,

Medium parameters used: $f = 5800$ MHz; $\sigma = 6.26$ S/m; $\epsilon_r = 46.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY52 Configuration:

- Probe: EX3DV4 - SN3503; ConvF(5.35, 5.35, 5.35); Calibrated: 30.12.2017, ConvF(5.15, 5.15, 5.15); Calibrated: 30.12.2017, ConvF(4.7, 4.7, 4.7); Calibrated: 30.12.2017, ConvF(4.65, 4.65, 4.65); Calibrated: 30.12.2017, ConvF(4.53, 4.53, 4.53); Calibrated: 30.12.2017;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 26.10.2017
- Phantom: Flat Phantom 5.0 (back); Type: QD 000 P50 AA; Serial: 1002
- DASY52 52.10.0(1446); SEMCAD X 14.6.10(7417)

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5200 MHz/Zoom Scan,

dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.64 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 26.6 W/kg

SAR(1 g) = 7.15 W/kg; SAR(10 g) = 2.01 W/kg

Maximum value of SAR (measured) = 16.5 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5300 MHz 2/Zoom Scan,

dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.66 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 30.0 W/kg

SAR(1 g) = 7.74 W/kg; SAR(10 g) = 2.18 W/kg

Maximum value of SAR (measured) = 18.3 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5500 MHz/Zoom Scan,

dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 66.17 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 33.1 W/kg

SAR(1 g) = 8.07 W/kg; SAR(10 g) = 2.25 W/kg

Maximum value of SAR (measured) = 19.3 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5600 MHz/Zoom Scan,

dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 65.58 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 33.7 W/kg

SAR(1 g) = 8.05 W/kg; SAR(10 g) = 2.26 W/kg

Dipole Calibration for Body Tissue/Pin=100mW, dist=10mm, f=5800 MHz/Zoom Scan,


dist=1.4mm (8x8x7)/Cube 0: Measurement grid: dx=4mm, dy=4mm, dz=1.4mm

Reference Value = 63.54 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 33.1 W/kg

SAR(1 g) = 7.63 W/kg; SAR(10 g) = 2.14 W/kg

Maximum value of SAR (measured) = 18.7 W/kg



Impedance Measurement Plot for Body TSL (5200, 5300, 5500, 5600, 5800 MHz)

