

SONY

Sony EMCS EMC/RF Test Laboratory Main Lab.
8-4 Shiomi Kisarazu City, Chiba Pref., 292-0834 Japan

RF Evaluation Exemption

Date: May 1, 2015

FCC ID : AK8NWA20
Applicant: Sony Corporation

To whom it may concern,

We, Sony EMCS EMC/RF Test Laboratory Main Lab., hereby declare that Digital Media Player, model: NW-A25, NW-A26, and NW-A27 (FCC ID: AK8NWA20) of Sony Corporation is exempt from RF exposure SAR evaluation, as its output power meets the exclusion limits, stated in FCC Part 2 §2.1093.

According to KDB 447498 D01 (v05r02), section 4.3.1:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

For above devices, $f = 2.48$ GHz, distance = 5mm (the min. separation distance is < 5 mm), and the max. power of channel including tune-up tolerance is 8 mW.

Therefore,

$$8 / 5 * (\sqrt{2.48}) = 2.5 < 3.0$$

and no SAR evaluation is required.

Thank you for your attention to this matter.

Sincerely,



Teruki Kurihara
Technical Manager
EMC/ RF Test Laboratory Main Lab.
Design Technology Division
Sony EMCS Corporation