




<b>System / software:</b>	SARA2 / 2.54 VPM coloc	<b>Input Power Drift:</b>	
<b>Date / Time:</b>	10/30/2009 2:06:39 PM	<b>DUT Battery Model/No:</b>	
<b>Filename:</b>	GSM 1909_with case.txt	<b>Probe Serial Number:</b>	M0024
<b>Ambient Temperature:</b>	21.5°C	<b>Liquid Simulant:</b>	850
<b>Device Under Test:</b>	Sony	<b>Relative Permittivity:</b>	53.84
<b>Relative Humidity:</b>	36.1%	<b>Conductivity:</b>	1.019
<b>Phantom S/No:</b>	Head04_37.csv	<b>Liquid Temperature:</b>	20.5°C
<b>Phantom Rotation:</b>	0°	<b>Max SAR X-axis Location:</b>	-20.00 mm
<b>DUT Position:</b>	Accessory Cover	<b>Max SAR Y-axis Location:</b>	5.00 mm
<b>Antenna Configuration:</b>	Integral	<b>Max E Field:</b>	22.61 V/m
<b>Test Frequency:</b>	848.8MHz	<b>SAR 1g:</b>	0.479 W/kg
<b>Air Factors:</b>	2573 / 2262 / 2365	<b>SAR 10g:</b>	
<b>Conversion Factors:</b>	.395 / .395 / .395	<b>SAR Start:</b>	0.125 W/kg
<b>Type of Modulation:</b>		<b>SAR End:</b>	0.131 W/kg
<b>Modn. Duty Cycle:</b>		<b>SAR Drift during Scan:</b>	2.84 %
<b>Diode Compression Factors (V*200):</b>	20 / 20 / 20	<b>Probe battery last changed:</b>	10/19/09
<b>Input Power Level:</b>	2 uplink timeslots	<b>Extrapolation:</b>	poly4




<b>System / software:</b>	SARA2 / 2.54 VPM coloc	<b>Input Power Drift:</b>	
<b>Date / Time:</b>	11/23/2009 2:14:41 PM	<b>DUT Battery Model/No:</b>	
<b>Filename:</b>	FDD5.txt	<b>Probe Serial Number:</b>	M0024
<b>Ambient Temperature:</b>	21.5°C	<b>Liquid Simulant:</b>	850
<b>Device Under Test:</b>	Sony ebook	<b>Relative Permittivity:</b>	54.1
<b>Relative Humidity:</b>	33.8%	<b>Conductivity:</b>	1.01
<b>Phantom S/No:</b>	Head04_37.csv	<b>Liquid Temperature:</b>	20.5°C
<b>Phantom Rotation:</b>	180°	<b>Max SAR X-axis Location:</b>	-18.00 mm
<b>DUT Position:</b>	accessory cover	<b>Max SAR Y-axis Location:</b>	-2.00 mm
<b>Antenna Configuration:</b>	Integral	<b>Max E Field:</b>	13.64 V/m
<b>Test Frequency:</b>	836.6MHz	<b>SAR 1g:</b>	0.264 W/kg
<b>Air Factors:</b>	2573 / 2262 / 2365	<b>SAR 10g:</b>	
<b>Conversion Factors:</b>	.395 / .395 / .395	<b>SAR Start:</b>	0.063 W/kg
<b>Type of Modulation:</b>		<b>SAR End:</b>	0.065 W/kg
<b>Modn. Duty Cycle:</b>		<b>SAR Drift during Scan:</b>	3.40 %
<b>Diode Compression Factors (V*200):</b>	20 / 20 / 20	<b>Probe battery last changed:</b>	11/20/09
<b>Input Power Level:</b>	All bits up	<b>Extrapolation:</b>	poly4




<b>System / software:</b>	SARA2 / 2.54 VPM	<b>Input Power Drift:</b>	
<b>System / software:</b>	SARA2 / 2.54 VPM coloc	<b>Input Power Drift:</b>	
<b>Date / Time:</b>	10/30/2009 1:14:51 PM	<b>DUT Battery Model/No:</b>	
<b>Filename:</b>	GSM 1880_with case.txt	<b>Probe Serial Number:</b>	M0024
<b>Ambient Temperature:</b>	21.5°C	<b>Liquid Simulant:</b>	1900
<b>Device Under Test:</b>	Sony	<b>Relative Permittivity:</b>	52.2
<b>Relative Humidity:</b>	36.1%	<b>Conductivity:</b>	1.55
<b>Phantom S/No:</b>	Head04_37.csv	<b>Liquid Temperature:</b>	20.5°C
<b>Phantom Rotation:</b>	0°	<b>Max SAR X-axis Location:</b>	-6.00 mm
<b>DUT Position:</b>	Accessory Cover	<b>Max SAR Y-axis Location:</b>	3.00 mm
<b>Antenna Configuration:</b>	Integral	<b>Max E Field:</b>	20.30 V/m
<b>Test Frequency:</b>	1909.8MHz	<b>SAR 1g:</b>	0.794 W/kg
<b>Air Factors:</b>	2573 / 2262 / 2365	<b>SAR 10g:</b>	
<b>Conversion Factors:</b>	.476 / .476 / .476	<b>SAR Start:</b>	0.062 W/kg
<b>Type of Modulation:</b>		<b>SAR End:</b>	0.064 W/kg
<b>Modn. Duty Cycle:</b>		<b>SAR Drift during Scan:</b>	3.27 %
<b>Diode Compression Factors (V*200):</b>	20 / 20 / 20	<b>Probe battery last changed:</b>	10/19/09
<b>Input Power Level:</b>	2 uplink timeslots	<b>Extrapolation:</b>	poly4




<b>System / software:</b>	SARA2 / 2.54 VPM coloc	<b>Input Power Drift:</b>	
<b>Date / Time:</b>	11/23/2009 3:04:39 PM	<b>DUT Battery Model/No:</b>	
<b>Filename:</b>	FDD2.txt	<b>Probe Serial Number:</b>	M0024
<b>Ambient Temperature:</b>	21.5°C	<b>Liquid Simulant:</b>	1900
<b>Device Under Test:</b>	Sony ebook	<b>Relative Permittivity:</b>	51.97
<b>Relative Humidity:</b>	33.8%	<b>Conductivity:</b>	1.458
<b>Phantom S/No:</b>	Head04_37.csv	<b>Liquid Temperature:</b>	20.5°C
<b>Phantom Rotation:</b>	180°	<b>Max SAR X-axis Location:</b>	-12.00 mm
<b>DUT Position:</b>	accessory cover	<b>Max SAR Y-axis Location:</b>	8.00 mm
<b>Antenna Configuration:</b>	Integral	<b>Max E Field:</b>	17.78 V/m
<b>Test Frequency:</b>	1852.6MHz	<b>SAR 1g:</b>	0.621 W/kg
<b>Air Factors:</b>	2573 / 2262 / 2365	<b>SAR 10g:</b>	
<b>Conversion Factors:</b>	.476 / .476 / .476	<b>SAR Start:</b>	0.148 W/kg
<b>Type of Modulation:</b>		<b>SAR End:</b>	0.148 W/kg
<b>Modn. Duty Cycle:</b>		<b>SAR Drift during Scan:</b>	-0.06 %
<b>Diode Compression Factors (V*200):</b>	20 / 20 / 20	<b>Probe battery last changed:</b>	11/20/09
<b>Input Power Level:</b>	All bits up	<b>Extrapolation:</b>	poly4




<b>System / software:</b>	SARA2 / 2.54 VPM	<b>Input Power Drift:</b>	
<b>System / software:</b>	SARA2 / 2.54 VPM coloc	<b>Input Power Drift:</b>	
<b>Date / Time:</b>	10/30/2009 1:48:41 PM	<b>DUT Battery Model/No:</b>	
<b>Filename:</b>	temp.txt	<b>Probe Serial Number:</b>	M0024
<b>Ambient Temperature:</b>	21.5°C	<b>Liquid Simulant:</b>	850
<b>Device Under Test:</b>	System	<b>Relative Permittivity:</b>	54.07
<b>Relative Humidity:</b>	36.1%	<b>Conductivity:</b>	1.012
<b>Phantom S/No:</b>	Head04_37.csv	<b>Liquid Temperature:</b>	20.5°C
<b>Phantom Rotation:</b>	0°	<b>Max SAR X-axis Location:</b>	6.00 mm
<b>DUT Position:</b>	15mm	<b>Max SAR Y-axis Location:</b>	3.00 mm
<b>Antenna Configuration:</b>	Dipole	<b>Max E Field:</b>	88.71 V/m
<b>Test Frequency:</b>	835MHz	<b>SAR 1g:</b>	9.551 W/kg
<b>Air Factors:</b>	2573 / 2262 / 2365	<b>SAR 10g:</b>	6.366 W/kg
<b>Conversion Factors:</b>	.395 / .395 / .395	<b>SAR Start:</b>	2.401 W/kg
<b>Type of Modulation:</b>		<b>SAR End:</b>	2.505 W/kg
<b>Modn. Duty Cycle:</b>		<b>SAR Drift during Scan:</b>	4.34 %
<b>Diode Compression Factors (V*200):</b>	20 / 20 / 20	<b>Probe battery last changed:</b>	10/19/09
<b>Input Power Level:</b>	1W	<b>Extrapolation:</b>	poly4



<b>System / software:</b>	SARA2 / 2.54 VPM coloc	<b>Input Power Drift:</b>	
<b>Date / Time:</b>	10/30/2009 12:13:17 PM	<b>DUT Battery Model/No:</b>	
<b>Filename:</b>	temp.txt	<b>Probe Serial Number:</b>	M0024
<b>Ambient Temperature:</b>	21.5°C	<b>Liquid Simulant:</b>	1900
<b>Device Under Test:</b>	System	<b>Relative Permittivity:</b>	52.24
<b>Relative Humidity:</b>	36.1%	<b>Conductivity:</b>	1.484
<b>Phantom S/No:</b>	Head04_37.csv	<b>Liquid Temperature:</b>	20.5°C
<b>Phantom Rotation:</b>	0°	<b>Max SAR X-axis Location:</b>	0.00 mm
<b>DUT Position:</b>	10mm	<b>Max SAR Y-axis Location:</b>	0.00 mm
<b>Antenna Configuration:</b>	Dipole	<b>Max E Field:</b>	145.58 V/m
<b>Test Frequency:</b>	1880MHz	<b>SAR 1g:</b>	38.911 W/kg
<b>Air Factors:</b>	2573 / 2262 / 2365	<b>SAR 10g:</b>	20.313 W/kg
<b>Conversion Factors:</b>	.476 / .476 / .476	<b>SAR Start:</b>	5.382 W/kg
<b>Type of Modulation:</b>		<b>SAR End:</b>	5.567 W/kg
<b>Modn. Duty Cycle:</b>		<b>SAR Drift during Scan:</b>	3.43 %
<b>Diode Compression Factors (V*200):</b>	20 / 20 / 20	<b>Probe battery last changed:</b>	10/19/09
<b>Input Power Level:</b>	1W	<b>Extrapolation:</b>	poly4



<b>System / software:</b>	SARA2 / 2.54 VPM coloc	<b>Input Power Drift:</b>	
<b>Date / Time:</b>	11/23/2009 8:42:29 AM	<b>DUT Battery Model/No:</b>	
<b>Filename:</b>	Right Touch_1880_baseline.txt	<b>Probe Serial Number:</b>	M0024
<b>Ambient Temperature:</b>	21.5°C	<b>Liquid Simulant:</b>	850
<b>Device Under Test:</b>	System	<b>Relative Permittivity:</b>	54.1
<b>Relative Humidity:</b>	33.8%	<b>Conductivity:</b>	1.01
<b>Phantom S/No:</b>	Head04_37.csv	<b>Liquid Temperature:</b>	20.5°C
<b>Phantom Rotation:</b>	180°	<b>Max SAR X-axis Location:</b>	0.00 mm
<b>DUT Position:</b>	15mm	<b>Max SAR Y-axis Location:</b>	-4.80 mm
<b>Antenna Configuration:</b>	Dipole	<b>Max E Field:</b>	88.38 V/m
<b>Test Frequency:</b>	835MHz	<b>SAR 1g:</b>	9.653 W/kg
<b>Air Factors:</b>	2573 / 2262 / 2365	<b>SAR 10g:</b>	6.359 W/kg
<b>Conversion Factors:</b>	.395 / .395 / .395	<b>SAR Start:</b>	2.362 W/kg
<b>Type of Modulation:</b>		<b>SAR End:</b>	2.359 W/kg
<b>Modn. Duty Cycle:</b>		<b>SAR Drift during Scan:</b>	-0.12 %
<b>Diode Compression Factors (V*200):</b>	20 / 20 / 20	<b>Probe battery last changed:</b>	11/20/09
<b>Input Power Level:</b>	1W	<b>Extrapolation:</b>	poly4



<b>System / software:</b>	SARA2 / 2.54 VPM coloc	<b>Input Power Drift:</b>	
<b>Date / Time:</b>	11/23/2009 9:27:13 AM	<b>DUT Battery Model/No:</b>	
<b>Filename:</b>	1880_lap.txt	<b>Probe Serial Number:</b>	M0024
<b>Ambient Temperature:</b>	21.2°C	<b>Liquid Simulant:</b>	1900
<b>Device Under Test:</b>	System	<b>Relative Permittivity:</b>	52.06
<b>Relative Humidity:</b>	54.2%	<b>Conductivity:</b>	1.51
<b>Phantom S/No:</b>	Head04_37.csv	<b>Liquid Temperature:</b>	20.7°C
<b>Phantom Rotation:</b>	0°	<b>Max SAR X-axis Location:</b>	-1.50 mm
<b>DUT Position:</b>	10mm	<b>Max SAR Y-axis Location:</b>	6.75 mm
<b>Antenna Configuration:</b>	dipole	<b>Max E Field:</b>	142.73 V/m
<b>Test Frequency:</b>	1900MHz	<b>SAR 1g:</b>	38.472 W/kg
<b>Air Factors:</b>	2573 / 2262 / 2365	<b>SAR 10g:</b>	20.358 W/kg
<b>Conversion Factors:</b>	.476 / .476 / .476	<b>SAR Start:</b>	5.153 W/kg
<b>Type of Modulation:</b>		<b>SAR End:</b>	5.201 W/kg
<b>Modn. Duty Cycle:</b>		<b>SAR Drift during Scan:</b>	0.94 %
<b>Diode Compression Factors (V*200):</b>	20 / 20 / 20	<b>Probe battery last changed:</b>	11/20/09
<b>Input Power Level:</b>	1W	<b>Extrapolation:</b>	poly4

