

Test Laboratory: JAPAN QUALITY ASSURANCE ORGANIZATION

File Name: [Flat_high_left_1M.da4](#)

Body-worn 11ch (2462MHz) - Left back (with Headphone)

DUT: Portable Game; Type: PSP; Serial: 00-27400000-0000100

Program: Flat

Communication System: WLAN; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: M2450 ($\sigma = 1.956 \text{ mho/m}$, $\epsilon_r = 53.19$, $\rho = 1000 \text{ kg/m}^3$)

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ET3DV6 - SN1678; ConvF(4.39, 4.39, 4.39); Calibrated: 2004/02/15
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn508; Calibrated: 2004/02/06
- Phantom: SAM 1194; Type: QD 000 P40 CA; Serial: 1194
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

Body-worn/Area Scan (9x9x1): Measurement grid: dx=10mm, dy=10mm

Reference Value = 2.86 V/m

Power Drift = 0.002 dB

Maximum value of SAR = 0.25 mW/g

Body-worn/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Peak SAR (extrapolated) = 0.574 W/kg

SAR(1 g) = 0.238 mW/g; SAR(10 g) = 0.0979 mW/g

Reference Value = 2.86 V/m

Power Drift = 0.002 dB

Maximum value of SAR = 0.262 mW/g

