

Maximum Permissive Exposure

FCC ID: AK8SAWSC40 System Name: Sound Bar[Active Speaker System: SA-SC40; Active Subwoofer: SA-WSC40] M/N: HT-SC40 EUT: Active Subwoofer M/N: SA-WSC40

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure											
Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time							
(MHz)	Strength (V/m)	Strength (A/m)	(mW/cm^2)	(Minutes)							
(A) Limits for Occupational / Control Exposures (f = frequency)											
30-300	61.4 0.163		1.0	6							
300-1500			f/300	6							
1500-100,000			5.0	6							
(B) Limits for General Population / Uncontrolled Exposures (f = frequency)											
30-300	27.5	0.073	0.2	30							
300-1500			f/1500	30							
1500-100,000			1.0	30							

Table 1 Limits for M . ъ .

Tel: 0755 26639496 Fax: 0755 26632877

2. MPE Calculation

KYE SYSTEMS CORP. declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

RF Exposure Calculations: S = (P * G) / (4* π * r^2) or r = $\sqrt{(P * G) / (4 * \pi * S)}$

2.1. Estimation Result

Test Mode	Frequency (MHz)	Por	Peak Output Power (dBm)		Peak Output Power (mW)		Antenna Gain (dBi)		Antenna Gain (Linear)		MPE	
		ANT A	ANT B	ANT A	ANT B	ANT A	ANT B	ANT A	ANT B	ANT A	ANT B	
GFSK	2404	6.409	6.232	4.37	4.20	2.95	2.95	1.97	1.97	0.00172	0.00165	
	2440	6.665	6.556	4.64	4.52	2.95	2.95	1.97	1.97	0.00182	0.00178	
	2476	6.580	6.556	4.55	4.52	2.95	2.95	1.97	1.97	0.00179	0.00178	

Based on safety distance (r) **20cm**, the power density (S) is **0.00182mW/cm²**.