

RADIO TEST REPORT

(for Bluetooth Low Energy)

Project No. : JB-Z0497
 Client : Sony Corporation
 Client's Address : 1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan
 Product Name : Wireless Noise Canceling Stereo Headset
 Model No. : WF-1000XM3 (Left part:WF-1000XM3L, Right part:WF-1000XM3R)
 FCC ID : AK8WF1000XM3
 Test Standard : 47 CFR Part 15 Subpart C
 Sample Receipt Date : January 10, 2019
 Test Date : January 24, 2019 to March 6, 2019
 Report Date : March 14, 2019
 Test Result : Complied

Notice:

- * These test results relate only to the items (combination equipment, test configuration, operation condition etc.) tested.
- * This report shall not be reproduced except in full, without written approval of the laboratory.
- * This report must not be used by the client to claim product endorsement by A2LA or any agency of the U.S.
- * Hereby certify that no party is subject to a denial of federal benefits pursuant to section 5301 of the Anti-Drug Abuse Act.
- * All test results are traceable to the national and /or international standards.
- * The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in Sony Global Manufacturing & Operations Corporation EMC/RF Test Laboratory.

Reported by:



Takanori Oho
 Technical Manager
 EMC/RF Test Laboratory, Main Lab.
 Design Technology Division

Approved Signatory:



Teruki Kurihara
 Technical Manager
 EMC/RF Test Laboratory, Main Lab.
 Design Technology Division



Format No.: NV1-1-01 Version 5.0

Sony Global Manufacturing & Operations Corporation EMC/RF Test Laboratory, Main Lab.

A2LA Cert. #3203.01

8-4 Shiomi Kisarazu-shi Chiba-ken, 292-0834, Japan
PHONE +81 438 37 2750 FAX +81 438 371021

TABLE OF CONTENTS

1.	General Information.....	3
1.1.	Description of Equipment Under Test (EUT).....	3
1.2.	Summary of Test Result.....	4
1.3.	Tested Methodology	5
1.4.	Measurement Procedures	5
1.5.	Test Location.....	8
1.6.	Uncertainty	8
2.	Test Specification.....	9
2.1.	Validation	9
2.2.	Operating Condition.....	9
2.3.	Special Accessories	9
2.4.	EUT Modifications	9
2.5.	Configuration of EUT System.....	10
3.	Test Data.....	12
3.1.	6dB Bandwidth.....	12
3.2.	Maximum Peak Conducted Output Power.....	14
3.3.	Power Spectral Density	15
3.4.	Radiated Spurious Emissions.....	17
3.5.	Conducted Spurious Emissions for Band Edge.....	58
4.	Method of Calculation	59
4.1.	Maximum Peak Conducted Output Power.....	59
4.2.	Power Spectral Density	59
4.3.	Radiated Spurious Emissions.....	60
4.4.	Conducted Spurious Emissions for Band Edge.....	60
5.	List of Test Equipment.....	61
5.1.	Antenna-port Conducted Measurements.....	61
5.2.	Radiated Spurious Emissions.....	61
6.	Photographs of test setup.....	62
6.1.	Antenna-port Conducted Measurements Photo(s)	62
6.2.	Radiated Spurious Emissions Photo(s).....	63

Note

- indicates that the listed condition, standard or equipment is applicable for this report.
-indicates that the listed condition, standard or equipment is not applicable for this report.

Revision History

Revision	Date	Overview	Page
JB-Z0497 (Original)	March 14, 2019	-	-

1. General Information

1.1. Description of Equipment Under Test (EUT)

General Specification

Test Sample Condition : Prototype Pre-production Mass-production
Product Name : Wireless Noise Canceling Stereo Headset
Trade Name : SONY
Model No. : WF-1000XM3 (Left part:WF-1000XM3L, Right part:WF-1000XM3R)
Serial No. : L3, L4, L5
Power Rating of the EUT : DC 3.7 V (The EUT was supplied with the power from built-in battery)
Software Ver. : 1.00

Similar model(s) to be covered by this report

Model No. : WF-1000XM3L (Left part), WF-1000XM3R (Right part)
* RF characteristics of left and right part are the same.

Radio Specification

Function of the Equipment : Transceiver
Operating Frequency : 2402 - 2480 MHz
Modulation Type : GFSK
Channel Spacing : 2 MHz
Channel Bandwidth : 1 MHz, 2 MHz
Number of channels : 40
Antenna Type : Dipole Pattern Antenna
Antenna Connector Type : None
Antenna Gain : -1.0 dBi
Operating Temperature : +0 to +40 deg.C

1.2. Summary of Test Result

Test Item	Worst Margin	Results	Note
AC Power-line Conducted Emissions	-	N/A	*2
6dB Bandwidth	Refer to the test data	Complied	-
Maximum Peak Conducted Output Power	27.31 dB	Complied	-
Power Spectral Density	21.45 dB	Complied	-
Radiated Spurious Emissions	9.9 dB (AV) 4960.000 MHz Vertical	Complied	-
Conducted Spurious Emissions for Band Edge	11.22 dB 2400.00 MHz	Complied	*1

Note

- *1: Conducted Spurious Emissions measurement was tested for the only frequencies in the non-restricted carrier band edges, since the spurious emissions in other non-restricted band were complied with Radiated Spurious Emissions measurement.
- *2: This item was not applied to the EUT since its transmission is stopped when the battery is being charged by the PC connected to AC Power-line.

Other requirements

- Part 15.31(e) Supply voltage requirement
: Complied (The EUT was tested with a new battery)
- Part 15.203 / 212 Antenna requirement
: Complied (The EUT has an internal antenna which cannot be replaced by users)

1.3. Tested Methodology

Test Standard : 47 CFR Part15 Subpart C
 Test Method : ANSI C63.10 - 2013
 KDB 558074 D01 15.247 Meas Guidance v05r01

Test Condition

Radiated Spurious Emissions

Test Distance : 3 m 10m (9 kHz to 30 MHz)
 3 m 10m (30 MHz to 1000 MHz)
 3 m (1 GHz to 26.5 GHz)

Dimensions of the EUT table : 0.8 m (below 1 GHz) or 1.5 m (above 1 GHz) height, 2 m width and 1 m depth.

1.4. Measurement Procedures

We performed the measurements in accordance with NV3-06, available upon the request.

- No deviation
- Deviation from the above procedure

The summary of the above procedure is mentioned below

Antenna-port Conducted Measurements

1. Antenna-port of the EUT was connected to the power sensor (Maximum Peak Conducted Output Power) or the spectrum analyzer. (other test items).
2. For each EUT operation mode, the Antenna-port Conducted Measurements were measured with the power sensor or the spectrum analyzer.

Test Item	Detector	RBW
Antenna-port Conducted Measurements		
6dB Bandwidth	Peak	100 kHz
Maximum Peak Conducted Output Power	Peak	-
Power Spectral Density	Peak	3 kHz
Conducted Spurious Emissions for Band Edge	Peak	100 kHz

Radiated Spurious Emissions

- The non-conductive table (EUT table) made of (FRP, Styrene Foam, other non-conductive material) was placed in the center of the turntable.
- The EUT was placed on the center of the tabletop.
- The test antenna was placed away from the EUT at test distance.
- The limits were compensated the distance factor with follows:
 $9 \text{ kHz to } 490 \text{ kHz [Limit at 3 m]} = [\text{Limit at 300 m}] + 40\log(300[\text{m}] / 3[\text{m}])$
 $490 \text{ kHz to } 30 \text{ MHz [Limit at 3 m]} = [\text{Limit at 30 m}] + 40\log(30[\text{m}] / 3[\text{m}])$
- Find the worst arrangement of the EUT according to follows:
 - Rotating the turntable and/ or scanning the antenna.
 - On every condition, exploring the highest emissions with the spectrum analyzer. (9 kHz to 26.5 GHz, peak detector)
- On the worst arrangement of the EUT found in above, choose the six highest harmonics or spurious emissions on the spectrum data.(*excluding carrier band edges)
 The final measurements of all test operating modes carried out on these emissions as follows:

The test antenna and the turntable were performed with follows;

	9 kHz to 30 MHz	30 MHz to 1000 MHz	1 GHz to 26.5 GHz
Antenna	Loop Antenna	Bi-conical Antenna, Log-periodic Antenna	Horn Antenna
Antenna scanning range	1 m, Vertical, 360 degrees	1 m to 4 m, Horizontal and Vertical	1 m to 4 m *, Horizontal and Vertical
Turntable rotating range	360 degrees	360 degrees	360 degrees

*: When the measurement frequencies above 1 GHz, final measurements are performed keeping the antenna in the "cone of radiation" from EUT area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.

Instruments settings were carried out with follows;

	9 kHz to 90 kHz 110 kHz to 490 kHz	90 kHz to 110 kHz 490 kHz to 30 MHz	30 MHz to 1000 MHz	1 GHz to 26.5 GHz
Detector	Peak / Average	Quasi-peak	Quasi-peak	Peak / Average
RBW	200 Hz (6 dB) or 9 kHz (6 dB) *1	200 Hz (6 dB) or 9 kHz (6 dB) *1	120 kHz (6 dB)	1 MHz (6 dB)
VBW	N/A	N/A	N/A	3 MHz (for peak) 10 kHz (for average) *2
Instrument	EMI test receiver	EMI test receiver	EMI test receiver	Spectrum analyzer

*1: When the measurement frequencies below 150 kHz, RBW: 200 Hz was used.

*2: VBW setting (for average) was higher than 1/T. (T is the minimum transmission duration)

7. If the final measurement result exceeded the limit in non-restricted band(excluding carrier band edges), the measurement is carried out additionally with follows;

Measurement points

- Fundamental Frequency
- Frequency that exceeded the limit in non-restricted band (excluding carrier band edges)

	9 kHz to 150 kHz	150 kHz to 30 MHz	30 MHz to 26.5 GHz
Detector	Peak	Peak	Peak
RBW	300 Hz (6 dB) *	10 kHz (6 dB) *	100 kHz (6 dB)
Instrument	Spectrum analyzer	Spectrum analyzer	Spectrum analyzer

*: Correction factor of RBW was compensated to a measurement result by the following formula.

$$\text{C.F. of RBW [dB]} = 10 \cdot \log(100 \text{ kHz} / \text{used RBW})$$

8. If the final average measurement result exceeded the limit in the authorized band edge, the integration method is carried out with follows;

	2.4835 GHz to 2.4855 GHz
Detector	Peak
RBW	100 kHz (6 dB)
Instrument	Spectrum analyzer
Function	Channel Power (integration BW : 1 MHz)

9. Although these tests were performed other than open field area test site, adequate comparison measurements were confirmed against 30 m open field area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788 D01.

1.5. Test Location

Test Facility Name : Sony Global Manufacturing & Operations Corporation
EMC/RF Test Laboratory, Main Lab.
Address : 8-4 Shiomi Kisarazu-shi, Chiba-ken, 292-0834, Japan
Phone : +81 438 37 2750

A2LA Certificate No. : 3203.01
Cert. Validated Date : Oct. 31, 2019

Antenna-port Conducted Measurements

Shielded Room

 4th Site SR1Radiated Spurious Emissions

Semi-Anechoic chamber

 4th Site EMC Site**1.6. Uncertainty**

Test Item	Frequency	4th Site SR1
Maximum Conducted Output Power	1 GHz to 6 GHz	± 0.84 dB
Power Spectral Density, Conducted Spurious Emissions	below 6 GHz	± 1.25 dB

Test Item	Frequency	Distance	4th Site	EMC Site
AC Power-line Conducted Emissions	150 kHz to 30 MHz	-	± 3.34 dB	± 3.35 dB
Radiated Emissions	9 kHz to 30 MHz	3m	± 2.60 dB	± 3.13 dB
	30 MHz to 1000 MHz	3m	± 4.96 dB	± 5.26 dB
	1 GHz to 18 GHz	3m	± 5.22 dB	± 5.50 dB
	18 GHz to 26.5 GHz	3m	± 5.36 dB	± 5.63 dB

2. Test Specification

2.1. Validation

The system was configured for testing in a typical (as a customer would normally use it).
The tests were conducted with the worst-case modes as follows.

2.2. Operating Condition

The tests have been carried out the following conditions.

[Transmitting mode]

Test Items	Test Channels	Data Rate
Radiated Spurious Emissions (below 1GHz) *1	2480 MHz	1 Mbps
6dB Bandwidth, Maximum Conducted Output Power, Power Spectral Density, Radiated Spurious Emissions (above 1GHz)	2402 MHz 2440 MHz 2480 MHz	1 Mbps 2 Mbps
Conducted Spurious Emissions for Band Edge	2402 MHz	1 Mbps 2 Mbps

Note

*1: The test was performed with the representative mode that had been found as the worst emissions while exploratory testing.

The Software for Operating Mode

Software Name : MT2811S_BT_Test
Software Version : V0.09

2.3. Special Accessories

Special accessories needed for connecting the EUT to achieve compliance:

Item	Manufacturer	Model No.	Serial No.	Remark
-	-	-	-	-

2.4. EUT Modifications

- No equipment modification to achieve compliance to the standard levels was done during the tests.
 Equipment was modified to achieve compliance to the standard level as below.

Responsible Party Signature

Typed/ Print Name :
Responsible Party :
Position :
Date :

2.5. Configuration of EUT System

Antenna-port Conducted Measurements


[EUT and Associated Equipment (AE)]

Symbol	EUT/AE	Item	Manufacturer	Model No.	Serial No.
A	EUT	Wireless Noise Canceling Stereo Headset	SONY	WF-1000XM3L	L4
B	AE	Personal Computer	SONY	PCG-4121AN	27547114 1000852
C	AE	AC Adapter	SONY	VPG-AC19C37	0099484
D	AE	JIG Board	CSR	CNS10020V5A	343455
E	AE	Regulated DC Power Supply	KENWOOD	PW18-1.3AT	08046429

[Type of Cable]

Symbol	Description	Identification (Manufacturer etc.)	Shielded Yes / No	Ferrite Core	Length (m)	Bundled
1	DC Cable	-	No	No	1.8	-
2	AC Cable	-	No	No	0.8	-
3	JIG Cable	-	No	No	0.2	-
4	USB Cable	ELECOM	Yes	No	1.0	-
5	DC Cable	-	No	No	1.8	-
6	AC Cable	-	No	No	0.9	-

[Connecting Diagram]



Radiated Spurious Emissions


[EUT and Associated Equipment (AE)]

Symbol	EUT/AE	Item	Manufacturer	Model No.	Serial No.
A	EUT	Wireless Noise Canceling Stereo Headset	SONY	WF-1000XM3L	L3
B	EUT	Wireless Noise Canceling Stereo Headset	SONY	WF-1000XM3L	L5

[Type of Cable]

Symbol	Description	Identification (Manufacturer etc.)	Shielded Yes / No	Ferrite Core	Length (m)	Bundled
-	-	-	-	-	-	-

[Connecting Diagram]




3. Test Data

3.1. 6dB Bandwidth

- 1) Ambient temperature : 21.5 deg.C
- 2) Relative humidity : 39.0 %
- 3) Date of measurement : 31 January 2019
- 4) Measured by : M.KOUGA
- 5) Operating mode : Transmitting mode

Mode	Rate [Mbps]	Channel [MHz]	Result [MHz]	Limit [MHz]
BLE	1	2402	0.713	0.5
		2440	0.713	0.5
		2480	0.713	0.5
	2	2402	1.248	0.5
		2440	1.249	0.5
		2480	1.251	0.5

[1 Mbps / 2402 MHz]




[1 Mbps / 2440 MHz]




[1 Mbps / 2480 MHz]




[2 Mbps / 2402 MHz]



[2 Mbps / 2442 MHz]



[2 Mbps / 2480 MHz]



3.2. Maximum Peak Conducted Output Power

- 1) Ambient temperature : 20.4 deg.C
- 2) Relative humidity : 30.8 %
- 3) Date of measurement : 24 January 2019
- 4) Measured by : M.KOUGA
- 5) Operating mode : Transmitting mode

Maximum Peak Conducted Output Power

Mode	Rate [Mbps]	Channel [MHz]	Reading(PK) [dBm]	C.F. [dB]	Result(PK) [dBm]	Result(PK) [W]	Limit [dBm]	Margin [dB]
BLE	1	2402	1.33	0.80	2.13	0.00163	30.0	27.87
		2440	1.64	0.80	2.44	0.00175	30.0	27.56
		2480	1.88	0.80	2.68	0.00185	30.0	27.32
	2	2402	1.30	0.80	2.10	0.00162	30.0	27.90
		2440	1.65	0.80	2.45	0.00176	30.0	27.55
		2480	1.89	0.80	2.69	0.00186	30.0	27.31

Maximum Average Conducted Output Power (for SAR measurement)


Mode	Rate [Mbps]	Channel [MHz]	Reading(AV) [dBm]	C.F. [dB]	Duty Factor [dB]	Result(AV) [dBm]	Result(AV) [W]
BLE	1	2402	-1.21	0.80	2.23	1.82	0.00152
		2440	-0.87	0.80	2.23	2.16	0.00164
		2480	-0.61	0.80	2.23	2.42	0.00175
	2	2402	-4.13	0.80	5.15	1.82	0.00152
		2440	-3.79	0.80	5.15	2.16	0.00164
		2480	-3.53	0.80	5.15	2.42	0.00175

3.3. Power Spectral Density


- 1) Ambient temperature : 21.5 deg.C
 2) Relative humidity : 39.0 %
 3) Date of measurement : January 31, 2019
 4) Measured by : M.KOUGA
 5) Operating mode : Transmitting mode

Mode	Rate [Mbps]	Channel [MHz]	Reading(PK) [dBm]	C.F. [dB]	Result(PK) [dBm]	Limit [dBm]	Margin [dB]
BLE	1	2402	-15.20	1.10	-14.10	8.0	22.10
		2440	-14.81	1.10	-13.71	8.0	21.71
		2480	-14.55	1.10	-13.45	8.0	21.45
	2	2402	-17.61	1.10	-16.51	8.0	24.51
		2440	-17.20	1.10	-16.10	8.0	24.10
		2480	-16.96	1.10	-15.86	8.0	23.86


[1 Mbps / 2402 MHz]




[1 Mbps / 2440 MHz]




[1 Mbps / 2480 MHz]




[2 Mbps / 2402 MHz]



[2 Mbps / 2440 MHz]



[2 Mbps / 2480 MHz]




3.4. Radiated Spurious Emissions

1) Date of measurement

9 kHz to 30 MHz	: March 6, 2019	(all mode)
30 MHz to 1000 MHz	: March 6, 2019	(all mode)
1 GHz to 6 GHz	: February 6, 2019	(all mode)
	February 6, 2019 to February 7, 2019	(band edge plot data)
6 GHz to 18 GHz	: February 7, 2019	(all mode)
18 GHz to 26.5 GHz	: February 8, 2019	(all mode)

The test data is mentioned as follows.

9 kHz to 30 MHz
 [1 Mbps / 2480 MHz]




Final Result

--- Vertical Polarization (QP)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	0.847	24.2	19.7	43.9	69.1	25.2	100.0	221.8

30 MHz to 1000 MHz
 [1 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (QP)---

No.	Frequency [MHz]	Reading [dB(μV)]	c.f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	940.383	19.4	1.2	20.6	46.0	25.4	143.0	221.6

--- Vertical Polarization (QP)---

No.	Frequency [MHz]	Reading [dB(μV)]	c.f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	937.703	19.7	1.1	20.8	46.0	25.2	172.6	81.7

1 GHz to 6 GHz
[1 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2390.000	37.6	2.7	40.3	54.0	13.7	109.6	256.2
2	4804.000	31.9	10.9	42.8	54.0	11.2	100.0	121.7
3	5520.398	30.7	11.6	42.3	54.0	11.7	205.4	308.3

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2166.047	37.3	1.8	39.1	54.0	14.9	304.9	159.7
2	2390.000	37.6	2.7	40.3	54.0	13.7	100.0	38.1
3	4804.000	31.8	10.9	42.7	54.0	11.3	172.4	309.4

[1 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (AV) ---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	4880.000	31.3	11.0	42.3	54.0	11.7	151.9	336.7
2	5591.704	30.5	11.9	42.4	54.0	11.6	100.0	328.0

--- Vertical Polarization (AV) ---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	4880.000	32.8	11.0	43.8	54.0	10.2	171.0	29.2
2	5426.402	31.5	11.7	43.2	54.0	10.8	227.6	144.1

[1 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2483.500	37.4	3.1	40.5	54.0	13.5	143.6	170.5
2	4960.000	31.9	11.3	43.2	54.0	10.8	100.0	123.1
3	5386.298	31.5	11.5	43.0	54.0	11.0	290.0	81.7

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2483.500	37.7	3.1	40.8	54.0	13.2	132.6	266.5
2	4960.000	32.8	11.3	44.1	54.0	9.9	121.7	34.1
3	5362.726	31.2	11.4	42.6	54.0	11.4	100.0	359.4

[1 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2390.000	47.9	2.7	50.6	74.0	23.4	108.5	255.0
2	4804.000	40.7	10.9	51.6	74.0	22.4	123.7	117.8
3	5529.145	41.0	11.7	52.7	74.0	21.3	205.4	306.4

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2165.749	47.2	1.8	49.0	74.0	25.0	304.9	157.8
2	2390.000	47.1	2.7	49.8	74.0	24.2	100.0	48.7
3	4804.000	41.0	10.9	51.9	74.0	22.1	172.4	309.4

[1 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	4880.000	40.4	11.0	51.4	74.0	22.6	152.0	335.7
2	5595.434	39.8	11.9	51.7	74.0	22.3	100.0	333.6

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	4880.000	41.9	11.0	52.9	74.0	21.1	172.5	39.8
2	5414.249	41.1	11.6	52.7	74.0	21.3	231.7	149.8

[1 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2483.500	47.8	3.1	50.9	74.0	23.1	147.4	163.3
2	4960.000	41.9	11.3	53.2	74.0	20.8	100.0	121.2
3	5391.644	40.7	11.6	52.3	74.0	21.7	297.0	70.0

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2483.500	48.0	3.1	51.1	74.0	22.9	133.2	267.0
2	4960.000	42.1	11.3	53.4	74.0	20.6	121.7	34.1
3	5353.067	40.7	11.3	52.0	74.0	22.0	100.0	5.5

[2 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2390.000	37.5	2.7	40.2	54.0	13.8	129.1	75.6
2	4804.000	31.3	10.9	42.2	54.0	11.8	131.1	29.3
3	5439.346	30.9	11.7	42.6	54.0	11.4	190.3	225.4

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2390.000	37.2	2.7	39.9	54.0	14.1	130.3	127.1
2	4804.000	30.8	10.9	41.7	54.0	12.3	100.0	151.0
3	5447.023	30.8	11.7	42.5	54.0	11.5	190.7	353.0

[2 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (AV) ---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	4880.000	31.1	11.0	42.1	54.0	11.9	131.7	143.3
2	5446.196	30.7	11.7	42.4	54.0	11.6	377.5	94.2

--- Vertical Polarization (AV) ---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	4880.000	31.6	11.0	42.6	54.0	11.4	117.0	47.2
2	5429.289	30.9	11.7	42.6	54.0	11.4	192.2	33.3

[2 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2483.500	37.6	3.1	40.7	54.0	13.3	251.7	4.9
2	4960.000	31.4	11.3	42.7	54.0	11.3	100.0	122.0
3	5070.704	30.3	11.7	42.0	54.0	12.0	244.0	84.2

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2483.500	37.6	3.1	40.7	54.0	13.3	219.0	317.9
2	4960.000	32.3	11.3	43.6	54.0	10.4	100.0	47.5
3	5374.268	30.7	11.5	42.2	54.0	11.8	130.8	100.9

[2 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2390.000	47.6	2.7	50.3	74.0	23.7	129.1	77.6
2	4804.000	40.2	10.9	51.1	74.0	22.9	131.1	27.4
3	5438.768	40.4	11.7	52.1	74.0	21.9	190.3	227.4

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2390.000	48.2	2.7	50.9	74.0	23.1	130.3	128.5
2	4804.000	40.4	10.9	51.3	74.0	22.7	101.0	153.0
3	5447.707	40.4	11.7	52.1	74.0	21.9	190.7	353.0

[2 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	4880.000	40.9	11.0	51.9	74.0	22.1	131.7	141.3
2	5447.027	41.0	11.7	52.7	74.0	21.3	377.5	94.2

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	4880.000	40.3	11.0	51.3	74.0	22.7	117.0	49.3
2	5428.612	41.9	11.7	53.6	74.0	20.4	192.2	35.1

[2 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c.f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2483.500	48.7	3.1	51.8	74.0	22.2	251.7	4.9
2	4960.000	40.8	11.3	52.1	74.0	21.9	100.0	120.1
3	5068.692	40.3	11.7	52.0	74.0	22.0	244.0	82.3

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c.f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	2483.500	47.3	3.1	50.4	74.0	23.6	219.0	319.8
2	4960.000	41.2	11.3	52.5	74.0	21.5	100.0	49.5
3	5362.855	40.3	11.4	51.7	74.0	22.3	130.8	98.9

6 GHz to 18 GHz
[1 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7211.822	42.3	-7.6	34.7	54.0	19.3	285.4	53.9
2	9607.565	39.4	-6.0	33.4	54.0	20.6	118.6	84.0
3	17622.592	34.6	6.4	41.0	54.0	13.0	100.0	332.2

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7205.523	42.9	-7.6	35.3	54.0	18.7	119.4	101.9
2	17625.638	34.9	6.4	41.3	54.0	12.7	211.1	359.1

[1 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	9759.734	38.8	-5.5	33.3	54.0	20.7	104.2	66.7
2	17316.448	35.0	4.6	39.6	54.0	14.4	296.0	200.2

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7320.614	41.4	-7.8	33.6	54.0	20.4	233.0	83.1
2	17593.484	34.8	6.4	41.2	54.0	12.8	325.2	235.1

[1 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	9919.686	38.1	-4.8	33.3	54.0	20.7	100.0	12.9
2	17617.370	34.8	6.4	41.2	54.0	12.8	161.7	250.4

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7440.000	42.0	-7.9	34.1	54.0	19.9	382.6	136.0
2	17621.744	34.5	6.4	40.9	54.0	13.1	431.0	35.4

[1 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μ V)]	c. f [dB(1/m)]	Result [dB(μ V/m)]	Limit [dB(μ V/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7206.000	52.0	-7.6	44.4	74.0	29.6	285.4	53.2
2	9608.217	49.5	-6.0	43.5	74.0	30.5	105.5	82.0
3	17621.774	45.8	6.4	52.2	74.0	21.8	106.0	337.5

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μ V)]	c. f [dB(1/m)]	Result [dB(μ V/m)]	Limit [dB(μ V/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7205.764	52.0	-7.6	44.4	74.0	29.6	119.0	106.0
2	17633.822	44.2	6.4	50.6	74.0	23.4	221.7	12.6

[1 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	9759.141	48.2	-5.5	42.7	74.0	31.3	103.2	56.5
2	17316.244	44.6	4.6	49.2	74.0	24.8	296.0	200.2

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7320.622	52.7	-7.8	44.9	74.0	29.1	233.0	83.1
2	17596.310	45.8	6.4	52.2	74.0	21.8	325.2	233.2

[1 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	9920.705	47.1	-4.8	42.3	74.0	31.7	100.2	14.3
2	17621.596	44.8	6.4	51.2	74.0	22.8	161.7	255.1

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7440.000	51.5	-7.9	43.6	74.0	30.4	339.9	116.6
2	17621.538	44.6	6.4	51.0	74.0	23.0	100.0	2.0

[2 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μ V)]	c. f [dB(1/m)]	Result [dB(μ V/m)]	Limit [dB(μ V/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7206.000	42.1	-7.6	34.5	54.0	19.5	177.7	101.8
2	17641.594	34.5	6.3	40.8	54.0	13.2	431.8	26.2

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μ V)]	c. f [dB(1/m)]	Result [dB(μ V/m)]	Limit [dB(μ V/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7206.000	42.1	-7.6	34.5	54.0	19.5	213.0	59.6
2	17626.108	34.5	6.4	40.9	54.0	13.1	230.4	256.5

[2 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7320.000	41.0	-7.8	33.2	54.0	20.8	413.6	181.7
2	17598.148	35.1	6.4	41.5	54.0	12.5	115.8	248.9

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7320.000	42.5	-7.8	34.7	54.0	19.3	332.0	209.0
2	17559.012	34.5	6.2	40.7	54.0	13.3	373.6	358.0

[2 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7440.000	41.8	-7.9	33.9	54.0	20.1	321.9	266.8
2	17645.848	34.8	6.3	41.1	54.0	12.9	360.8	159.8

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7440.000	42.5	-7.9	34.6	54.0	19.4	205.4	296.9
2	17544.198	34.4	6.1	40.5	54.0	13.5	221.6	334.9

[2 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7206.000	51.6	-7.6	44.0	74.0	30.0	177.7	101.8
2	17648.880	44.7	6.3	51.0	74.0	23.0	431.8	28.2

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7206.000	52.3	-7.6	44.7	74.0	29.3	214.9	58.1
2	17650.504	44.0	6.3	50.3	74.0	23.7	230.4	258.6

[2 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7320.000	51.8	-7.8	44.0	74.0	30.0	413.6	183.6
2	17599.630	44.2	6.4	50.6	74.0	23.4	115.8	246.9

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7320.000	50.8	-7.8	43.0	74.0	31.0	332.0	211.1
2	17558.482	44.3	6.2	50.5	74.0	23.5	373.6	358.0

[2 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7440.000	52.1	-7.9	44.2	74.0	29.8	321.9	264.9
2	17645.030	43.9	6.3	50.2	74.0	23.8	360.8	159.8

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	7440.000	51.5	-7.9	43.6	74.0	30.4	205.4	294.9
2	17600.690	44.0	6.4	50.4	74.0	23.6	221.6	332.9

18 GHz to 26.5 GHz
 [1 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19216.000	38.7	-0.8	37.9	54.0	16.1	207.4	81.3

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	24020.000	41.0	-2.3	38.7	54.0	15.3	405.5	267.0

[1 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19520.000	38.6	-0.8	37.8	54.0	16.2	381.1	88.3

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	24400.000	40.5	-2.6	37.9	54.0	16.1	134.5	323.1

[1 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19840.000	38.5	-0.9	37.6	54.0	16.4	162.3	135.6

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	22320.000	39.6	-2.0	37.6	54.0	16.4	281.9	119.6

[1 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19216.000	47.8	-0.8	47.0	74.0	27.0	207.4	79.4

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	24020.000	50.4	-2.3	48.1	74.0	25.9	398.0	272.9

[1 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19520.000	48.7	-0.8	47.9	74.0	26.1	358.1	122.9

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	24400.000	50.1	-2.6	47.5	74.0	26.5	130.8	324.6

[1 Mbps / 2480 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19840.000	48.1	-0.9	47.2	74.0	26.8	162.3	135.2

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	22320.000	49.8	-2.0	47.8	74.0	26.2	271.1	135.2

[2 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	24020.000	40.3	-2.3	38.0	54.0	16.0	172.2	213.4

--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19216.000	38.5	-0.8	37.7	54.0	16.3	140.1	55.4

[2 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19520.000	38.6	-0.8	37.8	54.0	16.2	220.8	249.9


--- Vertical Polarization (AV)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	21960.000	39.5	-2.0	37.5	54.0	16.5	266.3	220.4

[2 Mbps / 2480 MHz]



[2 Mbps / 2402 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	24020.000	50.0	-2.3	47.7	74.0	26.3	166.0	219.6

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19216.000	47.8	-0.8	47.0	74.0	27.0	133.1	64.2

[2 Mbps / 2440 MHz]



Final Result


--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19520.000	48.1	-0.8	47.3	74.0	26.7	214.7	257.9

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	21960.000	49.4	-2.0	47.4	74.0	26.6	257.7	234.1

[2 Mbps / 2480 MHz]



Final Result

--- Horizontal Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	22320.000	49.1	-2.0	47.1	74.0	26.9	124.1	232.9

--- Vertical Polarization (PK)---

No.	Frequency [MHz]	Reading [dB(μV)]	c. f [dB(1/m)]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]	Height [cm]	Angle [°]
1	19840.000	48.3	-0.9	47.4	74.0	26.6	359.2	112.3


2.4 GHz Restricted-Band Edge (Plot data)

These plot data show peak (trace blue) and average (trace black) spectrum for worst case emissions in the restricted-band edges. (Restricted band edges: below 2390 MHz and above 2483.5 MHz)


The result of the final radiated spurious emissions measurement refers in previous pages.

[1 Mbps / 2402 MHz]

Horizontal




Vertical




[1 Mbps / 2480 MHz]

Horizontal




Vertical




[2 Mbps / 2402 MHz]

Horizontal



Date: 6.FEB.2019 22:34:36


Vertical



Date: 6.FEB.2019 22:47:29


[2 Mbps / 2442 MHz]

Horizontal



Date: 7.FEB.2019 00:45:21

Vertical




Date: 7.FEB.2019 00:59:26

3.5. Conducted Spurious Emissions for Band Edge


- 1) Ambient temperature : 20.4 deg.C
- 2) Relative humidity : 30.8 %
- 3) Date of measurement : January 24, 2019
- 4) Measured by : M.KOUGA
- 5) Operating mode : Transmitting mode

Mode	Rate [Mbps]	Channel [MHz]	Frequency [MHz]	Reading(PK) [dBm]	C.F. [dB]	Result [dBm]	Limit [dBm]	Margin [dB]
BLE	1	2402	2401.99	-0.39	1.10	0.71	-	-
			2399.96	-59.17	1.10	-58.07	-19.3	38.78
	2	2402	2401.99	-0.89	1.10	0.21	-	-
			2400.00	-32.11	1.10	-31.01	-19.8	11.22

[1 Mbps / 2402 MHz]



[2 Mbps / 2402 MHz]



4. Method of Calculation

4.1. Maximum Peak Conducted Output Power

Method of calculation : Software
Software Name : SW-0316
Software Version : Ver.2

Test Result (PK) [dBm] = Meter Reading [dBm] + C.F. [dB]

Test Result (AV) [dBm] = Meter Reading [dBm] + C.F. [dB] + Duty Factor [dB]

Note (a) Meter Reading : Reading of the power meter
(b) C.F. : System Cable Loss + EUT Cable Loss
(c) Duty Factor : $10\log \{(\text{Tx ON Time} + \text{Tx OFF Time}) / (\text{Tx ON Time})\}$

4.2. Power Spectral Density

Method of calculation : Software
Software Name : SW-0316
Software Version : Ver.2

Test Result [dBm] = Meter Reading [dBm] + C.F. [dB]

Note (a) Meter Reading : Reading of the spectrum analyzer
(b) C.F. : System Cable Loss + EUT Cable Loss

4.3. Radiated Spurious Emissions

Method of calculation : Software
Software Name : V-Scan
Software Version : Ver.4.0.30

Test Result [dBuV/ m] = Meter Reading [dBuV] + C.F. [dB/ m]

Note (a) Meter Reading : Reading of the EMI test receiver or the spectrum analyzer.
(b) C.F. : Antenna Factor (including Balun Loss) + System GainLoss
: Antenna Factor (including Balun Loss) + System GainLoss + 20 log (3 m/ 10 m)

4.4. Conducted Spurious Emissions for Band Edge

Method of calculation : Software
Software Name : SW-0316
Software Version : Ver.2

Test Result [dBm] = Meter Reading [dBm] + C.F. [dB]

Note (a) Meter Reading : Reading of the spectrum analyzer.
(b) C.F. : System Cable Loss + EUT Cable Loss

5. List of Test Equipment

All test results are traceable to the national and/or international standards.

5.1. Antenna-port Conducted Measurements

	Ctrl.#	Equipment	Model No.	Serial No.	Manufacturer	Cal.Interval	Last Cal.
-	W0140	Spectrum Analyzer	FSU26	200717	Rohde & Schwarz	12 months	18.09.01
x	W0100	Spectrum Analyzer	MS2692A	6201338954	Anritsu	12 months	18.04.03
x	W0006	Power Meter	N1911A	MY50000295	Agilent Technologies	12 months	18.10.06
x	W0007	Power Sensor	N1922A	MY50180022	Agilent Technologies	12 months	18.10.06
-	W0029	10dB Attenuator	8493C	76549	Agilent Technologies	12 months	18.09.01
-	WC0002	RF Cable	SUCOFLEX 102	34124/2	HUBER + SUHNER	12 months	18.09.01
-	WC0003	RF Cable	SUCOFLEX 102	34127/2	HUBER + SUHNER	12 months	18.09.01
-	WC0004	RF Cable	SUCOFLEX 102	34288/2	HUBER + SUHNER	12 months	18.09.01
x	WC0005	RF Cable	SUCOFLEX 102	34287/2	HUBER + SUHNER	12 months	18.09.01
-	WC0006	RF Cable	SUCOFLEX 102	34289/2	HUBER + SUHNER	12 months	18.09.01
-	WC0007	RF Cable	SUCOFLEX 102	34286/2	HUBER + SUHNER	12 months	18.09.01
x	M0719	Thermo Meter	TH-321	140053	AS ONE	12 months	18.04.11

5.2. Radiated Spurious Emissions

	Ctrl.#	Equipment	Model No.	Serial No.	Manufacturer	Cal.Interval	Last Cal.
x	M0686	EMI Receiver	N9038A	MY52260113	Agilent Technologies	12 months	18.11.13
x	M0486	EMI Receiver	ESU40	100050	Rohde & Schwarz	12 months	18.10.01
-	M0562	EMI Receiver	ESU26	100068	Rohde & Schwarz	12 months	18.07.25
x	A0073	Loop Antenna	HFH2-Z2	100171	Rohde & Schwarz	12 months	18.12.10
x	A0089	Biconical Antenna	BBA9106	VHA91032835	Schwarzbeck	12 months	18.12.03
x	A0088	Log periodic Antenna	UHALP9108A1	0649	Schwarzbeck	12 months	18.12.03
x	A0064	Horn Antenna	BBHA9120D	746	Schwarzbeck	12 months	18.11.04
x	A0078	Horn Antenna	HAP06-18W	00000070	Toyo Corporation	12 months	18.11.04
x	A0058	Horn Antenna	HAP18-26W	00000016	Toyo Corporation	12 months	18.12.01
x	CS0017	N-RE Cable System 1	-	-	-	12 months	18.11.04
x	CS0018	N-RE Cable System 2	-	-	-	12 months	18.11.04
x	CS0045	N-3m EMF Cable System	-	-	-	12 months	18.11.04
x	CS0074/0075	N-RE Cable SYSTEM 4	-	-	-	12 months	18.11.04
x	M0126	Step Attenuator	8494H	3837M01144	Agilent Technologies	12 months	18.11.04
x	M0752	Pre Amplifier	310N	320621	SONOMA INSTRUMENT	12 months	18.11.04
x	M0128	3dB Attenuator	8491A	53541	Agilent Technologies	12 months	18.11.04
x	M0609	3dB Attenuator	8491B	MY39265960	Agilent Technologies	12 months	18.11.04
x	M0737	GHz Filter Box	FB-G1	001	Sony EMCS	12 months	18.11.04
x	M5079	Temperature Meter	608-H2	41475953	testo	12 months	18.10.18
x	M5062	Scientific Ambient Monitor	0560 6220	39515563/802	testo	12 months	18.07.17

About calibration interval

Valid until the end of the month listed in "Cal. Int." column.