

Sony Global Manufacturing & Operations Corporation EMC/RF Test Laboratory, Main Lab.

8-4 Shiomi Kisarazu-shi Chiba-ken, 292-0834, Japan

Date: July 14, 2023

FCC ID : AK8WW351513

Applicant: Sony Group Corporation

## **SAR Evaluation Exemption**

To whom it may concern,

We, Sony Global Manufacturing & Operations Corporation EMC/RF Test Laboratory, Main Lab., hereby declare that Radio Equipment, model: WW351513 (WW351513) of Sony Corporation is exempted from RF exposure SAR evaluation, as its output power meets the exclusion limits, stated in FCC Part 2 §2.1093.

## According to KDB 447498 D01 (v06), section 4.3.1:

... These test exclusion conditions are based on source-based time-averaged (i.e. frame averaged) maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

... The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] •  $[\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- · Power and distance are rounded to the nearest mW and mm before calculation
- · The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

For above device,

f = 2.48 GHz, distance = 5mm,

the max. possible duty cycle = 100 % = 0.00 dB,

the max. possible burst averaged power incl. tune-up tolerance = 8.16 dBm, and

the max. possible frame averaged power incl. tune-up tolerance =  $8.16 + (0.00) = 8.16 \text{ dBm} \approx 7 \text{ mW}$ .

Therefore,

 $7 \text{ mW} / 5 \text{ mm} * (\sqrt{2.48 \text{ GHz}}) = 2.2 < 3.0$ 

and no SAR evaluation is required.

Thank you for your attention to this matter.

Sincerely,

Koii Havama

Technical Manager

EMC/RF Test Laboratory Main Lab.

Koji Hayama.

Design Technology Division

Sony Global Manufacturing & Operations Corporation