

## **RF Exposure / SAR Statement**

**No. : 31BE0252-SH-02-A**

**Applicant** : Sony EMCS Corporation Kisarazu TEC  
**Type of Equipment** : AV Center  
**Model No.** : XAV-62BT  
**FCC ID** : AK8XAV62BT

---

Sony EMCS Corporation Kisarazu TEC declares that Model : AV Center complies with FCC radiation exposure requirement specified in the FCC Rules 2.1091. The "XAV-62BT" has 1.47 mW of conducted Peak Output power and 0.56 mW of EIRP. This equipment is considered as a mobile device so that SAR testing is excluded. The Following calculation is the reference data for 20cm distance.

### **RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided with the "XAV-62BT" as calculated from FCC OET Bulletin 65 Appendix A, Table (B) Limits for General Population / Uncontrolled Exposure. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0mW/cm<sup>2</sup> uncontrolled exposure limit. The Friis formula used was:

$$S = (P * G) / (4 * \pi * r^2)$$

Where

**P = 1.47 mW (Maximum peak output power)**  
**G = 0.38 Numerical Antenna gain; equal -4.20 dBi**  
**r = 20.0 cm**

**For: XAV-62BT**

$$S = 0.00011 \text{ mW/cm}^2$$

---

**UL Japan, Inc.**

**Shonan EMC Lab.**

1-22-3 Megumigaoka, Hiratsuka-shi, Kanagawa-ken, 259-1220 JAPAN

Telephone : +81 463 50 6400

Facsimile : +81 463 50 6401