

# SAR TEST REPORT

for

Sony Group Corporation

Digital Media Player

Model No.: YY1301B1

S/N: 0400346; 0400347

FCC ID: AK8YY1301B1

IC: 409B-YY1301B1

The MAX Report SAR(1g)	
Head SAR	1.396W/Kg

Prepared for : Sony Group Corporation  
1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Kefeng Road, Science & Technology Park,  
Nanshan District, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Fax: (0755) 26632877

Report No. : ACS-SF22005

Date of Test : Aug.24~27, 2022

Date of Report : Sep.29, 2022

**TABLE OF CONTENTS**

<u>Description</u>	<u>Page</u>
<b>TEST REPORT VERIFICATION.....</b>	<b>3</b>
<b>1. GENERAL INFORMATION.....</b>	<b>4</b>
1.1. Description of Equipment Under Test.....	4
1.2. Feature of Equipment under Test.....	5
<b>2. GENERAL DESCRIPTION.....</b>	<b>6</b>
2.1. Product Description For EUT.....	6
2.2. Applied Standards.....	6
2.3. Device Category and SAR Limits.....	6
2.4. Test Conditions.....	6
2.5. Exposure Positions Consideration.....	7
2.6. Standalone SAR Test Exclusion Considerations.....	8
2.7. EUT Configuration and operation conditions for test.....	8
2.8. Test Equipments.....	9
2.9. Laboratory Environment.....	11
2.10. Measurement Uncertainty.....	11
<b>3. MEASURE PROCEDURES.....</b>	<b>14</b>
3.1. General description of test procedures.....	14
<b>4. SAR MEASUREMENTS SYSTEM.....</b>	<b>15</b>
4.1. SAR Measurement Set-up.....	15
4.2. ELI Phantom.....	16
4.3. Device Holder for SAM Twin Phantom.....	17
4.4. DASYS E-field Probe System.....	18
4.5. E-field Probe Calibration.....	19
4.6. Scanning procedure.....	20
<b>5. DATA STORAGE AND EVALUATION.....</b>	<b>22</b>
5.1. Data Storage.....	22
5.2. Data Evaluation by SEMCAD.....	22
<b>6. SYSTEM CHECK.....</b>	<b>24</b>
<b>7. TEST RESULTS.....</b>	<b>26</b>
7.1. Output power.....	26
7.2. System Check for Head Tissue simulating liquid.....	29
7.3. Dielectric Performance for Head Tissue simulating liquid.....	30
7.4. Test Results.....	32

**ANNEX A: System Check Results****ANNEX B: Test Plots****ANNEX C: DASYS Calibration Certificate****ANNEX D: Test Setup Photos**

**SAR TEST REPORT**

Applicant : Sony Group Corporation  
Product : Digital Media Player  
Model No. : YY1301B1  
S/N : 0400346; 0400347  
FCC ID : AK8YY1301B1  
IC : 409B-YY1301B1  
Test Voltage : DC 3.7V

## Measurement Standard Used:

- FCC 47 CFR Part 2 (2.1093)
- IEEE C95.1-1999
- IEC/IEEE 62209-1528: 2020
- IEC62209-1:2016
- IEC62209-2:2010
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- RSS-102 ISSUE 5: 2015+A1: 2021
- FCC KDB 447498 D01 v06
- FCC KDB 447498 D04 v01
- FCC KDB 865664 D01/D02
- FCC KDB 248227 D01 v02r02

The device described above is tested by Audix Technology (Shenzhen) Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Audix Technology (Shenzhen) Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. This report contains data that are not covered by the NVLAP accreditation. Also, this report shows that the EUT is technically compliant with the FCC and RSS-102 test requirements.

This report applies to single evaluation of one sample of above mentioned product. This report shall not be reproduced in part without written approval of Audix Technology (Shenzhen) Co., Ltd.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Aug.24~27, 2022 Report of date: Sep.29, 2022

Prepared by : Crush Liu Reviewed by : Sunny Lu  
Crush Liu / Assistant Sunny Lu / Manager



## 1. GENERAL INFORMATION

### 1.1. Description of Equipment Under Test

Applicant	Sony Group Corporation
Applicant Address	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan
Product	Digital Media Player
Model No.	YY1301B1
FCC ID	AK8YY1301B1
IC	409B-YY1301B1
Radio	BDR+EDR; BLE; 2.4GHz Wi-Fi; 5GHz Wi-Fi
Sample Type	Prototype production
Date of Receipt	Jul.04, 2022
Date of Test	Aug.24~27, 2022

1.2.Feature of Equipment under Test

Product Feature & Specification		
Product	Digital Media Player	
Model No.	YY1301B1	
Power Source	<input type="checkbox"/> Commercial Power	AC 100~240 V
	<input checked="" type="checkbox"/> External Power Source	DC 5V
	<input checked="" type="checkbox"/> Li-ion Battery	DC 3.7V, 1500mAh
	<input type="checkbox"/> UM battery	DC V
Bluetooth		
Radio	Bluetooth V3.0+EDR; Bluetooth V4.0	
Frequency Range	2402-2480MHz	
Type of Modulation	GFSK, $\pi/4$ DQPSK, 8DPSK	
Data Rate	1Mbps, 2Mbps, 3Mbps	
Quantity of Channels	79/40	
Channel Separation	1MHz/2MHz	
2.4GHz Wi-Fi		
Support Modes	802.11b/g/n20/n40	
Frequency Range	2412-2462MHz	
Type of Modulation	802.11b(DSSS): CCK, QPSK, BPSK; 802.11g/n(OFDM): 64QAM,16QAM, QPSK, BPSK	
Data Rate	802.11b: 1/2/5.5/11 Mbps; 802.11g: 6/9/12/18/24/36/48/54 Mbps; 802.11n: up to 150Mbps	
Channel Separation	5MHz	
5GHz Wi-Fi		
Support Modes	802.11a/n20/n40/ac20/ac40/ac80	
Frequency Range	5180-5240MHz, 5260-5320MHz, 5650-5720MHz, 5745-5825MHz	
Type of Modulation	802.11a/n (OFDM): QPSK, BPSK, 16QAM, 64QAM 802.11ac (OFDM): QPSK, BPSK, 16QAM, 64QAM,256QAM	
Data Rate	802.11a: 6/9/12/18/24/36/48/54 Mbps; 802.11n: up to 150Mbps; 802.11ac: up to 433Mbps	
Channel Separation	5MHz	
Antenna System		
Type of Antenna	PIFA Antenna	
Antenna Peak Gain	Bluetooth Peak Gain: -0.3dBi DTS/DSS Band (2400-2483.5MHz) Peak Gain: -0.3dBi. U-NII-1 Band(5150-5250MHz) Peak Gain: 0.3dBi. U-NII-2A Band(5250-5350MHz) Peak Gain: -0.7dBi. U-NII-2C Band(5500-5720MHz) Peak Gain: 0.9dBi. U-NII-3 Band (5725-5850MHz) Peak Gain: 2.1dBi.	

## 2. GENERAL DESCRIPTION

### 2.1. Product Description For EUT [None]

### 2.2. Applied Standards

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- IEEE C95.1-1999
- IEC/IEEE 62209-1528: 2020
- IEC62209-1:2016
- IEC62209-2:2010
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- RSS-102 ISSUE 5: 2015+A1: 2021
- FCC KDB 447498 D01 v06
- FCC KDB 447498 D04 v01
- FCC KDB 865664 D01/D02
- FCC KDB 248227 D01 v02r02

### 2.3. Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

### 2.4. Test Conditions


#### 2.4.1. Ambient Condition

<b>Ambient Temperature</b>	20 to 24 °C
<b>Humidity</b>	< 60 %

#### 2.4.2. Test Configuration

The distance between the EUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during all tests.

2.5.Exposure Positions Consideration



Sides for SAR tests										
Test distance: 5 mm(Body)										
Band	Body						Head Touch		Head (15°)	
	Back	Front	Top	Bottom	Left	Right	Left	Right	Left	Right
BT	✓	✓	✓	✓	✓	✓	X	X	X	X
WLAN 2.4GHz	✓	✓	✓	✓	✓	✓	X	X	X	X
WLAN 5GHz	✓	✓	✓	✓	✓	✓	X	X	X	X

**Note:**

1. The length of the diagonal dimension of the EUT is less than 20cm.
2. The side which has a distance larger than 2.5cm from antenna can be excluded from SAR measurement.

### 2.6. Standalone SAR Test Exclusion Considerations

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied. The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

According to the KDB447498 Table B.2, the SAR test exclusion threshold for 2450MHz at 5mm test separation distances is 3 mW, 5.2GHz is 7 mW, 5.4GHz and 5.8GHz is 6mW

**Table B.2—Example Power Thresholds (mW)**

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

### 2.7. EUT Configuration and operation conditions for test.



( EUT: Digital Media Player)



2.8. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal Date	Validity Date	Cal. Agency
1.	DASY5 SAR Test System	Speag	TX60 L speag	F09/5B1H1/01	NCR	NCR	N/A
2.	ENA Series Analyzer	Agilent	E5071B	MY42403549	2022.04.06	2023.04.05	CCIC
3.	ENA SERIES NETWORK ANALYZER	Agilent	E5071C	MY46316760	2021.10.09	2022.10.09	CCIC
4.	Power Meter	Anritsu	ML2487A	6K00003262	2022.07.01	2023.06.30	CCIC
5.	Power Sensor	Anritsu	MA2491A	032516	2022.07.01	2023.06.30	CCIC
6.	Signal Generator	Rohde&Schwarz	SMB100A	181375	2022.04.06	2023.04.05	CCIC
7.	Amplifier	Milmega	ZHL-42W	C620601316	NCR	NCR	N/A
8.	Dipole Validation Kits	Speag	D2450V2	862	2020.06.15	2023.06.15	SPEAG
9.	Dipole Validation Kits	Speag	D5GHzV2	1102	2020.06.15	2023.06.15	SPEAG
10.	Attenuator(20dB)	N/A	1527	001	2021.10.09	2022.10.09	CCIC
11.	Date Acquisition Electronics	Speag	DAE4	899	2022.06.06	2023.06.06	CCTL
12.	E-Field Probe	Speag	EX3DV4	3767	2022.05.26	2023.05.26	CCTL
13.	Test Software	Schmid&Partner Englinnering AG	DASY5	52.8.7.1137	NCR	NCR	NCR
14.	Radio Communication Analyzer	ANRITSU	MT8821C	6201547828	2022.04.06	2023.04.06	CCIC
15.	Radio Communication Analyzer	Rohde & Schwarz	CMW500	103249	2021.10.09	2022.10.09	CCIC

Note: NCR means no calibration required(calibrated with system).

Note: Dipole antenna calibration interval is 3 year, annual check result to be follow (Refer to KDB 865664, Dipole calibration)

**Dipole: 2450V2-SN862**

Antenna Parameters with Head TSL

Date	2021.06.21	2022.06.13
Impedance, Transformed to Feed point	48.1Ω-6.09jΩ	48.63Ω-6.06jΩ
Return Loss	-23.8dB	-24.04dB

**Dipole: D5GHzV2-SN1102**

Antenna Parameters with Head TSL at 5250MHz

Date	2021.06.21	2022.06.13
Impedance, Transformed to Feed point	50.2Ω-8.19jΩ	49.34Ω-2.68j
Return Loss	-25.4dB	-31.17dB

## Antenna Parameters with Head TSL at 5600MHz

Date	2021.06.21	2022.06.13
Impedance, Transformed to Feed point	59.1 $\Omega$ -0.72j $\Omega$	59.11 $\Omega$ -0.78j $\Omega$
Return Loss	-21.5dB	-21.54dB

## Antenna Parameters with Head TSL at 5750MHz

Date	2021.06.21	2022.06.13
Impedance, Transformed to Feed point	60.15 $\Omega$ -0.88j $\Omega$	54.78 $\Omega$ -1.56j $\Omega$
Return Loss	-26.5dB	-26.54dB

**2.9. Laboratory Environment**

Temperature	Min:20°C,Max.25°C
Relative humidity	Min. = 30%, Max. = 70%
Note: Ambient noise is checked and found very low and in compliance with requirement of standards.	

**2.10. Measurement Uncertainty**

Test Item	Uncertainty
Uncertainty for SAR test	1g: 21.1
	10g: 20.6
Uncertainty for test site temperature	0.6°C

Source	Type	Uncertainty Value (%)	Probability Distribution	K	C1(1g)	C1(10g)	Standard uncertainty u1(%)1g	Standard uncertainty u1(%)10g	Degree of freedom Veff or Vi
<b>Measurement system repeatability</b>	A	0.5	N	1		1	0.5	0.5	9
Probe calibration	B	5.9	N	1	1	1	5.9	5.9	∞
Isotropy	B	4.7	R	√3	1	1	2.7	2.7	∞
Linearity	B	4.7	R	√3	1	1	2.7	2.7	∞
Probe modulation response	B	0	R	√3	1	1	0	0	∞
Detection limits	B	1.0	R	√3	1	1	0.6	0.6	∞
Boundary effect	B	1.9	R	√3	1	1	1.1	1.1	∞
Readout electronics	B	1.0	N	1	1	1	1.0	1.0	∞
Response time	B	0	R	√3	1	1	0	0	∞
Integration time	B	4.32	R	√3	1	1	2.5	2.5	∞
RF ambient conditions – noise	B	0	R	√3	1	1	0	0	∞
RF ambient conditions – reflections	B	3	R	√3	1	1	1.73	1.73	∞
Probe positioner mech. Restrictions	B	0.4	R	√3	1	1	0.2	0.2	∞
Probe positioning with respect to phantom shell	B	2.9	R	√3	1	1	1.7	1.7	∞
Post-processing	B	0	R	√3	1	1	0	0	∞
<b>Test sample related</b>									
Device holder uncertainty	A	2.94	N	1	1	1	2.94	2.94	M-1
Test sample positioning	A	4.1	N	1	1	1	4.1	4.1	M-1
Power scaling	B	5.0	R	√3	1	1	2.9	2.9	∞
Drift of output power (measured SAR drift)	B	5.0	R	√3	1	1	2.9	2.9	∞
<b>Phantom and set-up</b>									
Phantom uncertainty (shape and thickness tolerances)	B	4.0	R	√3	1	1	2.3	2.1	∞
Algorithm for correcting SAR for deviations in permittivity and conductivity	B	1.9	N	1	1	0,84	1,9	1,6	∞
Liquid conductivity (meas.)	A	0.55	N	1	0.78	0.71	0.24	0.21	M-1
Liquid permittivity (meas.)	A	0.19	N	1	0.23	0.26	0.09	0.06	M
Liquid permittivity – temperature uncertainty	A	5.0	R	√3	0,78	0,71	1.4	1.1	∞
Liquid conductivity – temperature uncertainty	A	5.0	R	√3	0.23	0,26	1.2	0.8	∞
<b>Combined standard uncertainty</b>	$u_c = \sqrt{\sum_{i=1}^{23} c_i^2 u_i^2}$						<b>10.57</b>	<b>10.32</b>	
<b>Expanded uncertainty (95 % conf. interval)</b>	$u_e = 2u_c$		N	K=2		<b>21.14</b>	<b>20.64</b>		

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% by weight)	Frequency (MHz)									
	450		835		915		1900		2450	
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	38.56	51.16	41.45	52.4	41.05	56.0	54.9	40.4	62.7	73.2
Salt (NaCl)	3.95	1.49	1.45	1.4	1.35	0.76	0.18	0.5	0.5	0.04
Sugar	56.32	46.78	56.0	45.0	56.5	41.76	0.0	58.0	0.0	0.0
HEC	0.98	0.52	1.0	1.0	1.0	1.21	0.0	1.0	0.0	0.0
Bactericide	0.19	0.05	0.1	0.1	0.1	0.27	0.0	0.1	0.0	0.0
Triton X-100	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	0.0	0.0	0.0	0.0	44.92	0.0	0.0	26.7
Dielectric Constant	43.42	58.0	42.54	56.1	42.0	56.8	39.9	54.0	39.8	52.5
Conductivity (S/m)	0.85	0.83	0.91	0.95	1.0	1.07	1.42	1.45	1.88	1.78

Salt: 99+% Pure Sodium Chloride

Sugar: 98+% Pure Sucrose

Water: De-ionized, 16 MΩ+ resistivity

HEC: Hydroxyethyl Cellulose

DGBE: 99+% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1,3,3-tetramethylbutyl)phenyl]ether

**Simulating Liquids for 5 GHz, Manufactured by SPEAG**

Ingredients	(% by weight)
Water	78
Mineral oil	11
Emulsifiers	9
Additives and Salt	2

### 3. MEASURE PROCEDURES

#### 3.1. General description of test procedures

For the 802.11b/g SAR body tests, a communication link is set up with the test mode software for WIFI mode test. The Absolute Radiofrequency Channel Number (ARFCN) is allocated to 1,6 and 11 respectively in the case of 2450 MHz. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Each channel should be tested at the lowest data rate. Testing at higher data rates is not required when the maximum average output power is less than 0.25dB higher than those measured at the lowest data rate.

802.11b/g operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g modes are tested on channels 1,6,11; however, if output power reduction is necessary for channels 1 and /or 11 to meet restricted band requirements the highest output channels closest to each of these channels must be tested instead.

SAR is not required for 802.11g channels when the maximum average output power is less than 0.25dB higher than that measured on the corresponding 802.11b channels. When the maximum average output channel in each frequency band is not included in the “default test channels”, the maximum channel should be tested instead of an adjacent “default test channels”, these are referred to as the “required test channels” and are illustrated in table 1.

Mode	GHz	Channel	Turbo Channel	“Default Test Channels”	
				15.247	
				802.11b	802.11g
802.11b/g	2.412	1 <sup>#</sup>	1 <sup>#</sup>	√	*
	2.437	6	6	√	*
	2.462	11 <sup>#</sup>	11 <sup>#</sup>	√	*

Table 1

Note: #= when output power is reduced for channel 1 and /or 11 to meet restricted band requirements the highest out put channels closet to each of these channels should be tested.

√= ” default test channels”

\* = possible 802.11g channels with maximum average output 0.25dB>=the “default test channels”

Please apply the following guidance for SAR testing:

1. Please use a 0 mm (touching) test separation distance on the flat phantom during SAR testing of this device. This separation distance is based on the guidance found in FCC KDB Publication 447498 D01, Section 5.2.3 3)
2. Please utilize a body tissue simulating liquid (TSL) of the appropriate frequency during SAR testing.
3. Please use the guidance found in FCC KDB Publication 447498 D01 to determine which sides of the device need to be tested for SAR.
4. FCC KDB Publication 248227 D01 should be used for selection of the WiFi channels, data rates, etc.

## 4. SAR MEASUREMENTS SYSTEM

### 4.1. SAR Measurement Set-up

DASY5 system for performing compliance tests consists of the following items:

- (1) A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).
- (2) A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage. It issues simulating liquid. The probe is equipped with an optical surface detector system.
- (3) A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- (4) A unit to operate the optical surface detector which is connected to the EOC.
- (5) The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.
- (6) The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.
- (7) DASY5 software and SEMCAD data evaluation software.
- (8) Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.
- (9) The generic twin phantom enabling the testing of left-hand and right-hand usage.
- (10) The device holder for handheld mobile phones.
- (11) Tissue simulating liquid mixed according to the given recipes.
- (12) System validation dipoles allowing to validate the proper functioning of the system.





Figure 4.1 SAR Lab Test Measurement Set-up

#### 4.2. ELI Phantom

Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.



Material	Vynylester, glass fiber reinforced (VE-GF)
Liquid Compatibility	Compatible with all SPEAG tissue simulating liquids (incl. DGBE type)
Shell Thickness	2.0 ± 0.2 mm (bottom plate)
Dimensions	Major axis: 600 mm Minor axis: 400 mm
Filling Volume	approx. 30 liters
Wooden Support	SPEAG standard phantom table

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections.

#### Figure 6.2 Top View of Twin Phantom

A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters.

On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

The phantom can be used with the following tissue simulating liquids:

- \*Water-sugar based liquid
- \*Glycol based liquids



#### 4.3. Device Holder for SAM Twin Phantom

The SAR in the Phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source in 5 mm distance, a positioning uncertainty of  $\pm 0.5\text{mm}$  would produce a SAR uncertainty of  $\pm 20\%$ . An accurate device position is therefore crucial for accurate and repeatable measurement. The position in which the devices must be measured, are defined by the standards.

The DASY5 device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (EPR).

Thus the device needs no repositioning when changing the angles.

The DASY5 device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon_r=3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



**Figure 4.3 Device Holder**

#### 4.4.DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe EX3DV4 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.



Figure 4.4 EX3DV4 E-field Probe

##### 4.4.1. EX3DV4 Probe Specification

Construction	Symmetrical design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration	ISO/IEC 17025 calibration service available
Frequency	10 MHz to > 6 GHz Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)
Directivity	$\pm 0.3$ dB in HSL (rotation around probe axis) $\pm 0.5$ dB in tissue material (rotation normal to probe axis)
Dynamic Range	10 $\mu$ W/g to > 100 mW/g Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)
Dimensions	Overall length: PRS-T2 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm
Application	High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.

#### 4.5. E-field Probe Calibration

Each probe is calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm 10\%$ . The spherical isotropy was evaluated and found to be better than  $\pm 0.25\text{dB}$ . The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested.

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz, and in a wave guide above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

Where:  $\Delta t$  = Exposure time (30 seconds),  
C = Heat capacity of tissue (brain or muscle),  
 $\Delta T$  = Temperature increase due to RF exposure.  
Or

$$\text{SAR} = \frac{|E|^2 \sigma}{\rho}$$

Where:  
 $\sigma$  = Simulated tissue conductivity,  
 $\rho$  = Tissue density (kg/m<sup>3</sup>).

#### 4.6. Scanning procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The "reference" and "drift" measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the EUT's output power and should vary max.  $\pm 5\%$ .

The "surface check" measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above  $\pm 0.1\text{mm}$ ). To prevent wrong results tests are only executed when the liquid is free of air bubbles.

The difference between the optical surface detection and the actual surface depends on the Probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within  $\pm 30^\circ$ .)

##### **Area Scan**

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged.

After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

##### **Zoom Scan**

Zoom Scans are used to estimate the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan is done by 7x7x7 points within a cube whose base is centered around the maxima found in the preceding area scan.

**Spatial Peak Detection**

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 7x7x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1g and 10g cubes.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube 7x7x7 scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

## 5. DATA STORAGE AND EVALUATION

### 5.1. Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm<sup>2</sup>], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

### 5.2. Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters: - Sensitivity	Normi, ai0, ai1, ai2
- Conversion factor	ConvFi
- Diode compression point	Dcpi

Device parameters: - Frequency	f
- Crest factor	cf

Media parameters: - Conductivity	
- Density	

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_{i2} \cdot c f / d c p_i$$

With  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$U_i$  = input signal of channel  $i$  ( $i = x, y, z$ )

$cf$  = crest factor of exciting field (DASY parameter)

$dcpi$  = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes:  $E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$

H-field probes:  $H_i = (V_i)^{1/2} \cdot (ai_0 + ai_1 f + ai_2 f^2) / f$

With  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$Norm_i$  = sensor sensitivity of channel  $i$  ( $i = x, y, z$ )

$ConvF$  = sensitivity enhancement in solution

$ai_j$  = sensor sensitivity factors for H-field probes

$f$  = carrier frequency [GHz]

$E_i$  = electric field strength of channel  $i$  in V/m

$H_i$  = magnetic field strength of channel  $i$  in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}^2 \cdot \rho) / (1000) \text{ with}$$

$SAR$  = local specific absorption rate in mW/g

$E_{tot}$  = total field strength in V/m

$\rho$  = conductivity in [mho/m] or [Siemens/m]

$\rho_{eq}$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \text{ or } P_{pwe} = H_{tot}^2 \cdot 37.7$$

with  $P_{pwe}$  = equivalent power density of a plane wave in mW/cm<sup>2</sup>

$E_{tot}$  = total electric field strength in V/m

$H_{tot}$  = total magnetic field strength in A/m

## 6. SYSTEM CHECK

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulates were measured every day using the dielectric probe kit and the network analyzer. A system check measurement was made following the determination of the dielectric parameters of the simulates, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system check results (dielectric parameters and SAR values) are given in the ANNEX A.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ( $\pm 10\%$ ).

System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.




Figure 6.1: System Check Set-up






Figure 6.3: photos of system

## 7. TEST RESULTS

### 7.1. Output power

(BDR+EDR)

Mode	Frequency (MHz)	Peak output power (dBm)	Maximum Tune-up Power (dBm)
GFSK	2402	12.379	13.5
	2441	13.300	
	2480	12.956	
8-DPSK	2402	12.101	
	2441	13.047	
	2480	12.836	

(BLE)

Mode	Frequency (MHz)	Peak output power (dBm)	Maximum Tune-up Power (dBm)
GFSK	2402	8.277	11
	2440	9.331	
	2480	10.498	

(WiFi 2.4GHz)

Mode	Frequency (MHz)	Conducted output power (dBm)	Maximum Tune-up Power (dBm)
11b	2412	12.23	15.5
	2437	11.44	
	2462	11.89	
11g	2412	14.25	
	2437	14.08	
	2462	14.39	
11n HT20	2412	13.98	
	2437	13.89	
	2462	14.16	
11n HT40	2422	14.39	
	2437	15.07	
	2452	14.99	

**Note:** Use the data rate with the maximum output level for the SAR test.

(U-NII-1 Band)

Mode	Frequency (MHz)	Conducted output power (dBm)	Maximum Tune-up Power (dBm)
11a	5180	12.50	15
	5200	14.43	
	5240	12.44	
11n HT20	5180	12.22	
	5200	12.17	
	5240	12.22	
11n HT40	5190	12.45	
	5230	12.52	
11ac VHT20	5180	12.22	
	5200	12.16	
	5240	12.20	
11ac VHT40	5190	12.43	
	5230	12.46	
11ac VHT80	5210	10.45	

(U-NII-2A Band)

Mode	Frequency (MHz)	Conducted output power (dBm)	Maximum Tune-up Power (dBm)
11a	5260	12.65	15
	5300	13.00	
	5320	12.96	
11n HT20	5260	12.47	
	5300	12.84	
	5320	12.77	
11n HT40	5270	11.85	
	5310	12.86	
11ac VHT20	5260	11.08	
	5300	11.78	
	5320	12.82	
11ac VHT40	5270	12.70	
	5310	12.85	
11ac VHT80	5290	11.46	

(U-NII-2C Band)

Mode	Frequency (MHz)	Conducted output power (dBm)	Maximum Tune-up Power (dBm)
11a	5500	12.84	15
	5580	13.12	
	5720	13.89	
11n HT20	5500	12.63	
	5580	12.90	
	5720	13.67	
11n HT40	5510	12.76	
	5550	12.73	
	5710	13.44	
11ac VHT20	5500	12.64	
	5580	12.94	
	5720	13.69	
11ac VHT40	5510	12.74	
	5550	12.76	
	5710	13.49	
11ac VHT80	5530	11.24	
	5690	12.15	

(U-NII-3 Band)

Mode	Frequency (MHz)	Conducted output power (dBm)	Maximum Tune-up Power (dBm)
11a	5745	13.86	15
	5785	14.58	
	5825	14.46	
11n HT20	5745	13.82	
	5785	14.37	
	5825	14.27	
11n HT40	5755	13.88	
	5795	14.42	
11ac VHT20	5745	13.79	
	5785	14.40	
	5825	14.28	
11ac VHT40	5755	14.83	
	5795	14.43	
11ac VHT80	5775	12.59	

**Note:** Use the data rate with the maximum output level for the SAR test.

7.2. System Check for Head Tissue simulating liquid

Frequency	Description	SAR(W/kg) (1g±18.8% window; 10g±18.7% window)		Dielectric Parameters (±10% window)		Temp
		1g	10g	εr	σ(s/m)	°C
2450MHz	Recommended value	13.2 10.7184 – 15.6816	6.05 4.91865 – 7.18135	39.20 35.28-43.12	1.80 1.62-1.98	/
	Measurement value 2022-08-24	12.3	5.5	39.2	1.8	21.05
5250MHz	Recommended value	7.76 6.30112 – 9.21888	2.22 1.80486 – 2.63514	35.90 32.31- 39.49	4.76 4.284 - 5.236	/
	Measurement value 2022-08-25	8.2	2.39	35.53	4.51	21.04
5600MHz	Recommended value	8.10 6.5772 – 9.6228	2.31 1.87803 – 2.74197	35.5 31.95 - 39.05	5.07 4.563 - 5.577	/
	Measurement value 2022-08-26	8.47	2.46	35	4.82	21.02
5750MHz	Recommended value	7.73 6.27676 – 9.18324	2.19 1.78047– 2.59953	35.4 31.86 – 38.94	5.22 4.698 – 5.742	/
	Measurement value 2022-08-27	8.66	2.27	34.54	5.12	21.02

7.3. Dielectric Performance for Head Tissue simulating liquid

Frequency		Description	Dielectric Parameters (±10% window)		Temp
			$\epsilon_r$	$\sigma$ (s/m)	°C
2450		Recommended value	39.20 35.28-43.12	1.80 1.62-1.98	/
BT3.0	2402MHz	Measurement value 2022-08-24	38.913	1.828	21.03
	2441MHz	Measurement value 2022-08-24	38.734	1.878	21.03
	2480MHz	Measurement value 2022-08-24	38.579	1.917	21.03
BLE	2402MHz	Measurement value 2022-08-24	38.913	1.828	21.03
	2440MHz	Measurement value 2022-08-24	38.738	1.876	21.03
	2480MHz	Measurement value 2022-08-24	38.579	1.917	21.03
WiFi 2.4GHz	2422MHz	Measurement value 2022-08-24	38.849	1.841	21.03
	2437MHz	Measurement value 2022-08-24	38.753	1.873	21.03
	2452MHz	Measurement value 2022-08-24	38.666	1.899	21.03

WiFi 5GHz Band 1	5180MHz	Recommended value	35.90 32.31- 39.49	4.76 4.284 - 5.236	/
		Measurement value 2022-08-25	35.53	4.51	21.07
	5200MHz	Recommended value	35.90 32.31- 39.49	4.76 4.284 - 5.236	/
		Measurement value 2022-08-25	35.53	4.51	21.07
	5240MHz	Recommended value	35.90 32.31- 39.49	4.76 4.284 - 5.236	/
		Measurement value 2022-08-25	35.53	4.51	21.07
WiFi 5GHz Band 2A	5260MHz	Recommended value	35.90 32.31- 39.49	4.76 4.284 - 5.236	/
		Measurement value 2022-08-25	37.018	4.523	21.06
	5300MHz	Recommended value	35.90 32.31- 39.49	4.76 4.284 - 5.236	/
		Measurement value 2022-08-25	37.015	4.579	21.06
	5320MHz	Recommended value	35.90 32.31- 39.49	4.76 4.284 - 5.236	/
		Measurement value 2022-08-25	37.015	4.611	21.06
WiFi 5GHz Band 2C	5500MHz	Recommended value	35.5 31.95 - 39.05	5.07 4.563 - 5.577	/
		Measurement value 2022-08-26	35.891	4.733	21.02
	5580MHz	Recommended value	35.5 31.95 - 39.05	5.07 4.563 - 5.577	/
		Measurement value 2022-08-26	36.707	4.729	21.02
	5720MHz	Recommended value	35.5 31.95 - 39.05	5.07 4.563 - 5.577	/
		Measurement value 2022-08-26	35.887	4.941	21.02
WiFi 5GHz Band 3	5755MHz	Recommended value	35.4 31.86 - 38.94	5.22 4.698 - 5.742	/
		Measurement value 2022-08-27	34.833	5.042	21.02
	5795MHz	Recommended value	35.4 31.86 - 38.94	5.22 4.698 - 5.742	/
		Measurement value 2022-08-27	34.842	5.134	21.02

7.4. Test Results

**(BDR+EDR)**

Test Position	Test CH	Duty Cycle	Measure SAR 1g(W/kg)	Measure SAR 10g(W/kg)	Conducted Power(dBm)	Tune up Power(dBm)	Factor	Scaled Final SAR 1g	Scaled Final SAR 10g	power drift
Top	0	0.7732	0.281	0.169	12.38	13.5	1.294	0.470	0.283	-0.13
Back	39	0.7732	0.205	0.125	13.3	13.5	1.047	0.278	0.169	0.18
Front	39	0.7732	0.101	0.04	13.3	13.5	1.047	0.137	0.054	0.13
Top	39	0.7732	0.262	0.175	13.3	13.5	1.047	0.355	0.237	-0.16
Bottom	39	0.7732	0.00652	0.00268	13.3	13.5	1.047	0.009	0.004	0.18
Left	39	0.7732	0.027	0.012	13.3	13.5	1.047	0.037	0.016	0.1
Right	39	0.7732	0.017	0.00749	13.3	13.5	1.047	0.023	0.010	0.11
Top	78	0.7732	0.274	0.183	12.96	13.5	1.132	0.401	0.268	-0.13
Conclusion: PASS										
Note: Factor= Max. Scaled AV Power(W)/Measured Power(W) Scaled SAR-1= Measured SAR*Factor Scaled-Final= Scaled SAR-1*(1/Duty Cycle)										

**(BLE)**

Test Position	Test CH	Duty Cycle	Measure SAR 1g(W/kg)	Measure SAR 10g(W/kg)	Conducted Power(dBm)	Tune up Power(dBm)	Factor	Scaled Final SAR 1g	Scaled Final SAR 10g	power drift
Top	0	0.7732	0.122	0.055	8.28	11	1.871	0.295	0.133	-0.08
Back	39	0.7732	0.142	0.057	10.5	11	1.122	0.206	0.083	-0.03
Front	39	0.7732	0.137	0.057	10.5	11	1.122	0.199	0.083	0.18
Top	39	0.7732	0.166	0.079	10.5	11	1.122	0.241	0.115	-0.11
Bottom	39	0.7732	0.00592	0.00224	10.5	11	1.122	0.009	0.003	0.11
Left	39	0.7732	0.036	0.015	10.5	11	1.122	0.052	0.022	0.13
Right	39	0.7732	0.024	0.01	10.5	11	1.122	0.035	0.015	0.13
Top	19	0.7732	0.133	0.078	9.33	11	1.469	0.253	0.148	-0.19
Conclusion: PASS										
Note: Factor= Max. Scaled AV Power(W)/Measured Power(W) Scaled SAR-1= Measured SAR*Factor Scaled-Final= Scaled SAR-1*(1/Duty Cycle)										



**(WiFi 2.4GHz)**

Test Position	Test CH	Duty Cycle	Measure SAR 1g(W/kg)	Measure SAR 10g(W/kg)	Conducted Power(dBm)	Tune up Power(dBm)	Factor	Scaled Final SAR 1g	Scaled Final SAR 10g	power drift
Top	3	1	0.808	0.279	14.59	15.5	1.233105	0.996	0.344	-0.1
Front	6	1	0.628	0.241	15.27	15.5	1.054387	0.662	0.254	-0.19
Back	6	1	0.726	0.301	15.27	15.5	1.054387	0.765	0.317	0.09
Top	6	1	1.07	0.371	15.27	15.5	1.054387	1.128	0.391	-0.1
Bottom	6	1	0.046	0.02	15.27	15.5	1.054387	0.049	0.021	0.18
Left	6	1	0.089	0.046	15.27	15.5	1.054387	0.094	0.049	0.11
Right	6	1	0.096	0.048	15.27	15.5	1.054387	0.101	0.051	0.16
Top	9	1	0.532	0.181	15.19	15.5	1.073989	0.571	0.194	-0.15
Conclusion: PASS										
Note: Factor= Max. Scaled AV Power(W)/Measured Power(W) Scaled SAR-1= Measured SAR*Factor Scaled-Final= Scaled SAR-1*(1/Duty Cycle)										

**(U-NII-1 Band)**

Test Position	Test CH	Duty Cycle	Measure SAR 1g(W/kg)	Measure SAR 10g(W/kg)	Conducted Power(dBm)	Tune up Power(dBm)	Factor	Scaled Final SAR 1g	Scaled Final SAR 10g	power drift
Top	36	1	0.677	0.255	12.56	15	1.754	1.187	0.447	-0.1
Back	40	1	0.589	0.232	14.49	15	1.125	0.662	0.261	0.12
Front	40	1	0.3	0.109	14.49	15	1.125	0.337	0.123	0.17
Top	40	1	1.1	0.385	14.49	15	1.125	1.237	0.433	0.05
Bottom	40	1	0.032	0.01	14.49	15	1.125	0.036	0.011	0.14
Left	40	1	0.116	0.05	14.49	15	1.125	0.130	0.056	-0.18
Right	40	1	0.061	0.027	14.49	15	1.125	0.069	0.030	0.19
Top	48	1	0.632	0.268	12.5	15	1.778	1.124	0.477	0.05
Conclusion: PASS										
Note: Factor= Max. Scaled AV Power(W)/Measured Power(W) Scaled SAR-1= Measured SAR*Factor Scaled-Final= Scaled SAR-1*(1/Duty Cycle)										

**(U-NII-2A Band)**

Test Position	Test CH	Duty Cycle	Measure SAR 1g(W/kg)	Measure SAR 10g(W/kg)	Conducted Power(dBm)	Tune up Power(dBm)	Factor	Scaled Final SAR 1g	Scaled Final SAR 10g	power drift
Top	52	1	0.861	0.335	12.9	15	1.62181	1.396	0.543	0.1
Back	60	1	0.636	0.25	13.09	15	1.552387	0.987	0.388	0.18
Front	60	1	0.306	0.108	13.09	15	1.552387	0.475	0.168	0.12
Top	60	1	0.888	0.351	13.09	15	1.552387	1.379	0.545	0.11
Bottom	60	1	0.036	0.01	13.09	15	1.552387	0.056	0.016	0.1
Left	60	1	0.137	0.059	13.09	15	1.552387	0.213	0.092	-0.18
Right	60	1	0.065	0.028	13.09	15	1.552387	0.101	0.043	0.15
Top	64	1	0.856	0.342	13.02	15	1.577611	1.350	0.540	0.09

Conclusion: PASS

Note:

Factor= Max. Scaled AV Power(W)/Measured Power(W)

Scaled SAR-1= Measured SAR\*Factor

Scaled-Final= Scaled SAR-1\*(1/Duty Cycle)

**(U-NII-2C Band)**

Test Position	Test CH	Duty Cycle	Measure SAR 1g(W/kg)	Measure SAR 10g(W/kg)	Conducted Power(dBm)	Tune up Power(dBm)	Factor	Scaled Final SAR 1g	Scaled Final SAR 10g	power drift
Top	100	1	0.842	0.376	12.9	15	1.621810097	1.366	0.610	0.06
Back	144	1	0.754	0.298	13.95	15	1.273503081	0.960	0.380	0.01
Front	144	1	0.405	0.145	13.95	15	1.273503081	0.516	0.185	0.1
Top	144	1	1.01	0.422	13.95	15	1.273503081	1.286	0.537	0.07
Bottom	144	1	0.044	0.014	13.95	15	1.273503081	0.056	0.018	0.15
Left	144	1	0.149	0.06	13.95	15	1.273503081	0.190	0.076	0.12
Right	144	1	0.075	0.032	13.95	15	1.273503081	0.096	0.041	0.01
Top	116	1	0.855	0.401	13.18	15	1.52054753	1.300	0.610	0.09

Conclusion: PASS

Note:

Factor= Max. Scaled AV Power(W)/Measured Power(W)

Scaled SAR-1= Measured SAR\*Factor

Scaled-Final= Scaled SAR-1\*(1/Duty Cycle)

**(U-NII-3 Band)**

Test Position	Test CH	Duty Cycle	Measure SAR 1g(W/kg)	Measure SAR 10g(W/kg)	Conducted Power(dBm)	Tune up Power(dBm)	Factor	Scaled Final SAR 1g	Scaled Final SAR 10g	power drift
Back	151	1	0.767	0.304	14.96	15	1.009253	0.774	0.307	0.17
Front	151	1	0.353	0.13	14.96	15	1.009253	0.356	0.131	0.13
Top	151	1	1.14	0.437	14.96	15	1.009253	1.151	0.441	0.05
Bottom	151	1	0.036	0.012	14.96	15	1.009253	0.036	0.012	0.18
Left	151	1	0.195	0.075	14.96	15	1.009253	0.197	0.076	0.11
Right	151	1	0.077	0.033	14.96	15	1.009253	0.078	0.033	0.15
Top	159	1	1.11	0.428	14.56	15	1.106624	1.228	0.474	0.04
Conclusion: PASS										
Note: Factor= Max. Scaled AV Power(W)/Measured Power(W) Scaled SAR-1= Measured SAR*Factor Scaled-Final= Scaled SAR-1*(1/Duty Cycle)										

- Notes:**
1. For WiFi 2.4GHz: According to KDB 248227 D01, Because the highest reported SAR for 11n HT40 is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg, so the SAR for 11b/g/n HT20 mode can be exempted.
  2. For WiFi 5GHz: The initial test configuration for 2.4 GHz and 5 GHz OFDM transmission modes is determined by the 802.11 configuration with the highest maximum output power specified for production units, 11a mode has the maximum output power compared with other mode. So use the 11a as the initial SAR test configuration mode.
  3. The WIFI Duty cycle is 100%.
  4. WiFi and Bluetooth equipped with the same one antenna and use smart antenna switching technology, the WIFI and Bluetooth antenna can't transmit simultaneously, so the Simultaneously transmission SAR can be excluded.

## ANNEX A: System Check Results

Test Laboratory: Audix SAR Lab

Date: 24/08/2022

**CW 2450**

DUT: Dipole 2450 MHz D2450V2; Type: D2450V2; Serial: D2450V2 - SN:862

Communication System: UID 0, CW (0); Communication System Band: D2450 (2450.0 MHz); Frequency: 2450 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.8$  S/m;  $\epsilon_r = 39.2$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CW 2450MHz/Area Scan (61x71x1):** Interpolated grid: dx=2.000 mm, dy=2.000 mm

Maximum value of SAR (interpolated) = 15.5 W/kg


**Configuration/CW 2450MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.18 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 28.0 W/kg

**SAR(1 g) = 12.3 W/kg; SAR(10 g) = 5.5 W/kg**

Maximum value of SAR (measured) = 13.9 W/kg



Test Laboratory: Audix SAR Lab

Date: 25/08/2022

**CW 5250**

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1102

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5250 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 5200$  MHz;  $\sigma = 4.51$  S/m;  $\epsilon_r = 35.53$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(5.46, 5.46, 5.46); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CW 5250MHz/Area Scan (61x71x1):** Interpolated grid: dx=2.000 mm, dy=2.000 mm

Maximum value of SAR (interpolated) = 6.15 W/kg

**Configuration/CW 5250MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 46.79 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 28.7 W/kg

**SAR(1 g) = 8.2 W/kg; SAR(10 g) = 2.39 W/kg**

Maximum value of SAR (measured) = 9.67 W/kg



Test Laboratory: Audix SAR Lab

Date: 26/08/2022

**CW 5600**

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1102

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5600 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 5500$  MHz;  $\sigma = 4.82$  S/m;  $\epsilon_r = 35$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.8, 4.8, 4.8); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CW 5600MHz/Area Scan (61x71x1):** Interpolated grid: dx=2.000 mm, dy=2.000 mm

Maximum value of SAR (interpolated) = 6.38 W/kg

**Configuration/CW 5600MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 46.05 V/m; Power Drift = -0.20 dB

Peak SAR (extrapolated) = 30.7 W/kg

**SAR(1 g) = 8.47 W/kg; SAR(10 g) = 2.46 W/kg**

Maximum value of SAR (measured) = 10.3 W/kg



Test Laboratory: Audix SAR Lab

Date: 27/08/2022

**CW 5750**

DUT: Dipole D5GHzV2; Type: D5GHzV2; Serial: D5GHzV2 - SN:1102

Communication System: UID 0, CW (0); Communication System Band: D5GHz (5000.0 - 6000.0 MHz); Frequency: 5750 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.12$  S/m;  $\epsilon_r = 34.54$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(4.81, 4.81, 4.81); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CW 5750MHz/Area Scan (61x71x1):** Interpolated grid: dx=2.000 mm, dy=2.000 mm

Maximum value of SAR (interpolated) = 6.24 W/kg

**Configuration/CW 5750MHz/Zoom Scan (7x7x7)/Cube 0:** Measurement grid:


dx=5mm, dy=5mm, dz=5mm

Reference Value = 45.41 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 33.4 W/kg

**SAR(1 g) = 8.66 W/kg; SAR(10 g) = 2.27 W/kg**

Maximum value of SAR (measured) = 10.7 W/kg



## ANNEX B: Graph Results

### BDR+EDR:

Test Laboratory: Audix SAR Lab

Date: 24/08/2022

#### CH0(2402MHz Top)

DUT: Digital Media player M/N: YY1301B1

Communication System: UID 0, Blue Tooth (0); Communication System Band; Frequency: 2402 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 2402$  MHz;  $\sigma = 1.828$  S/m;  $\epsilon_r = 38.913$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH0(2402MHz Top)/Area Scan (61x81x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.624 W/kg

**Configuration/CH0(2402MHz Top)/Zoom Scan (5x5x7)/Cube 0:** Measurement


grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 15.16 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.56 W/kg

**SAR(1 g) = 0.281 W/kg; SAR(10 g) = 0.169 W/kg**

Maximum value of SAR (measured) = 0.575 W/kg





Test Laboratory: Audix SAR Lab

Date: 24/08/2022

**CH39(2441MHz Back)**

DUT: Digital Media player M/N: YY1301B1

Communication System: UID 0, Blue Tooth (0); Communication System Band; Frequency: 2441 MHz; Communication System PAR: 0 dB

Medium parameters used (interpolated):  $f = 2441$  MHz;  $\sigma = 1.878$  S/m;  $\epsilon_r = 38.734$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH39(2441MHz Back)/Area Scan (61x81x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.318 W/kg

**Configuration/CH39(2441MHz Back)/Zoom Scan (5x5x7)/Cube 0:**


Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 5.643 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.960 W/kg

**SAR(1 g) = 0.205 W/kg; SAR(10 g) = 0.125 W/kg**

Maximum value of SAR (measured) = 0.376 W/kg



**Test Laboratory: Audix SAR Lab**

Date: 24/08/2022

**CH39(2441MHz Bottom)**

**DUT: Digital Media player M/N: YY1301B1**

Communication System: UID 0, Blue Tooth (0); Communication System Band; Frequency: 2441 MHz; Communication System PAR: 0 dB

Medium parameters used (interpolated):  $f = 2441$  MHz;  $\sigma = 1.878$  S/m;  $\epsilon_r = 38.734$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH39(2441MHz Bottom)/Area Scan (61x81x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.0198 W/kg

**Configuration/CH39(2441MHz Bottom)/Zoom Scan (5x5x7)/Cube 0:**


Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 1.377 V/m; Power Drift = 0.18 dB

Peak SAR (extrapolated) = 0.0130 W/kg

**SAR(1 g) = 0.00652 W/kg; SAR(10 g) = 0.00268 W/kg**

Maximum value of SAR (measured) = 0.00723 W/kg



Test Laboratory: Audix SAR Lab

Date: 24/08/2022

**CH39(2441MHz Front)**

DUT: Digital Media player M/N: YY1301B1

Communication System: UID 0, Blue Tooth (0); Communication System Band; Frequency: 2441 MHz; Communication System PAR: 0 dB

Medium parameters used (interpolated):  $f = 2441$  MHz;  $\sigma = 1.878$  S/m;  $\epsilon_r = 38.734$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH39(2441MHz Front)/Area Scan (61x81x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.108 W/kg

**Configuration/CH39(2441MHz Front)/Zoom Scan (5x5x7)/Cube 0:**


Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 3.550 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 0.294 W/kg

**SAR(1 g) = 0.101 W/kg; SAR(10 g) = 0.040 W/kg**

Maximum value of SAR (measured) = 0.100 W/kg



Test Laboratory: Audix SAR Lab

Date: 24/08/2022

**CH39(2441MHz Left)**

DUT: Digital Media player M/N: YY1301B1

Communication System: UID 0, Blue Tooth (0); Communication System Band:; Frequency: 2441 MHz; Communication System PAR: 0 dB

Medium parameters used (interpolated):  $f = 2441$  MHz;  $\sigma = 1.878$  S/m;  $\epsilon_r = 38.734$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH39(2441MHz Left)/Area Scan (61x81x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.0328 W/kg

**Configuration/CH39(2441MHz Left)/Zoom Scan (5x5x7)/Cube 0:** Measurement


grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 1.849 V/m; Power Drift = 0.10 dB

Peak SAR (extrapolated) = 0.0580 W/kg

**SAR(1 g) = 0.027 W/kg; SAR(10 g) = 0.012 W/kg**

Maximum value of SAR (measured) = 0.0337 W/kg



Test Laboratory: Audix SAR Lab

Date: 24/08/2022

**CH39(2441MHz Right)**

DUT: Digital Media player M/N: YY1301B1

Communication System: UID 0, Blue Tooth (0); Communication System Band; Frequency: 2441 MHz; Communication System PAR: 0 dB

Medium parameters used (interpolated):  $f = 2441$  MHz;  $\sigma = 1.878$  S/m;  $\epsilon_r = 38.734$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH39(2441MHz Right)/Area Scan (61x81x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.0238 W/kg

**Configuration/CH39(2441MHz Right)/Zoom Scan (5x5x7)/Cube 0:**


Measurement grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 2.972 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.0300 W/kg

**SAR(1 g) = 0.017 W/kg; SAR(10 g) = 0.00749 W/kg**

Maximum value of SAR (measured) = 0.0203 W/kg



Test Laboratory: Audix SAR Lab

Date: 24/08/2022

**CH39(2441MHz Top)**

DUT: Digital Media player M/N: YY1301B1

Communication System: UID 0, Blue Tooth (0); Communication System Band; Frequency: 2441 MHz; Communication System PAR: 0 dB

Medium parameters used (interpolated):  $f = 2441$  MHz;  $\sigma = 1.878$  S/m;  $\epsilon_r = 38.734$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH39(2441MHz Top)/Area Scan (61x81x1):** Interpolated grid:

$dx = 1.500$  mm,  $dy = 1.500$  mm

Maximum value of SAR (interpolated) = 0.649 W/kg

**Configuration/CH39(2441MHz Top)/Zoom Scan (5x5x7)/Cube 0:** Measurement


grid:  $dx = 8$ mm,  $dy = 8$ mm,  $dz = 5$ mm

Reference Value = 14.47 V/m; Power Drift = -0.16 dB

Peak SAR (extrapolated) = 1.65 W/kg

**SAR(1 g) = 0.262 W/kg; SAR(10 g) = 0.175 W/kg**

Maximum value of SAR (measured) = 0.632 W/kg



**Test Laboratory: Audix SAR Lab**

Date: 24/08/2022

**CH78(2480MHz Top)****DUT: Digital Media player M/N: YY1301B1**

Communication System: UID 0, Blue Tooth (0); Communication System Band; Frequency: 2480 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 2480$  MHz;  $\sigma = 1.917$  S/m;  $\epsilon_r = 38.579$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH78(2480MHz Top)/Area Scan (61x81x1):** Interpolated grid:

dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.674 W/kg

**Configuration/CH78(2480MHz Top)/Zoom Scan (5x5x7)/Cube 0:** Measurement


grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.41 V/m; Power Drift = -0.13 dB

Peak SAR (extrapolated) = 1.81 W/kg

**SAR(1 g) = 0.274 W/kg; SAR(10 g) = 0.183 W/kg**

Maximum value of SAR (measured) = 0.619 W/kg



**BLE:**

**Test Laboratory: Audix SAR Lab**

Date: 24/08/2022

**CH0(2402MHz Top)**

**DUT: Digital Media player M/N: YY1301B1**

Communication System: UID 0, Blue Tooth (0); Communication System Band: Mid;

Frequency: 2402 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 2402$  MHz;  $\sigma = 1.828$  S/m;  $\epsilon_r = 38.913$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH0(2402MHz Top)/Area Scan (61x81x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.588 W/kg

**Configuration/CH0(2402MHz Top)/Zoom Scan (5x5x7)/Cube 0:** Measurement


grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 7.501 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.66 W/kg

**SAR(1 g) = 0.122 W/kg; SAR(10 g) = 0.055 W/kg**

Maximum value of SAR (measured) = 0.593 W/kg





Test Laboratory: Audix SAR Lab

Date: 24/08/2022

**CH19(2440MHz Top)**

DUT: Digital Media player M/N: YY1301B1

Communication System: UID 0, Blue Tooth (0); Communication System Band: Mid;

Frequency: 2440 MHz; Communication System PAR: 0 dB

Medium parameters used:  $f = 2440$  MHz;  $\sigma = 1.876$  S/m;  $\epsilon_r = 38.738$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3767; ConvF(7.61, 7.61, 7.61); Calibrated: 26/05/2022;
- Modulation Compensation:
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn899; Calibrated: 06/06/2022
- Phantom: SAM1; Type: SAM; Serial: TP-1543
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

**Configuration/CH19(2440MHz Top)/Area Scan (61x81x1):** Interpolated grid:

$dx=1.500$  mm,  $dy=1.500$  mm

Maximum value of SAR (interpolated) = 0.601 W/kg

**Configuration/CH19(2440MHz Top)/Zoom Scan (5x5x7)/Cube 0:** Measurement

grid:  $dx=8$ mm,  $dy=8$ mm,  $dz=5$ mm

Reference Value = 5.646 V/m; Power Drift = -0.19 dB

Peak SAR (extrapolated) = 1.73 W/kg

**SAR(1 g) = 0.133 W/kg; SAR(10 g) = 0.078 W/kg**

Maximum value of SAR (measured) = 0.654 W/kg

