

## FCC PART 15C TEST REPORT FOR CERTIFICATION

On Behalf of

Sony Group Corporation

Product: Sound Bar

Model No.: YY2088C; YY2091C

Active Speaker System: YY2088C1; YY2091C1

Active Subwoofer: YY2088C2; YY2091C2

FCC ID: AK8YY2088C1

Brand: SONY

EUT Name	EUT Model No.
Active Speaker System	YY2088C1

Prepared for : Sony Group Corporation  
1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Kefeng Road, Science & Technology Park,  
Nanshan District , Shenzhen, Guangdong, China

Tel: (0755) 26639496



Report Number : ACS-F24189  
Date of Test : Aug.08~Sep.30, 2024  
Date of Report : Oct.17, 2024

## TABLE OF CONTENTS

Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS</b> .....	<b>5</b>
1.1. Description of Standards and Results .....	5
<b>2. GENERAL INFORMATION</b> .....	<b>6</b>
2.1. Description of Equipment Under Test .....	6
2.2. Channel list of EUT .....	7
2.3. Tested Supporting System Details .....	7
2.4. Block Diagram of connection between EUT and simulators .....	8
2.5. Test information .....	8
2.6. Test Facility .....	9
2.7. Measurement Uncertainty (95% confidence levels, k=2) .....	9
<b>3. POWER LINE CONDUCTED EMISSION TEST</b> .....	<b>10</b>
3.1. Test Equipments .....	10
3.2. Block Diagram of Test Setup .....	10
3.3. Power Line Conducted Emission Test Limits .....	10
3.4. Configuration of EUT on Test .....	10
3.5. Operating Condition of EUT .....	11
3.6. Test Procedure .....	11
3.7. Power Line Conducted Emission Test Results .....	11
<b>4. RADIATED EMISSION MEASUREMENT</b> .....	<b>16</b>
4.1. Test Equipments .....	16
4.2. Block Diagram of Test Setup .....	17
4.3. Radiated Emission Limits Standard: .....	18
4.4. EUT Configuration on Test .....	18
4.5. Operating Condition of EUT .....	18
4.6. Test Procedure .....	19
4.7. Radiated Emission Test Results .....	19
<b>5. CONDUCTED SPURIOUS EMISSIONS</b> .....	<b>62</b>
5.1. Test Equipments .....	62
5.2. Limit .....	62
5.3. Test Procedure .....	62
5.4. Test result .....	62
<b>6. 6DB &amp; 99% BANDWIDTH TEST</b> .....	<b>69</b>
6.1. Test Equipments .....	69
6.2. Limit .....	69
6.3. Test Procedure .....	69
6.4. Test Results .....	70
<b>7. MAXIMUM PEAK OUTPUT POWER TEST</b> .....	<b>75</b>
7.1. Test Equipments .....	75
7.2. Limit .....	75
7.3. Test Procedure .....	75
7.4. Test Results .....	75
<b>8. BAND EDGE COMPLIANCE TEST</b> .....	<b>79</b>
8.1. Test Equipments .....	79
8.2. Limit .....	79
8.3. Test Produce .....	79
8.4. Test Results .....	80

<b>9.</b>	<b>POWER SPECTRAL DENSITY TEST .....</b>	<b>89</b>
9.1.	Test Equipments.....	89
9.2.	Limit.....	89
9.3.	Test Procedure .....	89
9.4.	Test Results.....	90
<b>10.</b>	<b>ANTENNA REQUIREMENT .....</b>	<b>93</b>
10.1.	STANDARD APPLICABLE.....	93
10.2.	ANTENNA CONNECTED CONSTRUCTION.....	93
<b>11.</b>	<b>DEVIATION TO TEST SPECIFICATIONS .....</b>	<b>94</b>

- Appendix A. Setup Photographs
- Appendix B. General Appearance of the EUT
- Appendix C. Inside Configuration of the EUT

## TEST REPORT

Applicant : Sony Group Corporation  
 Product : Sound Bar  
 Model No. : YY2088C; YY2091C  
 Active Speaker System : YY2088C1; YY2091C1  
 Active Subwoofer : YY2088C2; YY2091C2  
 Brand : SONY  
 FCC ID : AK8YY2088C1  
 Test Voltage : AC 120V/60Hz

Tested for comply with:  
 FCC CFR47 Part 15 Subpart C

Test procedure used:  
 ANSI C63.10:2020+COR1:2023;  
 KDB 558074 D01v05r02

The device described above is tested by Audix Technology (Shenzhen) Co., Ltd. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and Audix Technology (Shenzhen) Co., Ltd. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1074. No modifications were required during testing to bring this product into compliance.

This report applies to single evaluation of one sample of above mentioned product and shall not be reproduced in part without written approval of Audix Technology (Shenzhen) Co., Ltd..

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Date of Test : Aug.08~Sep.30, 2024 Date of Report: Oct.17, 2024

Prepared by : Dora Yang Reviewed by : Thomas Chen  
 Dora Yang / Assistant Manager Thomas Chen / Assistant Manager



Approved & Authorized Signer : Signature: Sunny Lu  
 Sunny Lu / Manager

# 1. SUMMARY OF STANDARDS AND RESULTS

## 1.1. Description of Standards and Results

The EUT has been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10:2020+COR1:2023	PASS
Radiated Emission Test	FCC Part 15: 15.209 FCC Part 15: 15.205 FCC Part 15: 15.247(d) ANSI C63.10:2020+COR1:2023	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(d) ANSI C63.10:2020+COR1:2023	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10:2020+COR1:2023	N/A
6dB Bandwidth Test	FCC Part 15: 15.247(a)(2) ANSI C63.10:2020+COR1:2023	PASS
Maximum Peak Output Power Test	FCC Part 15: 15.247(b)(1) ANSI C63.10:2020+COR1:2023	PASS
Band Edge Compliance Test	FCC Part 15: 15.247(d) ANSI C63.10:2020+COR1:2023	PASS
Power Spectral Density Test	FCC Part 15: 15.247(e) ANSI C63.10:2020+COR1:2023	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Note 1:N/A is an abbreviation for Not Applicable.		
Note 2: Measurement uncertainty affection to the result is not considered, the EUT is technically compliant with standard requirements.		

## 2. GENERAL INFORMATION

### 2.1. Description of Equipment Under Test

Applicant	Sony Group Corporation
Applicant Address	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan
Manufacturer	Sony Group Corporation
Manufacturer Address	1-7-1 Konan Minato-ku Tokyo, 108-0075 Japan
Product	Sound Bar
Model No.	YY2088C; YY2091C Model differences (Declared by the Applicant): Only model name different.
Active Speaker System	YY2088C1; YY2091C1
Active Subwoofer	YY2088C2; YY2091C2
Brand	SONY
EUT Name	Active Speaker System
EUT Model No.	YY2088C1
FCC ID	AK8YY2088C1
Radio	BDR+EDR, BLE, SRD
Frequency Range	BT(BDR+EDR, BLE): 2402-2480MHz SRD: 2403-2479MHz
Type of Modulation(BT)	GFSK, $\pi/4$ DQPSK, 8DPSK
Type of Modulation(SRD)	GFSK
Remote Control	Manufacturer: Sony; Model: RMT-AH513U
Power Cord	Unshielded, Detachable, 1.5m (2 pins)
HDMI Cable	Shielded, Detachable, 1.5m
Sample Type	Prototype production
Date of Receipt	Aug.06, 2024
Date of Test	Aug.08~Sep.30, 2024
The EUT covered in this report is Active Speaker System; This product (YY2088C,YY2091C) consists of Active Speaker System (YY2088C1,YY2091C) and Active Subwoofer (YY2088C2,YY2091C2)..	

Antenna System	
Type of Antenna	Active Speaker System SRD: PCB antenna Active Speaker System BT: PCB Antenna Active Subwoofer SRD: PCB Antenna
Antenna Peak Gain	Active Speaker System SRD: 3.35dBi Active Speaker System BT: 2.1dBi Active Subwoofer SRD: 2.95dBi


2.2.Channel list of EUT

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	---	---
13	2428	27	2456	---	---

2.3.Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number
1.	Monitor	ACS-EMC-BenQ-1	BenQ	EW3270-T	N/A
		Power Cord(3C): Unshielded, Detachabled, 1.8m			
2.	DVD Player	ACS-EMC-DVD02	PIONEER	DV-410v-G	N/A
		Power Cord(3C): Unshielded, Detachabled, 1.8m			
3.	Notebook	N/A	ACER	ZOW	N/A
		Power Cord(3C): Unshielded, Detachabled, 1.8m			
		Power Adaptor: Manufacturer: Lite-On, M/N: PA-1900-32 Cable: Unshielded, Undetectable, 4.0m(Bond one ferrite core)			

2.4. Block Diagram of connection between EUT and simulators



**(EUT: Active Speaker System)**

2.5. Test information

A special software (BT FCC Tool V2.24) was used to control EUT work in TX mode (GFSK modulation), and select test channel.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)	Channel	Frequency (MHz)
Tx Mode GFSK modulation	1	Low :CH0	2402
	1	Middle: CH19	2440
	1	High: CH39	2480
	2	Low :CH0	2402
	2	Middle: CH19	2440
	2	High: CH39	2480



2.6. Test Facility

Site Description

Name of Firm

: Audix Technology (Shenzhen) Co., Ltd.  
 No. 6, Kefeng Road, Science & Technology Park,  
 Nanshan District , Shenzhen, Guangdong, China

EMC Lab.

: Certificated by ISED, Canada  
 Company Number: 5183A  
 CAB identifier: CN0034  
 Valid Date: Mar.31, 2025

Certificated by FCC, USA  
 Designation No.: CN5022  
 Valid Date: Mar.31, 2025

Accredited by NVLAP, USA  
 NVLAP Code: 200372-0  
 Valid Date: Mar.31, 2026

2.7. Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	$\pm 2.6\text{dB}(150\text{KHz to } 30\text{MHz})$
Uncertainty for Radiation Emission test in 3m chamber	$\pm 3.8\text{dB}(30\sim 200\text{MHz, Polarization: H})$
	$\pm 3.8\text{dB}(30\sim 200\text{MHz, Polarization: V})$
	$\pm 4.0\text{dB}(200\text{M}\sim 1\text{GHz, Polarization: H})$
	$\pm 4.0\text{dB}(200\text{M}\sim 1\text{GHz, Polarization: V})$
Uncertainty for Radiation Emission test in 3m chamber(1GHz-18GHz)	$\pm 4.0\text{dB}(1\sim 6\text{GHz, Distance: } 3\text{m})$
	$\pm 4.0\text{dB}(6\sim 18\text{GHz, Distance: } 3\text{m})$
Uncertainty for $S_{\text{vswr}}$ in 3m Chamber	$\pm 2.8\text{dB}(1\sim 6\text{GHz})$
	$\pm 2.8\text{dB}(6\sim 18\text{GHz})$
Uncertainty for Radiated Spurious Emission test in RF chamber	$\pm 3.7\text{dB}(30\text{MHz}\sim 1000\text{MHz})$
	$\pm 3.3\text{dB}(1\sim 26.5\text{GHz})$
Uncertainty for Conduction Spurious emission test	$\pm 2.0\text{dB}$
Uncertainty for Output power test	$\pm 0.8\text{dB}$
Uncertainty for Bandwidth test	$\pm 4.6\%$
Uncertainty for DC power test	$\pm 0.1\%$
Uncertainty for test site temperature and humidity	$\pm 0.6^{\circ}\text{C}$
	$\pm 3\%$


### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Nov.09,22	3 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100842	Mar.16,24	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ENV216	102160	Jun.19,24	1 Year
4.	RF Cable	Eastsheep	RG223	190424	Sep.12,24	1Year
5.	Test Software	AUDIX	e3	6.100913a	N/A	N/A

Note: N/A means Not applicable.

#### 3.2. Block Diagram of Test Setup



#### 3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

- Notes: 1. \* Decreasing linearly with logarithm of frequency.  
 2. The lower limits shall apply at the transition frequencies.  
 3. Emission Level (dBμV) = Factor (L.I.S.N.) (dB) + Cable Loss (dB)+Reading (Receiver) (dBμV)

#### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

##### 3.4.1. Active Speaker System (EUT)

Model No. : YY2088C1  
 Serial No. : N/A

##### 3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.3.

### 3.5. Operating Condition of EUT

- 3.5.1. Setup the EUT as shown as Section 3.2.
- 3.5.2. Turn on the power of EUT.
- 3.5.3. PC run test software to control EUT work in Tx mode.

### 3.6. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. #1). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESCI) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.7. Power Line Conducted Emission Test Results


**PASS.** (All emissions not reported below are too low against the prescribed limits.)

BLE-1Mbps:

Data: 3

File: E:\1#CE\2024 Report Data\SI\SONYA1Z2408012-RF.EM6 (12)

Date: 2024-09-30




Trace: (Discrete)

Site no :1# CE Data No :3  
 Dis./Lisn :2024 ENV216-N  
 Limit :FCC PART 15 C  
 Env./Ins. :24.2\*C/54% Engineer :Hongjie  
 Power Rating :AC 120V/60Hz  
 Test Mode :BLE 1M TX Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	1.153	9.80	0.02	16.19	26.01	56.00	29.99	QP
2	2.692	9.81	0.04	23.45	33.30	56.00	22.70	QP
3	3.074	9.81	0.05	22.44	32.30	56.00	23.70	QP
4	4.598	9.83	0.06	23.02	32.91	56.00	23.09	QP
5	4.978	9.83	0.06	23.88	33.77	56.00	22.23	QP
6	5.683	9.84	0.06	26.45	36.35	60.00	23.65	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Data: 4 File: E:\1#CE\2024 Report Data\S\SONYA1Z2408012-RF.EM6 (12) Date: 2024-09-30



Trace: (Discrete)  
 Site no :1# CE Data No :4  
 Dis./Lisn :2024 ENV216-L  
 Limit :FCC PART 15 C  
 Env./Ins. :24.2°C/54% Engineer :Hongjie  
 Power Rating :AC 120V/60Hz  
 Test Mode :BLE 1M TX Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	1.153	9.78	0.02	16.71	26.51	56.00	29.49	QP
2	2.692	9.79	0.04	24.26	34.09	56.00	21.91	QP
3	3.074	9.80	0.05	21.36	31.21	56.00	24.79	QP
4	3.681	9.81	0.05	19.42	29.28	56.00	26.72	QP
5	4.598	9.81	0.06	23.11	32.98	56.00	23.02	QP
6	5.005	9.82	0.06	23.74	33.62	60.00	26.38	QP


Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

BLE-2Mbps:

Data: 5

File: E:\1#CE\2024 Report Data\SONYA1Z2408012-RF.EM6 (12)

Date: 2024-09-30




Trace: (Discrete)

Site no :1# CE Data No :5  
 Dis./Lisn :2024 ENV216-L  
 Limit :FCC PART 15 C  
 Env./Ins. :24.2°C/54% Engineer :Hongjie  
 Power Rating :AC 120V/60Hz  
 Test Mode :BLE 2M TX Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	1.153	9.78	0.02	15.71	25.51	56.00	30.49	QP
2	1.535	9.78	0.03	16.78	26.59	56.00	29.41	QP
3	2.692	9.79	0.04	21.95	31.78	56.00	24.22	QP
4	4.114	9.81	0.05	20.66	30.52	56.00	25.48	QP
5	4.598	9.81	0.06	23.01	32.88	56.00	23.12	QP
6	5.005	9.82	0.06	23.34	33.22	60.00	26.78	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

Data: 6 File: E:\1#CE\2024 Report Data\S\SONYA1Z2408012-RF.EM6 (12) Date: 2024-09-30



Trace: (Discrete)

Site no :1# CE Data No :6  
 Dis./Lisn :2024 ENV216-N  
 Limit :FCC PART 15 C  
 Env./Ins. :24.2°C/54% Engineer :Hongjie  
 Power Rating :AC 120V/60Hz  
 Test Mode :BLE 2M TX Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	2.692	9.81	0.04	22.64	32.49	56.00	23.51	QP
2	3.241	9.81	0.05	20.24	30.10	56.00	25.90	QP
3	3.642	9.82	0.05	19.58	29.45	56.00	26.55	QP
4	4.478	9.82	0.06	20.87	30.75	56.00	25.25	QP
5	4.978	9.83	0.06	22.26	32.15	56.00	23.85	QP
6	5.362	9.83	0.06	24.03	33.92	60.00	26.08	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION MEASUREMENT

### 4.1. Test Equipments

Frequency range: 30~1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3m Chamber(NSA)	AUDIX	N/A	N/A	Aug.11,22	3Year
2.	3m Chamber(SE)	AUDIX	N/A	N/A	Sep.16,22	3 Year
3.	Signal Analyzer	Rohde & Schwarz	FSV40	101608	Nov.07,23	1 Year
4.	Tri-log-Broadband Antenna	SCHWARZBECK	VULB 9168	429	Oct.10,23	1 Year
5.	NSA Cable	HUBER+SUHNER	CFD400NL-LW	No.3+190411	Sep.13,24	1 Year
6.	Coaxial Switch	Anritsu	MP59B	6201397223	Mar.17,24	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESR3	101931	Mar.17,24	1 Year
8.	Amplifier	HP	8447D	2944A11159	Mar.17,24	1 Year
9.	Test Software	AUDIX	e3	6.100913a	N/A	N/A

Note: N/A means Not applicable.


Frequency range: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3mChamber(Svswr)	AUDIX	N/A	N/A	Aug.09,22	3Year
2.	3mChamber(SE)	AUDIX	N/A	N/A	Sep.16,22	3Year
3.	Signal Analyzer	Rohde & Schwarz	FSV40	101608	Nov.07,23	1 Year
4.	Amplifier	EMCI	EMC0518A45S E	980965	Aug.13,24	1 Year
5.	RF Cable	TIMES MICROWAVE	SFT205-NMSM- 10.00M	689241	Aug.13,24	1 Year
6.	Test Software	AUDIX	e3	6.100913a	N/A	N/A
7.	Horn Antenna	EMCO	3115	9510-4580	Jan.08,22	3 Year


Note: N/A means Not applicable.



4.2. Block Diagram of Test Setup  
For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



4.3. Radiated Emission Limits Standard:

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

- Remark :
- (1) Emission Level (dBμV/m) = Reading (Receiver) (dBμV) + Antenna Factor (dB/m) + Cable Loss (dB)  
Emission Level (dBμV/m) = Reading (Spectrum) (dBμV) + Antenna Factor (dB/m) – Amp Factor (dB) + Cable Loss (dB)(above 1000MHz)
  - (2) The smaller limits shall apply at the cross point between two frequency bands.
  - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
  - (4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Active Speaker System (EUT)

Model Number : YY2088C1  
Serial Number : N/A

4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT and simulator as shown as Section 4.2.
- 4.5.2. Turn on the power of all equipments.
- 4.5.3. Let EUT work in BLE Tx mode.

#### 4.6. Test Procedure

##### **Frequency below 30MHz:**

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10 regulation.

##### **Frequency Above 30MHz:**

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)\*2.4m(W)\*0.3m(H) on the ground . The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it.EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10 on radiated emission Test.

The bandwidth of the EMI test receiver (R&S ESR3) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz.

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

#### 4.7. Radiated Emission Test Results

##### **PASS.**


All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.

Note1: The duty cycle factor for calculate average level is BLE-1Mbps: -1.253dB;  
BLE-2Mbps: -1.130dB.

Note 2: The emissions (9kHz~30MHz) not reported for there is no emission be found.


### BLE-1Mbps:

Duty cycle factor =  $20\log(\text{duty cycle}) = -1.253\text{dB}$




### BLE-2Mbps:

Duty cycle factor =  $20\log(\text{duty cycle}) = -1.130\text{dB}$



**Frequency: 30MHz~1GHz**  
**BLE-1Mbps:**


Data: 3 File: F:\2024 Report\SI\SONYA\A1Z2408012\A1Z2408012-RF.EM6 (12) Date: 2024-09-26



Site no. : 3m Chamber Data no. : 3  
 Dis. / Ant. : 3m 2023 VULB 9168-429 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 22.9\*C/53% Engineer : Abel  
 Test Mode : BLE1M TX MODE

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	95.96	14.60	0.85	14.29	29.74	43.50	13.76	QP
2	131.85	18.39	0.96	6.42	25.77	43.50	17.73	QP
3	144.46	19.30	1.00	7.67	27.97	43.50	15.53	QP
4	156.10	19.30	1.03	8.53	28.86	43.50	14.64	QP
5	168.71	18.83	1.07	9.15	29.05	43.50	14.45	QP
6	274.44	18.78	1.37	10.41	30.56	46.00	15.44	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2023 VULB 9168-429 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 22.9\*C/53% Engineer : Abel  
 Test Mode : BLE1M TX MODE

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	95.96	14.60	0.85	20.52	35.97	43.50	7.53	QP
2	204.60	15.72	1.18	18.05	34.95	43.50	8.55	QP
3	215.27	15.61	1.23	18.78	35.62	43.50	7.88	QP
4	251.16	17.92	1.33	17.87	37.12	46.00	8.88	QP
5	276.38	18.86	1.38	18.83	39.07	46.00	6.93	QP
6	287.05	19.14	1.40	17.62	38.16	46.00	7.84	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

**BLE-2Mbps:**




Site no. : 3m Chamber Data no. : 5  
 Dis. / Ant. : 3m 2023 VULB 9168-429 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 22.9\*C/53% Engineer : Abel  
 Test Mode : BLE2M TX MODE

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	95.96	14.60	0.85	19.59	35.04	43.50	8.46	QP
2	204.60	15.72	1.18	19.08	35.98	43.50	7.52	QP
3	216.24	15.62	1.23	19.47	36.32	46.00	9.68	QP
4	251.16	17.92	1.33	18.35	37.60	46.00	8.40	QP
5	276.38	18.86	1.38	18.53	38.77	46.00	7.23	QP
6	288.02	19.16	1.40	17.42	37.98	46.00	8.02	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 6 File: F:\2024 Report\SI\SONYA\1Z2408012\A\1Z2408012-RF.EM6 (12) Date: 2024-09-26



Site no. : 3m Chamber Data no. : 6  
 Dis. / Ant. : 3m 2023 VULB 9168-429 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 22.9\*C/53% Engineer : Abel  
 Test Mode : BLE2M TX MODE

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	48.43	19.64	0.64	3.84	24.12	40.00	15.88	QP
2	95.96	14.60	0.85	14.36	29.81	43.50	13.69	QP
3	143.49	19.25	1.00	7.53	27.78	43.50	15.72	QP
4	155.13	19.39	1.03	7.81	28.23	43.50	15.27	QP
5	167.74	18.90	1.07	8.91	28.88	43.50	14.62	QP
6	276.38	18.86	1.38	9.95	30.19	46.00	15.81	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



**Frequency: 1GHz~18GHz**

Test Mode	ANT. PLO.	Frequency (MHz)	Peak(dBuv/m)		Margin	Duty cycle factor (dB)	AV(dBuv/m)		Margin	Conclusion
			Emission Level	Limit			Emission Level	Limit		
BLE-1M	V	4804	45.97	74	28.03	-1.253	44.717	54	9.283	Pass
BLE-1M	H	4804	46.43	74	27.57	-1.253	45.177	54	8.823	Pass
BLE-1M	H	4880	46.55	74	27.45	-1.253	45.297	54	8.703	Pass
BLE-1M	V	4880	47.20	74	26.80	-1.253	45.947	54	8.053	Pass
BLE-1M	V	4960	46.91	74	27.09	-1.253	45.657	54	8.343	Pass
BLE-1M	H	4960	46.33	74	27.67	-1.253	45.077	54	8.923	Pass
BLE-2M	H	4804	46.06	74	27.94	-1.130	44.930	54	9.070	Pass
BLE-2M	V	4804	46.14	74	27.86	-1.130	45.010	54	8.990	Pass
BLE-2M	V	4880	46.08	74	27.92	-1.130	44.950	54	9.050	Pass
BLE-2M	H	4880	46.71	74	27.29	-1.130	45.580	54	8.420	Pass
BLE-2M	H	4960	46.94	74	27.06	-1.130	45.810	54	8.190	Pass
BLE-2M	V	4960	47.35	74	26.65	-1.130	46.220	54	7.780	Pass

**BLE-1Mbps:**




Site no. : 3m Chamber Data no. : 49  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2402MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	28.11	5.32	91.10	31.70	92.83	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 50 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-27




Site no. : 3m Chamber Data no. : 50  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2402MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	28.11	5.32	98.16	31.70	99.89	-----	-----	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 51 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29



Site no.	: 3m Chamber	Data no.	: 51
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK	Engineer	: epoch
Env. / Ins.	: 21.8*C/53.9%		
Test Mode	: BLE1M 2402MHz TX Mode		


Data: 52 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29



Site no. : 3m Chamber Data no. : 52  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2402MHz TX Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4804.00	32.71	7.41	36.27	30.42	45.97	74.00	28.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 53
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8*C/53.9%	Engineer	: epoch
Test Mode	: BLE1M 2402MHz TX Mode		

Data: 54 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29




Site no. : 3m Chamber Data no. : 54  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2402MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4804.00	32.71	7.41	36.73	30.42	46.43	74.00	27.57	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 55 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-27




Site no. : 3m Chamber Data no. : 55  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2440MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	28.26	5.37	89.97	31.68	91.92	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




Data: 56 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-27



Site no. : 3m Chamber Data no. : 56  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2440MHz TX Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	28.26	5.37	96.86	31.68	98.81	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 57
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8°C/53.9%	Engineer	: epoch
Test Mode	: BLE1M 2440MHz TX Mode		


Data: 58 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29



Site no. : 3m Chamber Data no. : 58  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2440MHz TX Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4880.00	32.86	7.45	36.65	30.41	46.55	74.00	27.45	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 59
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8*C/53.9%	Engineer	: epoch
Test Mode	: BLE1M 2440MHz TX Mode		


Data: 60 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29



Site no. : 3m Chamber Data no. : 60  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2440MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4880.00	32.86	7.45	37.30	30.41	47.20	74.00	26.80	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 61  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2480MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	28.30	5.41	96.05	31.66	98.10	-----	-----	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 62  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2480MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	28.30	5.41	88.40	31.66	90.45	-----	-----	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 63
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8*C/53.9%	Engineer	: epoch
Test Mode	: BLE1M 2480MHz TX Mode		




Data: 64 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29



Site no. : 3m Chamber Data no. : 64  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2480MHz TX Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4960.00	33.02	7.50	36.79	30.40	46.91	74.00	27.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 65
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8*C/53.9%	Engineer	: epoch
Test Mode	: BLE1M 2480MHz TX Mode		

Data: 66 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29




Site no. : 3m Chamber Data no. : 66  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE1M 2480MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4960.00	33.02	7.50	36.21	30.40	46.33	74.00	27.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

**BLE-2Mbps:**




Site no. : 3m Chamber Data no. : 67  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2402MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	28.11	5.32	90.54	31.70	92.27	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.


Data: 68 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-27



Site no. : 3m Chamber Data no. : 68  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2402MHz TX Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	28.11	5.32	97.53	31.70	99.26	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 69
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8*C/53.9%	Engineer	: epoch
Test Mode	: BLE2M 2402MHz TX Mode		


Data: 70 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29



Site no. : 3m Chamber Data no. : 70  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2402MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4804.00	32.71	7.41	36.36	30.42	46.06	74.00	27.94	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 71
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8*C/53.9%	Engineer	: epoch
Test Mode	: BLE2M 2402MHz TX Mode		



Data: 72 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29




Site no. : 3m Chamber Data no. : 72  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2402MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4804.00	32.71	7.41	36.44	30.42	46.14	74.00	27.86	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 73 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-27




Site no. : 3m Chamber Data no. : 73  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2440MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	28.26	5.37	97.12	31.68	99.07	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.


Data: 74 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-27



Site no. : 3m Chamber Data no. : 74  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2440MHz TX Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2440.00	28.26	5.37	88.92	31.68	90.87	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 75
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8°C/53.9%	Engineer	: epoch
Test Mode	: BLE2M 2440MHz TX Mode		

Data: 76 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29




Site no. : 3m Chamber Data no. : 76  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2440MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4880.00	32.86	7.45	36.18	30.41	46.08	74.00	27.92	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 77 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29



Site no.	: 3m Chamber	Data no.	: 77
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8*C/53.9%	Engineer	: epoch
Test Mode	: BLE2M 2440MHz TX Mode		

Data: 78 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29




Site no. : 3m Chamber Data no. : 78  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2440MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4880.00	32.86	7.45	36.81	30.41	46.71	74.00	27.29	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 79 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-27




Site no. : 3m Chamber Data no. : 79  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2480MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	28.30	5.41	95.54	31.66	97.59	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.







Site no. : 3m Chamber Data no. : 80  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2480MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	28.30	5.41	87.47	31.66	89.52	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no.	: 3m Chamber	Data no.	: 81
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: HORIZONTAL
Limit	: FCC PART 15C PEAK	Engineer	: epoch
Env. / Ins.	: 21.8*C/53.9%		
Test Mode	: BLE2M 2480MHz TX Mode		



Site no. : 3m Chamber Data no. : 82  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8°C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2480MHz TX Mode


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4960.00	33.02	7.50	36.82	30.40	46.94	74.00	27.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no.	: 3m Chamber	Data no.	: 83
Dis. / Ant.	: 3m 2022 3115-4580	Ant. pol.	: VERTICAL
Limit	: FCC PART 15C PEAK		
Env. / Ins.	: 21.8°C/53.9%	Engineer	: epoch
Test Mode	: BLE2M 2480MHz TX Mode		

Data: 84 File: F:\2024 Report\SI\SONYA1Z2408012\A1Z2408012.EM6 (148) Date: 2024-09-29



Site no. : 3m Chamber Data no. : 84  
 Dis. / Ant. : 3m 2022 3115-4580 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 21.8\*C/53.9% Engineer : epoch  
 Test Mode : BLE2M 2480MHz TX Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	4960.00	33.02	7.50	37.23	30.40	47.35	74.00	26.65	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.  
 2. The emission levels that are 20dB below the official limit are not reported.

## 5. CONDUCTED SPURIOUS EMISSIONS

### 5.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Mar.16,24	1 Year
2.	RF Cable	Eastsheep	RM086-SMA/N-JJ-2000	NO.1	Jun.19,24	1 Year
3.	Attenuator(10dB)	Agilent	8491B	MY39269201	Mar.16,24	1 Year

### 5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30dB instead of 20dB.

### 5.3. Test Procedure

Use the test method described in ANSI C63.10:

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions With peak detector.

### 5.4. Test result


**PASS** (The testing data was attached in the next pages.)

EUT: Active Speaker System		
M/N: YY2088C1		
Test date: 2024-08-21	Pressure: 102.4±1.0 kpa	Humidity: 54.7±3.0%
Tested by: Lili	Test site: RF site	Temperature:23.6±0.6 °C


**BLE-1Mbps:**

**GFSK**


**2402MHz**




**2402MHz(10GHz – 26GHz)**





**2402MHz(30MHz – 1GHz)**




**2402MHz(2.3GHz – 2.4GHz)**




**2402MHz(1GHz – 10GHz)**




2440MHz




2440MHz(1GHz – 10GHz)



2440MHz(30MHz – 1GHz)




2440MHz(10GHz – 26GHz)







2480MHz




2480MHz(10GHz – 26GHz)





2480MHz(30MHz – 1GHz)



2480MHz(2.4GHz – 2.5GHz)




2480MHz(1GHz – 10GHz)




**BLE-2Mbps:**

**GFSK**


**2402MHz**




**2402MHz(10GHz – 26GHz)**




**2402MHz(30MHz – 1GHz)**



**2402MHz(2.3GHz – 2.4GHz)**




**2402MHz(1GHz – 10GHz)**




---

---


2440MHz




2440MHz(1GHz – 10GHz)




2440MHz(30MHz – 1GHz)




2440MHz(10GHz – 26GHz)




2480MHz



2480MHz(10GHz – 26GHz)





2480MHz(30MHz – 1GHz)



2480MHz(2.4GHz – 2.5GHz)



2480MHz(1GHz – 10GHz)



## 6. 6DB & 99% BANDWIDTH TEST

### 6.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Mar.16,24	1 Year
2.	RF Cable	Eastsheep	RM086-SMA/ N-JJ-2000	NO.1	Jun.19,24	1 Year
3.	Attenuator(10dB)	Agilent	8491B	MY39269201	Mar.16,24	1 Year

### 6.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

### 6.3. Test Procedure

Use the test method described in ANSI C63.10 clause 11.8.2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e.,  $RBW = 100 \text{ kHz}$ ,  $VBW \geq 3 \times RBW$ , and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6 \text{ dB}$ .

Use the test method described in ANSI C63.10 clause 6.9.2:

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (OBW/RBW)]$  below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.

- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

#### 6.4. Test Results

**BLE-1Mbps:**

EUT: Active Speaker System

M/N: YY2088C1

Test date: 2024-08-21

Pressure: 101.3±1.0 kpa

Humidity: 52.4±3.0%

Tested by: Lili

Test site: RF site

Temperature: 23.1±0.6°C

Test Mode	Frequency (MHz)	6dB Bandwidth (KHz)	Limit (KHz)
GFSK	2402	725.0	≥500
	2440	722.0	≥500
	2480	725.6	≥500


Conclusion : PASS

**GFSK**

**2402MHz**



**2440MHz**



**2480MHz**

