



Audix Technology (Shenzhen) Co., Ltd.
 No. 6, Kefeng Road, Science & Technology Park,
 Nanshan District, Shenzhen, Guangdong, China

Tel: 0755 26639496
Fax: 0755 26632877

Maximum Permissive Exposure

FCC ID: AK8YY2088C1
 EUT Name: Active Speaker System
 M/N: YY2088C1

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	---	---	f/300	6
1500-100,000	---	---	5.0	6
(B) Limits for General Population / Uncontrolled Exposures (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	---	---	f/1500	30
1500-100,000	---	---	1.0	30

2. MPE Calculation

We declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

RF Exposure Calculations: $S = (P * G) / (4 * \pi * r^2)$ or $r = \sqrt{(P * G) / (4 * \pi * S)}$

Note: $\pi=3.1416$ in this report.



Audix Technology (Shenzhen) Co., Ltd.
No. 6, Kefeng Road, Science & Technology Park,
Nanshan District, Shenzhen, Guangdong, China

Tel: 0755 26639496
Fax: 0755 26632877

2.1. Estimation Result

EUT: Active Speaker System		
M/N:YY2088C1		
Date: 2024-10-24	Pressure: 102.6±1.0 kpa	Humidity: 54.4±3.0%
Tested by: Lili	Test Site: RF site	Temperature:23.6±0.6℃

Test Mode	Output Power (dBm)	Output Power (mW)	Antenna Gain (dBi)	Antenna Gain (Linear)	Power Density (mW/cm ²)	Result
BDR	6.863	4.8562	2.1	1.62	0.0016	PASS
EDR	7.661	5.8358	2.1	1.62	0.0019	PASS
BLE 1M	5.602	3.6325	2.1	1.62	0.0012	PASS
BLE 2M	5.480	3.5318	2.1	1.62	0.0011	PASS
2.4G	3.930	2.4717	3.35	2.16	0.0011	PASS
2.4G+BT	--	--	--	--	0.003	PASS