

Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-0066/20-01-04

Certification numbers and labeling requirements	
FCC ID	AL8-CB7321
ISED number	457A-CB7321
HVIN (Hardware Version Identification Number)	CB7321 CD CB7321-M CD
PMN (Product Marketing Name)	Savi 7310 Office Savi 7320 Office
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Mihail Dorongovskij
Lab Manager
Radio Communications



Marco Scigliano
Testing Manager
Radio Communications

EUT technologies:

Technologies:	Max. power conducted: (Peak)	Max. antenna gain
UPCS (Proprietary) 1925 MHz	Declared: 20.8 dBm Measured: 18.4 dBm	Measured: 0.8 dBi

NOTE: Results extracted from: Test report 1-0066_20-01-05.
CB7321 - 1-3753-1-4-Conducted-TuneUpInfo - WPKbaseR25-FW59
CB7321_S73XXT_Theory_of_Operation_v1

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
P = Power input to the antenna
G = Antenna gain
R = Distance to the center of radiation of the antenna

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

	1925 MHz
Technology	UPCS (Proprietary)
P Max power input to the antenna	20.8 dBm
R Distance	20 cm
G Antenna gain	0.8 dBi
S MPE limit for uncontrolled exposure	1 mW/cm ²
Calculated Power density:	0.0288 mW/cm ²
Calculated percentage of limit:	2.88 %

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

Prediction: worst case

	Frequency range	1925 MHz
	Technology	UPCS (Proprietary)
	Frequency	1920 MHz
P	Max power input to the antenna	20.8 dBm
R	Distance	20 cm
G	Antenna gain	0.8 dBi
	Maximum EIRP	144.5 mW
	Exclusion Limit from above:	2.30 W
	Calculated percentage of limit:	1.59 %

Conclusion: RF exposure evaluation is not required.