

## #01\_Bluetooth\_1Mbps\_Back\_0mm\_Ch0

Communication System: Bluetooth; Frequency: 2402.0 MHz; Duty Cycle: 1:1.299

Medium: HSL\_2450\_221102 Medium parameters used:  $f = 2402.0$  MHz;  $\sigma = 1.78$  S/m;  $\epsilon_r = 39.5$

Ambient Temperature: 23.5°C; Liquid Temperature: 22.5°C

### DASY6 Configuration:

- Probe: EX3DV4 - SN3728; ConvF(7.44, 7.44, 7.44); Calibrated: 2022-03-02
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn656; Calibrated: 2022-01-19
- Phantom: ELI V8.0 (20deg probe tilt); Serial: 2155; Section: Flat
- Measurement Software: 16.0.2.83
- UID: Bluetooth, 10032-CAA

**Area Scan (100.0 mm x 120.0 mm):** Measurement Grid: 10.0 mm x 10.0 mm

SAR (1g) = 0.197 W/kg; SAR (10g) = 0.097 W/kg;

**Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm):** Measurement Grid: 5.0 mm x 5.0 mm x 1.5 mm

Power Drift = 0.05 dB

SAR (1g) = 0.221 W/kg; SAR (8g) = 0.126 W/kg; SAR (10g) = 0.118 W/kg

