

Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-3165/21-01-04 MPE (FCC_ISED)

Certification numbers and labeling requirements	
FCC ID	AL8-W8200B1
ISED number	457A-W8200B1
HVIN (Hardware Version Identification Number)	W8200B1
PMN (Product Marketing Name)	Savi 8200 Office
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC



Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. power [dBm]		Antenna gain max.: [dBi]	Max declared EIRP	#
	conducted	EIRP			
BT EDR 2450 MHz	meas. 9.5	meas. 14.6	5.1 (declared)	14.0 dBm +/-1 dB	A
DECT UPCS 1925 MHz	meas. 18.3	meas.18.6	meas.1.4	18.0 dBm +/-1 dB	B

Details and origins of the measurements shown in the table above:

#	Results from:	Additional information
A	1-3165/21-01-05 CTC advanced GmbH	Antenna gain page 21, Max conducted page 25
B	1-2859/16-01-11-B CTC advanced GmbH	Antenna gain and max conducted page 17

Collocation overview:

Active scenario: Technology	1	2	3	4
BT EDR	x		x	
UPCS 1925		x	x	

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
P = Power input to the antenna
G = Antenna gain
R = Distance to the center of radiation of the antenna
PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

Technologies:		UPCS	BT EDR	
	Frequency (MHz)	1925	2450	
PG	Declared max power (EIRP)	19	15	dBm
R	Distance	20	20	cm
S	MPE limit for uncontrolled exposure	1	1	mW/cm ²
	Calculated Power density:	0.0158	0.0063	mW/cm ²
	Calculated percentage of Limit:	1.58%	0.63%	
Collocation:				
	Scenario 3: UPCS + BT EDR Calculated percentage of Limit:	2.21%		

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

Prediction: worst case

		UPCS	BT EDR	
	Frequency	1925	2450	MHz
R	Distance	20	20	cm
PG	Maximum EIRP	19	15	dBm
PG	Maximum EIRP	79.4	31.6	mW
	Exclusion Limit from above:	2.30	2.71	W
	Calculated percentage of Limit:	3.45%	1.17%	
Collocation:				
	Scenario 3: UPCS + BT DER	4.62%		
	Calculated percentage of Limit:			

Conclusion: RF exposure evaluation is not required.