

FCC Test Report

Report No.: AGC00036171201FE03

FCC ID : ALE12018

APPLICATION PURPOSE : Original Equipment

PRODUCT DESIGNATION: True wireless bluetooth earbuds

BRAND NAME: Jabees

MODEL NAME : 12018

CLIENT: FreeTek International Co., Ltd.

DATE OF ISSUE : Jan. 10, 2018

STANDARD(S)

TEST PROCEDURE(S) : FCC Part 15 Subpart C Section 15.249

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

& AGC PALAGE

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 2 of 58

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	2 / 2	Jan. 10, 2018	Valid	Initial release

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.

Attestation of Global Compliance



TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	
5.1. CONFIGURATION OF EUT SYSTEM 5.2. EQUIPMENT USED IN EUT SYSTEM 5.3. SUMMARY OF TEST RESULTS	8
6. TEST FACILITY	10
7. TEST METHOD	11
8. TEST EQUIPMENT LIST	11
9. RADIATED EMISSION	12
9.1TEST LIMIT	12
9.2. MEASUREMENT PROCEDURE	12
9.3. TEST SETUP 9.4. TEST RESULT	15
10. BAND EDGE EMISSION	
10.1. MEASUREMENT PROCEDURE	
10.2 TEST SETUP 10.3 RADIATED TEST RESULT	32 33
11. 20DB BANDWIDTH	
11.1. MEASUREMENT PROCEDURE	37
11.1. MEASUREMENT PROCEDURE	37 37
11.3. LIMITS AND MEASUREMENT RESULTS	37
12. FCC LINE CONDUCTED EMISSION TEST	
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	44
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	44
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	45
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	45 45
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	
	48
APPENDIX R. DHOTOGRADAS OF ELLI	48



age 4 of 58

1. VERIFICATION OF CONFORMITY

Applicant	FreeTek International Co., Ltd.
Address	Unit D, 15/F, Tai Ping Ind.Ctr., Blk 2, 55 Ting Kok Rd., Tai Po, HK
Manufacturer	FreeTek International Co., Ltd
Address	2nd Floor, NO.21-10 Xin'tang Road, Xin'tian Community, Fuyong, Bao'an District, Shenzhen, Guangdong, China
Product Designation	True wireless bluetooth earbuds
Brand Name	Jabees
Test Model	12018
Date of test	Jan. 02, 2018 to Jan. 05, 2018
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249. The test results of this report relate only to the tested sample identified in this report.

Tested By	pary lu	
Total By	Berg Lu(Lu Bing)	Jan. 05, 2018
Reviewed By	Forversto ce	
The State of the S	Forrest Lei(Lei Yonggang)	Jan. 10, 2018

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance



Page 5 of 58

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	1.83dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V5.0
Modulation	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK, BLE □GFSK
Number of channels	79 for BR/EDR
Hardware Version	V0.5
Software Version	V1.8
Antenna Designation	Fixed Antenna
Antenna Gain	0dBi
Power Supply	DC 3.7V
Note: 1. The EUT didn't support	C CC P P S

2.2. TABLE OF CARRIER FREQUENCYS

2. The BT function of EUT didn't work when charging.

BR/EDR channel List

Frequency Band	Channel Number	Frequency
Th. 18. 18.	0	2402MHz
23000	GO1 100	2403MHz
CC NO		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
4	38	2440 MHz
2400~2483.5MHz	39	2441 MHz
CO'S	40	2442 MHz
		5 - 65 CC
453	77	2479 MHz
G.	78	2480 MHz



Page 6 of 58

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.


- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB

4. DESCRIPTION OF TEST MODES


NO.	TEST MODE DESCRIPTION			
1	Low channel GFSK			
2 2 0	Middle channel GFSK			
3	High channel GFSK			
4	Low channel π /4-DQPSK			
5	Middle channel π /4-DQPSK			
6	High channel π /4-DQPSK			
7	Low channel 8DPSK			
8	Middle channel 8DPSK			
9	High channel 8DPSK			
10	BT Link			

Note:

- 1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT used fully-charged battery when tested.







The results shown in this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a type://www.agc.gett.com.

Attestation of Global Compliance



Page 8 of 58


5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)

EUT

Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Mfr/Brand	Model/Type No.	Remark	
1	True wireless bluetooth earbuds	Jabees	12018	EUT	
2	Battery	DING SHARP	DR501015	Accessory	
3	PC	APPLE	A1465	A.E	
4	Control box	AIROHA	N/A	A.E	
5	USB Cable	N/A	1m unshielded	A.E	



Page 9 of 58

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249(a) §15.209	Radiated Emission	Compliant
§15.249(d)	Band Edges	Compliant
§15.207	Conduction Emission	N/A
§15.215	Bandwidth	Compliant

Note: N/A means it's not applicable to this item.



Page 10 of 58

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd			
Location	1-2F., Bldg.2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District B112-B113, Bldg.12, Baoan Bldg Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen 518012			
NVLAP Lab Code	600153-0			
Designation Number	CN5028			
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by National Voluntary Laboratory Accreditation program, NVLAP Code 600153-0			



age 11 of 58

7. TEST METHOD

All measurements contained in this report were conducted with ANSI C63.10-2013

8. TEST EQUIPMENT LIST

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Jun.20, 2017	Jun.19, 2018
LISN	R&S	ESH2-Z5	100086	Aug.21, 2017	Aug.20, 2018

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun.20, 2017	Jun.19, 2018
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec.08, 2017	Dec.07, 2018
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.20, 2017	Sep.19, 2018
preamplifier	ChengYi	EMC184045SE	980508	Sep.15, 2017	Sep.14, 2018
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May 18, 2017	May 17, 2019
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun.20, 2017	Jun.19, 2018
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep.28, 2017	Sep.27, 2018
Loop Antenna	A.H.Systems,Inc	SAS-562B	.C =	Mar. 01, 2016	Feb. 28, 2018



Page 12 of 58

9. RADIATED EMISSION

9.1TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency	Distance	Field Str	engths Limit
(MHz)	Meters	μ V/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	30
0.490 ~ 1.705	30	24000/F(kHz)	- at 22
1.705 ~ 30	30	30	4-15-16-16-16-16-16-16-16-16-16-16-16-16-16-
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(µV)/m (Average)	(Peak) 54.0 dB(μV)/m

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



Page 13 of 58

9.2. MEASUREMENT PROCEDURE

- 1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
- 2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
- 3. The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
- 4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- 5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
- 6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.


Attestation of Global Compliance



Page 14 of 58

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz RBW 2MHz/ VBW 6MHz for Peak, RBW 1.5MHz/ VBW 10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP







9.3. TEST SETUP

RADIATED EMISSION TEST-SETUP FREQUENCY BELOW 30MHz




RADIATED EMISSION TEST SETUP 30MHz-1000MHz







RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 17 of 58

9.4. TEST RESULT

(Worst modulation: GFSK)


FOR BR/EDR

RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHz

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu√/m	dB		cm	degree	
1		114.0666	14.82	7.23	22.05	43.50	-21.45	peak			
2		269.2667	8.94	10.18	19.12	46.00	-26.88	peak			
3		374.3500	4.79	18.90	23.69	46.00	-22.31	peak			
4		548.9500	0.93	22.45	23.38	46.00	-22.62	peak			
5		733.2500	1.06	26.16	27.22	46.00	-18.78	peak			
6	*	854.5000	2.71	27.43	30.14	46.00	-15.86	peak			

RESULT: PASS



Page 18 of 58

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		164.1833	6.05	15.07	21.12	43.50	-22.38	peak			
2		266.0333	11.66	14.38	26.04	46.00	-19.96	peak			
3		384.0500	3.36	18.96	22.32	46.00	-23.68	peak			
4		607.1500	1.68	22.89	24.57	46.00	-21.43	peak			
5	*	778.5167	2.25	27.02	29.27	46.00	-16.73	peak			
6		972.5167	2.23	29.78	32.01	54.00	-21.99	peak			

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



Page 19 of 58

RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL




No). N	Иk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		- [MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1			102.7500	9.92	9.84	19.76	43.50	-23.74	peak			
2			301.6000	0.23	15.52	15.75	46.00	-30.25	peak			
3			367.8833	5.57	18.86	24.43	46.00	-21.57	peak			
4			523.0833	0.86	21.75	22.61	46.00	-23.39	peak			
5			772.0500	1.34	26.93	28.27	46.00	-17.73	peak			
6		*	899.7667	4.52	28.60	33.12	46.00	-12.88	peak			

RESULT: PASS



Page 20 of 58

RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL -VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		138.3167	4.45	14.50	18.95	43.50	-24.55	peak			
2		170.6500	4.84	14.66	19.50	43.50	-24.00	peak			
3		335.5500	6.77	17.78	24.55	46.00	-21.45	peak			
4		608.7667	1.20	22.93	24.13	46.00	-21.87	peak			
5	*	789.8333	2.13	27.18	29.31	46.00	-16.69	peak			
6		972.5167	2.91	29.78	32.69	54.00	-21.31	peak			

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



Page 21 of 58

RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL




	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
7		-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
	1	*	97.9000	26.86	8.38	35.24	43.50	-8.26	peak			
	2		136.7000	8.54	13.66	22.20	43.50	-21.30	peak			
ſ	3		375.9667	9.24	18.91	28.15	46.00	-17.85	peak			
	4		607.1500	1.52	23.75	25.27	46.00	-20.73	peak			
	5		859.3500	1.59	27.55	29.14	46.00	-16.86	peak			
	6		938.5667	2.24	29.68	31.92	46.00	-14.08	peak			

RESULT: PASS



Page 22 of 58

RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1		130.2332	9.79	11.13	20.92	43.50	-22.58	peak			
2		160.9499	8.63	15.27	23.90	43.50	-19.60	peak			
3		270.8833	7.38	14.53	21.91	46.00	-24.09	peak			
4		358.1832	5.85	18.79	24.64	46.00	-21.36	peak			
5		636.2500	2.18	23.54	25.72	46.00	-20.28	peak			
6	*	948.2667	1.58	29.95	31.53	46.00	-14.47	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.




Page 23 of 58

RADIATED EMISSION ABOVE 1GHz

(Worst modulation: GFSK)

FOR BR/EDR

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




N	0.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1			2402.000	86.71	10.32	97.03	114.00	-16.97	peak			
2	2	*	2402.000	78.37	10.32	88.69	94.00	-5.31	AVG	100	294	
3	3		3491.667	30.67	12.10	42.77	74.00	-31.23	peak			
4	ļ		4804.000	40.24	7.69	47.93	74.00	-26.07	peak			

RESULT: PASS



Page 24 of 58

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1		2402.000	86.32	10.32	96.64	114.00	-17.36	peak			
2	*	2402.000	77.99	10.32	88.31	94.00	-5.69	AVG	100	51	
3		3700.000	30.50	13.34	43.84	74.00	-30.16	peak			
4		4804.000	41.38	7.69	49.07	74.00	-24.93	peak			

RESULT: PASS



Page 25 of 58

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




ſ	Jo.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
3		-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
	1		2441.000	85.24	10.36	95.60	114.00	-18.40	peak			
ı	2	*	2441.000	77.00	10.36	87.36	94.00	-6.64	AVG	100	297	
	3		3616.667	30.42	12.83	43.25	74.00	-30.75	peak			
	4		4882.000	41.38	7.89	49.27	74.00	-24.73	peak			

RESULT: PASS



Page 26 of 58

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2441.000	84.99	10.36	95.35	114.00	-18.65	peak			
2	*	2441.000	76.70	10.36	87.06	94.00	-6.94	AVG	100	58	
3		3650.000	29.50	13.03	42.53	74.00	-31.47	peak			
4		4882.000	40.31	7.89	48.20	74.00	-25.80	peak			

RESULT: PASS



Page 27 of 58

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL




N	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
ı		-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
	1		2480.000	86.47	10.41	96.88	114.00	-17.12	peak			
Г	2	*	2480.000	78.06	10.41	88.47	94.00	-5.53	AVG	100	289	
	3		3758.333	28.91	13.70	42.61	74.00	-31.39	peak			
	4		4960.000	40.01	8.09	48.10	74.00	-25.90	peak			

DECIII T. DACC



Page 28 of 58

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



	No. Mk	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
3		-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
	1		2480.000	86.19	10.41	96.60	114.00	-17.40	peak			
	2	*	2480.000	77.73	10.41	88.14	94.00	-5.86	AVG	100	62	
	3		3600.000	30.15	12.73	42.88	74.00	-31.12	peak			
	4		4960.000	39.66	8.09	47.75	74.00	-26.25	peak			

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true and the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true and the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a sample (s) are retained for 30 days only.



Page 29 of 58

Field strength of the fundamental signal

1Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	86.71	10.32	97.03	114	-16.97	Horizontal	
2402	86.32	10.32	96.64	114	-17.36	Vertical	
2441	85.24	10.36	95.60	114	-18.40	Horizontal	
2441	84.99	10.36	95.35	114	-18.65	Vertical	
2480	86.47	10.41	96.88	114	-17.12	Horizontal	
2480	86.19	10.41	96.60	114	-17.40	Vertical	

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna Polarization	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)		
2402	78.37	10.32	88.69	94	-5.31	Horizontal	
2402	77.99	10.32	88.31	94	-5.69	Vertical	
2441	77.00	10.36	87.36	94	-6.64	Horizontal	
2441	76.70	10.36	87.06	94	-6.94	Vertical	
2480	78.06	10.41	88.47	94	-5.53	Horizontal	
2480	77.73	10.41	88.14	94	-5.86	Vertical	



Page 30 of 58

2Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	85.96	10.32	96.28	114	-17.72	Horizontal	
2402	85.57	10.32	95.89	114	-18.11	Vertical	
2441	84.44	10.36	94.80	114	-19.20	Horizontal	
2441	84.19	10.36	94.55	114	-19.45	Vertical	
2480	85.71	10.41	96.12	114	-17.88	Horizontal	
2480	85.43	10.41	95.84	114	-18.16	Vertical	

Average value

ASS - 10 - 10 - 10 - 10 - 10 - 10 - 10 -							
Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	77.57	10.32	87.89	94	-6.11	Horizontal	
2402	77.19	10.32	87.51	94	-6.49	Vertical	
2441	76.24	10.36	86.60	94	-7.40	Horizontal	
2441	75.94	10.36	86.30	94	-7.70	Vertical	
2480	77.28 10.41 8		87.69	94	-6.31	Horizontal	
2480	76.95	10.41	87.36	94	-6.64	Vertical	



Page 31 of 58

3Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	85.61	10.32	95.93	114	-18.07	Horizontal	
2402	85.29	10.32	95.61	114	-18.39	Vertical	
2441	84.12	10.36	94.48	114	-19.52	Horizontal	
2441	83.79	10.36	94.15	114	-19.85	Vertical	
2480	85.38	10.41	95.79	114	-18.21	Horizontal	
2480	85.04	10.41	95.45	114	-18.55	Vertical	

Average value

ACC - 10 - 10 - 10 - 10 - 10 - 10 - 10 -							
Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	77.23	10.32	87.55	94	-6.45	Horizontal	
2402	76.86	10.32	87.18	94	-6.82	Vertical	
2441	75.87	10.36	86.23	94	-7.77	Horizontal	
2441	75.55	10.36	85.91	94	-8.09	Vertical	
2480	76.96	10.41	87.37	94	-6.63	Horizontal	
2480	2480 76.62		87.03	94	-6.97	Vertical	



Page 32 of 58

10. BAND EDGE EMISSION


10.1. MEASUREMENT PROCEDURE

- 1. The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission.

Start frequency(MHz)	Stop frequency(MHz)
2200	2405
2478	2500

10.2 TEST SETUP

RADIATED EMISSION TEST SETUP





Page 33 of 58

10.3 RADIATED TEST RESULT

(Worst modulation: GFSK)

FOR BR/EDR

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal




No	No. Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1		2376.642	32.04	10.29	42.33	74.00	-31.67	peak			
2		2390.000	33.00	10.31	43.31	74.00	-30.69	peak			
3		2400.000	42.47	10.32	52.79	74.00	-21.21	peak			
4	*	2402.000	87.22	10.32	97.54	74.00	23.54	peak			
5	Х	2402.000	78.80	10.32	89.12	74.00	15.12	AVG	100	303	



Page 34 of 58

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu√/m	dB		cm	degree	
1		2377.667	31.97	10.30	42.27	74.00	-31.73	peak			
2		2390.000	31.71	10.31	42.02	74.00	-31.98	peak			
3		2400.000	36.06	10.32	46.38	74.00	-27.62	peak			
4	*	2402.000	87.09	10.32	97.41	74.00	23.41	peak			
5	Х	2402.000	78.54	10.32	88.86	74.00	14.86	AVG	100	59	



Page 35 of 58

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal




N	о.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
	1	*	2480.000	86.55	10.41	96.96	74.00	22.96	peak			
	2	Х	2480.000	78.34	10.41	88.75	74.00	14.75	AVG	100	297	
,	3		2483.500	33.69	10.41	44.10	74.00	-29.90	peak			
4	4		2487.716	33.68	10.42	44.10	74.00	-29.90	peak			



Page 36 of 58

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
1	*	2480.000	86.32	10.41	96.73	74.00	22.73	peak			
2	Х	2480.000	77.93	10.41	88.34	74.00	14.34	AVG	100	55	
3		2483.500	33.26	10.41	43.67	74.00	-30.33	peak			
4		2487.827	33.82	10.42	44.24	74.00	-29.76	peak			

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.



Report No.: AGC00036171201FE03


Page 37 of 58

11. 20DB BANDWIDTH

11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 2. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW; Sweep = auto; Detector function = peak
- 3. Set SPA Trace 1 Max hold, then View.

11.2. TEST SET-UP



11.3. LIMITS AND MEASUREMENT RESULTS


FOR BR/EDR

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT						
	Measurement Result					
Applicable Limits	Test Data (MHz)			D		
		99%OBW (MHz)	-20dB BW(MHz)	Result		
N/A	Low Channel	0.954	1.098	PASS		
	Middle Channel	0.951	1.104	PASS		
	High Channel	0.956	1.099	PASS		


The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XQC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.




TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.






TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.gott.com.


Attestation of Global Compliance





BLUET	OOTH 2MBPS LIN	MITS AND MEASU	REMENT RESULT		
	Measurement Result				
Applicable Limits	Test Data (MHz)			Decelle	
		99%OBW (MHz)	-20dB BW(MHz)	Result	
N/A	Low Channel	1.206	1.363	PASS	
	Middle Channel	1.211	1.358	PASS	
	High Channel	1.179	1.328	PASS	

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.gott.com.


Attestation of Global Compliance




TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XQC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.





BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT Measurement Result Applicable Limits Test Data (MHz) Result 99%OBW (MHz) -20dB BW(MHz) Low Channel 1.216 **PASS** 1.373 Middle Channel 1.216 1.380 **PASS** 1.375 **High Channel** 1.218 **PASS**

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.gott.com.


Attestation of Global Compliance



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Report No.: AGC00036171201FE03

Page 44 of 58

12. FCC LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF Line Voltage			
Frequency	Q.P.(dBuV)	Average(dBuV)		
150kHz~500kHz	66-56	56-46		
500kHz~5MHz	56	46		
5MHz~30MHz	60	50		

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XQC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Report No.: AGC00036171201FE03

Page 45 of 58

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- The test data of the worst case condition(s) was reported on the Summary Data page

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

Note: The BT function of EUT didn't work when charging.


The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago-gent.com.






APPENDIX A: PHOTOGRAPHS OF TEST SETUP


FCC RADIATED EMISSION TEST SETUP







The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance









The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.cett.com.



APPENDIX B: PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT



The results spowth this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true; //www.agc-gett.com.

Attestation of Global Compliance



BACK VIEW OF EUT



LEFT VIEW OF EUT



The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a type and the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a type of the confirmed at a type of type of the confirmed at a type of type of the confirmed at a type of type


Attestation of Global Compliance



RIGHT VIEW OF EUT



LEFTVIEW OF EUT (Port)




The results shown if this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.


Attestation of Global Compliance



OPEN VIEW OF EUT



INTERNAL VIEW OF EUT-1




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc-gett.com.


Attestation of Global Compliance



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com. IGC 8

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484

E-mail: agc@agc-cert.com


@ 400 089 2118



RIGHTVIEW OF EUT (Port)



OPEN VIEW OF EUT




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.cett.com.


Attestation of Global Compliance



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (SC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a three-like this community of the report will be confirmed at a three-like three-like

GC ? Attestation of Global Compliance

Tel: +86-755 2908 1955

Fax: +86-755 2600 8484

E-mail: agc@agc-cert.com


@ 400 089 2118



Report No.: AGC00036171201FE03

Page 56 of 58

INTERNAL VIEW OF EUT-3



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance



CHARGING CACE

TOP VIEW OF EUT




BOTTOM VIEW OF EUT



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance





VIEW OF EUT (Port)-1



VIEW OF EUT (Port)-2



----END OF REPORT----

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a trp://www.agc.cett.com.

Attestation of Global Compliance