



M. Flom Associates, Inc. - Global Compliance Center

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

T R A N S M I T T E R C E R T I F I C A T I O N

of

FCC ID: ALH29373220

MODELS : TK-760HG-2 and TK-762HG-2

to

FEDERAL COMMUNICATIONS COMMISSION

Rule Part(s) 22, 74, 90

DATE OF REPORT: October 26, 2000

ON THE BEHALF OF THE APPLICANT:

Kenwood Communications Corporation

AT THE REQUEST OF:

P.O. 40470

Kenwood Communications Corporation
P.O. Box 22745
Long Beach, CA 90801-5745

Attention of:

Joel E. Berger, Research & Development
JBerger@kenwoodusa.com
(310) 761-4409; FAX: -8246

SUPERVISED BY:

A handwritten signature in black ink, reading 'M. Flom P. Eng.', is written over a horizontal line.

Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	2
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a)	Carrier Output Power (Conducted)	7
2.1051	Unwanted Emissions (Transmitter Conducted)	9
2.1053(a)	Field Strength of Spurious Radiation	13
2.1049(c)(1)	Emission Masks (Occupied Bandwidth)	17
90.214	Transient Frequency Behavior	28
2.1047(a)	Audio Low Pass Filter (Voice Input)	46
2.1047(a)	Audio Frequency Response	49
2.1047(b)	Modulation Limiting	51
2.1055(a)(1)	Frequency Stability (Temperature Variation)	54
2.1055(b)(1)	Frequency Stability (Voltage Variation)	57
2.202(g)	Necessary Bandwidth and Emission Bandwidth	58

PAGE NO. 1 of 58.

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a) TEST REPORT

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85224

c) Report Number: d0070093

d) Client: Kenwood Communications Corporation
P.O. Box 22745
Long Beach, CA 90801-5745

e) Identification: TK-760HG-2 and TK-762HG-2
FCC ID: ALH29373220
Description: VHF FM Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: July 31, 2000
EUT Received: July 18, 2000

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



Morton Flom, P. Eng.

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

PAGE NO. 2 of 58.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATION

IN ACCORDANCE WITH FCC RULES AND REGULATIONS,
VOLUME II, PART 2 AND TO

22, 74, 90

Sub-part 2.1033

(c)(1): NAME AND ADDRESS OF APPLICANT:

Kenwood Communications Corporation
2201 E. Dominguez St
P.O. Box 22745
Long Beach, CA 90801-5745

MANUFACTURER:

Kenwood Electronics Technologies PTE Ltd.
1 Ang Mo Kio Street 63
Singapore 569110

(c)(2): FCC ID: ALH29373220

MODEL NO: TK-760HG-2 and TK-762HG-2

(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 16K0F3E, 11K0F3E

(c)(5): FREQUENCY RANGE, MHz: 136 to 162

(c)(6): POWER RATING, Watts: 10 to 50
___ Switchable ___ x Variable ___ N/A


FCC GRANT NOTE: BF - The output power is continuously variable from the value listed in this entry to 20%-25% of the value listed.

(c)(7): MAXIMUM POWER RATING, Watts: 300

PAGE NO.

3 of 58.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



**THE AMERICAN
ASSOCIATION
FOR LABORATORY
ACCREDITATION**

ACCREDITED LABORATORY

A2LA has accredited


M. FLOM ASSOCIATES, INC.
Chandler, AZ

for technical competence in the field of

Electrical (EMC) Testing


The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25-1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 24th day of November, 1998.



Peter Nijzen
President
For the Accreditation Council
Certificate Number 1008.01
Valid to December 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25-1990 AND EN 45001

M. FLOM ASSOCIATES, INC.
Electronic Testing Laboratory
3356 North San Marcos Place, Suite 107
Chandler, AZ 85225
Morton Flom Phone: 480 926 3100

ELECTRICAL (EMC)

Valid to: December 31, 2000 Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

Tests	Standard(s)
RF Emissions	FCC Part 15 (Subparts B and C) using ANSI C63.4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; FCC Part 18; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1; CNS 13438
RF Immunity	EN 50082-1; EN 50082-2; AS/NZS 4251.1
Radiated Susceptibility	EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3
ESD	EN 61000-4-2; IEC 1000-4-2; IEC 801-2
EFT	EN 61000-4-4; IEC 1000-4-4; IEC 801-4
Surge	EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5
47 CFR (FCC)	2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97

Revised 2/2/2000

Peter Nijzen

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8370 • Phone: 301 644 3248 • Fax: 301 662 2974

"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not be covered by this laboratory's A2LA accreditation.

PAGE NO. 4 of 58.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE,
INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A = per manual
COLLECTOR VOLTAGE, Vdc = per manual
SUPPLY VOLTAGE, Vdc = 13.6

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for
determining and stabilizing frequency, for suppression of
spurious radiation, for limiting modulation and limiting
power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

 ATTACHED EXHIBITS
 x N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

5 of 58.

Sub-part

2.1033(c)(14):

TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- ☐ 21 - Domestic Public Fixed Radio Services
- ☒ 22 - Public Mobile Services
- ☐ 22 Subpart H - Cellular Radiotelephone Service
- ☐ 22.901(d) - Alternative technologies and auxiliary services
- ☐ 23 - International Fixed Public Radiocommunication services
- ☐ 24 - Personal Communications Services
- ☒ 74 Subpart H - Low Power Auxiliary Stations
- ☐ 80 - Stations in the Maritime Services
- ☐ 80 Subpart E - General Technical Standards
- ☐ 80 Subpart F - Equipment Authorization for Compulsory Ships
- ☐ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- ☐ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- ☐ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- ☐ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- ☐ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- ☐ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- ☐ 80 Subpart X - Voluntary Radio Installations
- ☐ 87 - Aviation Services
- ☒ 90 - Private Land Mobile Radio Services
- ☐ 94 - Private Operational-Fixed Microwave Service
- ☐ 95 Subpart A - General Mobile Radio Service (GMRS)
- ☐ 95 Subpart C - Radio Control (R/C) Radio Service
- ☐ 95 Subpart D - Citizens Band (CB) Radio Service
- ☐ 95 Subpart E - Family Radio Service
- ☐ 95 Subpart F - Interactive Video and Data Service (IVDS)
- ☐ 97 - Amateur Radio Service
- ☐ 101 - Fixed Microwave Services

PAGE NO.

6 of 58.

STANDARD TEST CONDITIONS
and
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

PAGE NO. 7 of 58.

NAME OF TEST: Carrier Output Power (Conducted)

SPECIFICATION: 47 CFR 2.1046(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an R. F. Power Meter.
2. Measurement accuracy is $\pm 3\%$.

MEASUREMENT RESULTS
(Worst case)

FREQUENCY OF CARRIER, MHz = 149.05, 136.05, 161.95

POWER SETTING	R. F. POWER, WATTS
Low	10
High	50

SUPERVISED BY:




Morton Flom, P. Eng.

PAGE NO.

8 of 58.

TRANSMITTER POWER CONDUCTED MEASUREMENTS

TEST 1: R. F. POWER OUTPUT
 TEST 2: FREQUENCY STABILITY



Asset	Description (as applicable)	s/n
(1)	<u>COAXIAL ATTENUATOR</u>	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(2)	<u>POWER METERS</u>	
i00014	HP 435A	1733A05836
i00039	HP 436A	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(3)	<u>FREQUENCY COUNTER</u>	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A FREQUENCY MODE	2105A01087

PAGE NO. 9 of 58.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)

SPECIFICATION: 47 CFR 2.1051

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The emissions were measured for the worst case as follows:
 - (a): within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - (b): from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
2. The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.
3. MEASUREMENT RESULTS: ATTACHED FOR WORST CASE

FREQUENCY OF CARRIER, MHz	=	149.05, 136.05, 161.95
SPECTRUM SEARCHED, GHz	=	0 to 10 x F _c
MAXIMUM RESPONSE, Hz	=	3160
ALL OTHER EMISSIONS	=	≥ 20 dB BELOW LIMIT
LIMIT(S), dBc		
	-(50+10xLOG P)	= -60 (10 Watts)
	-(50+10xLOG P)	= -67 (50 Watts)

SUPERVISED BY:




Morton Flom, P. Eng.

PAGE NO.

10 of 58.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)
 TEST B. OUT-OF-BAND SPURIOUS



Asset Description (as applicable)	s/n
(1) <u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010 HP 204D	1105A04683
i00017 HP 8903A	2216A01753
i00012 HP 3312A	1432A11250
(2) <u>COAXIAL ATTENUATOR</u>	
i00122 Narda 766-10	7802
i00123 Narda 766-10	7802A
i00069 Bird 8329 (30 dB)	1006
i00113 Sierra 661A-3D	1059
(3) <u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126 Eagle TNF-1	100-250
i00125 Eagle TNF-1	50-60
i00124 Eagle TNF-1	250-850
(4) <u>SPECTRUM ANALYZER</u>	
i00048 HP 8566B	2511A01467
i00029 HP 8563E	3213A00104

PAGE NO. 11 of 58.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
 g0070601: 2000-Jul-20 Thu 10:12:00
 STATE: 1:Low Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
136.050000	272.100000	-25.8	-65.8	-5.8
149.050000	298.114000	-41.8	-81.8	-21.8
161.950000	324.400000	-42.9	-82.9	-22.9
136.050000	408.154000	-43.4	-83.4	-23.4
149.050000	447.147000	-43.1	-83.1	-23.1
161.950000	485.423000	-42.1	-82.1	-22.1
136.050000	544.339000	-43.7	-83.7	-23.7
149.050000	595.723000	-42.4	-82.4	-22.4
161.950000	647.752000	-42.9	-82.9	-22.9
136.050000	680.160000	-43.4	-83.4	-23.4
149.050000	745.306000	-43.3	-83.3	-23.3
161.950000	809.741000	-43.6	-83.6	-23.6
136.050000	816.524000	-42.9	-82.9	-22.9
149.050000	894.254000	-43.5	-83.5	-23.5
136.050000	952.388000	-42	-82	-22
161.950000	971.485000	-42.9	-82.9	-22.9
149.050000	1042.861000	-42.9	-82.9	-22.9
136.050000	1088.671000	-43	-83	-23
161.950000	1133.654000	-42.7	-82.7	-22.7
149.050000	1192.147000	-43.3	-83.3	-23.3
136.050000	1224.721000	-43.2	-83.2	-23.2
161.950000	1295.504000	-43	-83	-23
149.050000	1341.795000	-42.8	-82.8	-22.8
136.050000	1360.978000	-43.3	-83.3	-23.3
161.950000	1457.635000	-42.7	-82.7	-22.7
149.050000	1490.560000	-42.6	-82.6	-22.6
136.050000	1496.331000	-41.9	-81.9	-21.9
161.950000	1619.202000	-42.1	-82.1	-22.1
136.050000	1632.219000	-42.5	-82.5	-22.5
149.050000	1639.521000	-42.6	-82.6	-22.6
136.050000	1768.381000	-42.6	-82.6	-22.6
161.950000	1780.974000	-42.1	-82.1	-22.1
149.050000	1788.872000	-42.4	-82.4	-22.4
136.050000	1904.339000	-42.2	-82.2	-22.2
149.050000	1937.831000	-41.4	-81.4	-21.4
161.950000	1943.021000	-42.3	-82.3	-22.3
136.050000	2040.801000	-41.9	-81.9	-21.9
149.050000	2087.175000	-41.5	-81.5	-21.5
161.950000	2105.469000	-41.9	-81.9	-21.9
149.050000	2236.173000	-41.3	-81.3	-21.3
161.950000	2267.035000	-41.8	-81.8	-21.8
161.950000	2429.239000	-41	-81	-21

PAGE NO. 12 of 58.

NAME OF TEST: Unwanted Emissions (Transmitter Conducted)
 g0070600: 2000-Jul-20 Thu 10:10:00
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	LEVEL, dBm	LEVEL, dBc	MARGIN, dB
136.050000	272.108000	-31.7	-78.6	-11.7
149.050000	298.092000	-32.8	-79.7	-12.8
161.950000	324.164000	-33.3	-80.2	-13.3
136.050000	408.169000	-32.8	-79.7	-12.8
149.050000	447.250000	-32.2	-79.1	-12.2
161.950000	485.891000	-32.4	-79.3	-12.4
136.050000	544.180000	-34	-80.9	-14
149.050000	596.494000	-32.3	-79.2	-12.3
161.950000	648.249000	-33.4	-80.3	-13.4
136.050000	680.625000	-33.3	-80.2	-13.3
149.050000	745.447000	-32.3	-79.2	-12.3
161.950000	810.023000	-33.1	-80	-13.1
136.050000	816.580000	-33.4	-80.3	-13.4
149.050000	894.743000	-32.2	-79.1	-12.2
136.050000	952.781000	-33.4	-80.3	-13.4
161.950000	971.589000	-33	-79.9	-13
149.050000	1043.450000	-32.6	-79.5	-12.6
136.050000	1088.078000	-32.6	-79.5	-12.6
161.950000	1133.412000	-32.5	-79.4	-12.5
149.050000	1192.195000	-33.2	-80.1	-13.2
136.050000	1224.194000	-33.1	-80	-13.1
161.950000	1295.557000	-32.9	-79.8	-12.9
149.050000	1341.738000	-32.4	-79.3	-12.4
136.050000	1360.078000	-33.1	-80	-13.1
161.950000	1457.914000	-32	-78.9	-12
149.050000	1490.890000	-32.5	-79.4	-12.5
136.050000	1496.103000	-32.9	-79.8	-12.9
161.950000	1619.708000	-33	-79.9	-13
136.050000	1632.482000	-32.8	-79.7	-12.8
149.050000	1639.425000	-32.7	-79.6	-12.7
136.050000	1768.526000	-33.1	-80	-13.1
161.950000	1781.509000	-31.9	-78.8	-11.9
149.050000	1788.288000	-32.8	-79.7	-12.8
136.050000	1905.163000	-30.5	-77.4	-10.5
149.050000	1938.039000	-32.1	-79	-12.1
161.950000	1943.598000	-32.8	-79.7	-12.8
136.050000	2040.888000	-31.3	-78.2	-11.3
149.050000	2086.815000	-31.9	-78.8	-11.9
161.950000	2104.990000	-30.2	-77.1	-10.2
149.050000	2235.572000	-32	-78.9	-12
161.950000	2266.875000	-32.5	-79.4	-12.5
161.950000	2429.744000	-30.7	-77.6	-10.7

PAGE NO. 13 of 58.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)


GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 1.2.12

MEASUREMENT PROCEDURE

1.2.12.1 Definition: Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

1.2.12.2 Method of Measurement


- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth ≤ 3 kHz.
 - 2) Video Bandwidth ≥ 10 kHz
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Positive Peak
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load which is placed on the turntable. The RF cable to this load should be of minimum length.



PAGE NO. 14 of 58.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

PAGE NO. 15 of 58.

NAME OF TEST: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =
 $10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step l)}$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment:

Asset Description (as applicable)	s/n	Cycle	Last Cal
<small>Per ANSI C63.4-1992/2000 Draft, 10.1.4</small>			
<u>TRANSDUCER</u>			
i00088 EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-00
i00065 EMCO 3301-B Active Monopole	2635	12 mo.	Sep-00
i00089 Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-00
i00103 EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-00
<u>AMPLIFIER</u>			
i00028 HP 8449A	2749A00121	12 mo.	Mar-00
<u>SPECTRUM ANALYZER</u>			
i00029 HP 8563E	3213A00104	12 mo.	Aug-00
i00033 HP 85462A	3625A00357	12 mo.	May-00
i00048 HP 8566B	2511AD1467	6 mo.	May-00

PAGE NO. 16 of 58.

NAME OF TEST: Field Strength of Spurious Radiation
 g0070792: 2000-Jul-21 Fri 08:55:00
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	@m	ERP, dBm	ERP, dbc
149.01	298.100000	3	-48.4	-92.4
149.01	447.163000	3	-44	-88.0
149.01	596.213000	3	-46.5	-90.5
149.01	745.263000	3	-38.6	-82.6
149.01	894.313000	3	-47.8	-91.8
149.01	1043.363000	3	-50.9	-94.9
149.01	1192.413000	3	-48.9	-92.9
149.01	1341.449000	3	-49.1	-93.1
149.01	1490.487000	3	-46.1	-90.1
149.01	1639.534000	3	-43.9	-87.9

PAGE NO. 17 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)

SPECIFICATION: 47 CFR 2.1049(c)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page, with the Spectrum Analyzer connected.
2. For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
3. For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
4. The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

18 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070591: 2000-Jul-19 Wed 14:32:00
 STATE: 1:Low Power



POWER:

LOW

MODULATION:

NONE


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

19 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070592: 2000-Jul-19 Wed 14:44:00
 STATE: 1:Low Power



POWER:
 MODULATION:

LOW
 VOICE: 2500 Hz SINE WAVE
 MASK: B, VHF/UHF 25kHz,
 w/LPF


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

20 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070595: 2000-Jul-19 Wed 14:49:00
 STATE: 1:Low Power



POWER:

LOW

MODULATION:

VOICE: 2500 Hz SINE WAVE

MASK: D, VHF/UHF 12.5kHz BW


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

21 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070597: 2000-Jul-20 Thu 09:30:00
 STATE: 1:Low Power



POWER:
 MODULATION:

LOW
 DATA @ 19200 BITS PER
 SECOND
 MASK: B, VHF/UHF 25kHz,
 w/LPF


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

22 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070598: 2000-Jul-20 Thu 09:35:00
 STATE: 1:Low Power



POWER:
 MODULATION:

LOW
 DATA @ 9600 BITS PER SECOND
 MASK: D, VHF/UHF 12.5kHz BW

M. Flom P. Eng.


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

23 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070590: 2000-Jul-19 Wed 14:30:00
 STATE: 2:High Power



POWER: HIGH
 MODULATION: NONE

M. Flom P. Eng.


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

24 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070593: 2000-Jul-19 Wed 14:45:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 VOICE: 2500 Hz SINE WAVE
 MASK: B, VHF/UHF 25kHz,
 w/LPF


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

25 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070594: 2000-Jul-19 Wed 14:48:00
 STATE: 2:High Power



POWER:

HIGH

MODULATION:

VOICE: 2500 Hz SINE WAVE

MASK: D, VHF/UHF 12.5kHz BW


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

26 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070596: 2000-Jul-20 Thu 09:26:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 DATA @ 19200 BITS PER
 SECOND
 MASK: B, VHF/UHF 25kHz,
 w/LPF


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

27 of 58.

NAME OF TEST: Emission Masks (Occupied Bandwidth)
 g0070599: 2000-Jul-20 Thu 09:37:00
 STATE: 2:High Power



POWER:
 MODULATION:

HIGH
 DATA @ 9600 BITS PER SECOND
 MASK: D, VHF/UHF 12.5kHz BW

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 28 of 58.

NAME OF TEST: Transient Frequency Behavior

SPECIFICATION: 47 CFR 90.214

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.
2. The transmitter was turned on.
3. Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded as step f.
4. The transmitter was turned off.
5. An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step f, as measured at the output of the combiner. This level was then fixed for the remainder of the test and is recorded at step h.
6. The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
7. The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded as step l.
8. The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.

LEVELS MEASURED:

<u>step f</u> , dBm	= -21.5
<u>step h</u> , dBm	= -45.2
<u>step l</u> , dBm	= 5.6




SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

29 of 58.


TRANSIENT FREQUENCY BEHAVIOR

Asset	Description (as applicable)	s/n
(1)	<u>ATTENUATOR</u> (Removed after 1st step)	
	i00112 Philco 30 dB	989
(2)	<u>ATTENUATOR</u>	
	i00112 Philco 30 dB	989
	i00172 Bird 30 dB	989
	i00122 Narda 10 dB	7802
	i00123 Narda 10 dB	7802A
	i00110 Kay Variable	145-387
(3)	<u>COMBINER</u>	
	i00154 4 x 25 Ω COMBINER	154
(4)	<u>CRYSTAL DETECTOR</u>	
	i00159 HP 8470B	1822A10054
(5)	<u>RF SIGNAL GENERATOR</u>	
	i00018 HP 8656A	2228A03472
	i00031 HP 8656A	2402A06180
	i00067 HP 8920A	3345U01242
(6)	<u>MODULATION ANALYZER</u>	
	i00020 HP 8901A	2105A01087
(7)	<u>SCOPE</u>	
	i00030 HP 54502A	2927A00209

PAGE NO.

30 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070768: 2000-Jul-20 Thu 11:53:00
 STATE: 2:High Power



Unit	Min/Max	Ref/Dev	Ref/Dev	Mod
F 00	0.00	0.0000	0.0000	0.0000
Channel 1	0.00	0.0000	0.0000	0.0000
Modulation	0.00	0.0000	0.0000	0.0000
Ref Gen	0.00	0.0000	0.0000	0.0000
Modulation	0.00	0.0000	0.0000	0.0000
Ref Gen	0.00	0.0000	0.0000	0.0000
Modulation	0.00	0.0000	0.0000	0.0000

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER ON TIME VOICE ONLY


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

31 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070769: 2000-Jul-20 Thu 11:53:00
 STATE: 2:High Power



Unit	Min/Max	Ref/Dev	Ref/Dev	Mod
F 00	0.00	00.0000	0.0000	0.0000
Channel 1	0.00	0.0000	0.0000	0.0000
Modulation	0.00	0.0000	0.0000	0.0000
Ref Gen	0.00	0.0000	0.0000	0.0000
Modulation	0.00	0.0000	0.0000	0.0000
Unit	0.00	0.0000	0.0000	0.0000
Unit	0.00	0.0000	0.0000	0.0000

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER ON TIME VOICE ONLY

M. Flom P. Eng.

SUPERVISED BY:

Morton Flom, P. Eng.


PAGE NO.

32 of 58.

NAME OF TEST: Transient Frequency Behavior

```
g0070770: 2000-Jul-20 Thu 11:58:00
```

STATE: 2:High Power

[illegible]

POWER:
MODULATION:
DESCRIPTION:

HIGH
Ref Gen=25 kHz Deviation
CARRIER OFF TIME VOICE ONLY

Am. Inst. P. Eng.


Morton Flom, P. Eng.

SUPERVISED BY:

PAGE NO.

33 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070771: 2000-Jul-20 Thu 11:58:00
 STATE: 2:High Power



POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER OFF TIME VOICE ONLY


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

34 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070772: 2000-Jul-20 Thu 12:02:00
 STATE: 2:High Power



Unit	Min/Max	Ref/Dev	Ref/Dev	Mod
Hz	0.00 MHz	00.0000 MHz	0.0000 MHz	0.0000 MHz
Channel 1	0.00 MHz	0.0000 MHz	1.000 1	0.0000 MHz
Modulation Mode: Freq				
No. Modulation Modes: 06				
Modulation Index: 1.000				
Unit	Min/Max	Ref/Dev	Ref/Dev	Mod
Hz	0.00 MHz	0.0000 MHz	1.000 1	0.0000 MHz

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER ON TIME VOICE ONLY


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

35 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070773: 2000-Jul-20 Thu 12:02:00
 STATE: 2:High Power



Unit	Min/Max	Ref (Peak)	Ref (Avg)	Mod
Hz	0.00 - 10.00	00.0000	00.0000	Modulation
Channel 1	0.00 - 10.00	00.0000	00.0000	Modulation
Modulation	0.00 - 10.00	00.0000	00.0000	Modulation
Ref Modulation	0.00 - 10.00	00.0000	00.0000	Modulation
Modulation	0.00 - 10.00	00.0000	00.0000	Modulation
Modulation	0.00 - 10.00	00.0000	00.0000	Modulation

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER ON TIME VOICE ONLY


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

36 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070774: 2000-Jul-20 Thu 12:16:00
 STATE: 2:High Power



Unit	Min/Max	Ref/Dev	Ref/Dev	Mod
	Fc	15.0000	15.0000	15.0000
Channel 1	300	0.0000	1.000	1.000
Modulation	12.5	0.0000	1.000	1.000
Ref Deviation	12.5	0.0000	1.000	1.000
Modulation Index	12.5	0.0000	1.000	1.000
Modulation Index	12.5	0.0000	1.000	1.000

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER OFF TIME VOICE ONLY


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

37 of 58.

```
NAME OF TEST:      Transient Frequency Behavior
g0070775: 2000-Jul-20 Thu 12:16:00
STATE: 2:High Power
```

[illegible]

POWER:
MODULATION:
DESCRIPTION:

HIGH
Ref Gen=12.5 kHz Deviation
CARRIER OFF TIME VOICE ONLY

Am. Inst. P. Eng.


Morton Flom, P. Eng.

SUPERVISED BY:

PAGE NO.

38 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070786: 2000-Jul-20 Thu 13:00:00
 STATE: 2:High Power



```

Main           Min             Max             Ref             Mod
F 00 mV/div   00.0000 uV   00.0000 uV   00.0000 uV   00.0000 uV

Channel 1      500 mV/div   00.0000 uV   1.000 1   2 (1M ohm)

Main           Min             Max             Ref             Mod
F 00 mV/div   00.0000 uV   00.0000 uV   00.0000 uV   00.0000 uV

Main           Min             Max             Ref             Mod
F 00 mV/div   00.0000 uV   00.0000 uV   00.0000 uV   00.0000 uV

Main           Min             Max             Ref             Mod
F 00 mV/div   00.0000 uV   00.0000 uV   00.0000 uV   00.0000 uV
  
```

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER ON TIME WITH DATA


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

39 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070787: 2000-Jul-20 Thu 13:00:00
 STATE: 2:High Power



POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER ON TIME WITH DATA


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

40 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070784: 2000-Jul-20 Thu 12:51:00
 STATE: 2:High Power



POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER OFF TIME WITH DATA


SUPERVISED BY:

Morton Flom P. Eng.
 Morton Flom, P. Eng.

PAGE NO.

41 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070785: 2000-Jul-20 Thu 12:51:00
 STATE: 2:High Power



POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=25 kHz Deviation
 CARRIER OFF TIME WITH DATA

M. Flom P. Eng.


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

42 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070788: 2000-Jul-20 Thu 13:05:00
 STATE: 2:High Power



Unit	Min/Max	Ref/Dev	Ref/Dev	Mod
Hz	0.00 MHz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Channel 1	0.00 MHz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Modulation	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Ref Gen	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Modulation	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Ref Gen	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Modulation	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER ON TIME WITH DATA


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

43 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070789: 2000-Jul-20 Thu 13:05:00
 STATE: 2:High Power



Unit	Min/Max	Ref/Dev	Ref/Dev	Mod
Hz	0.00 MHz	00.0000 Hz	0.0000 Hz	0.0000 Hz
Channel 1	0.00 MHz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Modulation	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Ref Gen	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Modulation	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Unit	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Ref Gen	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz
Modulation	0.00 Hz	0.0000 Hz	0.0000 Hz	0.0000 Hz

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER ON TIME WITH DATA


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

45 of 58.

NAME OF TEST: Transient Frequency Behavior
 g0070791: 2000-Jul-20 Thu 14:27:00
 STATE: 2:High Power



Unit	Min/Sec	Ref/Sec	Ref/Sec	Mod
Hz	0.00	15.0000	15.0000	Modulation
Channel 1	200	0.00000	1.000	1 (1M ohm)
Modulation	0.00	0.00	0.00	0.00
Ref/Sec	0.00	0.00	0.00	0.00
Modulation	0.00	0.00	0.00	0.00
Ref/Sec	0.00	0.00	0.00	0.00
Modulation	0.00	0.00	0.00	0.00

POWER:
 MODULATION:
 DESCRIPTION:

HIGH
 Ref Gen=12.5 kHz Deviation
 CARRIER OFF TIME WITH DATA

M. Flom P. Eng.

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 46 of 58.

NAME OF TEST: Audio Low Pass Filter (Voice Input)

SPECIFICATION: 47 CFR 2.1047(a)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
2. The audio output was connected at the output to the modulated stage.
3. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

47 of 58.

TRANSMITTER TEST SET-UP

TEST A. MODULATION CAPABILITY/DISTORTION
 TEST B. AUDIO FREQUENCY RESPONSE
 TEST C. HUM AND NOISE LEVEL
 TEST D. RESPONSE OF LOW PASS FILTER
 TEST E. MODULATION LIMITING




Asset	Description (as applicable)	s/n
(1)	<u>Audio Oscillator</u>	
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00118	HP 33120A	US36002064
(2)	<u>COAXIAL ATTENUATOR</u>	
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3)	<u>MODULATION ANALYZER</u>	
i00020	HP 8901A	2105A01087
(4)	<u>AUDIO ANALYZER</u>	
i00017	HP 8903A	2216A01753

PAGE NO.

48 of 58.

NAME OF TEST: Audio Low Pass Filter (Voice Input)
g0070491: 2000-Jul-19 Wed 13:33:00
STATE: 0:General



SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 49 of 58.
NAME OF TEST: Audio Frequency Response
SPECIFICATION: 47 CFR 2.1047(a)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6
TEST EQUIPMENT: As per previous page


MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. The audio signal generator was connected to the audio input circuit/microphone of the EUT.
3. The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
4. With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
5. The response in dB relative to 1 kHz was then measured, using the HP 8901A Modulation Analyzer.
6. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

50 of 58.

NAME OF TEST: Audio Frequency Response
 g0070488: 2000-Jul-19 Wed 13:30:00
 STATE: 0:General



Frequency of Maximum Audio Response, Hz = 3160

Additional points:

FREQUENCY, Hz	LEVEL, dB
300	-14.24
20000	-33.34
30000	-32.52
50000	-33.84

M. Flom P. Eng.

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 51 of 58.
NAME OF TEST: Modulation Limiting
SPECIFICATION: 47 CFR 2.1047(b)
GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3
TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The signal generator was connected to the input of the EUT as for "Frequency Response of the Modulating Circuit."
2. The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
3. The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
4. Measurements were performed for both negative and positive modulation and the respective results were recorded.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.


52 of 58.

NAME OF TEST: Modulation Limiting
 g0070494: 2000-Jul-19 Wed 13:39:00
 STATE: 0:General

Positive
 Peaks:



Negative
 Peaks:



M. Flom P. Eng.

SUPERVISED BY:


Morton Flom, P. Eng.

PAGE NO.


53 of 58.

NAME OF TEST: Modulation Limiting
 g0070497: 2000-Jul-19 Wed 13:43:00
 STATE: 0:General

Positive
 Peaks:



Negative
 Peaks:



M. Flom P. Eng.

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 54 of 58.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST CONDITIONS: As Indicated

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE


1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.
5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

55 of 58.

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY
 TEST B. CARRIER FREQUENCY STABILITY
 TEST C. OPERATIONAL PERFORMANCE STABILITY
 TEST D. HUMIDITY
 TEST E. VIBRATION
 TEST F. ENVIRONMENTAL TEMPERATURE
 TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION
 TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION




Asset	Description	s/n
(as applicable)		
(1)	<u>TEMPERATURE, HUMIDITY, VIBRATION</u>	
i00027	Tenny Temp. Chamber	9083-765-234
i00	Weber Humidity Chamber	
i00	L.A.B. RVH 18-100	
(2)	<u>COAXIAL ATTENUATOR</u>	
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3)	<u>R.F. POWER</u>	
i00014	HP 435A POWER METER	1733A05839
i00039	HP 436A POWER METER	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(4)	<u>FREQUENCY COUNTER</u>	
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A	2105A01087

PAGE NO.

56 of 58.

NAME OF TEST: Frequency Stability (Temperature Variation)
g0070717: 2000-Jul-28 Fri 07:30:00
STATE: 0:General



SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 57 of 58.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(b)(1)

GUIDE: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at 25±5°C and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)
g0070589: 2000-Jul-19 Wed 14:03:16
STATE: 0:General

LIMIT, ppm = 2.5
LIMIT, Hz = 373
BATTERY END POINT (Voltage) = 9.2

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	11.56	149.049990	-10	-0.07
100	13.6	149.050000	0	0.00
115	15.64	149.050000	0	0.00
68	9.2	149.050610	610	4.09



SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 58 of 58.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 16K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 16.0

MODULATION = 11K0F3E

NECESSARY BANDWIDTH CALCULATION:

MAXIMUM MODULATION (M), kHz	= 3
MAXIMUM DEVIATION (D), kHz	= 2.5
CONSTANT FACTOR (K)	= 1
NECESSARY BANDWIDTH (B _N), kHz	= (2xM)+(2xDxK)
	= 11.0

SUPERVISED BY:



Morton Flom, P. Eng.

TESTIMONIAL
AND
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:

A handwritten signature in black ink, reading "M. Flom P. Eng.", with a horizontal line drawn underneath the signature.

Morton Flom, P. Eng.