



M. Flom Associates, Inc.

International Compliance Testing Laboratory

3356 N. San Marcos Place, Suite 107
Chandler, AZ 85225

toll-free: (866) 311-3268
fax: (480) 926-3598

<http://www.mflom.com>
info@mflom.com

Date: December 6, 2004

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Kenwood USA Corporation
Equipment: TK-2212-1
FCC ID: ALH37683110
FCC Rules: 22, 74, 90, 90.210, Confidentiality

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

David E. Lee,
Compliance Test Manager

enclosure(s)
cc: Applicant
DEL/del



M. Flom Associates, Inc.
International Compliance Testing Laboratory
3356 N. San Marcos Place, Suite 107
Chandler, AZ 85225
toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.mflom.com>
info@mflom.com

Transmitter Certification

of

FCC ID: ALH37683110

Model: TK-2212-1

to

Federal Communications Commission

Rule Part(s) 22, 74, 90, 90.210, Confidentiality

Date of report: December 6, 2004

On the Behalf of the Applicant:

Kenwood USA Corporation

At the Request of:

P.O. UPS 9/23/2004

Kenwood USA Corporation
Communications Division
3975 Johns Creek Court, Suite 300
Suwanee, GA 30024

Attention of:

Joel E. Berger, Research & Development
JBerger@kenwoodusa.com
(678) 474-4722; FAX: -4731

Supervised by:

David E. Lee,
Compliance Test Manager

List of Exhibits

(FCC **Certification** (Transmitters) - Revised 9/28/98)

Applicant: Kenwood USA Corporation

FCC ID: ALH37683110

By Applicant:

1. Letter of Authorization
2. Confidentiality Request: 0.457 And 0.459
3. Part 90.203(e) & (g) Attestation
4. Identification Drawings, 2.1033(c)(11)
 - Label
 - Location of Label
 - Compliance Statement
 - Location of Compliance Statement
5. Photographs, 2.1033(c)(12)
6. Documentation: 2.1033(c)
 - (3) User Manual
 - (9) Tune Up Info
 - (10) Schematic Diagram
 - (10) Circuit Description
 - Block Diagram
 - Parts List
 - Active Devices
7. SAR Report

By M.F.A. Inc.:

- A. Testimonial & Statement of Certification

The Applicant has been cautioned as to the following:

15.21 **Information to the User.**

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) **Special Accessories.**

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

Table of Contents

| <u>Rule</u> | <u>Description</u> | <u>Page</u> |
|---------------|--|-------------|
| 2.1033(c)(14) | Rule Summary | 2 |
| | Standard Test Conditions and Engineering Practices | 3 |
| 2.1033(c) | General Information Required | 5 |
| 2.1046(a) | Carrier Output Power (Conducted) | 8 |
| 2.1046(a) | ERP Carrier Power (Radiated) | 10 |
| 2.1051 | Unwanted Emissions (Transmitter Conducted) | 12 |
| 2.1053(a) | Field Strength of Spurious Radiation | 14 |
| 2.1049(c)(1) | Emission Masks (Occupied Bandwidth) | 18 |
| 90.214 | Transient Frequency Behavior | 25 |
| 2.1047(a) | Audio Low Pass Filter (Voice Input) | 31 |
| 2.1047(a) | Audio Frequency Response | 33 |
| 2.1047(b) | Modulation Limiting | 35 |
| 2.1055(a)(1) | Frequency Stability (Temperature Variation) | 38 |
| 2.1055(b)(1) | Frequency Stability (Voltage Variation) | 40 |
| 2.202(g) | Necessary Bandwidth and Emission Bandwidth | 42 |

Required information per ISO/IEC Guide 25-1990, paragraph 13.2:

a) **Test Report**

b) Laboratory: M. Flom Associates, Inc.
(FCC: 31040/SIT) 3356 N. San Marcos Place, Suite 107
(Canada: IC 2044) Chandler, AZ 85225

c) Report Number: d04c0012

d) Client: Kenwood USA Corporation
Communications Division
3975 Johns Creek Court, Suite 300
Suwanee, GA 30024

e) Identification: TK-2212-1
FCC ID: ALH37683110
EUT Description: VHF/FM Handheld Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: December 6, 2004
EUT Received: September 24, 2004

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:



David E. Lee,
Compliance Test Manager

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

Sub-part

2.1033(c)(14):

Test and Measurement Data

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- 21 - Domestic Public Fixed Radio Services
- 22 - Public Mobile Services
- 22 Subpart H - Cellular Radiotelephone Service
- 22.901(d) - Alternative technologies and auxiliary services
- 23 - International Fixed Public Radiocommunication services
- 24 - Personal Communications Services
- 74 Subpart H - Low Power Auxiliary Stations
- 80 - Stations in the Maritime Services
- 80 Subpart E - General Technical Standards
- 80 Subpart F - Equipment Authorization for Compulsory Ships
- 80 Subpart K - Private Coast Stations and Marine Utility Stations
- 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- 80 Subpart V - Emergency Position Indicating Radio Beacons (EPIRB'S)
- 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- 80 Subpart X - Voluntary Radio Installations
- 87 - Aviation Services
- 90 - Private Land Mobile Radio Services
- 94 - Private Operational-Fixed Microwave Service
- 95 Subpart A - General Mobile Radio Service (GMRS)
- 95 Subpart C - Radio Control (R/C) Radio Service
- 95 Subpart D - Citizens Band (CB) Radio Service
- 95 Subpart E - Family Radio Service
- 95 Subpart F - Interactive Video and Data Service (IVDS)
- 97 - Amateur Radio Service
- 101 - Fixed Microwave Services

Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992/2001, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst-case measurements.



A2LA

"A2LA has accredited M. Flom Associates, Inc. Chandler, AZ for technical competence in the field of Electrical Testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC 17025 – 1999 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Certificate Number: **2152-01**



NIST

I am pleased to inform you that your laboratory has been validated by the Chinese Taipei Bureau of Standards, Metrology and Inspection (BSMI) under the Asia Pacific Economic Cooperation Mutual Recognition Agreement (APEC MRA). Your laboratory is now formally designated to act as a Conformity Assessment Body (CAB) under Appendix B, Phase I Procedures, of the APEC MRA between the American Institute in Taiwan (AIT) and the Taipei Economic and Cultural Representative Office (TECRO) in the United States, covering equipment subject to Electro-Magnetic Compatibility (EMC) requirements. The names of all validated and nominated laboratories will be posted on the NIST website at <http://ts.nist.gov/mra> under the 'Asia' category."

BSMI Number: **SL2-IN-E-041R**

List of General Information Required for Certification

In Accordance with FCC Rules and Regulations,
Volume II, Part 2 and to

22, 74, 90, 90.210, Confidentiality

Sub-part 2.1033

(c)(1): **Name and Address of Applicant:**

Kenwood USA Corporation
Communications Division
3975 Johns Creek Court, Suite 300
Suwanee, GA 30024

Manufacturer :

Kenwood Electronics Technologies PTE Ltd.
1 Ang Mo Kio Street 63
Singapore 569110

(c)(2): **FCC ID:** ALH37683110

Model Number : TK-2212-1

(c)(3): **Instruction Manual(s):**

Please see attached exhibits

(c)(4): **Type of Emission:** 16K0F3E, 11K0F3E

(c)(5): **Frequency Range, MHz:** 136 to 174

(c)(6): **Power Rating, Watts:** 1 to 5
 _____ Switchable X Variable _____ N/A

(c)(7): **Maximum Power Rating, Watts:** 300

DUT Results: Passes _____ X Fails _____

Information for Push-To-Talk Devices

Type and number of antenna to be used for this device:
Helical Whip Antenna, Broadband and Sub-Band

Maximum antenna gain for antenna indicated above:
0dBd

Can this device sustain continuous operation with respect to its hardware capabilities and allowable operating functions?
No

Other hardware or operating restrictions that could limit a person's RF Exposure:
Timeout Timer

Source-based time-averaging (see 2.1093 of rules) applicable to reduce the average output power:
No

If device has headset and belt-clip accessories that would allow body-worn operations, what is the minimum separation distance between the antenna and the user's body in this operating configuration?
Less than 2.5cm

Can device access wire-line services to make phone calls, either directly or through an operator?
No

Can specific operating instructions be given to users to eliminate any potential RF Exposure concerns for both front-of-the-face and body-worn operating configurations?
Yes - In manual

Other applicable information the applicant may provide that can serve as effective means for ensuring RF Exposure compliance:
Yes - Training as per manual

Subpart 2.1033 (continued)

(c)(8): Voltages & currents in all elements in final RF stage, including final transistor or solid-state device:

| | | |
|------------------------|---|------------|
| Collector Current, A | = | per manual |
| Collector Voltage, Vdc | = | per manual |
| Supply Voltage, Vdc | = | 7.5 |

(c)(9): **Tune-Up Procedure:**

Please see attached exhibits

(c)(10): **Circuit Diagram/Circuit Description:**

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

Please see attached exhibits

(c)(11): **Label Information:**

Please see attached exhibits

(c)(12): **Photographs:**

Please see attached exhibits

(c)(13): **Digital Modulation Description:**

Attached Exhibits
 N/A

(c)(14): **Test and Measurement Data:**


Follows

Name of Test: Carrier Output Power (Conducted)
Specification: 47 CFR 2.1046(a)
Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.1

Measurement Procedure

- A) The EUT was connected to a resistive coaxial attenuator of normal load impedance, and the unmodulated output power was measured by means of an RF Power Meter.
- B) Measurement accuracy is $\pm 3\%$.

Transmitter Test Set-Up: RF Power Output



| Asset | Description | s/n | Cycle | Last Cal |
|-------|--------------------------------------|---------------|--------|----------|
| (1) | Coaxial Attenuator | | | |
| X | i00231/2 PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR | |
| | i00122/3 NARDA 766 (10 dB) | 7802 or 7802A | NCR | |
| (2) | Power Meters | | | |
| X | i00020 HP 8901A Power Mode | 2105A01087 | 12 mo. | Apr-04 |
| (3) | Frequency Counter | | | |
| X | i00020 HP 8901A Frequency Mode | 2105A01087 | 12 mo. | Apr-04 |

Name of Test: Carrier Output Power (Conducted)

Measurement Results
(Worst case)

Frequency of Carrier, MHz = 155.1, 136.1, 173.9
Ambient Temperature = 23°C ± 3°C

| Power Setting | RF Power, dBm | RF Power, Watts |
|---------------|---------------|-----------------|
| Low | 30.00 | 1 |
| High | 37.27 | 5 |

Performed by:



Samir Mahmoud

Name of Test: ERP Carrier Power (Radiated)

Specification: TIA/EIA 603A (Substitution Method)


Measurement Procedure

Definition

The average radiated power of a licensed device is the equivalent power required, when delivered to a half-wave dipole or horn antenna, to produce at a distant point the same average received power as produced by the licensed device.

Method of Measurement:

- A) Connect the equipment as illustrated. Place the transmitter to be tested on the turntable in the standard test site.



- B) Raise and lower the test antenna from 1m to 6 m with the transmitter facing the antenna and record the highest received signal in dB as LVL.
- C) Repeat step B) for seven additional readings at 45° interval positions of the turntable.
- D) Replace the transmitter under test with a half-wave or horn vertically polarized antenna. The center of the antenna should be at the same location as the transmitter under test. Connect the antenna to a signal generator with a known output power and record the path loss in dB or LOSS.
- E) Calculate the average radiated output power from the readings in step C) and D) by the following:

$$\text{average radiated power} = 10 \log_{10} \left(\frac{10(LVL - LOSS)}{10} \right) \text{ (dBm)}$$

Name of Test: ERP Carrier Power (Radiated)

Test Equipment

| Asset | Description | s/n | Cycle | Last Cal |
|-------------------------------|---------------------------|------------|--------|----------|
| Transducer | | | | |
| X i00088 | EMCO 3109-B 25MHz-300MHz | 2336 | 24 mo. | Sep-03 |
| X i00089 | Aprlel 2001 200MHz-1GHz | 001500 | 24 mo. | Sep-03 |
| X i00103 | EMCO 3115 1GHz-18GHz | 9208-3925 | 24 mo. | Jan-04 |
| Amplifier | | | | |
| X i00028 | HP 8449A | 2749A00121 | 12 mo. | May-04 |
| Spectrum Analyzer | | | | |
| X i00029 | HP 8563E | 3213A00104 | 12 mo. | May-04 |
| X i00033 | HP 85462A | 3625A00357 | 12 mo. | Jul-04 |
| Substitution Generator | | | | |
| X i00067 | HP 8920A Communication TS | 3345U01242 | 12 mo. | Jun-04 |
| i00207 | HP 8753D Network Analyzer | 3410A08514 | 12 mo. | Jul-04 |

Measurement Results

| | 136.100MHz | | 155.100MHz | | 173.900MHz | |
|---------------------|------------|---------------|------------|---------------|------------|---------------|
| | LVL, dbm | Path Loss, db | LVL, dbm | Path Loss, db | LVL, dbm | Path Loss, db |
| 0° | 18.20 | | 27.80 | | 29.10 | |
| 45° | 26.30 | | 25.90 | | 33.90 | |
| 90° | 24.00 | | 32.90 | | 27.90 | |
| 135° | 25.30 | 2.10 | 25.20 | 4.20 | 33.80 | 3.50 |
| 180° | 23.50 | | 31.80 | | 33.60 | |
| 225° | 18.30 | | 30.60 | | 32.70 | |
| 270° | 21.10 | | 32.40 | | 32.00 | |
| 315° | 20.40 | | 29.50 | | 30.10 | |
| Av. Radiated Power: | | 24.24dBm | 33.71dBm | 35.14dBm | | |

Performed by:



Samir Mahmoud

Name of Test: Unwanted Emissions (Transmitter Conducted)


Specification: 47 CFR 2.1051

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.13

Measurement Procedure

- A) The emissions were measured for the worst case as follows:
- 1). within a band of frequencies defined by the carrier frequency plus and minus one channel.
 - 2). from the lowest frequency generated in the EUT and to at least the 10th harmonic of the carrier frequency, or 40 GHz, whichever is lower.
- B) The magnitude of spurious emissions that are attenuated more than 20 dB below the permissible value need not be specified.

Transmitter Test Set-Up: Spurious Emission



| Asset | Description | s/n | | |
|---------------------------------------|---------------|-----------------------------------|---------------|---------------|
| (1) Audio Oscillator/Generator | | | | |
| X | i00017 | HP 8903A Audio Analyzer | 2216A01753 | 12 mo. Apr-04 |
| | i00002 | HP 3336B Synthesizer / Level Gen. | 1931A01465 | 12 mo. Apr-04 |
| (2) Coaxial Attenuator | | | | |
| X | i00231/2 | PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR |
| | i0012/3 | NARDA 766 (10 dB) | 7802 or 7802A | NCR |
| (3) Filters; Notch, HP, LP, BP | | | | |
| | None required | | | |
| (4) Spectrum Analyzer | | | | |
| X | i00048 | HP 8566B Spectrum Analyzer | 2511A01467 | 12 mo. Oct-04 |
| | i00029 | HP 8563E Spectrum Analyzer | 3213A00104 | 12 mo. May-04 |

Name of Test: Unwanted Emissions (Transmitter Conducted)

Measurement Results
(Worst Case)

Summary:

| | | |
|----------------------------|---|---|
| Frequency of carrier, MHz | = | 155.1, 136.1, 173.9 |
| Spectrum Searched, GHz | = | 0 to 10 x F _C |
| Maximum Response, Hz | = | 2820 |
| All Other Emissions | = | = 20 dB Below Limit |
| Limit(s), dBc [Worst Case] | | 50 + 10 x Log (P) 50 + 10 x Log (5.0) -57dBc (-20dBm) |

Measurement Results

Note: All Emissions were below -40dBm on Low and High Power, for 25kHz and 12.5kHz channels

Supervised by:



David E. Lee,
Compliance Test Manager

Name of Test: Field Strength of Spurious Radiation

Specification: 47 CFR 2.1053(a)

Guide: ANSI/TIA/EIA-603-1992/2001, Paragraph 1.2.12 and Table 16, 47 CFR 22.917


Measurement Procedure

Definition:

Radiated spurious emissions are emissions from the equipment when transmitting into a non-radiating load on a frequency or frequencies which are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.


Method of Measurement:

- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHz), 1 MHz (> 1GHz).
 - 2) Video Bandwidth = 3 times Resolution Bandwidth, or 30 kHz (22.917)
 - 3) Sweep Speed ≤ 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load that is placed on the turntable. The RF cable to this load should be of minimum length.



Name of Test: Field Strength of Spurious Radiation (Cont.)

- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.



- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.

Name of Test: Field Strength of Spurious Radiation (Cont.)

- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB =

$$10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step I)}$$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.

Test Equipment

| Asset | Description | s/n | Cycle | Last Cal |
|-------------------------------|-------------|---------------------------|------------|---------------|
| Transducer | | | | |
| | i00088 | EMCO 3109-B 25MHz-300MHz | 2336 | 24 mo. Sep-03 |
| X | i00089 | Apriel 2001 200MHz-1GHz | 001500 | 24 mo. Sep-03 |
| X | i00103 | EMCO 3115 1GHz-18GHz | 9208-3925 | 24 mo. Jan-04 |
| Amplifier | | | | |
| X | i00028 | HP 8449A | 2749A00121 | 12 mo. May-04 |
| Spectrum Analyzer | | | | |
| X | i00029 | HP 8563E | 3213A00104 | 12 mo. May-04 |
| X | i00033 | HP 85462A | 3625A00357 | 12 mo. Sep-04 |
| Substitution Generator | | | | |
| X | i00067 | HP 8920A Communication TS | 3345U01242 | 12 mo. Jun-04 |
| | i00207 | HP 8753D Network Analyzer | 3410A08514 | 12 mo. Jul-04 |

Microphone, Antenna Port, and Cabling

| | | | | |
|------------------------------|------------|--------------|--------------|--------------|
| Microphone | <u>Yes</u> | Cable Length | <u>1.0</u> | Meters |
| Antenna Port Terminated | <u>Yes</u> | Load | <u>50ohm</u> | Antenna Gain |
| All Ports Terminated by Load | <u>Yes</u> | Peripheral | <u>-</u> | <u>-</u> |

Name of Test: Field Strength of Spurious Radiation

Measurement Results

g04a0063: 2004-Oct-01 Fri 08:54:00

STATE: 2:High Power

Ambient Temperature: 23°C ± 3°C

| Frequency Tuned, MHz | Frequency Emission, MHz | ERP, dBm | ERP, dBc |
|----------------------|-------------------------|----------|----------|
| 136.100000 | 272.201500 | -45.6 | -82.87 |
| 136.100000 | 408.323800 | -51.1 | -88.37 |
| 136.100000 | 544.398800 | -59.0 | -96.27 |
| 136.100000 | 680.498000 | -49.3 | -86.57 |
| 136.100000 | 816.598800 | -54.3 | -91.57 |
| 136.100000 | 952.698800 | -51.3 | -88.57 |
| 136.100000 | 1088.798800 | -51.6 | -88.87 |
| 136.100000 | 1224.898800 | -48.4 | -85.67 |
| 136.100000 | 1360.998800 | -50.2 | -87.47 |

Note: The EUT was tested with fundamental frequencies of 136.10, 155.10 and 173.90MHz. Measurements at 136.10MHz yielded the highest levels of spurious emissions, which are tabulated above.

Performed by:



Samir Mahmoud

Name of Test: Emission Masks (Occupied Bandwidth)


Specification: 47 CFR 2.1049(c)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.11

Measurement Procedure

- A) The EUT and test equipment were set up as shown below
- B) For EUTs supporting audio modulation, the audio signal generator was adjusted to the frequency of maximum response and with output level set for $\pm 2.5/\pm 1.25$ kHz deviation (or 50% modulation). With level constant, the signal level was increased 16 dB.
- C) For EUTs supporting digital modulation, the digital modulation mode was operated to its maximum extent.
- D) The Occupied Bandwidth was measured with the Spectrum Analyzer controls set as shown on the test results.

Transmitter Test Set-Up: Occupied Bandwidth



| Asset | Description | s/n | Cycle | Last Cal |
|---------------------------------------|--------------------------------|------------|--------|----------|
| (1) Audio Oscillator/Generator | | | | |
| X i00017 | HP 8903A Modulation Meter | 2216A01753 | 12 mo. | Apr-04 |
| (2) Coaxial Attenuator | | | | |
| X i00231/2 | PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR | |
| i00123 | NARDA 766 (10 dB) | 7802A | NCR | |
| (3) Interface | | | | |
| X i00021 | HP 8954A Transceiver Interface | 2146A00159 | NCR | |
| (4) Spectrum Analyzer | | | | |
| X i00048 | HP 8566B Spectrum Analyzer | 2511A01467 | 12 mo. | Oct-04 |
| i00029 | HP 8563E Spectrum Analyzer | 3213A00104 | 12 mo. | May-04 |


Name of Test: Emission Masks (Occupied Bandwidth)

Measurement Results

g04a0069: 2004-Oct-04 Mon 15:30:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:

HIGH

Modulation:

NONE

MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:



Samir Mahmoud


Name of Test: Emission Masks (Occupied Bandwidth)

Measurement Results

g04a0070: 2004-Oct-04 Mon 15:31:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:
Modulation:

HIGH
NONE
MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:



Samir Mahmoud


Name of Test: Emission Masks (Occupied Bandwidth)

Measurement Results

g04a0071: 2004-Oct-04 Mon 15:34:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power: HIGH
 Modulation: NONE
 MASK: B, VHF/UHF 25kHz, w/LPF

Performed by:



Samir Mahmoud


Name of Test: Emission Masks (Occupied Bandwidth)

Measurement Results

g04a0072: 2004-Oct-04 Mon 15:36:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power: HIGH
Modulation: NONE
MASK: D, VHF/UHF 12.5kHz BW

Performed by:




Samir Mahmoud

Name of Test: Emission Masks (Occupied Bandwidth)

Measurement Results

g04a0073: 2004-Oct-04 Mon 15:37:00
State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power: HIGH
Modulation: NONE
MASK: D, VHF/UHF 12.5kHz BW

Performed by:



Samir Mahmoud


Name of Test: Emission Masks (Occupied Bandwidth)

Measurement Results

g04a0074: 2004-Oct-04 Mon 15:37:00

State: 2:High Power

Ambient Temperature: 23°C ± 3°C



Power:
Modulation:

HIGH
NONE
MASK: D, VHF/UHF 12.5kHz BW

Performed by:



Samir Mahmoud

Name of Test: Transient Frequency Behavior
Specification: 47 CFR 90.214
Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.19

Measurement Procedure

- A) The EUT was setup as shown on the attached page, following TIA/EIA-603 steps a, b, and c as a *guide*.
- B) The transmitter was turned on.
- C) Sufficient attenuation was provided so that the transmitter carrier level measured at the output of the combiner was 40 dB below the maximum input level of the test receiver. This level was recorded.
- D) The transmitter was turned off.
- E) An RF signal generator (1) modulated with a 1 kHz tone at either 25, 12.5, or 6.25 kHz deviation, and set to the same frequency as the assigned transmitter frequency, (2) was adjusted to a level -20 dB below the level recorded for step C) above, measured at the output of the combiner. This level was then fixed for the remainder of the test.
- F) The oscilloscope was setup using TIA/EIA-603 steps j and k as a guide, and to either 10 ms/div (UHF) or 5 ms/div (VHF).
- G) The 30 dB attenuator was removed, the transmitter was turned on, and the level of the carrier at the output of the combiner was recorded.
- H) The carrier on-time as referenced in TIA/EIA-603 steps m, n, and o was captured and plotted. The carrier off-time as referenced in TIA/EIA-603 steps p, q, r, and s was captured and plotted.


Performed by:



Samir Mahmoud

Name of Test: Transient Frequency Behavior

Transmitter Set-Up




| Asset | Description | s/n | Cycle | Last Cal |
|-------------------------|--------------------------------|---------------|--------|----------|
| (1) Attenuator | (Removed after 1st step) | | | |
| X i00231/2 | PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR | |
| (2) Attenuator | | | | |
| X i00231/2 | PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR | |
| i00122/3 | NARDA 766 (10 dB) | 7802 or 7802A | NCR | |
| (3) Combiner | | | | |
| X i00154 | 4 x 25 Ω Combiner | 154 | NCR | |
| (4) Crystal Decoder | | | | |
| X i00159 | HP 8470B Crystal Detector | 1822A10054 | NCR | |
| (5) RF Signal Generator | | | | |
| X i00067 | HP 8920A Communication TS | 3345U01242 | 12 mo. | Jun-04 |
| (6) Modulation Analyzer | | | | |
| X i00020 | HP 8901A Modulation Meter | 2105A01087 | 12 mo. | Apr-04 |
| (7) Oscilloscope | | | | |
| X i00030 | HP 54502A Digital Oscilloscope | 2927A00209 | 12 mo. | Jan-04 |

Name of Test: Transient Frequency Behavior

2004-Oct-18 Mon 9:56:00

Ambient Temperature: 23°C ± 3°C




| | | | | |
|-----------|----------------------------|--------------------------|-------------------|-------------------------|
| Main | Timebase 5.00 ms/div | Delay/Pos -20.0000 ms | Reference Left | Mode Repetitive |
| Channel 1 | Sensitivity 50.0 mV/div | Offset 5.000 mV | Probe 1.000 :1 | Coupling ac (1M ohm) |

Trigger mode : Edge
 On Negative Edge Of Chan2
 Trigger Level
 Chan2 = -27.500 mV (noise reject ON)
 Holdoff = 40.000 ns

Power:
 Modulation:
 Description:

High
 25 kHz Deviation
 Carrier On

Performed by:




Samir Mahmoud,
 Test Technician

Name of Test: Transient Frequency Behavior

2004-Oct-18 Mon 10:14:00


Ambient Temperature: 23°C ± 3°C



Power:
 Modulation:
 Description:

High
 12.5 kHz Deviation
 Carrier On

Performed by:




Samir Mahmoud,
 Test Technician

Name of Test: Transient Frequency Behavior

2004-Oct-18 Mon 11:28:00

Ambient Temperature: 23°C ± 3°C



| | | | |
|-----------|-------------|-------------|-------------|
| Main | Timebase | Delay/Pos | Reference |
| | 5.00 ms/div | -40.0000 ms | Left |
| Channel 1 | Sensitivity | Offset | Probe |
| | 50.0 mV/div | 5.000 mV | 1.000 :1 ac |

Trigger mode :
On Positive Edge Of
Trigger
Chan2 = -22.500 mV (noise reject)
Holdoff = 40.000

Power:
Modulation:
Description:

High
12.5 kHz Deviation
Carrier Off

Performed by:




Samir Mahmoud,
Test Technician

Name of Test: Transient Frequency Behavior

2004-Oct-18 Mon 11:45:00

Ambient Temperature: 23°C ± 3°C




| | | | | |
|-----------|----------------------------|--------------------------|-------------------|-------------------------|
| Main | Timebase 5.00 ms/div | Delay/Pos -40.0000 ms | Reference Left | Mode Repetitive |
| Channel 1 | Sensitivity 70.0 mV/div | Offset 5.000 mV | Probe 1.000 :1 | Coupling ac (1M ohm) |

Trigger mode : Edge
 On Positive Edge Of Chan2
 Trigger Level
 Chan2 = -22.500 mV (noise reject ON)
 Holdoff = 40.000 ns

Power:
 Modulation:
 Description:

High
 25 kHz Deviation
 Carrier Off

Performed by:




Samir Mahmoud,
 Test Technician

Name of Test: Audio Low Pass Filter (Voice Input)
Specification: 47 CFR 2.1047(a)
Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.15

Measurement Procedure

- A) The EUT and test equipment were set up such that the audio input was connected at the input to the modulation limiter, and the modulated stage.
- B) The audio output was connected at the output to the modulated stage.

Transmitter Test Set-Up: Response of Low Pass Filter




| Asset | Description | s/n | Cycle | Last Cal |
|--------------------------------|--|---------------|--------|----------|
| (1) Audio Oscillator | | | | |
| X | i00002 HP 3336B Synthesizer / Level Gen. | 1931A01465 | 12 mo | Apr-04 |
| (2) Coaxial Attenuator | | | | |
| | i00122/3 NARDA 766 (10dB)10 | 7802 or 7802A | NCR | |
| X | i00231/2 PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR | |
| (3) Modulation Analyzer | | | | |
| X | i00020 HP 8901A Modulation Meter | 2105A01087 | 12 mo. | Apr-04 |
| (4) Audio Analyzer | | | | |
| X | i00001 HP 3586B Selective Level Meter | 1928A01360 | 12 mo. | Apr-04 |

Name of Test: Audio Low Pass Filter (Voice Input)

Measurement Results

g04a0023: 2004-Oct-04 Mon 09:23:00
 State: 0:General

Ambient Temperature: 23°C ± 3°C



Performed by:




Samir Mahmoud

Name of Test: Audio Frequency Response
Specification: 47 CFR 2.1047(a)
Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.6

Measurement Procedure

- A) The EUT and test equipment were set up as shown below.
- B) The audio signal generator was connected to the audio input circuit/microphone of the EUT.
- C) The audio signal input was adjusted to obtain 20% modulation at 1 kHz, and this point was taken as the 0 dB reference level.
- D) With input levels held constant and below limiting at all frequencies, the audio signal generator was varied from 100 Hz to 50 kHz.
- E) The response in dB relative to 1 kHz was measured, using the HP 8901A Modulation Meter.

Transmitter Test Set-Up: Audio Frequency Response



| Asset | Description | s/n | Cycle | Last Cal |
|--------------------------------|--------------------------------------|---------------|--------|----------|
| (1) Audio Oscillator | | | | |
| X | i00017 HP 8903A Audio Analyzer | 2216A01753 | 12 mo. | Apr-04 |
| (2) Coaxial Attenuator | | | | |
| | i00122/3 NARDA 766-(10 dB) | 7802 or 7802A | NCR | |
| X | i00231/2 PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR | |
| (3) Modulation Analyzer | | | | |
| X | i00020 HP 8901A Modulation Meter | 2105A01087 | 12 mo. | Apr-04 |
| (4) Audio Analyzer | | | | |
| X | i00017 HP 8903A Audio Analyzer | 2216A01753 | 12 mo. | Apr-04 |


Name of Test: Audio Frequency Response

Measurement Results

g04a0022: 2004-Oct-04 Mon 09:13:00

State: 0:General

Ambient Temperature: 23°C ± 3°C



Frequency of Maximum Audio Response, Hz = 2820

Additional points:

| Frequency, Hz | Level, dB |
|---------------|-----------|
| 300 | -11.78 |
| 20000 | -78.79 |
| 30000 | -73.06 |
| 50000 | -71.69 |

Performed by:




Samir Mahmoud

Name of Test: Modulation Limiting
Specification: 47 CFR 2.1047(b)
Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.3

Measurement Procedure

- A) The signal generator was connected to the input of the EUT as shown below.
- B) The modulation response was measured for each of three frequencies (one of which was the frequency of maximum response), and the input voltage was varied and was observed on an HP 8901A Modulation Analyzer.
- C) The input level was varied from 30% modulation (± 1.5 kHz deviation) to at least 20 dB higher than the saturation point.
- D) Measurements were performed for both negative and positive modulation and the respective results were recorded.

Transmitter Test Set-Up: Modulation Limiting



| Asset | Description | s/n | | |
|--------------------------------|-------------|-----------------------------|---------------|---------------|
| (1) Audio Oscillator | | | | |
| X | i00017 | HP 8903A Audio Analyzer | 2216A01753 | 12 mo. Apr-04 |
| (2) Coaxial Attenuator | | | | |
| | i0012/23 | NARDA 766-(10 dB) | 7802 or 7802A | NCR |
| X | i00231/2 | PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR |
| (3) Modulation Analyzer | | | | |
| X | i00020 | HP 8901A Modulation Meter | 2105A01087 | 12 mo. Apr-04 |
| (4) Audio Analyzer | | | | |
| X | i00017 | HP 8903A Audio Analyzer | 2216A01753 | 12 mo. Apr-04 |


Name of Test: Modulation Limiting

Measurement Results


g04a0025: 2004-Oct-04 Mon 09:54:00
 State: 0: 25kHz Channels

Ambient Temperature: 23°C ± 3°C

Positive
 Peaks:



Negative
 Peaks:



Performed by:



Samir Mahmoud


Name of Test: Modulation Limiting

Measurement Results


g04a0029: 2004-Oct-04 Mon 11:13:00
 State: 0: 12.5kHz Channels

Ambient Temperature: 23°C ± 3°C

Positive
 Peaks:



Negative
 Peaks:



Performed by:



Samir Mahmoud

Name of Test: Frequency Stability (Temperature Variation)


Specification: 47 CFR 2.1055(a)(1)

Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

Measurement Procedure

- A) The EUT and test equipment were set up as shown on the following page.
- B) With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
- C) With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
- D) The temperature tests were performed for the worst case.

Transmitter Test Set-Up: Temperature Variation




| Asset | Description | s/n | Cycle | Last Cal |
|---|--------------------------------------|---------------|--------|----------|
| (1) Temperature, Humidity, Vibration | | | | |
| X | i00027 Tenney Temp. Chamber | 9083-765-234 | NCR | |
| (2) Coaxial Attenuator | | | | |
| X | i00231/2 PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR | |
| | i00122/3 NARDA 766 (10 dB) | 7802 or 7802A | NCR | |
| (3) RF Power | | | | |
| X | i00067 HP 8920A Communications TS | 3345U01242 | 12 mo. | Jun-04 |
| (4) Frequency Counter | | | | |
| X | i00067 HP 8920A Communications TS | 3345U01242 | 12 mo. | Jun-04 |

Name of Test: Frequency Stability (Temperature Variation)

Measurement Results

State: Room Temperature: 23°C ± 3°C



Horizontal Axis = Degrees (C)
Vertical Axis = Frequency (MHz)

Performed by:




Samir Mahmoud

Name of Test: Frequency Stability (Voltage Variation)
Specification: 47 CFR 2.1055(d)(1)
Guide: ANSI/TIA/EIA-603-1992, Paragraph 2.2.2

Measurement Procedure

- A) The EUT was placed in a temperature chamber (if required) at 25±5°C and connected as shown below.
- B) The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- C) The variation in frequency was measured for the worst case.

Transmitter Test Set-Up: Voltage Variation



| Asset | Description | s/n | Cycle | Last Cal |
|---|-----------------------------|---------------|--------|----------|
| (1) Temperature, Humidity, Vibration | | | | |
| i00027 | Tenney Temp. Chamber | 9083-765-234 | NCR | |
| (2) Coaxial Attenuator | | | | |
| X i00231/2 | PASTERNAK PE7021-30 (30 dB) | 231 or 232 | NCR | |
| i00122/3 | NARDA 766 (10 dB) | 7802 or 7802A | NCR | |
| (3) RF Power | | | | |
| X i00020 | HP 8901A Power Mode | 2105A01087 | 12 mo. | Apr-04 |
| (4) Frequency Counter | | | | |
| X i00020 | HP 8901A Frequency Mode | 2105A01087 | 12 mo. | Apr-04 |

Results: Frequency Stability (Voltage Variation)

g04a0068: 2004-Oct-04 Mon 11:44:11

State: 0:General

Ambient Temperature: 23°C ± 3°C

Limit, ppm = 5
 Limit, Hz = 776
 Battery End Point (Voltage) = 5.9

| % of STV | Voltage | Frequency, MHz | Change, Hz | Change, ppm |
|----------|---------|----------------|------------|-------------|
| 85 | 6.37 | 155.100005 | 5 | <1.0 |
| 100 | 7.50 | 155.100010 | 10 | <1.0 |
| 115 | 8.62 | 155.100020 | 20 | <1.0 |
| 79 | 5.93 | 155.100005 | 5 | <1.0 |

Performed by:



Samir Mahmoud

Name of Test: Necessary Bandwidth and Emission Bandwidth

Specification: 47 CFR 2.202(g)

Modulation = 16K0F3E

Necessary Bandwidth Calculation:

| | | |
|--|---|---------------|
| Maximum Modulation (M), kHz | = | 3 |
| Maximum Deviation (D), kHz | = | 5 |
| Constant Factor (K) | = | 1 |
| Necessary Bandwidth (B _N), kHz | = | (2xM)+(2xDxK) |
| | = | 16.0 |

Modulation = 11K0F3E

Necessary Bandwidth Calculation:

| | | |
|--|---|---------------|
| Maximum Modulation (M), kHz | = | 3 |
| Maximum Deviation (D), kHz | = | 2.5 |
| Constant Factor (K) | = | 1 |
| Necessary Bandwidth (B _N), kHz | = | (2xM)+(2xDxK) |
| | = | 11.0 |

Performed by:



Samir Mahmoud

END OF TEST REPORT

**Testimonial
and
Statement of Certification**

This is to Certify:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

Certifying Engineer:



David E. Lee,
Compliance Test Manager