



Compliance Testing, LLC

Previously Flom Test Lab

RF, EMC and Safety Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Date: June 30, 2010

Applicant: Kenwood USA Corporation
Communications Division
3970 Johns Creek Court, Suite 100
Suwanee, GA 30024

Attention of: Joel E. Berger, Research & Development
JBerger@kenwoodusa.com
(678) 474-4722; FAX: -4731

Equipment: TK-3312-2, TK-3317-2
FCC ID: ALH413801
FCC Rules: Part 22, 74, 90

Enclosed please find your copy of the Engineering Test Report for which you are subject to the restrictions as listed on the attached summary.

Once a Telecommunication Certification Body (TCB) issues a Grant the Federal Communication Commission (FCC) has 30 days to review the application and request added information. It is your decision whether or not to market the equipment subject to a possible recall before the end of the 30 days.

If your equipment is still retained by us, it will be returned to you 30 days after approval is achieved. Our invoice for services has been directed to your Accounts Payable Department.

For any additional information please contact us.

Thank you.

Sincerely yours,

John Erhard: Engineering Manager



Summary of Restrictions

1. All submissions to the FCC are subject to **their** Examiner's interpretation.
2. Please allow from 60 to 90 days before hearing from the FCC with regard to any submission.
3. The FCC can set aside any action; modify or set aside any action, within 30 days. (FCC Rule 1.108, 1.113)
4. Under Rule 2.803, if device is not type accepted/certified then it must **not** be sold, leased, offered for sale, imported, shipped or distributed or advertised for sale.
5. FCC can revoke its certificates at any time if the equipment does not meet or **continue** to meet their Rules. (FCC Rule Parts 2.927, 2.939)
6. FCC can request a sample at any time (2.936).



Compliance Testing, LLC

Previously Flom Test Lab

RF, EMC and Safety Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Date: June 30, 2010

Federal Communications Commission
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Kenwood USA Corporation

Equipment: TK-3312-2, TK-3317-2

FCC ID: ALH413801

FCC Rules: Part 22, 74, 90

To Whom It May Concern:

On behalf of the Applicant, enclosed please find Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

We trust the same is in order. If you should need any further information, kindly contact the writer who is authorized to act as agent.

Best regards,

John Erhard: Engineering Manager



Compliance Testing, LLC

Previously Flom Test Lab

RF, EMC and Safety Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

for

FCC ID: ALH413801

Model: TK-3312-2, TK-3317-2

to

Federal Communications Commission

Rule Part(s) 22, 74, 90, 90.210

Date of report: June 30, 2010

On the Behalf of the Applicant: Kenwood USA Corporation

At the Request of: Kenwood USA Corporation
Communications Division
3970 Johns Creek Court, Suite 100
Suwanee, GA 30024

Attention of: Joel E. Berger, Research & Development
JBerger@kenwoodusa.com
(678) 474-4722; FAX: -4731

Reviewed by:

John Erhard: Engineering Manager



Test Report Revision History

Revision	Date	Revised By	Reason for revision
1.0	June 30, 2010	J. Erhard	Original Document
2.0	July 16, 2010	K. Springer	Added complete listing of standards



Compliance Testing, LLC

List of Exhibits

(FCC **Certification** (Transmitters) - Revised 9/28/98)

Applicant: Kenwood USA Corporation

FCC ID: ALH413801

By Applicant:

1. Letter of Authorization
2. Confidentiality Request: 0.457 And 0.459
3. Identification Drawings, 2.1033(c)(11)
 - Label
 - Location of Label
 - Compliance Statement
 - Location of Compliance Statement
4. Photographs, 2.1033(c)(12)
5. Documentation: 2.1033(c)
 - (3) User Manual
 - (9) Tune Up Info
 - (10) Schematic Diagram
 - (10) Circuit Description
 - Block Diagram
 - Parts List
 - Active Devices
6. MPE/SAR Report

By Compliance Testing:

- A. Testimonial & Statement of Certification



The Applicant has been cautioned as to the following:

15.21 Information to the User

The user's manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) Special Accessories

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.


Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.



Testimonial and Statement of Certification

This is to Certify:

1. **That** the application was prepared either by, or under the direct supervision of, the undersigned.
2. **That** the technical data supplied with the application was taken under my direction and supervision.
3. **That** the data was obtained on representative units, randomly selected.
4. **That**, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data is true and correct.

A handwritten signature in black ink, appearing to read "John B. Erhard".

Certifying Engineer:

John Erhard: Engineering Manager

Table of Contents

<u>Rule</u>	<u>Description</u>	<u>Page</u>
	Test Report	2
2.1033(c)(14)	Rule Summary	3
	Standard Test Conditions and Engineering Practices	4
2.1033(c)	General Information Required	5
	Test Results Summary	7
2.1046	Carrier Output Power (Conducted)	8
2.1051	Conducted Spurious Emissions	9
2.1053	Field Strength of Spurious Radiation	16
90.210	Emission Masks (Occupied Bandwidth)	20
90.214	Transient Frequency Behavior	30
2.1047	Audio Low Pass Filter (Voice Input)	33
2.1047	Audio Frequency Response	34
2.1047	Modulation Limiting	35
90.213	Frequency Stability (Temperature Variation)	38
90.213	Frequency Stability (Voltage Variation)	39
RSS-GEN	Receiver Spurious Emissions	40
	Necessary Bandwidth Calculations)	43
	Test Equipment Utilized	44

Required information per ISO 17025-2005, paragraph 5.10.2:

a)

Test Report

b) Laboratory:
(FCC: 933597)
(Canada: IC 2044-A) Compliance Testing
3356 N. San Marcos Place, Suite 107
Chandler, AZ 85225

c) Report Number: d1060012

d) Client: Kenwood USA Corporation
Communications Division
3970 Johns Creek Court, Suite 100
Suwanee, GA 30024

e) Identification: TK-3312-2, TK-3317-2

EUT Description: UHF FM Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: June 30, 2010

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Measurement Uncertainty: In accordance with Compliance Testing internal quality manual.

m) Reviewed by:



John Erhard: Engineering Manager

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.



Compliance Testing, LLC

Sub-part

2.1033(c)(14):

Test and Measurement Data

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts: 22, 74, 90, 90.210.



Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI/C63.4-2009, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Measurement results, unless otherwise noted, are worst-case measurements.

A2LA

"A2LA has accredited Compliance Testing in Chandler, AZ for technical competence in the field of Electrical testing. The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO 17025:2005 'General Requirements for the Competence of Testing and Calibration Laboratories' and any additional program requirements in the identified field of testing."

Please refer to www.a2la.org for current scope of accreditation.

Certificate number: 2152.01



FCC OATS Reg. #933597

IC Reg. # 2044A-1



List of General Information Required for Certification

In Accordance with FCC Rules and Regulations,
Volume II, Part 2 and to Parts 22, 74, 90 Sub-part 2.1033

(c)(1):

Name and Address of Applicant: Kenwood USA Corporation
Communications Division
3970 Johns Creek Court, Suite 100
Suwanee, GA 30024

Manufacturer: Kenwood Corporation
14-6, Dogenzaka 1-Chome
Shibuya-ku, Tokyo 150, Japan
OR
Kenwood Electronics Technologies PTE Ltd.
1 Ang Mo Kio Street 63
Singapore 569110

(c)(2): **FCC ID:** ALH413801

Model Number: TK-3312-2, TK-3317-2

(c)(3): **Instruction Manual(s):**

Please see attached exhibits

(c)(4): **Type of Emission:** FM

(c)(5): **Frequency Range, MHz:** 406.1 - 470

(c)(6): **Power Rating, Watts:** 5 Continuously variable to 1W

Switchable Variable N/A

FCC Grant Note:

(c)(7): **Maximum Allowable Power, Watts:** 5

DUT Results: Passes Fails



Subpart 2.1033 (continued)

(c)(8): Voltages & currents in all elements in final RF stage, including final transistor or solid-state device:

Collector Current, A	=	2
Collector Voltage, Vdc	=	7.5
Supply Voltage, Vdc	=	7.5

(c)(9): **Tune-Up Procedure:**

Please see attached exhibits

(c)(10): **Circuit Diagram/Circuit Description:**

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

Please see attached exhibits

(c)(11): **Label Information:**

Please see attached exhibits

(c)(12): **Photographs:**

Please see attached exhibits

(c)(13): **Digital Modulation Description:**

 Attached Exhibits
X N/A

(c)(14): **Test and Measurement Data:**

Follows



Test Results Summary

Specification	Test Name	Pass, Fail, N/A	Comments
2.1046	Carrier Output Power (Conducted)	Pass	
2.1051	Unwanted Emissions (Transmitter Conducted)	Pass	
2.1053	Field Strength of Spurious Radiation	Pass	
90.210	Emission Masks (Occupied Bandwidth)	Pass	
2.1047	Audio Low Pass Filter (Voice Input)	Pass	
2.1047	Audio Frequency Response	Pass	
2.1047	Modulation Limiting	Pass	
90.213	Frequency Stability (Temperature Variation)	Pass	
90.213	Frequency Stability (Voltage Variation)	Pass	
RSS-GEN	Receiver Spurious Emissions	Pass	




Name of Test: Carrier Output Power (Conducted)
Specification: 2.1046
Test Equipment Utilized: i00331

Engineer: J. Erhard
Test Date: 6/25/2010

Measurement Procedure

The Equipment Under Test (EUT) was connected to a Spectrum analyzer through an attenuator. The cable and attenuator losses were summed and input into the analyzer as a reference lever offset to ensure accurate readings.

Test Setup



High Power Transmitter Peak Output Power

Tuned Frequency MHz	Recorded Measurement dBm	Result
406.15	36.99	Pass
418.05	36.99	Pass
429.95	36.99	Pass
450.05	36.99	Pass
460.05	36.99	Pass
469.95	36.99	Pass




Name of Test: Conducted Spurious Emissions
Specification: 2.1051
Test Equipment Utilized: i00331, i00124

Engineer: J. Erhard
Test Date: 6/25/2010

Test Procedure



The EUT was connected directly to a spectrum analyzer to verify that the UUT met the requirements for spurious emissions. A tunable notch filter was utilized to ensure the fundamental did not put the spectrum analyzer into compression. The resolution bandwidth set for 100 kHz and the reference level was adjusted to ensure the system had sufficient dynamic range to measure spurious emissions. The frequency range from 30 MHz to the 10th harmonic of the fundamental transmitter was observed and plotted.

Test Setup





High Power Conducted Spurious Emissions Summary Test Table

Tuned Frequency (MHz)	Spurious Frequency (MHz)	Measured Spurious Level (dBm)	Specification Limit (dBm)	Result
406.15	2980	-39.97	-25	Pass
418.05	2660	-39.73	-25	Pass
429.95	2970	-38.62	-25	Pass
450.05	1350	-38.57	-25	Pass
460.05	1380	-36.24	-25	Pass
469.95	1410	-36.50	-25	Pass

Test Plots
406.15 MHz





418.05 MHz







429.95 MHz







450.05 MHz







460.05 MHz





469.95 MHz





Name of Test: Field Strength of Spurious Radiation
Specification: 2.1053
Test Equipment Utilized: i00124, i00266, i00042, i00047, i00048, i00033

Engineer: J. Erhard
Test Date: 7/4/2010

Test Procedure



- A) Connect the equipment as illustrated
- B) Adjust the spectrum analyzer for the following settings:
 - 1) Resolution Bandwidth 100 kHz (<1 GHZ), 1 MHZ (> 1GHz).
 - 2) Video Bandwidth \geq 3 times Resolution Bandwidth, or 30 kHz
 - 3) Sweep Speed \leq 2000 Hz/second
 - 4) Detector Mode = Mean or Average Power
- C) Place the transmitter to be tested on the turntable in the standard test site. The transmitter is transmitting into a non-radiating load that is placed on the turntable. The RF cable to this load should be of minimum length.
- D) For each spurious measurement the test antenna should be adjusted to the correct length for the frequency involved. This length may be determined from a calibration ruler supplied with the equipment. Measurements shall be made from the lowest radio frequency generated in the equipment to the tenth harmonic of the carrier, except for the region close to the carrier equal to \pm the test bandwidth (see section 1.3.4.4).
- E) For each spurious frequency, raise and lower the test antenna from 1 m to 4 m to obtain a maximum reading on the spectrum analyzer with the test antenna at horizontal polarity. Repeat this procedure to obtain the highest possible reading. Record this maximum reading.
- F) Repeat step E) for each spurious frequency with the test antenna polarized vertically.
- G) Reconnect the equipment as illustrated.
- H) Keep the spectrum analyzer adjusted as in step B).
- I) Remove the transmitter and replace it with a substitution antenna (the antenna should be half-wavelength for each frequency involved). The center of the substitution antenna should be approximately at the same location as the center of the transmitter. At lower frequencies, where the substitution antenna is very long, this will be impossible to achieve when the antenna is polarized vertically. In such case the lower end of the antenna should be 0.3 m above the ground.
- J) Feed the substitution antenna at the transmitter end with a signal generator connected to the antenna by means of a non-radiating cable. With the antennas at both ends horizontally polarized and with the signal generator tuned to a particular spurious frequency, raise and lower the test antenna to obtain a maximum reading at the spectrum analyzer. Adjust the level of the signal generator output until the previously recorded maximum reading for this set of conditions is obtained. This should be done carefully repeating the adjustment of the test antenna and generator output.
- K) Repeat step J) with both antennas vertically polarized for each spurious frequency.
- L) Calculate power in dBm into a reference ideal half-wave dipole antenna by reducing the readings obtained in steps J) and K) by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal half-wave dipole antenna.
- M) The levels recorded in step L) are absolute levels of radiated spurious emissions in dBm. The radiated spurious emissions in dB can be calculated by the following:

Radiated spurious emissions dB = $10\log_{10}(\text{TX power in watts}/0.001) - \text{the levels in step I}$

NOTE: It is permissible that other antennas provided can be referenced to a dipole.



Test Setup



**Peak Power Test Results**

Emission Frequency (MHz)	Measured Level (dBm)	Correction Factor (dB)	Corrected Value (dBm)	Antenna
406.15	11.9	19.4	31.3	17M
418.05	15.1	19.5	34.6	17M
429.95	14.9	19.5	34.4	17M
450.05	21.0	19.5	40.5	17M
460.05	19.0	19.8	38.8	17M
469.95	20.0	20.1	40.1	17M
406.15	13.0	19.4	32.4	23M
418.05	16.0	19.5	35.5	23M
429.95	16.1	19.5	35.6	23M
450.05	21.0	19.5	40.5	23M
460.05	18.8	19.8	38.6	23M
469.95	19.6	20.1	39.7	23M
406.15	16.5	19.4	35.9	27M
418.05	18.5	19.5	38.0	27M
429.95	17.7	19.5	37.2	27M
450.05	21.0	19.5	40.5	27M
460.05	19.3	19.8	39.1	27M
469.95	20.4	20.1	40.5	27M

**Radiated Spurious Emissions 17M Test Results**

Tuned Frequency (MHz)	Emission Frequency (MHz)	Measured Level (dBm)	Correction Factor (dB)	Corrected Value (dBm)	Limit (dBm)	Margin (dB)
406.15	812.3	-68.4	24.5	-43.9	-25	-18.9
418.05	836.1	-61.2	24.7	-36.5	-25	-11.5
429.95	859.9	-58.9	25.1	-33.8	-25	-8.8
450.05	900.1	-63.8	25.3	-38.5	-25	-13.5
460.05	920.1	-68.5	26.2	-42.3	-25	-17.3
469.95	939.9	-62.4	26.4	-36.0	-25	-11

Radiated Spurious Emissions 23M Test Results

Tuned Frequency (MHz)	Emission Frequency (MHz)	Measured Level (dBm)	Correction Factor (dB)	Corrected Value (dBm)	Limit (dBm)	Margin (dB)
406.15	812.3	-65.9	24.5	-41.4	-25	-16.4
418.05	836.1	-61.1	24.7	-36.4	-25	-11.4
429.95	859.9	-59.2	25.1	-34.1	-25	-9.1
450.05	900.1	-65.5	25.3	-40.2	-25	-15.2
460.05	920.1	-69.2	26.2	-43.0	-25	-18
469.95	939.9	-62.5	26.4	-36.1	-25	-11.1

Radiated Spurious Emissions 27M Test Results

Tuned Frequency (MHz)	Emission Frequency (MHz)	Measured Level (dBm)	Correction Factor (dB)	Corrected Value (dBm)	Limit (dBm)	Margin (dB)
406.15	812.3	-74.7	24.5	-50.2	-25	-25.2
418.05	836.1	-60.8	24.7	-36.1	-25	-11.1
429.95	859.9	-58.3	25.1	-33.2	-25	-8.2
450.05	900.1	-61.4	25.3	-36.1	-25	-11.1
460.05	920.1	-64.4	26.2	-38.2	-25	-13.2
469.95	939.9	-64.5	26.4	-38.1	-25	-13.1

No other emissions were detected. All emissions were greater than -25 dBm.




Name of Test: Emission Masks (Occupied Bandwidth)
Specification: 90.210
Test Equipment Utilized: i00331, i00118

Engineer: J. Erhard
Test Date: 6/25/2010


The EUT was connected directly to a spectrum analyzer to verify that the EUT meets the required emissions mask. A reference level plot is provided to verify that the peak power was established prior to testing the mask. A modulation frequency of 2.5 kHz at a level of 240 mVPP was input into the EUT for the analog tests and an internal test pattern was utilized for the digital input.

Test Setup




Occupied Bandwidth Plots

Reference Plots 406.15 MHz






418.05 MHz




429.95 MHz






450.05 MHz





460.05 MHz






469.95 MHz






418.05 MHz




429.95 MHz






450.05 MHz




460.05 MHz






469.95 MHz




Wide Band Mask
406.15 MHz






418.05 MHz




429.95 MHz






450.05 MHz




460.05 MHz





469.95 MHz






Name of Test: Transient Frequency Behavior
Specification: 90.214
Test Equipment Utilized: i00345, i00118

Engineer: J. Erhard
Test Date: 6/28/2010

Test Procedure


The EUT was connected to a real time spectrum analyzer with audio measurement capability. An arbitrary waveform generator was utilized to inject the required audio frequency. The low pass filter response was plotted.

Test Set-Up






Narrow Band Test Results On Time




Narrow Band Test Results Off Time






Wide Band Test Results On Time



Wide Band Test Results Off Time






Name of Test: Audio Low Pass Filter (Voice Input)
Specification: 2.1047
Test Equipment Utilized: i00345, i00118

Engineer: J. Erhard
Test Date: 6/24/2010


Test Procedure

The EUT was connected to a real time spectrum analyzer with audio measurement capability. An arbitrary waveform generator was utilized to inject the required audio frequency. The low pass filter response was plotted.


Test Set-Up



Narrow Band Test Results



Wide Band Test Results



This unit is a digital radio and the roll-off for the filter is very linear in the operational band and sharp out of the band




Name of Test: Audio Frequency Response
Specification: 2.1047
Test Equipment Utilized: i00345, i00118

Engineer: J. Erhard
Test Date: 6/24/2010


Test Procedure

The EUT was connected to a real time spectrum analyzer with audio measurement capability. An arbitrary waveform generator was utilized to inject the required audio frequency. The low pass filter response was plotted.


Test Set-Up



Narrow Band Test Results



Wide Band Test Results






Name of Test: Modulation Limiting
Specification: 2.1047(a)
Test Equipment Utilized: i00345, i00118

Engineer: J. Erhard
Test Date: 6/24/2010

Test Procedure

The EUT was connected to a real time spectrum analyzer with audio measurement capability. An arbitrary waveform generator was utilized to inject the required audio frequency. The low pass filter response was plotted.


Test Set-Up






Swept Frequency

Narrow Band Positive Peaks




Narrow Band Negative Peaks






Wide Band Positive Peaks

Positive Peak Deviation (kHz)



Wide Band Negative Peaks

Negative Peak Deviation (kHz)






Name of Test: Frequency Stability (Temperature Variation)
Specification: 90.213
Test Equipment Utilized: i00320, i00350, i00027, i00019

Engineer: J. Erhard
Test Date: 6/24/2010


Measurement Procedure

The EUT was placed in an environmental test chamber and the RF output was connected directly to a frequency counter. The temperature was varied from -30°C to 50°C in 10°C increments. After a sufficient time for temperature stabilization the RF output frequency was measured.

Measurement Setup



Measurement Results






Name of Test: Frequency Stability (Voltage Variation)
Specification: 90.213
Test Equipment Utilized: i00320, i00350, i00027, i00019

Engineer: J. Erhard
Test Date: 6/24/2010


Measurement Procedure

The EUT was placed in a temperature chamber at $25\pm5^{\circ}\text{C}$ and connected directly to a frequency counter and variable power supply. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value and the RF output was measured.

Measurement Setup



Measurement Results






Name of Test: Receiver Spurious Emissions
Specification: RSS-GEN
Test Equipment Utilized: i00331

Engineer: J. Erhard
Test Date: 6/26/2010

Test Procedure



The Equipment Under Test (EUT) was connected directly to a Spectrum analyzer. The cable loss was input into the analyzer as a reference lever offset to ensure accurate readings.

Test Setup







148 MHz





460 MHz





Modulation = 11K0F3E

Necessary Bandwidth Calculation:

Maximum Modulation (M), kHz	= 3
Maximum Deviation (D), kHz	= 2.5
Constant Factor (K)	= 1
Necessary Bandwidth (B _N), kHz	= $(2 \times M) + (2 \times D \times K)$
	= 11.0

Modulation = 16K0F3E

Necessary Bandwidth Calculation:

Maximum Modulation (M), kHz	= 3
Maximum Deviation (D), kHz	= 5
Constant Factor (K)	= 1
Necessary Bandwidth (B _N), kHz	= $(2 \times M) + (2 \times D \times K)$
	= 16.0

**Test Equipment Utilized**

Description	MFG	Model Number	Asset Number	Last Cal Date	Cal Due Date
Temperature Chamber	Tenney	Tenney Jr.	i00027	12/8/09	12/08/10
Tunable Notch Filter	Eagle	TNF-1	i00124	NCR	NCR
Signal Generator	R&S	SMT-03	i00266	NCR	NCR
Spectrum Analyzer	Agilent	E4407B	i00331	11/3/09	11/3/10
RTSA	Tektronix	RSA 3308A	i00345	8/21/09	8/21/10
Arbitrary Waveform Generator	HP	32120A	i00118	NCR	NCR
Dipole Antenna Set	Ailttech	DM105A-T1,T2, T3	i00042, 47, 48	NCR	NCR
Power Supply	HP	6654A	i00350	NCR	NCR
DMM	Fluke	75III	i00320	2/16/10	2/16/11
Frequency Counter	HP	5334B	i00019	2/15/10	2/15/11
Spectrum Analyzer	HP	8546A	i00033	11/4/09	11/4/10

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the described equipment. Prior to testing these components were tested to verify proper operation.

END OF TEST REPORT