



GD200M (GO Tracker 1.5) User Manual

Version: 1.00

International Telematics Solutions Innovator

www.queclink.com

Document Title	GD200M (GO Tracker 1.5) User Manual
Version	1.00
Date	2019-02-15
Status	Released

General Notes

Queclink offers this information as a service to its customers, to support application and engineering efforts that use the products designed by Queclink. The information provided is based upon requirements specifically provided to Queclink by the customers. Queclink has not undertaken any independent search for additional relevant information, including any information that may be in the customer's possession. Furthermore, system validation of this product designed by Queclink within a larger electronic system remains the responsibility of the customer or the customer's system integrator. All specifications supplied herein are subject to change.

Copyright

This document contains proprietary technical information which is the property of Queclink. Copying of this document, distribution to others or using or communication of the contents thereof is forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of a patent grant or the registration of a utility model or design. All specifications supplied herein are subject to change without notice at any time.

Copyright © Queclink Wireless Solutions Co., Ltd. 2019

Contents

0. Revision History.....	1
1. Introduction	2
1.1. GD200M (GO Tracker 1.5) Products	2
2. Product Specifications and Operation.....	3
2.1. Basic Feature Set	3
2.2. Transmit Mode	3
2.3. Reporting Interval.....	3
2.4. Activation	3
2.5. SIM	错误!未定义书签。
2.6. Internal Sensors.....	3
2.7. Color	3
3. Installation Precautions.....	4
4. Troubleshooting and Safety Info	5
4.1. Troubleshooting	5
4.2. Safety Info	5

0. Revision History

Revision	Date	Author	Description of Change
1.00	2019-11-15	Arry Wang	Initial

1. Introduction

The GD200MG Series is a professional LTE Cat M1/NB1 device used in cold-chain logistics and cold storage. It is developed by Queclink for Emerson.

It has excellent performance on humidity and temperature monitoring and motion detection, alongside with other features like door status detection (opening and closing) of cold storage through light sensor, extensive battery life with sophisticated power management.

1.1. GD200M (GO Tracker 1.5) Products

Table 1. GD200M (GO Tracker 1.5) Products

Models	Technology	Operating Band (MHz)
GO Real-Time 4G/CATM	eMTC/NB-IoT	Cat.M1/Cat.NB1: LTE FDD: B1/B2/B3/B4/B5/B8/B12/B13/B18/ B19/B20/B26/B28 LTE TDD: B39 (For Cat.M1 Only) EGPRS: 850/900/1800/1900MHz
GO Real-Time XL 4G/CATM		
GO Real-Time Reusable 4G/CATM		

2. Product Specifications and Operation

2.1. Basic Feature Set

- Single Use
- Operating range: -20C to 60C with a target of -30C for low temps
- Temp+Humidity – anticipate Sensirion SHT3C (NIST Certified)
- Shock, Tilt (Device reports X,Y,Z values. Server does further processing)
- LUX
- Location - Quectel BG96 tower information
- Single SIM, Nano SIM – size SIM card
- Pull Tab Start. No on/off button
- Micro USB charging port on bottom of unit, also used for redundant data transmission
- LEDs

2.2. Transmit Mode

- CAT.M1, CAT.NB1, EGPRS.
- Micro USB will allow for manual data download with cellular signal not available. Note same Micro USB will enable recharging during recycling process.

2.3. Activation

- Pull Tab which connects the battery power to the unit.
- Visual indication of successful activation: LEDs flash.

2.4. Reporting Interval

- Models can be configured to 6, 6, 18 (record every six minutes and report every 18 minutes) and 60, 60 (record and report every 60 minutes)
- During “emergency mode,” where shipments are lost or stolen, interval changes to the minimum interval allowed by technology. (1 minute)

2.5. Internal Sensors

- Accelerometer – 3 axis accelerometer
- NIST traceable Temp Sensor
- Humidity
- LUX (light)

2.6. Color

Color of the plastic housing:

- GO Real-Time 4G/CATM – White
- GO Real-Time XL 4G/CATM – Blue
- GO Real-Time Reusable 4G/CATM - Green

3. Installation Precautions

- ◆ Firmly install the device to a reliable surface to prevent falling off.
- ◆ Do not install the device under metal surface or in enclosed environments having difficulty in getting network signal.

4. Troubleshooting and Safety Info

4.1. Troubleshooting

Table 2. 1.1. GD200M (GO Tracker 1.5) Troubleshooting List

Trouble	Possible Reason	Solution
Messages can't be reported to the backend server by network.	APN is not right.	Ask the network operator for the right APN.
	The IP address or port of the backend server is wrong.	Make sure the IP address for the backend server is an identified address in the internet.
There is no response from USB port when the device is configured by using USB.	The port is not ready or the device is not powered on.	Please check the port and the device to ensure they are working properly.

4.2. Safety Info

- Do not disassemble the device by yourself.
- Do not put the device in the overheated place. Too high temperature will damage the device or even cause battery explosion.
- Do not use the device on the airplane or near medical equipment.

FCC Regulations:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This device has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiated radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.

Caution: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

RF Exposure Information

This device meets the government's requirements for exposure to radio waves.

This device is designed and manufactured not to exceed the emission limits for exposure to radio frequency (RF) energy set by the Federal Communications Commission of the U.S. Government.

This device complies with FCC radiation exposure limits set forth for an uncontrolled environment. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, human proximity to the antenna shall not be less than 20cm (8 inches) during normal operation.

1.1.1 ISED Notice

This device complies with Innovation, Science and Economic Development Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:

- (1) this device may not cause interference, and
- (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes:

- (1) l'appareil ne doit pas produire de brouillage, et
- (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en

This device complies with the Canadian ICES-003 Class B specifications. CAN ICES-3(B)/ NMB-3(B)

IC: 10124A-101011

ISED RF Exposure Statement

This device complies with ISED RSS-102 RF exposure limits set forth for an uncontrolled environment. In order to avoid the possibility of exceeding the IC RSS-102 RF exposure limits, human proximity to the antenna shall not be less than 20cm (8 inches) during

normal operation.

Cet appareil est conforme aux limites d'exposition aux rayonnements de la CNR-102 définies pour un environnement non contrôlé. Afin d'éviter la possibilité de dépasser les limites d'exposition aux fréquences radio de la CNR-102, la proximité humaine à l'antenne ne doit pas être inférieure à 20 cm (8 pouces) pendant le fonctionnement normal.