

Federal Communications Commission
Authorization and Evaluation Division
7435 Oakland Mills Rd.
Columbia, MD. 21046

Date: Dec. 10, 1999

Attention: Authorization and Evaluation Division

Subject: RFI related modifications incorporated into unit LCD MONITOR
with - FCC ID: AMPL51A1

Dear Sirs:

This letter serves as our declaration that all modifications listed below were implemented in the sample submitted for testing. We further declare that the same modifications will be implemented into all production units to enhance compliance of the units to FCC limits.

The modifications include the following:

- 1) Added two ferrite cores on the video cable outside the LCD monitor. (see photo 2)
- 2) Added two ferrite cores on the DC output cable of the power adapter. (see photo21)
- 3) Added a ferrite core on the wire connected between control-key board and logical board. (see photo 6)
- 4) Added two ferrite cores on the wire connected between power board and logical board. (see photo 7)
- 5) Added a ferrite core on the wire connected between inverter board and logical board. (see photo 7)
- 6) Added four rows of copper foils around four sides of LCD panel. (see photo 10)
- 7) Added a piece of copper foil on the two wires connected between main board and the back of LCD panel. (see photo 11)
- 8) Added a capacitor on the solder side of power board. (see photo 15)

If you have any further questions or comments regarding the above, please don't hesitate to contact Mr. Mike Su of ADT Lab. at fax No.:886-2-2602-2943 or E-mail: mike@mail.adt.com.tw

Sincerely yours,



Kent Tsai / Safety Manager
Jean Co., Ltd.

cc. Mr. Harris W. Lai - Advance Data Technology Corporation