



EMC

TEST REPORT

REPORT NO. : F88051304

MODEL NO. : JT156E

DATE OF TEST : May 18, 1999

PREPARED FOR : JEAN CO., LTD.

ADDRESS : 5F, 167, FU HSING N. RD.,
TAIPEI, TAIWAN, R.O.C.

PREPARED BY: ADVANCE DATA TECHNOLOGY CORPORATION



11F, NO.1, SEC.4, NAN-KING EAST RD.,
TAIPEI, TAIWAN, R.O.C.

This test report consists of 15 pages in total. It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of our laboratory. It should not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. government. The test result in the report only applies to the tested sample.



TABLE OF CONTENTS

1. CERTIFICATION	3
2. GENERAL INFORMATION.....	4
2.1 GENERAL DESCRIPTION OF EUT	4
2.2 DESCRIPTION OF SUPPORT UNITS	5
2.3 TEST METHODOLOGY AND CONFIGURATION	5
3. TEST INSTRUMENTS.....	6
3.1 TEST INSTRUMENTS (EMISSION)	6
3.2 LIMITS OF CONDUCTED AND RADIATED EMISSION.....	7
4. TEST RESULTS (EMISSION).....	8
4.1 RADIO DISTURBANCE.....	8
4.2 EUT OPERATION CONDITION.....	8
4.3 TEST DATA OF CONDUCTED EMISSION	9
4.4 TEST DATA OF RADIATED EMISSION	11
5. PHOTOGRAPHS OF THE TEST CONFIGURATION WITH MINIMUM MARGIN	13
6. APPENDIX - INFORMATION OF THE TESTING LABORATORY.....	15



1.

CERTIFICATION

Issue Date: May 25, 1999

Product : LCD MONITOR
Trade Name : JEAN
Model No. : JT156E
Type No. : L51B
Applicant : JEAN CO., LTD.
Standard : FCC Part 15, Subpart B, Class B
ANSI C63.4-1992
CISPR 22: 1993+A1: 1995+A2: 1996

We hereby certify that one sample of the designation has been tested in our facility on May 18, 1999. The test record, data evaluation and Equipment Under Test (EUT) configurations represent herein are true and accurate representation of the measurements of the sample's EMC characteristics under the conditions herein specified.

The test results show that the EUT as described in this report is in compliance with the Class B limits of conducted and radiated emission of applicable standards.

TESTED BY : Bruce Lu , DATE: 5/18/99
(Bruce Lu)

CHECKED BY : Yemmy Soong , DATE: 5/25/99
(Yemmy Soong)

APPROVED BY : Mike Su , DATE: 5/25/99
(Mike Su)

ADVANCE DATA TECHNOLOGY CORPORATION

NVLAP
Accredited Laboratory



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Product	:	LCD MONITOR
Model No.	:	JT156E
Power Supply Type	:	Switching
Power Cord	:	Nonshielded 3-pin (1.8 m)
Data Cable	:	Shielded (1.5 m)

Note: The EUT is a 15" LCD monitor with resolution up to 1024 x 768.

There are two ferrite cores on the video cable of the EUT.

For more detailed features description, please refer to manufacturer's specification or User's Manual.



2.2 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories are used to form representative test configuration during the tests.

No.	Product	Brand	Model No.	FCC ID	I/O Cable
1	PERSONAL COMPUTER	HP	VL series 4 5/100	B94VECTRA500T	Nonshielded Power (1.8m)
2	KEYBOARD	FORWARD	FDA-104GA	F4ZDA-104G	Shielded Signal (1.4m)
3	MOUSE	DEXIN	A2P800A	NIYA2P800A	Shielded Signal (1.5m)
4	PRINTER	HP	2225C+	DSI6XU2225	Shielded Signal (2.1m) Nonshielded Power (1.5m)
5	MODEM	ACEEX	1414	IFAXDM1414	Shielded signal (1.2m) Nonshielded Power (1.5m)
6	VGA CARD	GORDIA	DSV3365	LUT-DSV3365	NA

2.3 TEST METHODOLOGY AND CONFIGURATION

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 1992. Radiated testing was performed at an antenna to EUT distance of 10 m on an open area test site.

Please refer to the photos of test configuration in Item 5.



3. TEST INSTRUMENTS

3.1 TEST INSTRUMENTS (EMISSION)

CONDUCTED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
ROHDE & SCHWARZ Test Receiver	ESH3	893495/006	July 15, 1999
ROHDE & SCHWARZ Spectrum Monitor	EZM	893787/013	July 16, 1999
ROHDE & SCHWARZ Artificial Mains Network	ESH3-Z5	839135/006	July 14, 1999
EMCO-L.I.S.N.	3825/2	9204-1964	July 14, 1999
Shielded Room	Site 2	ADT-C02	NA

Note: 1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months.

And the calibrations are traceable to NML/ROC and NIST/USA.

RADIATED EMISSION MEASUREMENT

Description & Manufacturer	Model No.	Serial No.	Calibrated until
HP Spectrum Analyzer	8590L	3544A00941	Dec. 06, 1999
HP Pre-Amplifier	8447D	2944A08312	Sept. 15, 1999
HP Preamplifier	8347A	3307A01088	Sept. 9, 1999
R&S Receiver	ESVS10	844594/010	Sept. 24, 1999
SCHWARZBECK Tunable Dipole Antenna	VHA 9103 UHA 9105	E101051 E101055	Nov. 25, 1999
CHASE BILOG Antenna	CBL6111A	1500	Sept. 4, 1999
EMCO Double Ridged Guide Antenna	3115	9312-4192	April 5, 2000
EMCO Turn Table	1060-04	1196	NA
EMCO Tower	1051	1264	NA
Open Field Test Site	Site 1	ADT-R01	Aug. 28, 1999

Note: 1. The measurement uncertainty is less than +/- 3dB, which is calculated as per NAMAS document NIS81.

2. The calibration interval of the above test instruments is 12 months.

And the calibrations are traceable to NML/ROC and NIST/USA.



3.2 LIMITS OF CONDUCTED AND RADIATED EMISSION

LIMIT OF RADIATED EMISSION OF CISPR 22

FREQUENCY (MHz)	Class A (at 10m) *	Class B (at 10m) *
	dBuV/m	dBuV/m
30 - 230	40	30
230 - 1000	47	37

* Detector Function: Quasi-Peak

LIMIT OF RADIATED EMISSION OF FCC PART 15, SUBPART B FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (MHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	Peak	Average	Peak	Average
Above 1000	80.0	60.0	74.0	54.0

Note: (1) The lower limit shall apply at the transition frequencies.
 (2) Emission level (dBuV/m) = $20 \log$ Emission level (uV/m).
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

LIMIT OF CONDUCTED EMISSION OF CISPR 22

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

Note: (1) The lower limit shall apply at the transition frequencies.
 (2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz
 (3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



4. TEST RESULTS (EMISSION)

4.1 RADIO DISTURBANCE

Frequency Range : 0.15 - 30 MHz (Conducted Emission)
 : 30 - 1000 MHz (Radiated Emission)
 Input Voltage : 120 Vac, 60 Hz
 Temperature : 24 °C
 Humidity : 84 %
 Atmospheric Pressure : 991 mbar

TEST RESULT	Remarks
PASS	Minimum passing margin of conducted emission: -16.8 dB at 2.106 MHz Minimum passing margin of radiated emission: -2.1 dB at 708.88 MHz

Note: The EUT was pre-tested under the following resolution & horizontal synchronization speed mode:

- * 1024x768 mode (60 kHz),
- * 800x600 mode (48 kHz),
- * 640x480 mode (31.5 kHz)

The worst emission levels were found under 1024x768 (60 kHz) and therefore the test data of only this mode is recorded.

4.2 EUT OPERATION CONDITION

1. Turn on the power of all equipment.
2. PC runs a test program to enable all functions.
3. PC reads and writes messages from FDD and HDD.
4. PC sends "H" messages to LCD monitor (EUT) and the LCD monitor displays "H" patterns on their screen.
5. PC sends "H" messages to modem.
6. PC sends "H" messages to printer, and the printer prints them on paper.
7. Repeat steps 3-7.



4.3 TEST DATA OF CONDUCTED EMISSION

EUT: **LCD MONITOR**MODEL: **JT156E**MODE: **1024x768 (60 kHz)**6 dB Bandwidth: **10 kHz**PHASE: **LINE (L)**

Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.150	0.2	44.5	-	44.7	-	66.0	56.0	-21.3	-
0.324	0.2	33.6	-	33.8	-	59.6	49.6	-25.8	-
1.777	0.2	36.9	-	37.1	-	56.0	46.0	-18.9	-
2.106	0.2	37.1	-	37.3	-	56.0	46.0	-18.7	-
21.089	1.2	38.8	-	40.0	-	60.0	50.0	-20.0	-
23.712	1.6	39.8	-	41.4	-	60.0	50.0	-18.6	-


Remarks: 1. **: Undetectable

2. Q.P. and AV. are abbreviations of quasi-peak and average individually.

3. -: The Quasi-peak emission level also meets average limit and measurement with the average detector is unnecessary.

4. The emission levels of other frequencies were very low against the limit.

5. Margin value = Emission level - Limit value





TEST DATA OF CONDUCTED EMISSION

EUT: LCD MONITORMODEL: JT156EMODE: 1024x768 (60 kHz)6 dB Bandwidth: 10 kHzPHASE: NEUTRAL (N)

Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.150	0.2	44.6	-	44.8	-	66.0	56.0	-21.2	-
0.324	0.2	33.8	-	34.0	-	59.6	49.6	-25.6	-
1.777	0.2	38.6	-	38.8	-	56.0	46.0	-17.2	-
2.106	0.2	39.0	-	39.2	-	56.0	46.0	-16.8	-
21.089	1.1	38.9	-	40.0	-	60.0	50.0	-20.0	-
23.712	1.5	39.3	-	40.8	-	60.0	50.0	-19.2	-

Remarks: 1. "*" : Undetectable

2. Q.P. and AV. are abbreviations of quasi-peak and average individually.

3. "-": The Quasi-peak emission level also meets average limit and measurement with the average detector is unnecessary.


4. The emission levels of other frequencies were very low against the limit.

5. Margin value = Emission level - Limit value

Report No F88051304

Page 9-1

Tested by Bruce L.



MODEL:	JT156E (TYPE NO: L51B)	DATE:	18.MAY.'99	TIME:	16:14:36
CISPR	22	CLASS	B	CONDUCTION TEST (PEAK VALUE)	
				1024X768	75Hz/60k
				EMCTEST	110V/60Hz
ADT CORP.					
LISN: L					



4.4 TEST DATA OF RADIATED EMISSION

EUT: LCD MONITORMODEL: JT156EMODE: 1024x768 (60 kHz)ANT.POLARITY: HorizontalDETECTOR FUNCTION: Quasi-peak6 dB BANDWIDTH: 120 kHzFREQUENCY RANGE: 30-1000 MHzMEASURED DISTANCE: 10 M

Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
47.97	11.3	9.2	20.5	30.0	-9.5	400	114
118.16	15.1	5.1	20.2	30.0	-9.8	400	230
173.29	12.4	6.2	18.6	30.0	-11.4	400	143
196.92	12.6	14.8	27.4	30.0	-2.6	373	147
212.67	13.7	9.5	23.2	30.0	-6.8	389	235
220.56	14.4	7.3	21.7	30.0	-8.3	383	158
236.30	15.7	14.0	29.7	37.0	-7.3	301	198
497.33	23.5	4.6	28.1	37.0	-8.9	400	135
708.88	28.5	6.4	34.9	37.0	-2.1	100	192
800.02	30.3	4.2	34.5	37.0	-2.5	303	170

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB) + Reading value (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



TEST DATA OF RADIATED EMISSION

EUT: **LCD MONITOR**MODEL: **JT156E**MODE: **1024x768 (60 kHz)**ANT. POLARITY: **Vertical**DETECTOR FUNCTION: **Quasi-peak**6 dB BANDWIDTH: **120 kHz**FREQUENCY RANGE: **30-1000 MHz**MEASURED DISTANCE: **10 M**

Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
47.26	11.2	14.6	25.8	30.0	-4.2	100	290
48.01	10.9	16.5	27.4	30.0	-2.6	100	290
63.03	7.5	15.5	23.0	30.0	-7.0	219	78
110.28	13.8	6.3	20.1	30.0	-9.9	100	207
118.15	15.5	10.1	25.6	30.0	-4.4	100	232
126.05	15.6	6.2	21.8	30.0	-8.2	100	28
133.91	15.3	8.5	23.8	30.0	-6.2	100	329
157.52	13.9	10.1	24.0	30.0	-6.0	100	322
173.29	12.9	11.2	24.1	30.0	-5.9	100	226
176.27	12.7	6.8	19.5	30.0	-10.5	100	218
181.17	12.5	7.6	20.1	30.0	-9.9	100	219
196.92	13.2	10.6	23.8	30.0	-6.2	100	324
214.15	14.0	11.0	25.0	30.0	-5.0	100	330
220.55	14.3	11.8	26.1	30.0	-3.9	100	317
228.43	14.6	8.6	23.2	30.0	-6.8	100	324
236.30	15.0	16.5	31.5	37.0	-5.5	100	303
315.06	18.3	16.0	34.3	37.0	-2.7	100	310
464.18	23.3	10.8	34.1	37.0	-2.9	100	345
497.33	23.0	6.3	29.3	37.0	-7.7	100	334
630.11	26.5	4.3	30.8	37.0	-6.2	255	364
800.01	29.6	3.4	33.0	37.0	-4.0	193	174

REMARKS:

1. Emission level (dBuV/m) = Correction Factor (dB) + Reading value (dBuV).
2. Correction Factor (dB) = Ant. Factor (dB)+Cable loss (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level - Limit value



6. APPENDIX - INFORMATION OF THE TESTING LABORATORY

Information of the testing laboratory

We, ADT Corp., are founded in 1988, to provide our best service in EMC and Safety consultation. Our laboratory is accredited by the following approval agencies according to ISO/IEC Guide 25 or EN 45001:

● USA	FCC, UL, NVLAP
● Germany	TUV Rheinland
	TUV Product Service
● Japan	VCCI
● New Zealand	RFS
● Norway	NEMKO, DNV
● U.K.	INCHCAPE, SGS
● R.O.C.	BSMI

Enclosed please find some certificates of our laboratory obtained from approval agencies. If you have any comments, please feel free to contact us with the following:

Lin Kou EMC Lab.:
Tel: 886-2-26032180
Fax: 886-2-26022943

Hsin Chu EMC Lab.:
Tel: 886-35-935343
Fax: 886-35-935342

Lin Kou Safety Lab.:
Tel: 886-2-26093195
Fax: 886-2-26093184

Design Center:
Tel: 886-2-26093195
Fax: 886-2-26093184

E-mail: service@mail.adt.com.tw
<http://www.adt.com.tw>