


Electromagnetic Emission
FCC MEASUREMENT REPORT
CERTIFICATION OF COMPLIANCE
FCC Part 15 Certification Measurement

PRODUCT : RADAR DETECTOR
MODEL/TYPE NO : R3 / Proto-type
FCC ID : AMWUA1702
MULTIPLE MODEL : -
BRAND NAME : **Uniden**
APPLICANT : Uniden America Corporation
3001 Gateway Drive, Suite 130,
Irving Texas 75038 United States
Attn.: Al Baum / Director of Engineering and Quality
MANUFACTURER : ATTOWAVE CO., LTD.
1005, 10F Leader's Tower, 60-15 Gasan-dong,
Gumchun-gu, Seoul, 153-801 Korea
FCC CLASSIFICATION : Class B Personal computers and peripherals
JBP - Part 15 Class B Computing Device Peripheral
RULE PART(S) : FCC Part 15 Subpart B
TEST PROCEDURE : ANSI C63.4-2014
TEST REPORT No. : ETLE170313.0277
DATES OF TEST : March 16, 2017 to March 18, 2017
REPORT ISSUE DATE : May 08, 2017
TEST LABORATORY : ETL Inc. (FCC Designation Number: KR0022)

This RADAR DETECTOR, Model R3 has been tested in accordance with the measurement procedures specified in ANSI C63.4-2014 at the ETL Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart B:

I attest to the accuracy of data. All measurement herein was performed by me or was made under my supervision and is correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Prepared by: 

Jeong Hwan, Pyo (Test Engineer)

May 08, 2017

Reviewed by: 

Hyung Min, Choi (Chief Engineer)

May 08, 2017

ETL Inc.

Head office: #371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea

Open site: #499-1, Sagot-ri, Seosin-myeon, Hwaseong-si, Gyeonggi-do, 445-882, Korea

Tel: 82-2-858-0786 Fax: 82-2-858-0788

*The test report merely corresponds to the test sample(s).
This report shall not be reproduced, in whole or in part without the written approval of ETL Inc.*

Table of Contents

FCC Measurement Report

- 1. Introduction**
- 2. Product Information**
- 3. Description of Tests**
- 4. Test Condition**
- 5. Test Results**
 - 5.1 Summary of Test Results**
 - 5.2 Conducted Emissions Measurement**
 - 5.3 Radiated Emissions Measurement**
- 6. Sample Calculation**
- 7. List of test Equipment used for Measurement**

Appendix B. Test Setup Photographs

FCC MEASUREMENT REPORT

Scope – Measurement and determination of electromagnetic emission(EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)

General Information

Applicant Name : Uniden America Corporation

**Address : 3001 Gateway Drive, Suite 130,
Irving Texas 75038 United States**

Attention : Al Baum / Director of Engineering and Quality

- **EUT Type :** RADAR DETECTOR
- **Model Number :** R3
- **FCC ID :** AMWUA1702
- **S/N :** Proto-type
- **Rule Part(s) :** FCC Part 15 Subpart B
- **Test Procedure :** ANSI C63.4-2014
- **FCC Classification :** Class B Personal computers and peripherals
JBP - Part 15 Class B Computing Device Peripheral
- **Dates of Tests :** March 16, 2017 to March 18, 2017
- **Environmental of Tests:** Temperature: (16.4 ± 6.1) °C
Humidity: (41 ± 5) % R.H.
Atmospheric Pressure: (102.2 ± 0.2) kPa
- **Place of Tests :** ETL Inc. Testing Lab. (FCC Designation Number : KR0022)

Radiated Emission test 1;
#499-1, Sagot-ri, Seosin-myeon, Hwaseong-si,
Gyeonggi-do, 445-882, Korea

Radiated Emission test 2 and Conducted Emission test;
#371-51, Gasan-dong, Geumcheon-gu, Seoul, 153-803, Korea
- **Test Report No. :** ETLE170313.0277

1. INTRODUCTION

The measurement tests for radiated and conducted emission test were conducted at the ETL Inc. The site is constructed in conformance with the requirements of the ANSI C63.4-2014 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 m and 10 m site configurations. Detailed description of test facility was found to be in compliance with FCC Rules according to the ANSI C63.4-2014 and registered to the Federal Communications Commission (FCC Designation Number : KR0022).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C63.4-2014) was used in determining radiated and conducted emissions from the Uniden America Corporation, Model: R3.

2. PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the RADAR DETECTOR (model: R3).

The model R3 is basic model that was tested.

2.2 General Specification

Receiver Type	
Radar	Double Conversion Super-heterodyne Self-Contained Antenna
Laser	Pulse Laser Signal Receiver
Frequency	
X Band	10.525 GHz
K Band	24.150 GHz
Ka Band (Super-wide)	(34.700 ± 1.300) GHz
Laser	(950 ± 150) nm
Detector Type	
Radar	Scanning Frequency Discriminator
Laser	Pulse Width Discriminator
Alarm Type	Beep (Detected Band and Signal strength)
Antenna Type	
Radar	Linear Polarized E-vector Vertical
Laser Front	Convex Condenser Lens
Laser Back	Concave Condenser Lens
General	
Dimensions	110.0 mm (D) x 69.0 mm (W) x 29.5 mm (H)
Weight	6.0 oz (170 g)
Operating Temperature	(90.5 ± 94.5) °F (Radar/Laser) (32.5 ± 52.5) °C (Radar/Laser)
Storage Temperature	(90.5 ± 112.5) °F (Radar/Laser) (32.5 ± 62.5) °C (Radar/Laser)
Operating Power Source	(13.5 ± 2.5) V DC
High Internal Frequency	X-tal → 27 MHz

3. DESCRIPTION OF TESTS

3.1 Conducted Emission Measurement

Conducted emissions measurements were made in accordance with section 11, "Measurement of Information Technology Equipment" of ANSI C63.4-2014. The measurements were performed over the frequency range of 0.15 MHz to 30 MHz using a 50 Ω /50 μ H LISN as the input transducer to a Spectrum Analyzer or a Test Receiver. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 9 kHz or for "quasi-peak" within a bandwidth of 9 kHz.

The line-conducted emission test is conducted inside a shielded anechoic chamber room with 1 m x 1.5 m x 0.8 m wooden table which is placed 40 cm away from the vertical wall and 1.5 m away from the side wall of the chamber room. Two LISN are bonded to the shielded room. The EUT is powered from the LISN and the support equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the LISN. Non-inductive bundling to a 1 m length shortened all interconnecting cables more than 1 m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the EMI Test Receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0.15 MHz to 30 MHz. The bandwidth of the spectrum analyzer was set to 9 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission.

Photographs of the worst-case emission can be seen in photographs of conducted emission test setup in Appendix B.

3.2 Radiated Emission Measurement

Radiated emission measurements were made in accordance with section 11, "Measurement of Information Technology Equipment" of ANSI C63.4-2014. The measurements were performed over the frequency range of 30 MHz to 40 GHz (or 5th harmonic of the highest frequency) in using antenna as the input transducer to a spectrum analyzer or a field intensity meter. The measurements below 1 GHz were made with the detector set for "Quasi-peak" within a bandwidth of 120 kHz. The measurements above 1 GHz were made with the detector set for "Peak and Average" within a bandwidth of 1 MHz.

Preliminary measurements were made at 3 m using broadband antennas, and spectrum analyzer to determined the frequency producing the maximum emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30 MHz to 1 000 MHz using Log-Bicon antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site or SVSWR chamber at 3 m. The test equipment was placed on a styrofoam table. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the maximum emission for the frequency and were placed on top of a 0.8 m high nonmetallic 1 m x 1.5 m table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 m to 4 m and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or support equipment and changing the polarity of the antenna, whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

4. TEST CONDITION

4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the EUT and the supported equipments were installed to meet FCC requirement and operated in a manner and which tends to maximize its emission level in a typical application.

4.2 EUT operation

The equipment under test was operated during the measurement under following conditions:

- Data update mode (Program: R3 DB Update Program V1.00)


4.3 Support Equipment Used

Description	Model Name	Serial No.	Manufacturer	FCC
Notebook Computer	6550b	CNU1240LOC	Hewlett-Packard Company	-
Adapter (for Notebook Computer)	Series PPP012H-S	F129411202212 91	Chicony Power Technology (Suzhou) Co., Ltd.	-

4.4 Type of Cables Used

Device from	Device to	Type of I/O port	Length [m]	Type of shield	Used ferrite core
EUT	Notebook Computer	Mini USB	1.0	Unshielded	X
Notebook Computer	Adapter	DC Input	1.2	Shielded	O

4.5 The setup drawing(s)



- : Data Line
- : AC Power Line
- : DC Power Line
- : Adapter

5. TEST RESULTS

5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

FCC Rule	Measurement Required	Result
15.107(a),(d)	Conducted Emission Measurement	Passed by 16.17 dB *
15.109(a)	Radiated Emission Measurement (Below 1 GHz)	Passed by 6.86 dB
15.109(a)	Radiated Emission Measurement (Above 1 GHz)	Passed by 10.00 dB

* This test was tested at host computer (EUT was connected USB port of the host computer).

The data collected shows that the **Uniden America Corporation / RADAR DETECTOR / R3** complies with technical requirements of above rules part 15.107(a),(d) and 15.109(a) Class B Limits.

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.

5.2 Conducted Emissions Measurement

5.2.1 Conducted Emissions Data

EUT	RADAR DETECTOR / R3 (S/N: Proto-type)
Limit apply to	FCC Part 15.107(a),(d) Class B
Test Date	March 18, 2017
Environmental of test	(22.4 ± 0.0) °C, (36 ± 0) % R.H., (102.4 ± 0.0) kPa
Operating Condition	Data update mode (Program: R3 DB Update Program V1.00)
Result	Passed by 16.17 dB

Conducted Emission Test Data

The following data and graph shows the highest levels of conducted emissions on both polarizations of hot and neutral line.

Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth: 9 kHz)


NOTES:

1. Please see the measured data and graph in next page.
2. The Level (Result) value was included the reading, LISN factor and cable loss.
3. Delta (Margin) value = Limit - Level (Result)
4. Measurement were performed at the AC Power Inlet in the frequency band of 150 kHz ~ 30 MHz according to the FCC Part 15.107(a),(d) Class B.
5. If the Quasi-Peak limit is met when using a Peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the Quasi-Peak detector receiver is unnecessary.
6. If the average limit is met when using a Quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

Line: HOT

ETL EMC Laboratory
 Conducted Emission Test Result
 EUT: ETLE170313.0277
 Manuf:
 Op Cond:
 Operator:
 Test Spec:
 Comment: HOT

Prescan Measurement: Detectors: X PK / + AV
 Meas Time: see scan settings
 Peaks: 16
 Acc Margin: 10 dB



ETL EMC Laboratory
 Conducted Emission Test Result

EUT: ETLE170313.0277
 Manuf:
 Op Cond:
 Operator:
 Test Spec:
 Comment: HOT

Prescan Measurement: Detectors: X PK / + AV
 Meas Time: see scan settings
 Peaks: 16
 Acc Margin: 10 dB

Peak Search Results

Frequency MHz	PK Level dB μ V	PK Limit dB μ V	PK Delta dB
0.15	44.69	66.00	21.31
0.192	43.43	63.95	20.52
0.195	42.49	63.82	21.33
0.261	37.32	61.40	24.08
0.392	33.78	58.02	24.24
0.4	35.71	57.85	22.14
0.642	35.31	56.00	20.69
0.911	34.28	56.00	21.72
0.921	35.43	56.00	20.57
1.545	37.03	56.00	18.97
2.2	38.97	56.00	17.03
3.1	37.82	56.00	18.18
5.11	43.83	60.00	16.17
8.605	35.21	60.00	24.79
17.99	36.52	60.00	23.48
19.8	36.79	60.00	23.21

Frequency MHz	AV Level dB μ V	AV Limit dB μ V	AV Delta dB
0.15	23.55	56.00	32.45
0.192	25.67	53.95	28.28
0.195	26.95	53.82	26.87
0.261	21.54	51.40	29.86
0.392	20.46	48.02	27.56
0.4	18.51	47.85	29.34
0.642	20.99	46.00	25.01
0.911	22.14	46.00	23.86
0.921	21.18	46.00	24.82
1.545	25.11	46.00	20.89
2.2	27.04	46.00	18.96
3.1	28.13	46.00	17.87

* limit exceeded

Peak Search Results (continued)


Frequency MHz	AV Level dBμV	AV Limit dBμV	AV Delta dB
5.11	33.78	50.00	16.22
8.605	24.55	50.00	25.45
17.99	24.53	50.00	25.47
19.8	26.27	50.00	23.73

* limit exceeded

Line: Neutral

ETL EMC Laboratory
 Conducted Emission Test Result
 EUT: ETLE170313.0277
 Manuf:
 Op Cond:
 Operator:
 Test Spec:
 Comment: NEUTRAL

Prescan Measurement: Detectors: X PK / + AV
 Meas Time: see scan settings
 Peaks: 16
 Acc Margin: 10 dB



ETL EMC Laboratory
 Conducted Emission Test Result

EUT: ETLE170313.0277
 Manuf:
 Op Cond:
 Operator:
 Test Spec:
 Comment: NEUTRAL

Prescan Measurement: Detectors: X PK / + AV
 Meas Time: see scan settings
 Peaks: 16
 Acc Margin: 10 dB

Peak Search Results

Frequency MHz	PK Level dB μ V	PK Limit dB μ V	PK Delta dB
0.162	42.01	65.36	23.35
0.212	38.63	63.13	24.50
0.23	37.59	62.45	24.86
0.469	34.25	56.53	22.28
0.578	37.30	56.00	18.70
1.055	35.01	56.00	20.99
2.415	37.22	56.00	18.78
2.68	37.39	56.00	18.61
5.03	38.44	60.00	21.56
8.805	33.24	60.00	26.76
17.74	34.14	60.00	25.86
25.71	36.31	60.00	23.69

Frequency MHz	AV Level dB μ V	AV Limit dB μ V	AV Delta dB
0.162	29.31	55.36	26.05
0.212	26.53	53.13	26.60
0.23	24.07	52.45	28.38
0.469	19.43	46.53	27.10
0.578	21.20	46.00	24.80
1.055	20.52	46.00	25.48
2.415	25.54	46.00	20.46
2.68	25.88	46.00	20.12
5.03	28.89	50.00	21.11
8.805	22.94	50.00	27.06
17.74	23.79	50.00	26.21
25.71	23.50	50.00	26.50

* limit exceeded

5.3 Radiated Emissions Measurement

5.3.1 Radiated Emissions Data

- Below 1 GHz

EUT	RADAR DETECTOR / R3 (S/N: Proto-type)
Limit apply to	FCC Part 15.109(a) Class B
Test Date	March 16, 2017
Environmental of test	(10.4 ± 0.1) °C, (43 ± 2) % R.H., (102.0 ± 0.0) kPa
Operating Condition	Data update mode (Program: R3 DB Update Program V1.00)
Result	Passed by 6.86 dB


Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.
 Detector mode: CISPR Quasi-Peak mode (6 dB Bandwidth: 120 kHz)

Frequency [MHz]	Reading [dB(μV)]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB(μV)]	Height [cm]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
240.84	50.79	H	11.25	-28.46	114	33.58	46.00	12.42
288.59	53.95	H	13.11	-28.09	129	38.97	46.00	7.03
312.33	53.21	H	13.84	-27.91	130	39.14	46.00	6.86
331.81	51.25	H	14.30	-27.74	154	37.81	46.00	8.19
575.71	41.24	V	19.62	-25.76	122	35.10	46.00	10.90

NOTES:

1. * H : Horizontal polarization , ** V : Vertical polarization
2. The cable loss value was included the Amp. Gain.
3. Result = Reading + Antenna factor + Cable loss
4. Margin value = Limit - Result
5. The measurement was performed for the frequency range 30 MHz ~ 1 000 MHz according to FCC Part 15.109(a) Class B.



- Above 1 GHz

EUT	RADAR DETECTOR / R3 (S/N: Proto-type)
Limit apply to	FCC Part 15.109(a) Class B
Test Date	March 16, 2017
Environmental of test	(11.4 ± 0.3) °C, (44 ± 1) % R.H., (102.0 ± 0.0) kPa
Operating Condition	Data update mode (Program: R3 DB Update Program V1.00)
Result	Passed by 10.00 dB

Radiated Emission Test Data

The following data and graph shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Detector mode: CISPR Peak mode, Average mode


Frequency [MHz]	Reading [dB(μV)]		Polarity (*H/**V)	Height [cm]	Ant. Factor [dB/m]	Cable Loss [dB]	Result [dB(μV/m)]		Limit [dB(μV/m)]		Margin [dB]	
	Peak	Average					Peak	Average	Peak	Average	Peak	Average
5 539.38	59.69	46.02	H	100	31.92	-34.36	57.25	43.58	74.00	54.00	16.75	10.42
5 745.98	59.03	45.84	H	100	32.17	-34.01	57.19	44.00	74.00	54.00	16.81	10.00

NOTES:

1. * H : Horizontal polarization , **V : Vertical polarization
2. The cable loss value was included the Amp. Gain.
3. Result = Reading + Antenna factor + Cable loss
4. Margin value = Limit - Result
5. The measurement was performed for the frequency range 1 GHz ~ 6 GHz according to FCC Part 15.109(a) Class B.
6. Upper frequency of measurement range: 5th harmonic of the highest frequency.

Polarization: Horizontal

Limit : — Peak
— Average



Peak ◆ Average ▲

6. SAMPLE CALCULATION

Sample Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor - Preamplifier Factor

$$dB(\mu V) = 20 \log_{10} (\mu V) : \text{Equation}$$

$$dB(\mu V) = dBm + 107$$

Example : @ 312.33 MHz

Class B Limit	=	46.00 dB(μ V/m)
Reading	=	53.21 dB(μ V)
Antenna Factor + (Cable Loss - Amp. Gain)	=	13.84 + (-27.91) = -14.07 dB(μ V/m)
Total	=	39.14 dB(μ V/m)
Margin	=	46.00 – 39.14 = 6.86 dB
	=	6.86 dB below Limit

7. List of test equipments used for measurements

	Test Equipment	Model	Mfg.	Serial No.	Cal. Date	Cal. Due Date
<input checked="" type="checkbox"/>	EMI Test Receiver	ESPI3	R&S	100478	16.09.01	17.09.01
<input checked="" type="checkbox"/>	EMI Test Receiver	ESCS30	R&S	100087	17.03.13	18.03.13
<input checked="" type="checkbox"/>	EMI Test Receiver	ESCI7	R&S	100851	16.09.01	17.09.01
<input checked="" type="checkbox"/>	Amplifier	310N	Sonoma Instrument	284750	16.09.02	17.09.02
<input checked="" type="checkbox"/>	Two-Line V-Network	ENV216	R&S	102055	17.03.13	18.03.13
<input checked="" type="checkbox"/>	Horn Antenna	BBHA 9120D	Schwarzbeck	277	16.10.12	18.10.12
<input checked="" type="checkbox"/>	Amplifier	TK-PA18	TESTEK.	120020	16.09.01	17.09.01
<input checked="" type="checkbox"/>	LogBicon Antenna	VULB9160	Schwarzbeck	3164	15.06.08	17.06.08
<input checked="" type="checkbox"/>	Turn-Table	TT 1.35 SI	SES	-	N/A	N/A
<input checked="" type="checkbox"/>	Antenna Master	AM 4.5	SES	-	N/A	N/A