R7 Manual

Feature

- 1. GPS On/Off
- 2. User Mark Alert
- 3. Mute Memory
- 4. POI Alert On/Off
 - 1) Speed Camera Alarm On/Off
 - 2) Red-light Camera Alarm On/Off
- 5. Red-light Camera Delete
- 6. Red-light Camera Quiet Ride(Off, 50~85mph: 5mph unit, 80~140km/h: 10km/h unit)
- 7. X, K, MRCD, Ka Band, Laser Detection
- 8. Display: 176 x 60 OLED(Full Color)
- 9. Top Button

[MENU] [VOL-] [VOL+] [POWER]

10. Side Button

[MARK] [MUTE/DIM]

- 11. Volume: 0~6 Level
- 12. Dim Mode: AUTO -> BRIGHT -> DIM -> DIMMER-> DARK -> OFF
- 13. City Mode: HIGHWAY -> CITY -> ADVANCED
- 14. Mute On/Off
- 15. Scan Display
- 16. Mode Display
- 17. Time Display
- 18. Background Color: Blue->Amber->Green->Pink->Gray->Red->White->Purple
- 19. Arrow color selection: Red->Blue->Green->Orange->Yellow->White->Violet
- 20. Radar Band color selection: Signal->Arrow->Red->Blue->Green->Orange->Yellow->White->Violet
- 21. Alert display selection: Alert display #1 <-> #2
- 22. Speed Display (mph or km/h)
- 23. Speed + Compass Display
- 24. Compass Display
- 25. Voltage Display
- 26. Altitude Display
- 27. Speed Unit: mph or km/h
- 28. Quiet Ride Mode (Off, 5~90mph: 5mph unit, 10~140km/h: 10km/hunit)
- 29. User Speed Limit Alarm (Off, 50~100mph: 5mph unit, 80~160km/h: 10km/h unit)
- 30. GMT setting($-12 \sim +12hr$)
- 31. DST(Daylight Saving Time) On/Off
- 32. POI Alarm
- 33. Mute Memory Point
- 34. X, K, MRCD, Ka Band, Laser On/Off
- 35. Voice On/Off
- 36. Ka Frequency voice On/Off

- 37. K POP On/Off
- 38. Ka POP On/Off
- 39. K Band Filter On/Off
- 40. Ka Band Filter On/Off
- 41. TSF On/Off
- 42. K Narrow/ Wide
- 43. Ka Narrow/ Wide/Segmentation
- 44. Signal Priority / Ka Priority
- 45. All Threat Display On/Off
- 46. Selectable Alert Tone: X, K, MRCD, Ka, Ka Bogey tone, Laser
- 47. Auto Mute (Off, On: 0~5 Level)
- 48. Dark Mode Bright Setting
- 49. Auto Dim Setting
- 50. Low Battery Voltage Warning(On/Off)
- 51. Vehicle Battery Saver (On/Off)
- 52. Self Test (On/Off)
- 53. User Setting memory
- 54. Factory Reset Mode
- 55. Mute Memory All Delete
- 56. User Mark All Delete
- 57. Software Version Display
- 58. DB Version Display

Alert Display #1 or #2(different signal strength level display)

Alert Display #1



Alert Display #2



Button operation

| [POWER] | | Power On/Off | |
|------------|--------------|--|--|
| [VOL+] | | Volume Level Up: 0 -> 6 Level | |
| [VOL-] | | Volume Level Down: 6 -> 0 Level | |
| [MENU] | press | Menu Mode | |
| [INICINO] | Press & hold | Highway -> City -> Advanced | |
| | Press | Mute On <-> Mute Off (Mute radar, laser, Red-light camera & Overspeed alarms) Press button again to save a Mute location(Mute Memory) Delete Mute Memory while Mute Memory displays | |
| [MUTE/DIM] | Press & hold | Auto-> Bright -> Dim -> Dimmer -> Dark -> OFF Delete Red-light Camera point by pressing during Red light cameraalert | |
| [MARK] | Short press | User Mark registration or deletion | |
| | 3 sec press | User Mark All Delete | |

Mute On & Off

MUTE on - Press *MUTE/DIM* to mute an alarm. Returns to normal operation 10 seconds after the alert ends or if a different band is detected during Mute mode. *Mute On displays for a few seconds.*MUTE off - Press *MUTE/DIM* to restore audible alarms before the 10 second automatic mute time-

City Mode

out.

| | X Band | K Band | Ka Band |
|------------------|------------------------------|---------|---------|
| Highway | Full | Full | Full |
| City | Reduced | Reduced | Full |
| Advanced Mode | User adjusts the sensitivity | | |

Menu when GPS on

| Mode | Kind of Mode | |
|-------------------------------|--|--|
| City Mode | "Highway" -> "City" -> "Advanced" | |
| X Band Attenuation | 100~30% (10% unit decrease) | |
| K Band Attenuation | 100~30% (10% unit decrease) | |
| Ka Band Attenuation | 100~30% (10% unit decrease) | |
| GPS On/Off | "GPS On"<-> "GPS Off" | |
| Speed Comers Alerm On/Off | "Speed Camera On" | |
| Speed Camera Alarm On/Off | <-> "Speed Camera Off" | |
| Red Light Camera Alarm On/Off | "Redlight Cam On" | |
| Red Light Camera Alami On/On | <-> "Redlight Cam Off" | |
| RLC Q-Ride | Off, 50~85mph (5mph unit) | |
| 1128 & 11188 | or 80~140km/h (10km/h unit) | |
| Voice On/Off | "Voice On" <-> "Voice Off" | |
| Ka Frequency Voice On/Off | "Ka Freq Voice On" <-> "Ka Freq Voice Off" | |
| X Band On/Off | "X Band On" <-> "X Band Off" | |
| K Band On/Off | "K Band On" <-> "K Band Off" | |
| Ka Band On/Off | "Ka Band On" <-> "Ka Band Off" | |

| Laser On/Off | "Laser On" <-> "Laser Off" | | |
|------------------------------|--|--|--|
| K POP On/Off | "K POP On" <-> "K POP Off" | | |
| MRCD On/Off | "MRCD On" <-> "MRCD Off" | | |
| Ka POP On/Off | "Ka POP On" <-> "Ka POP Off" | | |
| K Band Filter On/Off | "K Filter On" <-> K Filter Off | | |
| Ka Band Filter On/Off | "Ka Filter On" <-> Ka Filter Off | | |
| TSF On/Off | "TSF On" <-> TSF Off | | |
| K Narrow/Wide | "K Narrow" <-> "K Wide" | | |
| Ka Narrow/Wide/Segmentation | "Ka Narrow" -> "Ka Wide" -> "Ka Segmentation" | | |
| Ka Seg 1 | "Ka 1:33.399 - 33.705 On"<->"Ka 1:33.399 - 33.705 Off" | | |
| Ka Seg 2 | "Ka 2 : 33.705 - 33.903 On"<->"Ka 2 : 33.705 - 33.903 Off" | | |
| Ka Seg 3 | "Ka 3 : 33.903 – 34.191 On"<-> Ka 3 : 33.903 – 34.191 Off" | | |
| Ka Seg 4 | "Ka 4 : 34.191 - 34.587 On"<-> "Ka 4 : 34.191 - 34.587 Off" | | |
| Ka Seg 5 | "Ka 5 : 34.587 - 34.803 On"<->"Ka 5 : 34.587 - 34.803 Off" | | |
| Ka Seg 6 | "Ka 6:34.803 - 35.163 On"<->"Ka 6:34.803 - 35.163 Off" | | |
| Ka Seg 7 | "Ka 7:35.163 - 35.379 On"<->"Ka 7:35.163 - 35.379 Off" | | |
| Ka Seg 8 | "Ka 8 : 35.379 - 35.613 On"<->"Ka 8 : 35.379 - 35.613 Off | | |
| Ka Seg 9 | "Ka 9 : 35.613 - 35.701 On"<->"Ka 9 : 35.613 - 35.701 Off" | | |
| Signal Priority/ Ka Priority | "Signal Priority" <-> "KA Priority" | | |
| Mute Mem Band Option Set | "Mute Mem: X & K" <-> "Mute Mem: X K Ka" | | |
| All Threat Display On/Off | "All Threat On" <-> "All Threat Off" | | |
| Background Color | "Color: Blue"->"Color: Amber"->"Color: Green"- >"Color: Pink"->"Color: Gray"-> "Color: Red" -> "Color: White" -> "Color: Purple" | | |
| X Band Color | "Red"->"Blue"->"Green"->"Orange"->"Yellow"- | | |
| K Band Color | >"White"->"Violet" "Red"->"Blue"->"Green"->"Orange"->"Yellow"- | | |
| MRCD Color | >"White"->"Violet" "Red"->"Blue"->"Green"->"Orange"->"Yellow"- >"White"->"Violet" | | |
| Ka Band Color | >"White"->"Violet" "Red"->"Blue"->"Green"->"Orange"->"Yellow"- >"White"->"Violet" | | |
| Radar Band Color | | | |

| X Band Color | "Signal"->"Arrow"->"Red"->"Blue"->"Green"- >"Orange"->"Yellow"->"White"->"Violet" | |
|---|---|--|
| K Band Color | "Signal"->"Arrow"->"Red"->"Blue"->"Green"- >"Orange"->"Yellow"->"White"->"Violet" | |
| MRCD Color | "Signal"->"Arrow"->"Red"->"Blue"->"Green"- >"Orange"->"Yellow"->"White"->"Violet" | |
| Ka Band Color | "Signal"->"Arrow"->"Red"->"Blue"->"Green"- >"Orange"->"Yellow"->"White"->"Violet" | |
| Display Mode (GPS On) | "Scan Display" -> "Mode Display" -> "Time Display" | |
| Left Display (GPS On) | "Speed" -> "Spd+Comp" -> "Compass" -> "Voltage" -> "Altitude" | |
| Alert Display Type | "Alert Display #1"<->"Alert Display #2" | |
| Speed Unit | "Speed Unit:mph" <-> "Speed Unit:Km/h" | |
| X Band Tone | "X Band Tone∶1~12" | |
| K Band Tone | "K Band Tone∶1~12" | |
| MRCD Tone | "MRCD Tone: 1~12" | |
| Ka Band Tone | "Ka Band Tone: 1~12" | |
| Bogey Tone | "Bogey Tone∶1~5" | |
| Laser Tone | "Laser Tone: 1~12" | |
| Auto Mute On/Off | "Auto Mute On" <-> "Auto Mute Off" | |
| Auto Mute Volume | "Auto Mute Vol: 0~5" | |
| Dark mode Brightness setting "Dark mode: Bright" -> "Dark mode: Dim" -: mode: Dimmer" | | |
| Auto Dim Setting | | |
| Bright level | Bright->Dim->Dimmer | |
| Dim level | Bright->Dim->Dimmer->Dark->Off | |
| Quiet Ride | Off, 5~90mph (5mph unit) or 10~140km/h (10km/h unit) | |
| Limit Speed | Off, 50~100mph (5mph unit) or 80~160km/h (10km/h unit) | |
| GMT Mode | "GMT -12 Hour" ~ "GMT +12 Hour" | |
| DST (Daylight Saving Time) | "DST On" <-> "DST Off" | |
| Low Battery Voltage Warning | "BAT Warning On" <-> "BAT Warning Off" | |
| Vehicle Battery Saver | "BAT Saver On" <-> "BAT Saver Off" | |
| Self Test On/Off | "Self Test On" <-> "Self Test Off" | |
| Factory Reset | "Factory Reset? -> Reset Completed" | |
| · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · | |

| Mute Memory All Delete | "Delete All Mute?" -> "Delete Completed" |
|---|--|
| User Mark Point All Delete | "Delete All User?" -> "Delete Completed" |
| UI Version / DSP Version / GPS Version | Ex. Ver: 101.101.114 |
| DB Version | Ex. "DB Ver: 19/01/04" |
| MENU Exit | |
| | |

Factory Reset Default

| Mode | Kind of Mode | Factory Default |
|--|---|------------------------------|
| Dim Mode | Auto-> Bright -> Dim -> Dimmer-> Dark -> Off | Auto |
| City Mode | Highway -> City -> Advanced | Highway |
| X Band Attenuation (Advanced Mode) | 100~30% | 100% |
| K Band Attenuation (Advanced Mode) | 100~30% | 100% |
| Ka Band Attenuation (Advanced Mode) | 100~30% | 100% |
| GPS On/Off | GPS On <-> GPS Off | GPS On |
| Speed Camera Alarm On/Off | Speed Camera Alarm On <-> Speed Camera Alarm Off | Speed Camera Alarm On |
| Red Light Camera Alarm On/Off | Red Light Camera Alarm On <-> Red Light Camera Alarm Off | Red Light Camera Alarm On |
| RLC Q-Ride | Off, 50~85mph (5mph unit) 80~140km/h (10km/h unit) | RLC Q-Ride Off |
| Voice On/Off | Voice On <-> Voice Off | Voice On |
| Ka Frequency Voice On/Off | Ka Freq Voice On <-> Ka Freq Voice Off | Ka Freq Voice Off |
| X Band On/Off | X Band On <-> X Band Off | X Band Off |
| K Band On/Off | K Band On <-> K Band Off | K Band On |
| Ka Band On/Off | Ka Band On <-> Ka Band Off | Ka Band On |
| Laser On/Off | Laser On <-> Laser Off | Laser On |
| K POP On/Off | K POP On <-> K POP Off | K POP Off |
| MRCD On/Off | MRCD On <-> MRCD Off | MRCD Off |
| Ka POP On/Off | Ka POP On <-> Ka POP Off | Ka POP Off |
| K Band Filter On/Off | K Band Filter On <-> K Band Filter Off | K Band Filter On |
| Ka Band Filter On/Off | Ka Band Filter On <-> Ka Band Filter Off | Ka Band Filter Off |

| TSF On/Off | TSF On <-> TSF Off | TSF Off |
|------------------------------|--|------------------------|
| K Narrow/Wide | K Narrow <-> K Wide | K Wide |
| Ka Narrow/Wide/Segmentation | Ka Narrow-> Ka Wide -> Ka Segmentation | Ka Narrow |
| Ka Seg 1 | Ka 1:33.399 - 33.705 On<->Off | On |
| Ka Seg 2 | Ka 2:33.705 - 33.903 On<->Off | On |
| Ka Seg 3 | Ka 3: 33.903 - 34.191 On<->Off | On |
| Ka Seg 4 | Ka 4:34.191 - 34.587 On<->Off | On |
| Ka Seg 5 | Ka 5:34.587 - 34.803 On<->Off | On |
| Ka Seg 6 | Ka 6:34.803 - 35.163 On<->Off | On |
| Ka Seg 7 | Ka 7:35.163 - 35.379 On<->Off | On |
| Ka Seg 8 | Ka 8: 35.379 - 35.613 On<->Off | On |
| Ka Seg 9 | Ka 9: 35.613 - 35.701 On<->Off | On |
| Signal Priority/ Ka Priority | Signal Priority <-> Ka Priority | Ka Priority |
| Mute Mem Band Option | X & K <-> X K Ka | X & K |
| All Threat Display On/Off | All Threat Display On<-> All Threat Display Off | All Threat Display Off |
| Background Color | Blue->Amber->Green->Pink->Gray- >Red->White->Purple | Red |
| X Band Color | Red->Blue->Green->Orange->Yellow- >White->Violet | Red |
| K Band Color | Red->Blue->Green->Orange->Yellow- >White->Violet | Redl |
| MRCD Color | Red->Blue->Green->Orange->Yellow- >White->Violet | Red |
| Ka Band Color | Red->Blue->Green->Orange->Yellow- >White->Violet | Red |
| Band Color | | |
| X Band Color | Signal->Arrow->Red->Blue->Green- >Orange->Yellow->White->Violet | Signal |
| K Band Color | Signal->Arrow->Red->Blue->Green- >Orange->Yellow->White->Violet | Signal |
| MRCD Color | Signal->Arrow->Red->Blue->Green- >Orange->Yellow->White->Violet | Signal |
| Ka Band Color | Signal->Arrow->Red->Blue->Green- >Orange->Yellow->White->Violet | Signal |
| Display Mode (GPS On) | Scan Display -> Mode Display -> Time Display | Mode Display |
| Display Mode (GPS Off) | Scan Display<->Mode Display | Mode Display |
| Left Display (GPS On) | Speed -> Speed+Compass -> Compass-> Voltage ->Altitude | Speed |

| Alert Display Type | Alert Display #1 <-> Alert Display #2 | Alert Display #1 |
|------------------------------|--|------------------------------------|
| Speed Unit | mph <-> Km/h | mph |
| X Band Tone | X Band Tone: 1~12 | X Band Tone: 1 |
| K Band Tone | K Band Tone: 1~12 | K Band Tone: 2 |
| MRCD Tone | MRCD Tone: 1~12 | MRCD Tone: 2 |
| Ka Band Tone | Ka Band Tone : 1∼12 | Ka Band Tone: 3 |
| Bogey Tone | Bogey Tone: 1~5 | Bogey Tone: 1 |
| Laser Tone | Laser Tone: 1~12 | Laser Tone: 4 |
| Auto Mute On/Off | Auto Mute On <-> Auto Mute Off | Auto Mute On |
| Auto Mute Volume | Auto Mute Vol: 0~5 | Auto Mute Vole: 2 |
| Dark Mode Brightness Setting | Bright->Dim->Dimmer | Dimmer |
| Auto Dim Setting | Auto Dim Setting | |
| Bright Brightness Set | ●Brignt level: Bright -> Dim -> Dimmer | Bright |
| Dim Brightness Set | ●Dim level: Bright -> Dim -> Dimmer -> Dark -> Off | Dim |
| Auto Dim Setting | Auto Dim Setting | |
| Quiet Ride | Off, 5~90mph (5mph unit) 10~140km/h (10km/h unit) | Quiet Ride Off |
| Limit Speed | Off, 50~100mph (5mph unit) or 80~160km/h (10km/h unit) | Limit Speed Off |
| GMT Mode | −12 ~ +12 Hour | |
| DST (Daylight Saving Time) | DST On <-> DST Off | DST Off |
| Low Battery Voltage Warning | Low Battery Voltage Warning On <-> Low Battery Voltage Warning Off | Low Battery Voltage Warning Off |
| Vehicle Battery Saver | Vehicle Battery Saver On <-> Vehicle Battery Saver Off | Vehicle Battery Saver Off |
| Self Test On/Off | Self Test On <-> Self Test Off | Self Test On |
| Volume Level | 0 ~ 6 Level | 4 Level |
| | | |

Red Light Camera Point Deletion

^{1.} Red Light Camera alert



2. Press and hold [MUTE/DIM] button



3.Press [MUTE/DIM] button again to delete



Red Light Camera Q-ride

Mute Red light camera alert when current speed is over than user setting

Quiet Ride

Mutes radar alarms for K and X bands when you drive under the speed limit you set here.



Signal Priority / Ka Priority

- 1. Signal Priority: Alert the strongest radar band when detecting multiple radar bands
- 2. Ka Priority: Alert Ka band regardless of signal strength when detecting multiple radar bands
- 3. Laser is the top priority.

All Threat Display mode

Displays if more than one radar signals are detected at the same time. The signal with the strongest radar signal is considered the main signal; the other signals are displayed on the left side



Auto Mute

Auto Mute reduces alarm level to User Setting of Auto Mute Volume level after 3 seconds and returns to normal operation(Auto Mute OFF) 10 seconds after the alert ends. If the same alarm sounds within 10 seconds period, Auto Mute remains.

Low Battery Voltage Warning

Alert Low Battery Warning under 11.0v every 30 minutes.




Ka Bogey Tone


Set a tone to indicate the detector is responding to a different Ka band signal.

OLED Display Operation

1. Scan Display: Scan light moves left to right and right to left repeatedly as below.



2. Highway Mode display



3. City Mode display



4. Advanced Mode display



5. Time Display



6. Speed(Left display)



7. Speed + Compass(Left display)



8. Compass display(Left display)




9. Voltage display(Left display)



- 10. Attitude(Left display)
 - Speed unit: MPH



- Speed unit: KMPH



11. Speed Camera Alert



12. Red Light Camera Alert



13. User Mark Alert



14. POI Overspeed alert



LIMITED WARRANTY

The manufacturer warrants this product against all defects in materials and workmanship for a period of one (1) year from the date of the original purchase, subject to the following terms and conditions: The sole responsibility of the manufacturer under this Warranty is limited to either repair or, at the option of the manufacturer, replacement of the unit. There are no expressed or implied warranties, including those of fitness for a particular purpose of merchantability, which extend beyond the face hereof.

SPECIFICATIONS

Radar Frequencies:

10.500 - $10.550\ \text{GHz}\ (X\ Band)$

23.900 - 24.250 GHz (K Band)

33.400 - 35.700 GHz (Ka Superwideband)

Laser Wavelength: 905nm +/-50nm

Operating Temperature Range: -10C to +70C

Power Requirements: Operational 12 to 15 volts DC

FCC INFORMATION

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -Reorient or relocate the receiving antenna.
- -Increase the separation between the equipment and receiver.
- -Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

In addition, any changes or modifications to this product, which are not expressly approved by Uniden in writing, could void the user's authority to operate this product.

FCC ID AMWUA1901The end