



- NOTES:**
1. RESISTANCE VALUES ARE SHOWN IN OHMS UNLESS OTHERWISE NOTED. (K=KILO OHM, M=MEG OHM)
 2. RESISTOR WATTAGES ARE [1/10W] UNLESS OTHERWISE NOTED.
 3. CAPACITANCE VALUES ARE INDICATED IN MICRO FARADS UNLESS OTHERWISE NOTED. (P=PICTO-MICRO FARAD)
 4. ALL CAPACITORS TEMPERATURE CHARACTERISTICS ARE [C] (LESS THAN 100PPF) OR [S] (MORE THAN 100PPF) UNLESS OTHERWISE NOTED.
 5. CHIP PARTS ARE NOT SPECIFIED IN THIS DRAWING. PLEASE REFER TO THE PARTS LIST FOR THE CHIP PARTS.
 6. CHIP CAPACITORS TYPE ARE [2125] UNLESS OTHERWISE NOTED.

DESIGN	DRAWN BY	UNIDEN No.	MODEL No.
'99/4/1	'99/5/1/1	UB-380Z	BC128XLT
ICHIKAWA	ICHIKAWA	TITLE	MICOM PCB
CHK	APPD	SCHEMATIC DIAGRAM	
DRAWING No.			
REV. No	UNIDEN CORP.		