

AMWUC717

Base

CENTER 913.92MHz

Jammer Frequency	Transmitter Outputs	Signal Level	CW Level	Mj J/S ratio	Processing Gain
(MHz)	(dBm)	(dBm)	(dBm)	(dB)	(dB)
912.92	17.5	-38	-34.9	3.1	16.1
912.97	17.5	-38	-35.3	2.7	15.7
913.02	17.5	-38	-35.5	2.5	15.5
913.07	17.5	-38	-36.4	1.6	14.6
913.12	17.5	-38	-37.7	0.3	13.3
913.17	17.5	-38	-38.0	0.0	13.0
913.22	17.5	-38	-37.9	0.1	13.1
913.27	17.5	-38	-38.0	0.0	13.0
913.32	17.5	-38	-38.0	0.0	13.0
913.37	17.5	-38	-37.0	1.0	14.0
913.42	17.5	-38	-37.0	1.0	14.0
913.47	17.5	-38	-38.7	-0.7	12.3
913.52	17.5	-38	-38.8	-0.8	12.2
913.57	17.5	-38	-39.2	-1.2	11.8
913.62	17.5	-38	-39.3	-1.3	11.7
913.67	17.5	-38	-39.6	-1.6	11.4
913.72	17.5	-38	-39.8	-1.8	11.2
913.77	17.5	-38	-38.6	-0.6	12.4
913.82	17.5	-38	-39.5	-1.5	11.5
913.87	17.5	-38	-39.5	-1.5	11.5
913.92	17.5	-38	-39.5	-1.5	11.5
913.97	17.5	-38	-39.5	-1.5	11.5
914.02	17.5	-38	-39.5	-1.5	11.5
914.07	17.5	-38	-39.8	-1.8	11.2
914.12	17.5	-38	-39.4	-1.4	11.6
914.17	17.5	-38	-38.8	-0.8	12.2
914.22	17.5	-38	-38.3	-0.3	12.7
914.27	17.5	-38	-38.3	-0.3	12.7
914.32	17.5	-38	-37.8	0.2	13.2
914.37	17.5	-38	-37.0	1.0	14.0
914.42	17.5	-38	-36.5	1.5	14.5
914.47	17.5	-38	-36.4	1.6	14.6
914.52	17.5	-38	-35.5	2.5	15.5
914.57	17.5	-38	-35.2	2.8	15.8
914.62	17.5	-38	-35.0	3.0	16.0
914.67	17.5	-38	-34.7	3.3	16.3
914.72	17.5	-38	-34.1	3.9	16.9
914.77	17.5	-38	-33.3	4.7	17.7
914.82	17.5	-38	-32.1	5.9	18.9
914.87	17.5	-38	-31.4	6.6	19.6
914.92	17.5	-38	-34.3	3.7	16.7

Portable

CENTER 913.92MHz

Jammer Frequency	Transmitter Outputs	Signal Level	CW Level	Mj J/S ratio	Processing Gain
(MHz)	(dBm)	(dBm)	(dBm)	(dB)	(dB)
912.92	17.5	-38	-34.9	3.1	16.1
912.97	17.5	-38	-34.9	3.1	16.1
913.02	17.5	-38	-35.5	2.5	15.5
913.07	17.5	-38	-36.4	1.6	14.6
913.12	17.5	-38	-37.9	0.1	13.1
913.17	17.5	-38	-38.1	-0.1	12.9
913.22	17.5	-38	-38.0	0.0	13.0
913.27	17.5	-38	-38.5	-0.5	12.5
913.32	17.5	-38	-38.7	-0.7	12.3
913.37	17.5	-38	-38.3	-0.3	12.7
913.42	17.5	-38	-37.7	0.3	13.3
913.47	17.5	-38	-38.4	-0.4	12.6
913.52	17.5	-38	-38.8	-0.8	12.2
913.57	17.5	-38	-39.1	-1.1	11.9
913.62	17.5	-38	-39.3	-1.3	11.7
913.67	17.5	-38	-39.5	-1.5	11.5
913.72	17.5	-38	-39.8	-1.8	11.2
913.77	17.5	-38	-39.9	-1.9	11.1
913.82	17.5	-38	-39.7	-1.7	11.3
913.87	17.5	-38	-39.6	-1.6	11.4
913.92	17.5	-38	-39.6	-1.6	11.4
913.97	17.5	-38	-39.5	-1.5	11.5
914.02	17.5	-38	-39.7	-1.7	11.3
914.07	17.5	-38	-39.7	-1.7	11.3
914.12	17.5	-38	-39.4	-1.4	11.6
914.17	17.5	-38	-39.3	-1.3	11.7
914.22	17.5	-38	-38.6	-0.6	12.4
914.27	17.5	-38	-38.4	-0.4	12.6
914.32	17.5	-38	-37.7	0.3	13.3
914.37	17.5	-38	-37.1	0.9	13.9
914.42	17.5	-38	-36.5	1.5	14.5
914.47	17.5	-38	-36.3	1.7	14.7
914.52	17.5	-38	-35.3	2.7	15.7
914.57	17.5	-38	-35.2	2.8	15.8
914.62	17.5	-38	-35.0	3.0	16.0
914.67	17.5	-38	-34.5	3.5	16.5
914.72	17.5	-38	-33.6	4.4	17.4
914.77	17.5	-38	-32.6	5.4	18.4
914.82	17.5	-38	-32.0	6.0	19.0
914.87	17.5	-38	-31.3	6.7	19.7
914.92	17.5	-38	-34.5	3.5	16.5

AMWUC717

Base
LOW 905.728MHz

Jammer Frequency (MHz)	Transmitter Outputs (dBm)	Signal Level (dBm)	CW Level (dBm)	Mj J/S ratio (dB)	Processing Gain (dB)
904.728	17.5	-38	-34.4	3.6	16.6
904.778	17.5	-38	-34.4	3.6	16.6
904.828	17.5	-38	-35.1	2.9	15.9
904.878	17.5	-38	-36.1	1.9	14.9
904.928	17.5	-38	-37.6	0.4	13.4
904.978	17.5	-38	-38.0	0.0	13.0
905.028	17.5	-38	-38.0	0.0	13.0
905.078	17.5	-38	-39.6	-1.6	11.4
905.128	17.5	-38	-38.7	-0.7	12.3
905.178	17.5	-38	-37.7	0.3	13.3
905.228	17.5	-38	-37.4	0.6	13.6
905.278	17.5	-38	-37.6	0.4	13.4
905.328	17.5	-38	-38.0	0.0	13.0
905.378	17.5	-38	-38.1	-0.1	12.9
905.428	17.5	-38	-38.1	-0.1	12.9
905.478	17.5	-38	-38.1	-0.1	12.9
905.528	17.5	-38	-38.4	-0.4	12.6
905.578	17.5	-38	-38.8	-0.8	12.2
905.628	17.5	-38	-38.8	-0.8	12.2
905.678	17.5	-38	-38.8	-0.8	12.2
905.728	17.5	-38	-38.4	-0.4	12.6
905.778	17.5	-38	-38.4	-0.4	12.6
905.828	17.5	-38	-38.9	-0.9	12.1
905.878	17.5	-38	-38.6	-0.6	12.4
905.928	17.5	-38	-38.4	-0.4	12.6
905.978	17.5	-38	-38.4	-0.4	12.6
906.028	17.5	-38	-38.0	0.0	13.0
906.078	17.5	-38	-37.9	0.1	13.1
906.128	17.5	-38	-38.0	0.0	13.0
906.178	17.5	-38	-38.1	-0.1	12.9
906.228	17.5	-38	-38.2	-0.2	12.8
906.278	17.5	-38	-38.2	-0.2	12.8
906.328	17.5	-38	-38.5	-0.5	12.5
906.378	17.5	-38	-38.4	-0.4	12.6
906.428	17.5	-38	-36.7	1.3	14.3
906.478	17.5	-38	-36.6	1.4	14.4
906.528	17.5	-38	-36.6	1.4	14.4
906.578	17.5	-38	-36.4	1.6	14.6
906.628	17.5	-38	-36.4	1.6	14.6
906.678	17.5	-38	-34.5	3.5	16.5
906.728	17.5	-38	-34.0	4.0	17.0

Portable
LOW 905.728MHz

Jammer Frequency (MHz)	Transmitter Outputs (dBm)	Signal Level (dBm)	CW Level (dBm)	Mj J/S ratio (dB)	Processing Gain (dB)
904.728	17.5	-38	-34.6	3.4	16.4
904.778	17.5	-38	-34.6	3.4	16.4
904.828	17.5	-38	-36.1	1.9	14.9
904.878	17.5	-38	-36.3	1.7	14.7
904.928	17.5	-38	-37.9	0.1	13.1
904.978	17.5	-38	-37.9	0.1	13.1
905.028	17.5	-38	-37.9	0.1	13.1
905.078	17.5	-38	-38.3	-0.3	12.7
905.128	17.5	-38	-38.8	-0.8	12.2
905.178	17.5	-38	-38.7	-0.7	12.3
905.228	17.5	-38	-38.7	-0.7	12.3
905.278	17.5	-38	-38.1	-0.1	12.9
905.328	17.5	-38	-37.9	0.1	13.1
905.378	17.5	-38	-37.9	0.1	13.1
905.428	17.5	-38	-38.0	0.0	13.0
905.478	17.5	-38	-38.0	0.0	13.0
905.528	17.5	-38	-38.5	-0.5	12.5
905.578	17.5	-38	-39.5	-1.5	11.5
905.628	17.5	-38	-38.8	-0.8	12.2
905.678	17.5	-38	-39.0	-1.0	12.0
905.728	17.5	-38	-38.4	-0.4	12.6
905.778	17.5	-38	-38.7	-0.7	12.3
905.828	17.5	-38	-38.8	-0.8	12.2
905.878	17.5	-38	-39.0	-1.0	12.0
905.928	17.5	-38	-38.4	-0.4	12.6
905.978	17.5	-38	-38.4	-0.4	12.6
906.028	17.5	-38	-38.4	-0.4	12.6
906.078	17.5	-38	-38.1	-0.1	12.9
906.128	17.5	-38	-38.1	-0.1	12.9
906.178	17.5	-38	-37.9	0.1	13.1
906.228	17.5	-38	-38.4	-0.4	12.6
906.278	17.5	-38	-38.1	-0.1	12.9
906.328	17.5	-38	-38.1	-0.1	12.9
906.378	17.5	-38	-38.4	-0.4	12.6
906.428	17.5	-38	-37.2	0.8	13.8
906.478	17.5	-38	-35.0	3.0	16.0
906.528	17.5	-38	-36.3	1.7	14.7
906.578	17.5	-38	-36.0	2.0	15.0
906.628	17.5	-38	-36.4	1.6	14.6
906.678	17.5	-38	-34.0	4.0	17.0
906.728	17.5	-38	-34.0	4.0	17.0

AMWUC717

Base
HIGH 924.16MHz

Jammer Frequency	Transmitter Outputs	Signal Level	CW Level	Mj J/S ratio	Processing Gain
(MHz)	(dBm)	(dBm)	(dBm)	(dB)	(dB)
923.16	17.5	-38	-34.5	3.5	16.5
923.21	17.5	-38	-34.5	3.5	16.5
923.26	17.5	-38	-34.7	3.3	16.3
923.31	17.5	-38	-34.6	3.4	16.4
923.36	17.5	-38	-38.0	0.0	13.0
923.41	17.5	-38	-38.0	0.0	13.0
923.46	17.5	-38	-38.0	0.0	13.0
923.51	17.5	-38	-38.0	0.0	13.0
923.56	17.5	-38	-38.5	-0.5	12.5
923.61	17.5	-38	-38.4	-0.4	12.6
923.66	17.5	-38	-37.4	0.6	13.6
923.71	17.5	-38	-37.8	0.2	13.2
923.76	17.5	-38	-37.4	0.6	13.6
923.81	17.5	-38	-37.9	0.1	13.1
923.86	17.5	-38	-37.9	0.1	13.1
923.91	17.5	-38	-38.3	-0.3	12.7
923.96	17.5	-38	-38.5	-0.5	12.5
924.01	17.5	-38	-38.6	-0.6	12.4
924.06	17.5	-38	-38.8	-0.8	12.2
924.11	17.5	-38	-38.8	-0.8	12.2
924.16	17.5	-38	-38.3	-0.3	12.7
924.21	17.5	-38	-38.9	-0.9	12.1
924.26	17.5	-38	-39.0	-1.0	12.0
924.31	17.5	-38	-38.8	-0.8	12.2
924.36	17.5	-38	-38.5	-0.5	12.5
924.41	17.5	-38	-37.9	0.1	13.1
924.46	17.5	-38	-37.7	0.3	13.3
924.51	17.5	-38	-37.3	0.7	13.7
924.56	17.5	-38	-37.1	0.9	13.9
924.61	17.5	-38	-36.5	1.5	14.5
924.66	17.5	-38	-36.0	2.0	15.0
924.71	17.5	-38	-35.7	2.3	15.3
924.76	17.5	-38	-34.8	3.2	16.2
924.81	17.5	-38	-34.5	3.5	16.5
924.86	17.5	-38	-34.1	3.9	16.9
924.91	17.5	-38	-34.1	3.9	16.9
924.96	17.5	-38	-33.9	4.1	17.1
925.01	17.5	-38	-32.9	5.1	18.1
925.06	17.5	-38	-32.1	5.9	18.9
925.11	17.5	-38	-31.7	6.3	19.3
925.16	17.5	-38	-33.9	4.1	17.1

Portable
HIGH 924.16MHz

Jammer Frequency	Transmitter Outputs	Signal Level	CW Level	Mj J/S ratio	Processing Gain
(MHz)	(dBm)	(dBm)	(dBm)	(dB)	(dB)
923.16	17.5	-38	-34.3	3.7	16.7
923.21	17.5	-38	-34.3	3.7	16.7
923.26	17.5	-38	-34.6	3.4	16.4
923.31	17.5	-38	-36.0	2.0	15.0
923.36	17.5	-38	-37.6	0.4	13.4
923.41	17.5	-38	-37.8	0.2	13.2
923.46	17.5	-38	-37.6	0.4	13.4
923.51	17.5	-38	-37.9	0.1	13.1
923.56	17.5	-38	-39.1	-1.1	11.9
923.61	17.5	-38	-39.1	-1.1	11.9
923.66	17.5	-38	-37.7	0.3	13.3
923.71	17.5	-38	-37.7	0.3	13.3
923.76	17.5	-38	-37.5	0.5	13.5
923.81	17.5	-38	-38.2	-0.2	12.8
923.86	17.5	-38	-38.0	0.0	13.0
923.91	17.5	-38	-38.3	-0.3	12.7
923.96	17.5	-38	-38.7	-0.7	12.3
924.01	17.5	-38	-38.6	-0.6	12.4
924.06	17.5	-38	-38.8	-0.8	12.2
924.11	17.5	-38	-38.8	-0.8	12.2
924.16	17.5	-38	-38.7	-0.7	12.3
924.21	17.5	-38	-38.9	-0.9	12.1
924.26	17.5	-38	-39.0	-1.0	12.0
924.31	17.5	-38	-38.8	-0.8	12.2
924.36	17.5	-38	-38.5	-0.5	12.5
924.41	17.5	-38	-37.8	0.2	13.2
924.46	17.5	-38	-37.6	0.4	13.4
924.51	17.5	-38	-37.5	0.5	13.5
924.56	17.5	-38	-37.0	1.0	14.0
924.61	17.5	-38	-36.5	1.5	14.5
924.66	17.5	-38	-35.9	2.1	15.1
924.71	17.5	-38	-35.7	2.3	15.3
924.76	17.5	-38	-34.9	3.1	16.1
924.81	17.5	-38	-34.4	3.6	16.6
924.86	17.5	-38	-34.1	3.9	16.9
924.91	17.5	-38	-34.1	3.9	16.9
924.96	17.5	-38	-33.8	4.2	17.2
925.01	17.5	-38	-32.6	5.4	18.4
925.06	17.5	-38	-32.0	6.0	19.0
925.11	17.5	-38	-31.7	6.3	19.3
925.16	17.5	-38	-32.9	5.1	18.1