



Date(s) of Evaluation
July 20-28, 2015

Test Report Issue Date
26 Aug 2015

Test Report Serial No.
071515AMW-T1330-MPE

Description of Test(s)
Specific Absorption Rate

Test Report Revision No.
Rev. 1.3 (4th Release)

RF Exposure Category
General Population



**Prediction of MPE Limit
47 CFR § 2.1091/ § 2.1093**

$$S_{20} = \frac{P_A G_N}{4\pi R_{20}^2}$$

$$S_C = \frac{P_A G_N}{4\pi R_C^2}$$

$$R_C = \sqrt{\frac{P_A G_N}{4\pi S_L}}$$

$$S_L = \frac{180}{f^2} \text{ (mW/cm}^2\text{)}$$

- S_{20} = Power Density of the Device at 20cm
- S_L = Power Density Limit
- S_C = Power Density of the Device at the Compliance Distance R_C
- R_{20} = 20cm
- R_C = Minimum Distance to the Radiating Element to Meet Compliance
- P_T = Power Input to Antenna
- P_A = Adjust Power
- G_N = Numeric Gain of the Antenna
- f = Transmit Frequency

Transmit Duty Cycle = 50% Push-To-Talk Transmit Duty Cycle

Use Group = General Population

Transmit Duty Cycle:	50.00	(%)
Tx Frequency (f):	27.40	(MHz)
RF Power at Antenna Input Port (P_T):	4000.00	(mW)
Antenna Gain:	3.00	(dBi)
Numeric Antenna Gain (G_N):	2.00	(numeric)
Cable or Other Loss:	0.00	(dB)
Duty Cycle/Loss Adjusted Power (P_A):	2000.00	(mW)

S_L =	0.240	(mW/cm ²)
S_{20} at 20cm =	0.794	(mW/cm ²)
R_C =	36.4 (37)	(cm)
S_C at 37cm =	0.233	(mW/cm ²)

The Applicant's User's Manual must indicate a minimum separation distance of: **37cm**

Art Voss		Senior Engineer	Celltech Labs Inc.
-----------------	--	------------------------	---------------------------