

## TEST REPORT


**Application No. :** SZCR2204001065AT  
**Applicant:** Uniden America Corporation  
**Address of Applicant:** 6225 N. State Highway 161 Suite 300, Irving, Texas 75038 United States  
**Manufacturer:** Uniden Holding Corporation  
**Address of Manufacturer:** 2-12-7, Hacchobori, Chuo-ku, Tokyo, Japan, 104-8512  
**Factory:** Uniden Vietnam Limited  
**Address of Factory:** Lot 5. 1, Tan Truong Industrial Zone, Cam Giang District, Hai Duong Province, Vietnam

**Equipment Under Test (EUT):**  
**EUT Name:** Handheld VHF Marine Radio  
**Model No.:** MHS338BT  
**Trade mark:** Uniden  
**Standards:** IEC 62238:2003  
EN 301 025 V2.2.1

**Date of Receipt:** 2022-04-09  
**Date of Test:** 2022-04-14 to 2022-05-19  
**Date of Issue:** 2022-05-20

<b>Test Result :</b>	<b>Pass*</b>
----------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2022-05-20		Original

<b>Authorized for issue by:</b>			
		<i>Edison Li</i>	
		Edison Li/Project Engineer	
		<i>Eric Fu</i>	
		Eric Fu/Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

# 1 Test Summary

Transmitter				
Item	Standard	Method	Requirement	Result
Frequency error	EN 301 025 V2.2.1	EN 301 025 clause 8.1.2	EN 301 025 clause 8.1.1	Pass
Carrier power	EN 301 025 V2.2.1	EN 301 025 clause 8.2.2	EN 301 025 clause 8.2.1	Pass
Frequency deviation	EN 301 025 V2.2.1	EN 301 025 clause 8.3.2	EN 301 025 clause 8.3.1	Pass
Reduction of frequency deviation at modulation frequencies above 3 kHz	EN 301 025 V2.2.1	EN 301 025 clause 8.3.3	EN 301 025 clause 8.3.3.1	Pass
Sensitivity of the modulator, including microphone	EN 301 025 V2.2.1	EN 301 025 clause 8.4.2	EN 301 025 clause 8.4.1	Pass
Audio frequency response	EN 301 025 V2.2.1	EN 301 025 clause 8.5.2	EN 301 025 clause 8.5.1	Pass
Audio frequency harmonic distortion of the emission	EN 301 025 V2.2.1	EN 301 025 clause 8.6.2	EN 301 025 clause 8.6.1	Pass
Adjacent channel power	EN 301 025 V2.2.1	EN 301 025 clause 8.7.2	EN 301 025 clause 8.7.1	Pass
Conducted spurious emissions conveyed to the antenna	EN 301 025 V2.2.1	EN 301 025 clause 8.8.2	EN 301 025 clause 8.8.1	Pass
Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna	EN 301 025 V2.2.1	EN 301 025 clause 8.9.2	EN 301 025 clause 8.9.1	Pass
Transient frequency behaviour of the transmitter	EN 301 025 V2.2.1	EN 301 025 clause 8.10.2	EN 301 025 clause 8.10.1	Pass
Residual modulation of the transmitter	EN 301 025 V2.2.1	EN 301 025 clause 8.11.2	EN 301 025 clause 8.11.1	Pass
Frequency error (demodulated DSC signal)	EN 301 025 V2.2.1	EN 301 025 clause 8.12.2	EN 301 025 clause 8.12.1	Pass
Modulation index for DSC	EN 301 025 V2.2.1	EN 301 025 clause 8.13.2	EN 301 025 clause 8.13.1	Pass
Modulation rate for DSC	EN 301 025 V2.2.1	EN 301 025 clause 8.14.2	EN 301 025 clause 8.14.1	Pass
Testing of free channel transmission on DSC channel 70	EN 301 025 V2.2.1	EN 301 025 clause 8.15.2	EN 301 025 clause 8.15.1	Pass

Radiotelephone receiver				
Harmonic distortion and rated audio-frequency output power	EN 301 025 V2.2.1	EN 301 025 clause 9.1.2	EN 301 025 clause 9.1.1	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)  
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Audio frequency response	EN 301 025 V2.2.1	EN 301 025 clause 8.7.2	EN 301 025 clause 9.2.1	Pass
Maximum usable sensitivity	EN 301 025 V2.2.1	EN 301 025 clause 9.3.2	EN 301 025 clause 9.3.1	Pass
Co-channel rejection	EN 301 025 V2.2.1	EN 301 025 clause 9.4.2	EN 301 025 clause 9.4.1	Pass
Adjacent channel selectivity	EN 301 025 V2.2.1	EN 301 025 clause 9.5.2	EN 301 025 clause 9.5.1	Pass
Spurious response rejection	EN 301 025 V2.2.1	EN 301 025 clause 9.6.2	EN 301 025 clause 9.6.1	Pass
Intermodulation response	EN 301 025 V2.2.1	EN 301 025 clause 9.7.2	EN 301 025 clause 9.7.1	Pass
Blocking or desensitization	EN 301 025 V2.2.1	EN 301 025 clause 9.8.2	EN 301 025 clause 9.8.1	Pass
Spurious emissions	EN 301 025 V2.2.1	EN 301 025 clause 9.9.2	EN 301 025 clause 9.9.1	Pass
Receiver radiated spurious emissions	EN 301 025 V2.2.1	EN 301 025 clause 9.10.2	EN 301 025 clause 9.10.1	Pass
Receiver residual noise level	EN 301 025 V2.2.1	EN 301 025 clause 9.11.2	EN 301 025 clause 9.11.1	Pass
Squelch operation	EN 301 025 V2.2.1	EN 301 025 clause 9.12.2	EN 301 025 clause 9.12.1	Pass
Squelch hysteresis	EN 301 025 V2.2.1	EN 301 025 clause 9.13.2	EN 301 025 clause 9.13.1	Pass
Multiple watch characteristic	EN 301 025 V2.2.1	EN 301 025 clause 9.14.2	EN 301 025 clause 9.14.1	Pass
<b>Receiver for DSC decoder</b>				
<b>Item</b>	<b>Standard</b>	<b>Method</b>	<b>Requirement</b>	<b>Result</b>
Maximum usable sensitivity	EN 301 025 V2.2.1	EN 301 025 clause 10.1.2	EN 301 025 clause 10.1.1	Pass
Co-channel rejection	EN 301 025 V2.2.1	EN 301 025 clause 10.2.2	EN 301 025 clause 10.2.1	Pass
Adjacent channel selectivity	EN 301 025 V2.2.1	EN 301 025 clause 10.3.2	EN 301 025 clause 10.3.1	Pass
Spurious response and blocking immunity	EN 301 025 V2.2.1	EN 301 025 clause 10.4.2	EN 301 025 clause 10.4.1	Pass
Intermodulation response	EN 301 025 V2.2.1	EN 301 025 clause 10.5.2	EN 301 025 clause 10.5.1	Pass
Dynamic range	EN 301 025 V2.2.1	EN 301 025 clause 10.6.2	EN 301 025 clause 10.6.1	Pass
Spurious emissions	EN 301 025 V2.2.1	EN 301 025 clause 10.7.2	EN 301 025 clause 10.7.1	Pass
Simultaneous reception	EN 301 025 V2.2.1	EN 301 025 clause 10.8.2	EN 301 025 clause 10.8.1	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

DSC Signalling	EN 301 025 V2.2.1	EN 300 338 V1.2.1	EN 301 025 clause 10.9	Pass
----------------	-------------------	-------------------	------------------------	------

N/A: Not applicable.

EN 301 025, Electromagnetic compatibility and Radio Spectrum Matters (ERM); Technical characteristics and methods of measurement for VHF radiotelephone equipment for general communications and associated equipment for Class "D" Digital Selective Calling (DSC).

- The requirement for a dedicated channel 70 watchkeeping receiver for DSC decoder has been replaced by a channel 70 watchkeeping facility in order to permit alternative design methods. This facility, however, is still required to achieve continuous DSC monitoring (except when the transmitter is in use). A new test has been added to test that DSC reception is achieved simultaneously with radiotelephone reception.
- The requirement for a Numeric Keypad has been replaced by a more general means of easily entering a MMSI to allow more flexibility in design.
- The requirement for the transmitter to work for 30 min continuously in the high power transmit condition has been replaced by a period of 5 min to permit the use of a lower cost transmitter. Facilities have also been added to limit transmission time to 5 min.
- The requirement to protect information in volatile memories from interruptions in the power supply of up to 60 s duration has been removed as not being of practical benefit.
- A requirement to transmit and receive enhanced position information with a distress call has been added.
- EMC requirements have been added.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

## 2 Contents

	Page
1 COVER PAGE .....	1
1 TEST SUMMARY .....	3
2 CONTENTS.....	6
3 GENERAL INFORMATION .....	10
3.1 DETAILS OF E.U.T. ....	10
3.2 DESCRIPTION OF SUPPORT UNITS.....	11
3.3 TEST ENVIRONMENT .....	11
3.4 MEASUREMENT UNCERTAINTY.....	11
3.5 TEST LOCATION .....	12
3.6 TEST FACILITY .....	12
3.7 DEVIATION FROM STANDARDS .....	12
3.8 ABNORMALITIES FROM STANDARD CONDITIONS .....	12
4 EQUIPMENT LIST.....	13
5 RADIO SPECTRUM MATTER TEST RESULTS.....	15
5.1 FREQUENCY ERROR.....	15
5.1.1 E.U.T. Operation.....	15
5.1.2 Test Setup Diagram .....	15
5.1.3 Measurement Data.....	15
5.2 CARRIER POWER .....	16
5.2.1 E.U.T. Operation.....	16
5.2.2 Test Setup Diagram .....	16
5.2.3 Measurement Data.....	16
5.3 FREQUENCY DEVIATION .....	17
5.3.1 E.U.T. Operation.....	17
5.3.2 Test Setup Diagram .....	17
5.3.3 Measurement Data.....	17
5.4 REDUCTION OF FREQUENCY DEVIATION AT MODULATION FREQUENCIES ABOVE 3 KHZ .....	18
5.4.1 E.U.T. Operation.....	19
5.4.2 Test Setup Diagram .....	19
5.4.3 Measurement Data.....	19
5.5 SENSITIVITY OF THE MODULATOR, INCLUDING MICROPHONE .....	20
5.5.1 E.U.T. Operation.....	20
5.5.2 Test Setup Diagram .....	20
5.5.3 Measurement Data.....	20
5.6 AUDIO FREQUENCY RESPONSE .....	21
5.6.1 E.U.T. Operation.....	22
5.6.2 Test Setup Diagram .....	22
5.6.3 Measurement Data.....	22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

5.7	AUDIO FREQUENCY HARMONIC DISTORTION OF THE EMISSION .....	23
5.7.1	<i>E.U.T. Operation</i> .....	23
5.7.2	<i>Test Setup Diagram</i> .....	23
5.7.3	<i>Measurement Data</i> .....	23
5.8	ADJACENT CHANNEL POWER .....	24
5.8.1	<i>E.U.T. Operation</i> .....	24
5.8.2	<i>Test Setup Diagram</i> .....	24
5.8.3	<i>Measurement Data</i> .....	24
5.9	CONDUCTED SPURIOUS EMISSIONS CONVEYED TO THE ANTENNA.....	25
5.9.1	<i>E.U.T. Operation</i> .....	25
5.9.2	<i>Test Setup Diagram</i> .....	25
5.9.3	<i>Measurement Procedure and Data</i> .....	25
5.10	CABINET RADIATION SPURIOUS EMISSIONS .....	26
5.10.1	<i>E.U.T. Operation</i> .....	26
5.10.2	<i>Test Setup Diagram</i> .....	26
5.10.3	<i>Measurement Data</i> .....	27
5.11	TRANSIENT FREQUENCY BEHAVIOUR OF THE TRANSMITTER .....	28
5.11.1	<i>E.U.T. Operation</i> .....	28
5.11.2	<i>Test Setup Diagram</i> .....	28
5.11.3	<i>Measurement Procedure and Data</i> .....	28
5.12	RESIDUAL MODULATION OF THE TRANSMITTER.....	29
5.12.1	<i>E.U.T. Operation</i> .....	29
5.12.2	<i>Test Setup Diagram</i> .....	29
5.12.3	<i>Measurement Procedure and Data</i> .....	29
5.13	FREQUENCY ERROR (DEMODULATED DSC SIGNAL).....	30
5.13.1	<i>E.U.T. Operation</i> .....	30
5.13.2	<i>Test Setup Diagram</i> .....	30
5.13.3	<i>Measurement Data</i> .....	30
5.14	MODULATION INDEX FOR DSC .....	31
5.14.1	<i>E.U.T. Operation</i> .....	31
5.14.2	<i>Test Setup Diagram</i> .....	31
5.14.3	<i>Measurement Data</i> .....	31
5.15	MODULATION RATE FOR DSC .....	32
5.15.1	<i>E.U.T. Operation</i> .....	32
5.15.2	<i>Test Setup Diagram</i> .....	32
5.15.3	<i>Measurement Data</i> .....	32
5.16	TESTING OF FREE CHANNEL TRANSMISSION ON DSC CHANNEL 70 .....	33
5.16.1	<i>E.U.T. Operation</i> .....	33
5.16.2	<i>Test Setup Diagram</i> .....	33
5.16.3	<i>Measurement Data</i> .....	33
5.17	HARMONIC DISTORTION AND RATED AUDIO-FREQUENCY OUTPUT POWER .....	34
5.17.1	<i>E.U.T. Operation</i> .....	34
5.17.2	<i>Test Setup Diagram</i> .....	34
5.17.3	<i>Measurement Data</i> .....	34
5.18	AUDIO FREQUENCY RESPONSE .....	35
5.18.1	<i>E.U.T. Operation</i> .....	36
5.18.2	<i>Test Setup Diagram</i> .....	36
5.18.3	<i>Measurement Data</i> .....	36
5.19	MAXIMUM USABLE SENSITIVITY .....	37



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

5.19.1	<i>E.U.T. Operation</i> .....	37
5.19.2	<i>Test Setup Diagram</i> .....	37
5.19.3	<i>Measurement Data</i> .....	37
5.20	CO-CHANNEL REJECTION .....	38
5.20.1	<i>E.U.T. Operation</i> .....	38
5.20.2	<i>Test Setup Diagram</i> .....	38
5.20.3	<i>Measurement Data</i> .....	38
5.21	ADJACENT CHANNEL SELECTIVITY .....	39
5.21.1	<i>E.U.T. Operation</i> .....	39
5.21.2	<i>Test Setup Diagram</i> .....	39
5.21.3	<i>Measurement Data</i> .....	39
5.22	SPURIOUS RESPONSE REJECTION.....	40
5.22.1	<i>E.U.T. Operation</i> .....	40
5.22.2	<i>Test Setup Diagram</i> .....	40
5.22.3	<i>Measurement Data</i> .....	40
5.23	INTERMODULATION RESPONSE.....	41
5.23.1	<i>E.U.T. Operation</i> .....	41
5.23.2	<i>Test Setup Diagram</i> .....	41
5.23.3	<i>Measurement Data</i> .....	41
5.24	BLOCKING OR DESENSITIZATION .....	42
5.24.1	<i>E.U.T. Operation</i> .....	42
5.24.2	<i>Test Setup Diagram</i> .....	42
5.24.3	<i>Measurement Data</i> .....	42
5.25	SPURIOUS EMISSION .....	43
5.25.1	<i>E.U.T. Operation</i> .....	43
5.25.2	<i>Test Setup Diagram</i> .....	43
5.25.3	<i>Measurement Data</i> .....	43
5.26	RECEIVER RADIATED SPURIOUS EMISSIONS .....	44
5.26.1	<i>E.U.T. Operation</i> .....	44
5.26.2	<i>Test Setup Diagram</i> .....	44
5.26.3	<i>Measurement Data</i> .....	45
5.27	RECEIVER RESIDUAL NOISE LEVEL .....	46
5.27.1	<i>E.U.T. Operation</i> .....	46
5.27.2	<i>Test Setup Diagram</i> .....	46
5.27.3	<i>Measurement Procedure and Data</i> .....	46
5.28	SQUELCH OPERATION .....	47
5.28.1	<i>E.U.T. Operation</i> .....	47
5.28.2	<i>Test Setup Diagram</i> .....	47
5.28.3	<i>Measurement Procedure and Data</i> .....	47
5.29	SQUELCH HYSTERESIS .....	48
5.29.1	<i>E.U.T. Operation</i> .....	48
5.29.2	<i>Test Setup Diagram</i> .....	48
5.29.3	<i>Measurement Procedure and Data</i> .....	48
5.30	MULTIPLE WATCH CHARACTERISTIC .....	49
5.30.1	<i>E.U.T. Operation</i> .....	49
5.30.2	<i>Test Setup Diagram</i> .....	49
5.30.3	<i>Measurement Procedure and Data</i> .....	49
5.31	MAXIMUM USABLE SENSITIVITY .....	50
5.31.1	<i>E.U.T. Operation</i> .....	50



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

5.31.2	Test Setup Diagram.....	50
5.31.3	Measurement Data.....	50
5.32	CO-CHANNEL REJECTION .....	51
5.32.1	E.U.T. Operation.....	51
5.32.2	Test Setup Diagram.....	51
5.32.3	Measurement Data.....	51
5.33	ADJACENT CHANNEL SELECTIVITY .....	52
5.33.1	E.U.T. Operation.....	52
5.33.2	Test Setup Diagram.....	52
5.33.3	Measurement Data.....	52
5.34	SPURIOUS RESPONSE AND BLOCKING IMMUNITY .....	53
5.34.1	E.U.T. Operation.....	53
5.34.2	Test Setup Diagram.....	53
5.34.3	Measurement Data.....	53
5.35	INTERMODULATION RESPONSE.....	54
5.35.1	E.U.T. Operation.....	54
5.35.2	Test Setup Diagram.....	54
5.35.3	Measurement Data.....	54
5.36	DYNAMIC RANGE .....	55
5.36.1	E.U.T. Operation.....	55
5.36.2	Test Setup Diagram.....	55
5.36.3	Measurement Data.....	55
5.37	SPURIOUS EMISSIONS.....	56
5.37.1	E.U.T. Operation.....	56
5.37.2	Test Setup Diagram.....	56
5.37.3	Measurement Data.....	56
5.38	SIMULTANEOUS RECEPTION .....	57
5.38.1	E.U.T. Operation.....	57
5.38.2	Test Setup Diagram.....	57
5.38.3	Measurement Data.....	57
<b>6</b>	<b>PHOTOGRAPHS.....</b>	<b>58</b>
6.1	TRANSMITTER SPURIOUS EMISSIONS(30MHZ-2GHZ) TEST SETUP.....	58
6.2	RECEIVER SPURIOUS EMISSIONS(30MHZ-2GHZ) TEST SETUP .....	58
6.3	EUT CONSTRUCTIONAL DETAILS .....	59
<b>7</b>	<b>APPENDIX .....</b>	<b>60</b>
7.1	APPENDIX A---EN301 025 TEST DATA.....	60
7.2	APPENDIX B---TEST REQUIREMENT FOR CLASS D DSC EQUIPMENT. ....	89



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 3 General Information

3.1 Details of E.U.T.	
Power supply:	Power Supply: Model: SAW12-120-1000UD Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 12V, 1000mA  Li-ion POLYMER RECHARGEABLE BATTERY Input: 7.4V, 1800mAh, 13.32Wh Model: BT335
Cable(s):	DC cable:177cm unshielded
Sample Type:	Portable device
Internal Source:	More than 108MHz
Transceiver frequency Range:	156.025MHz-161.60MHz(TX) 156.050MHz-163.275MHz(RX)
DSC Transmitter Frequency Range:	156.525MHz(CH70), Meets Global DSC Class D standards.
Modulation Type:	VHF:FM for Analog DSC:FSK
Frequency Spacing:	VHF: 25KHz
Emission Type:	16K0G3E for VHF 16K0G2B for DSC
Rated Output Power:	6W/2.5W/1W for VHF/DSC;
VHF/DSC Antenna Connectors:	External Antenna
VHF/DSC Antenna Gain:	3dBi
Type of Equipment:	Ship stations

#### Test Channel

Modulation Type	Channel Separation	Test Channel	Test Frequency (MHz)	
			TX	RX
FM	25KHz	L	156.025	156.050
		M(Channel 16)	156.800	156.800
		H	157.425	157.425
FSK		Channel 70	156.525	156.525



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

### 3.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
DC power	ZHAOXIN	RXN-305D	REF. No.SEA2700
Coaxial Attenuator	Provided by client	TS4	HYT168793

### 3.3 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Value	Temperature(°C)	Voltage(V)
TNVN	25	7.4
TLVL	-20	6.29
TLVH	-20	8.51
THVL	55	6.29
THVH	55	8.51

Note:

- The EUT just work in such extreme temperature of -20°C~+55°C and the extreme voltage of 6.29V~8.51V, so here the EUT is tested in the temperature of -20°C~+55°C and the voltage of 6.29V~8.51V.
- |                                  |                                   |
|----------------------------------|-----------------------------------|
| VN: Normal Voltage               | TN: Normal Temperature            |
| VL: Low Extreme Test Voltage     | VH: High Extreme Test Voltage     |
| TL: Low Extreme Test Temperature | TH: High Extreme Test Temperature |

### 3.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10 <sup>-8</sup>
3	Duty cycle	0.37%
4	Occupied Bandwidth	3%
5	RF conducted power	0.75dB
6	Conducted Spurious emissions	0.75dB
7	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
8	Temperature test	1°C
9	Humidity test	3%
10	Supply voltages	1.5%
11	Time	3%



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 3.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 3.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

### 3.7 Deviation from Standards

None

### 3.8 Abnormalities from Standard Conditions

None



## 4 Equipment List

RF Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	SAEMC	MSR433	SEM001-11	2019-06-13	2022-06-12
EXA Signal Analyzer	KEYSIGHT	N9010A	SEM004-09	2021-04-09	2022-04-08
				2022-04-07	2023-04-06
DC Power Supply	KEYSIGHT	E3642A	SEM011-07	2021-03-24	2022-03-23
				2022-03-22	2023-03-21
Manual Step Attenuator	KEYSIGHT	8494B	SEM021-05	2021-04-09	2022-04-08
				2022-04-07	2023-04-06
Manual Step Attenuator	KEYSIGHT	8496B	SEM021-06	2021-04-09	2022-04-08
				2022-04-07	2023-04-06
Power Sensor	KEYSIGHT	U2021XA	SEM009-13	2021-03-25	2022-03-24
				2022-03-23	2023-03-22
Power Sensor	KEYSIGHT	U2021XA	SEM009-14	2021-03-25	2022-03-24
				2022-03-23	2023-03-22
Power Sensor	KEYSIGHT	U2021XA	SEM009-15	2021-03-25	2022-03-24
				2022-03-23	2023-03-22
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2021-03-25	2022-03-24
				2022-03-23	2023-03-22
Programmable Temperature&Humidity Chamber	Votsch Industrietechnik GmbH	VT 4002	SEM002-15	2021-03-24	2022-03-23
				2022-03-22	2023-03-21
Measurement Software	JS Tonscend	JS1120-2 BT/WIFI V2.6	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM028-01	2021-07-09	2022-07-08

Transmitter unwanted emissions in the spurious domain/Receiver spurious emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2021-03-26	2024-03-25



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2021-03-25	2022-03-24
				2022-03-23	2023-03-22
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2021-04-14	2023-04-13
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2021-09-23	2022-09-22
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2021-07-09	2022-07-08
Substitution Antenna	ETS-Lindgren	3142C	SEM003-01	2020-06-26	2023-06-25
Substitution Antenna	Schwarzbeck	VUSLP9111B	9111B-429	2021/10/17	2022/10/16
Signal Generator	R&S	SMA100A	102174	2022/3/22	2023/3/21

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2021-09-14	2022-09-13
Humidity/ Temperature Indicator	Anymetre	TH101B	SEM002-09	2021-09-14	2022-09-13
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2021-03-30	2022-03-29
				2022-03-28	2023-03-27



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 5 Radio Spectrum Matter Test Results


### 5.1 Frequency error

Test Requirement: EN 301 025 clause 8.1.1  
 Test Method: EN 301 025 clause 8.1.2  
 Limit: The frequency error shall be within  $\pm 1,5$  kHz.

#### 5.1.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.1.2 Test Setup Diagram



#### 5.1.3 Measurement Data

The detailed test data see: Appendix 301 025.



## 5.2 Carrier power

Test Requirement: EN 301 025 clause 8.2.1  
 Test Method: EN 301 025 clause 8.2.2  
 Limit: **Normal test conditions**

The rated output power of the equipment shall be between 6 W and 25 W.  
 With the output power switch set at maximum, the carrier power shall be within  $\pm 1,5$  dB of the rated output power under normal test conditions. The output power shall never however exceed 25 W.  
 With the output power switch set at minimum the carrier power shall remain between 0,1 W and 1 W.  
 The maximum continuous transmission time shall be between 5 min and 6 min.


### Extreme test conditions

With the output power switch set at maximum, the carrier power shall remain between 6 W and 25 W and be within +2 dB, -3 dB of the rated output power under extreme conditions. The output power shall never however exceed 25 W.  
 With the output power switch set at minimum the carrier power shall remain between 0,1 W and 1 W.  
 The maximum continuous transmission time shall be between 5 min and 6 min.

### 5.2.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

### 5.2.2 Test Setup Diagram



### 5.2.3 Measurement Data

The detailed test data see: Appendix 301 025.




### 5.3 Frequency deviation

Test Requirement	EN 301 025 clause 8.3.1
Test Method:	EN 301 025 clause 8.3.2
Limit:	The maximum permissible frequency deviation shall be: <ul style="list-style-type: none"> <li>• 25 kHz channels: <math>\pm 5</math> kHz.</li> <li>• 12,5 kHz channels: <math>\pm 2,5</math> kHz.</li> </ul>

#### 5.3.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.3.2 Test Setup Diagram



#### 5.3.3 Measurement Data

The detailed test data see: Appendix 301 025.




### 5.4 Reduction of frequency deviation at modulation frequencies above 3 kHz

Test Requirement EN 301 025 clause 8.3.3  
Test Method: EN 301 025 clause 8.3.3.1

**Limit:**

The frequency deviation at modulation frequencies between 3,0 kHz (for equipment operating with 20 kHz or 25 kHz channel separations) and 2,55 kHz (for equipment operating with 12,5 kHz channel separation) and 6,0 kHz shall not exceed the frequency deviation at a modulation frequency of 3,0 kHz/2,55 kHz. At 6,0 kHz the deviation shall be not more than 30,0 % of the maximum permissible frequency deviation.

The frequency deviation at modulation frequencies between 6,0 kHz and a frequency equal to the channel separation for which the equipment is intended shall not exceed that given by a linear representation of the frequency deviation (dB) relative to the modulation frequency, starting at the 6,0 kHz limit and having a slope of -14,0 dB per octave. These limits are illustrated in figure 1.



**NOTE:**

**Abbreviations:**

- $f_1$  lowest appropriate frequency
- $f_2$  3,0 kHz (for 25 kHz channel separation), or  
2,55 kHz (for 12,5 kHz channel separation)
- MPFD maximum permissible frequency deviation, clause 8.3.2.1
- A measured frequency deviation at  $f_2$
- $f_{cs}$  frequency equal to channel separation

**Figure 1: Frequency deviation**



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

**5.4.1 E.U.T. Operation**


Operating Environment:

Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
Test mode: 06: TX mode, Keep the EUT in transmitting mode.

**5.4.2 Test Setup Diagram**

The transmitter shall be placed in the test fixture connected as below. The frequency deviation shall be measured by means of a deviation meter capable of measuring the maximum permissible frequency deviation, including that due to any harmonics and intermodulation products, which may be produced in the transmitter. The deviation meter bandwidth shall be suitable to accommodate the highest modulating frequency and to achieve the required dynamic range.

The transmitter shall be operated under normal test conditions.



**Response of the transmitter to modulation frequencies above 3 kHz**

- a) The modulation frequency shall be varied between  $f_2$  (see note) and a frequency equal to the channel separation for which the equipment is intended. The level of this signal shall correspond to a deviation at 1 000 Hz of 12 % of the channel separation.
- b) The maximum (positive or negative) frequency deviation shall be measured by means of the deviation meter.

NOTE:  $f_2$  is equal to 3 kHz, for transmitters intended for 20 kHz and 25 kHz channel separation, or to 2,55 kHz for transmitters intended for 12,5 kHz channel separations.

**5.4.3 Measurement Data**

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


**5.5 Sensitivity of the modulator, including microphone**

Test Requirement EN 301 025 clause 8.4.1  
 Test Method: EN 301 025 clause 8.4.2  
 Limit: The resulting frequency deviation shall be between  $\pm 1,5$  kHz and  $\pm 3$  kHz.

**5.5.1 E.U.T. Operation**

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

**5.5.2 Test Setup Diagram**



**5.5.3 Measurement Data**

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

## 5.6 Audio frequency response

Test Requirement EN 301 025 clause 8.5.1  
 Test Method: EN 301 025 clause 8.5.2  
 Limit: The audio frequency response shall be within +1 dB and -3 dB of a 6 dB/octave line passing through the reference point. The upper limit frequency shall be 2,55 kHz for 12,5 kHz channels.




Figure 2: Audio frequency response



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


**5.6.1 E.U.T. Operation**

Operating Environment:

Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar

Test mode: 06: TX mode, Keep the EUT in transmitting mode.

**5.6.2 Test Setup Diagram**



**5.6.3 Measurement Data**

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


**5.7 Audio frequency harmonic distortion of the emission**

Test Requirement EN 301 025 clause 8.6.1  
 Test Method: EN 301 025 clause 8.6.2  
 Limit: The harmonic distortion shall not exceed 10 %.

**5.7.1 E.U.T. Operation**

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

**5.7.2 Test Setup Diagram**



**5.7.3 Measurement Data**

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


## 5.8 Adjacent channel power

Test Requirement	EN 301 025 clause 8.7.1
Test Method:	EN 301 025 clause 8.7.2
Limit:	The adjacent channel power shall not exceed a value of: <ul style="list-style-type: none"> <li>• 25 kHz channel: 70 dB below the carrier power of the transmitter without any need to be below the spurious emission limit of 0,25 uW.</li> <li>• 12,5 kHz channel: 60 dB below the carrier power of the transmitter without any need to be below the spurious emission limit of 0,25 uW.</li> </ul>

### 5.8.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

### 5.8.2 Test Setup Diagram



### 5.8.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.9 Conducted spurious emissions conveyed to the antenna

Test Requirement EN 301 025 clause 8.8.1  
 Test Method: EN 301 025 clause 8.8.2  
 Limit: The power of any conducted spurious emission on any discrete frequency shall not exceed 0,25 uW.

#### 5.9.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.9.2 Test Setup Diagram



#### 5.9.3 Measurement Procedure and Data

The detailed test data see: Appendix 301 025.




## 5.10 Cabinet radiation spurious emissions

Test Requirement	EN 301 025 clause 8.9.1
Test Method:	EN 301 025 clause 8.9.2
Measurement Distance:	3m
Limit:	When the transmitter is in stand-by the cabinet radiation and spurious emissions shall not exceed 2 nW. When the transmitter is in operation the cabinet radiation and spurious emissions shall not exceed 0,25 uW.

### 5.10.1 E.U.T. Operation

Operating Environment:			
Temperature:	25.5 °C	Humidity:	50.8 % RH
		Atmospheric Pressure:	1015 mbar
Test mode:	06: TX mode, Keep the EUT in transmitting mode.		

### 5.10.2 Test Setup Diagram



### 5.10.3 Measurement Data

1. Scan from 30MHz to 12.75GHz, find the maximum radiation frequency to measure.
2. The technique used to find the Spurious Emissions of the transmitter was the antenna substitution method. Substitution method was performed to determine the actual ERP/EIRP emission levels of the EUT.

Below 1GHz test procedure as below:

- 1) The EUT was powered on and placed on a table in the chamber. The antenna of the transmitter was extended to its maximum length. modulation mode and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- 2) Rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3) Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4) The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5) A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6) The output power into the substitution antenna was then measured.
- 7) Steps 5) and 6) were repeated with both antennas vertically polarized.
- 8) Calculate power in dBm by the following formula:

$$\text{ERP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

where:

Pg is the generator output power into the substitution antenna.

Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber.
- 2) Calculate power in dBm by the following formula:

$$\text{EIRP(dBm)} = \text{Pg(dBm)} - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

$$\text{EIRP} = \text{ERP} + 2.15\text{dB}$$

where:

Pg is the generator output power into the substitution antenna.

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.11 Transient frequency behaviour of the transmitter

Test Requirement	EN 301 025 clause 8.10.1
Test Method:	EN 301 025 clause 8.10.2
Limit:	<p>During the periods of time t1 and t3 the frequency difference shall not exceed <math>\pm 25</math> kHz.</p> <p>The frequency difference after the end of t2 shall be within the limit of the frequency error given in clause 8.1.</p> <p>During the period of time t2 the frequency difference shall not exceed <math>\pm 12,5</math> kHz.</p> <p>Before the start of t3 the frequency difference shall be within the limit of the frequency error given in clause 8.1.</p>

#### 5.11.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C    Humidity: 50.8 % RH    Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.11.2 Test Setup Diagram



#### 5.11.3 Measurement Procedure and Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


### 5.12 Residual modulation of the transmitter

Test Requirement	EN 301 025 clause 8.11.1
Test Method:	EN 301 025 clause 8.11.2
Limit:	The residual modulation shall not exceed -40 dB on either 12,5 kHz or 25 kHz channels.

#### 5.12.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.12.2 Test Setup Diagram



#### 5.12.3 Measurement Procedure and Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.13 Frequency error (demodulated DSC signal)

Test Requirement: EN 301 025 clause 8.12.1  
 Test Method: EN 301 025 clause 8.12.2  
 Limit: The measured frequency from the demodulator at any time for the B-state shall be within  $2\ 100\ \text{Hz} \pm 10\ \text{Hz}$  and for the Y-state within  $1\ 300\ \text{Hz} \pm 10\ \text{Hz}$ .

#### 5.13.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.13.2 Test Setup Diagram



#### 5.13.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.14 Modulation index for DSC

Test Requirement: EN 301 025 clause 8.13.1  
 Test Method: EN 301 025 clause 8.13.2  
 Limit: The modulation index shall be  $2,0 \pm 10 \%$ .

#### 5.14.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.14.2 Test Setup Diagram



#### 5.14.3 Measurement Data

The detailed test data see: Appendix 301 025.




### 5.15 Modulation rate for DSC

Test Requirement: EN 301 025 clause 8.14.1  
 Test Method: EN 301 025 clause 8.14.2  
 Limit: The frequency shall be 600 Hz  $\pm$  30 ppm corresponding to a modulation rate of 1 200 baud.

#### 5.15.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.15.2 Test Setup Diagram



#### 5.15.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.16 Testing of free channel transmission on DSC channel 70

Test Requirement: EN 301 025 clause 8.15.1  
 Test Method: EN 301 025 clause 8.15.2  
 Limit: If the format specifier is distress or the category is either distress, urgency or safety in the transmitted DSC call, the call shall be transmitted while the signal generator output is still on. Otherwise the call shall not be transmitted until the signal generator output has been turned off.

#### 5.16.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 06: TX mode, Keep the EUT in transmitting mode.

#### 5.16.2 Test Setup Diagram



#### 5.16.3 Measurement Data

It shall be verified that, after transmission of a DSC call, the transmitter re-tunes to the original channel. However in the case of a distress call the transmitter shall tune to channel 16 and automatically select the maximum power.



### 5.17 Harmonic distortion and rated audio-frequency output power

Test Requirement: EN 301 025 clause 9.1.1  
 Test Method: EN 301 025 clause 9.1.2  
 Limit: The rated audio-frequency output power shall be at least:


- 2 W in a loudspeaker;
- 1 mW in the handset earphone.

The harmonic distortion shall not exceed 10 %.

#### 5.17.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in receiving mode.

#### 5.17.2 Test Setup Diagram



#### 5.17.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 5.18 Audio frequency response

Test Requirement: EN 301 025 clause 9.2.1  
 Test Method: EN 301 025 clause 9.2.2  
 Limit: The audio frequency response shall not deviate by more than +1 dB or -3 dB from a characteristic giving the output level as a function of the audio frequency, decreasing by 6 dB per octave and passing through the measured point at 1 kHz (see figure 5).




Figure 5: Audio frequency response




**5.18.1 E.U.T. Operation**

Operating Environment:

Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar

Test mode: 06: TX mode, Keep the EUT in transmitting mode.

**5.18.2 Test Setup Diagram**



A test signal of +60 dB  $\mu$  V (e.m.f.), at a carrier frequency equal to the nominal frequency of the receiver and modulated with normal test modulation (see clause 6.4) shall be applied to the receiver antenna port under the conditions specified in clause 6.1.

The receiver's audiofrequency power control shall be set so as to produce a power level equal to 50 % of the rated output power (see clause 9.1). This setting shall remain unchanged during the test.

The frequency deviation shall then be reduced to  $\pm 1$  kHz and the audio output is the reference point in figure 5 (1 kHz corresponds to 0 dB).

The frequency deviation shall remain constant while the modulation frequency is varied between 300 Hz and 3 kHz and the output level shall then be measured.

The measurement shall be repeated with a test signal at frequencies 1,5 kHz above and below the nominal frequency of the receiver.

**5.18.3 Measurement Data**

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.19 Maximum usable sensitivity

Test Requirement: EN 301 025 clause 9.3.1  
 Test Method: EN 301 025 clause 9.3.2  
 Limit: The maximum usable sensitivity for either 25 kHz or 12,5 kHz channels shall not exceed +6 dBuV (e.m.f.) under normal test conditions and +12 dBuV (e.m.f.) under extreme test conditions.

#### 5.19.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in receiving mode.

#### 5.19.2 Test Setup Diagram



A test signal at a carrier frequency equal to the nominal frequency of the receiver, modulated by the normal test modulation (see clause 6.4) shall be applied to the receiver input. An audio frequency load and a measuring instrument for measuring SINAD ratio (through a psophometric network as specified in clause 9.3.1) shall be connected to the receiver output terminals.

The level of the test signal shall be adjusted until a SINAD ratio of 20 dB is obtained, using the psophometric network and with the receiver's audio-frequency power control adjusted to produce 50 % of the rated output power. Under these conditions, the level of the test signal at the input is the value of the maximum usable sensitivity.

The measurements shall be made under normal test conditions (see clause 6.13) and under extreme test conditions (see clauses 6.14.1 and 6.14.2 applied simultaneously).

A receiver output power variation of  $\pm 3$  dB relative to 50 % of the rated output power may be allowed for sensitivity measurements under extreme test conditions.

#### 5.19.3 Measurement Data

The detailed test data see: Appendix 301 025.




## 5.20 Co-channel rejection

Test Requirement	EN 301 025 clause 9.4.1
Test Method:	EN 301 025 clause 9.4.2
Limit:	The co-channel rejection ratio, at any frequency of the unwanted signal within the specified range, shall be between: <ul style="list-style-type: none"> <li>• -10 dB and 0 dB for 25 kHz channels;</li> <li>• -12 dB and 0 dB for 12,5 kHz channels.</li> </ul>

### 5.20.1 E.U.T. Operation

Operating Environment:			
Temperature:	25.5 °C	Humidity:	50.8 % RH
		Atmospheric Pressure:	1015 mbar
Test mode:	07: RX mode, Keep the EUT in receiving mode.		

### 5.20.2 Test Setup Diagram



### 5.20.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


## 5.21 Adjacent channel selectivity

Test Requirement	EN 301 025 clause 9.5.1
Test Method:	EN 301 025 clause 9.5.2
Limit:	25 kHz channels: the adjacent channel selectivity shall be not less than 70 dB under normal test conditions and not less than 60 dB under extreme test conditions. 12,5 kHz channels: the adjacent channel selectivity shall be not less than 60 dB under normal test conditions and not less than 50 dB under extreme test conditions.

### 5.21.1 E.U.T. Operation

Operating Environment:			
Temperature:	25.5 °C	Humidity:	50.8 % RH
		Atmospheric Pressure:	1015 mbar
Test mode:	07: RX mode, Keep the EUT in receiving mode.		

### 5.21.2 Test Setup Diagram



### 5.21.3 Measurement Data

The detailed test data see: Appendix 301 025.



## 5.22 Spurious response rejection

Test Requirement	EN 301 025 clause 9.6.1
Test Method:	EN 301 025 clause 9.6.2
Limit:	At any frequency separated from the nominal frequency of the receiver by more than 25 kHz, the spurious response rejection ratio shall be not less than 70 dB.


### 5.22.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C      Humidity: 50.8 % RH      Atmospheric Pressure: 1015 mbar

Test mode: 07: RX mode, Keep the EUT in receiving mode.

### 5.22.2 Test Setup Diagram



### 5.22.3 Measurement Data

The detailed test data see: Appendix 301 025.




### 5.23 Intermodulation response

Test Requirement EN 301 025 clause 9.7.1  
 Test Method: EN 301 025 clause 9.7.2  
 Limit: The intermodulation response ratio shall be greater than 68 dB.

#### 5.23.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in receiving mode.

#### 5.23.2 Test Setup Diagram



#### 5.23.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


## 5.24 Blocking or desensitization

Test Requirement	EN 301 025 clause 9.8.1
Test Method:	EN 301 025 clause 9.8.2
Limit:	The blocking level for any frequency within the specified ranges, shall be not less than 90 dBuV (e.m.f.), except at frequencies on which spurious responses are found.

### 5.24.1 E.U.T. Operation

Operating Environment:					
Temperature:	25.5 °C	Humidity:	50.8 % RH	Atmospheric Pressure:	1015 mbar
Test mode:	07: RX mode, Keep the EUT in receiving mode.				

### 5.24.2 Test Setup Diagram



### 5.24.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


## 5.25 Spurious emission

Test Requirement EN 301 025 clause 9.9.1  
 Test Method: EN 301 025 clause 9.9.2  
 Limit: The power of any spurious emission shall not exceed 2 nW at any frequency in the range between 9 kHz and 2 GHz.

### 5.25.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in receiving mode.

### 5.25.2 Test Setup Diagram



### 5.25.3 Measurement Data

The detailed test data see: Appendix 301 025.




## 5.26 Receiver radiated spurious emissions

Test Requirement	EN 301 025 clause 9.10.1
Test Method:	EN 301 025 clause 9.10.2
Limit:	The power of any spurious emission shall not exceed 2 nW at any frequency in the range between 9 kHz and 2 GHz.

### 5.26.1 E.U.T. Operation

Operating Environment:			
Temperature:	25.5 °C	Humidity:	50.8 % RH
		Atmospheric Pressure:	1015 mbar
Test mode:	07: RX mode, Keep the EUT in receiving mode.		

### 5.26.2 Test Setup Diagram



**5.26.3 Measurement Data**

1. Scan from 30MHz to 2GHz, find the maximum radiation frequency to measure.
2. The technique used to find the Spurious Emissions of the transmitter was the antenna substitution method. Substitution method was performed to determine the actual ERP/EIRP emission levels of the EUT.

Below 1GHz test procedure as below:

- 1) The EUT was powered on and placed on a table in the chamber. The antenna of the transmitter was extended to its maximum length. Receiver mode and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- 2) Rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3) Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4) The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5) A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6) The output power into the substitution antenna was then measured.
- 7) Steps 5) and 6) were repeated with both antennas vertically polarized.
- 8) Calculate power in dBm by the following formula:

$$ERP(dBm) = Pg(dBm) - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

where:

Pg is the generator output power into the substitution antenna.

Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber.
- 2) Calculate power in dBm by the following formula:

$$EIRP(dBm) = Pg(dBm) - \text{cable loss (dB)} + \text{antenna gain (dBi)}$$

$$EIRP = ERP + 2.15dB$$

where:

Pg is the generator output power into the substitution antenna.

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.27 Receiver residual noise level

Test Requirement EN 301 025 clause 9.11.1  
 Test Method: EN 301 025 clause 9.11.2  
 Limit: The receiver residual noise level shall not exceed -40 dB.

#### 5.27.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in receiving mode.

#### 5.27.2 Test Setup Diagram



#### 5.27.3 Measurement Procedure and Data

The detailed test data see: Appendix 301 025.




### 5.28 Squelch operation

Test Requirement	EN 301 025 clause 9.12.1
Test Method:	EN 301 025 clause 9.12.2
Limit:	Under the conditions specified in a) clause 9.12.2, the audio frequency output power shall not exceed -40 dB relative to the rated output power. Under the conditions specified in b) clause 9.12.2, the input level shall not exceed +6 dBuV (e.m.f.) and the SINAD ratio shall be at least 20 dB. Under the conditions specified in c) clause 9.12.2, the input signal shall not exceed +6 dBuV (e.m.f.) when the control is set at maximum.

#### 5.28.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C      Humidity: 50.8 % RH      Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in receiving mode.

#### 5.28.2 Test Setup Diagram



#### 5.28.3 Measurement Procedure and Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.29 Squelch hysteresis

Test Requirement EN 301 025 clause 9.13.1  
 Test Method: EN 301 025 clause 9.13.2  
 Limit: The squelch hysteresis shall be between 3 dB and 6 dB.

#### 5.29.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in receiving mode.

#### 5.29.2 Test Setup Diagram



#### 5.29.3 Measurement Procedure and Data

The detailed test data see: Appendix 301 025.




### 5.30 Multiple watch characteristic

Test Requirement	EN 301 025 clause 9.14.1
Test Method:	EN 301 025 clause 9.14.2
Limit:	The scanning period shall not exceed 2 s. The dwell time on the priority channel shall not exceed 150 ms. The dwell time on the additional channel shall be between 850 ms and 2 s as indicated by the time of the gap between two output bursts.

#### 5.30.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in receiving mode.

#### 5.30.2 Test Setup Diagram



#### 5.30.3 Measurement Procedure and Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 5.31 Maximum usable sensitivity

Test Requirement: EN 301 025 clause 10.1.1  
Test Method: EN 301 025 clause 10.1.2  
Limit: The bit error ratio shall be equal to or less than  $10^{-2}$ .

#### 5.31.1 E.U.T. Operation

Operating Environment:  
Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
Test mode: 07: RX mode, Keep the EUT in DSC receiving mode.

#### 5.31.2 Test Setup Diagram

DSC standard test signal containing DSC calls shall be applied to the receiver input. The input level shall be 0 dBuV under normal test conditions and +6 dBuV under extreme test conditions.

The measurement shall be repeated under normal test conditions at the nominal carrier frequency  $\pm 1,5$  kHz. The bit error ratio in the decoder output shall be determined.

#### 5.31.3 Measurement Data

The detailed test data see: Appendix 301 025.




### 5.32 Co-channel rejection

Test Requirement EN 301 025 clause 10.2.1  
 Test Method: EN 301 025 clause 10.2.2  
 Limit: The bit error ratio shall be equal to or less than  $10^{-2}$ .

#### 5.32.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in DSC receiving mode.

#### 5.32.2 Test Setup Diagram



#### 5.32.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


### 5.33 Adjacent channel selectivity

Test Requirement EN 301 025 clause 10.3.1  
 Test Method: EN 301 025 clause 10.3.2  
 Limit: The bit error ratio shall be equal to or less than  $10^{-2}$ .

#### 5.33.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in DSC receiving mode.

#### 5.33.2 Test Setup Diagram



#### 5.33.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.34 Spurious response and blocking immunity

Test Requirement EN 301 025 clause 10.4.1  
 Test Method: EN 301 025 clause 10.4.2  
 Limit: The bit error ratio shall be equal to or less than  $10^{-2}$ .

#### 5.34.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in DSC receiving mode.

#### 5.34.2 Test Setup Diagram



#### 5.34.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.35 Intermodulation response

Test Requirement EN 301 025 clause 10.5.1  
 Test Method: EN 301 025 clause 10.5.2  
 Limit: The bit error ratio shall be equal to or less than  $10^{-2}$ .

#### 5.35.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in DSC receiving mode.

#### 5.35.2 Test Setup Diagram



#### 5.35.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)


### 5.36 Dynamic range

Test Requirement EN 301 025 clause 10.6.1  
 Test Method: EN 301 025 clause 10.6.2  
 Limit: The bit error ratio shall be equal to or less than  $10^{-2}$ .

#### 5.36.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in DSC receiving mode.

#### 5.36.2 Test Setup Diagram



A test signal in accordance with the DSC standard test signal containing consecutive DSC calls, shall be applied to the receiver input. The level of the test signal shall alternate between 100 dBuV and 0 dBuV.

The bit error ratio in the decoder output shall be determined.

#### 5.36.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


### 5.37 Spurious emissions

Test Requirement EN 301 025 clause 10.7.1  
 Test Method: EN 301 025 clause 10.7.2  
 Limit: The power of any spurious emission shall not exceed 2 nW at any frequency in the range between 9 kHz and 2 GHz.

#### 5.37.1 E.U.T. Operation

Operating Environment:  
 Temperature: 25.5 °C Humidity: 50.8 % RH Atmospheric Pressure: 1015 mbar  
 Test mode: 07: RX mode, Keep the EUT in DSC receiving mode.

#### 5.37.2 Test Setup Diagram



#### 5.37.3 Measurement Data

The detailed test data see: Appendix 301 025.



### 5.38 Simultaneous reception

Test Requirement	EN 301 025 clause 10.8.1
Test Method:	EN 301 025 clause 10.8.2
Limit:	For radiotelephony operation the SINAD ratio shall be no less than 20 dB in the presence of the DSC test signal. The DSC bit error ratio shall be equal to or less than $10^{-2}$ .

#### 5.38.1 E.U.T. Operation

Operating Environment:					
Temperature:	25.5 °C	Humidity:	50.8 % RH	Atmospheric Pressure:	1015 mbar
Test mode:	07: RX mode, Keep the EUT in DSC receiving mode.				

#### 5.38.2 Test Setup Diagram

The radiotelephone shall be set for operation on channel 16.

Two input signals shall be connected to the receiver input terminal via combining network.

The radiotelephone test signal shall be at a carrier frequency equal to the nominal frequency of the receiver, modulated by the normal test modulation shall be applied to the receiver input.

An audiofrequency load and a measuring instrument for measuring SINAD ratio (through a psophometric network) shall be connected to the receiver output terminals.

The radiotelephone test signal level shall be set for +20 dBuV.

The SINAD shall be measured with and without the presence of the DSC test signal.

The DSC standard test signal input level shall be 0 dBuV containing DSC calls.

The bit error ratio in the decoder output shall be determined.

#### 5.38.3 Measurement Data

The detailed test data see: Appendix 301 025.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 6 Photographs

### 6.1 Transmitter spurious emissions(30MHz-2GHz) Test Setup



### 6.2 Receiver spurious emissions(30MHz-2GHz) Test Setup



### 6.3 EUT Constructional Details

Please Refer to external and internal photos for details.



## 7 Appendix

### 7.1 Appendix A---EN301 025 Test data.

#### 1. Transmitter/Frequency error

Test Frequency (MHz)	Temperature (°C)	Power Supplied (V Dc)	Measured Result for High Power (KHz)	Measured Result for Low Power (KHz)	Limit (KHz)	Verdict
Normal condition						
156.8	Tnor=25	Vnor=7.4	0.033	0.027	±1.5	Pass
Extreme condition						
156.8	Tmin=-20	Vmin=6.29	0.013	0.007	±1.5	Pass
	Tmin =-20	Vmax=8.51	0.046	0.035	±1.5	Pass
	Tmax=55	Vmin=6.29	0.038	0.036	±1.5	Pass
	Tmax =55	Vmax=8.51	0.016	0.032	±1.5	Pass

#### 2. Transmitter/Carrier power

Test Channel	Temp. (°C)	Power Supplied (V Dc)	Channel Separation (KHz)	Measured Result (dBm)	Limit (dBm)	Verdict
Highest RF output power (conducted)						
Normal condition						
L	Tnor=25	Vnor=7.4	25	37.95	Rated±1.5	Pass
M				37.88	Rated±1.5	Pass
H				37.89	Rated±1.5	Pass
Extreme condition						
L	Tmin=-20	Vmin=6.29	25	37.88	Rated+2,-3	Pass
	Tmin =-20	Vmax=8.51		37.91	Rated+2,-3	Pass
	Tmax=55	Vmin=6.29		37.84	Rated+2,-3	Pass



	Tmax =55	Vmax=8.51		37.89	Rated+2,-3	Pass
M	Tmin=-20	Vmin=6.29		37.86	Rated+2,-3	Pass
	Tmin =-20	Vmax=8.51		37.87	Rated+2,-3	Pass
	Tmax=55	Vmin=6.29		37.82	Rated+2,-3	Pass
	Tmax =55	Vmax=8.51		37.84	Rated+2,-3	Pass
	Tmin=-20	Vmin=6.29		37.86	Rated+2,-3	Pass
H	Tmin =-20	Vmax=8.51		37.84	Rated+2,-3	Pass
	Tmax=55	Vmin=6.29		37.89	Rated+2,-3	Pass
	Tmax =55	Vmax=8.51		37.84	Rated+2,-3	Pass
Lowest RF output power (conducted)						
Normal condition						
L				29.6	20~30dBm	Pass
M	Tnor=25	Vnor=7.4	25	29.3	20~30dBm	Pass
H				29.5	20~30dBm	Pass
Extreme condition						
L	Tmin=-20	Vmin=6.29		29.3	20~30dBm	Pass
	Tmin =-20	Vmax=8.51		29.9	20~30dBm	Pass
	Tmax=55	Vmin=6.29		29.4	20~30dBm	Pass
	Tmax =55	Vmax=8.51		29.3	20~30dBm	Pass
M	Tmin=-20	Vmin=6.29	25	28.8	20~30dBm	Pass
	Tmin =-20	Vmax=8.51		29.4	20~30dBm	Pass
	Tmax=55	Vmin=6.29		28.7	20~30dBm	Pass
	Tmax =55	Vmax=8.51		28.9	20~30dBm	Pass
H	Tmin=-20	Vmin=6.29		28.9	20~30dBm	Pass
	Tmin =-20	Vmax=8.51		29.3	20~30dBm	Pass
	Tmax=55	Vmin=6.29		29.1	20~30dBm	Pass
	Tmax =55	Vmax=8.51		29.5	20~30dBm	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

**3. Transmitter/Frequency deviation**

Test Frequency (MHz)	Modulation Frequency (Hz)	Input level	Maximum Deviation(KHz)		Limit (KHz)	Verdict
			High Power	Low Power		
156.8	100	20dB 3KHz	2.6	2.6	±5.0	Pass
	200	20dB 3KHz	3.7	3.4	±5.0	Pass
	300	20dB 3KHz	3.3	3.1	±5.0	Pass
	400	20dB 3KHz	3.8	3.8	±5.0	Pass
	500	20dB 3KHz	3.5	3.5	±5.0	Pass
	1000	20dB 3KHz	3.4	3.4	±5.0	Pass
	1500	20dB 3KHz	3.3	3.3	±5.0	Pass
	2000	20dB 3KHz	3.1	3.1	±5.0	Pass
	2500	20dB 3KHz	3.3	3.3	±5.0	Pass
	3000	20dB 3KHz	3.3	3.3	±5.0	Pass

**4. Transmitter/Reduction of frequency deviation at modulation freq. above 3kHz**

Test Frequency (MHz)	Modulation Frequency (Hz)	Input level	Maximum Deviation(KHz)		Limit (KHz)	Verdict
			High Power	Low Power		
156.8	3000	/	/	/	5	/
	3000	3KHz	+3.34	+2.75	5	Pass
	3100	3KHz	+1.82	+2.47	5	Pass
	4000	3KHz	+1.73	+2.07	3.92	Pass
	5000	3KHz	+2.35	+2.72	3.92	Pass
	6000	3KHz	+0.94	+0.89	1.5	Pass
	8000	3KHz	+0.66	+0.67	0.77	Pass
	10000	3KHz	+0.42	+0.38	0.46	Pass
	12000	3KHz	+0.13	+0.15	0.30	Pass
	15000	3KHz	+0.14	+0.07	0.18	Pass
	20000	3KHz	+0.06	+0.05	0.09	Pass
	25000	3KHz	+0.03	+0.03	0.05	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**5. Transmitter/Sensitivity of the modulator, including microphone**

Test Frequency (MHz)	Sound Level dB(A)	Frequency Deviation(KHz)		Limit(KHz)		Verdict
		High Power	Low Power	High	Low	
156.8	94	+2.1	+1.6	±3.0	±1.5	Pass
156.025	94	+2.1	+1.6	±3.0	±1.5	Pass
157.425	94	+2.1	+1.6	±3.0	±1.5	Pass

**6. Transmitter/Audio Frequency Response**

Test Frequency (MHz)	Modulation Frequency (Hz)	Upper Limit	Lower Limit	Modulation Index(dB) Relative. To 1KHz	Verdict
156.8	300	-9.5	-13.5	-9.74	Pass
	500	-5	-9	-6.68	Pass
	800	-0.9	-4.9	-2.25	Pass
	1000	1	-3	0.46	Pass
	1500	4.5	0.5	4.07	Pass
	1800	6.1	2.1	4.64	Pass
	2000	7	3	6.27	Pass
	2500	9	5	8.55	Pass
	3000	10.5	6.5	9.53	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

**7. Transmitter/Audio frequency harmonic distortion of the emission**

Test Frequency (MHz)	Temperature (°C)	Power Supplied (V Dc)	Modulation Frequency (Hz)	AF Distortion(%)		Limit (%)	Verdict
				High Power	Low Power		
Normal condition							
156.8	Tnor=25	Vnor=7.4	300	1.8	1.2	≤10	Pass
			500	1.8	1.2	≤10	Pass
			1000	1.8	1.2	≤10	Pass
Extreme condition							
156.8	Tmin=-20	Vmin=6.29	1000	2.1	1.6	≤10	Pass
	Tmin =-20	Vmax=8.51	1000	2.1	1.6	≤10	Pass
	Tmax=55	Vmin=6.29	1000	2.1	1.6	≤10	Pass
	Tmax =55	Vmax=8.51	1000	2.1	1.6	≤10	Pass



**8. Transmitter/Adjacent channel power**

Test Channel	Adjacent Channel	Adjacent channel Power(dBc)		Limit	Verdict
		High Power	Low High		
L	Fn + 25KHz	-74.2	-74.5	25 kHz channel: 70 dB below the carrier power of the transmitter without any need to be below the spurious emission limit of 0,25 μW.	Pass
M		-73.8	-74.1		Pass
H		-73.9	-74.7		Pass
L	Fn - 25KHz	-74.7	-74.5		Pass
M		-74.6	-74.2		Pass
H		-74.9	-74.8		Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


### 9. Transmitter/Conducted spurious emissions conveyed to the antenna




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)  
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Assigned Frequency: 156.025MHz, High Power, Modulation Type: FM, 30MHz-1GHz




Assigned Frequency: 156.025MHz, High Power, Modulation Type: FM, 1GHz-2GHz




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Assigned Frequency: 156.800MHz, High Power, Modulation Type: FM, 9KHz-150KHz




Assigned Frequency: 156.800MHz, High Power, Modulation Type: FM, 150KHz-30MHz




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Assigned Frequency: 156.800MHz, High Power, Modulation Type: FM, 30MHz-1GHz




Assigned Frequency: 156.800MHz, High Power, Modulation Type: FM, 1GHz-2GHz




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Assigned Frequency: 157.425MHz, High Power, Modulation Type: FM, 9KHz-150KHz




Assigned Frequency: 157.425MHz, High Power, Modulation Type: FM, 150KHz-30MHz




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Assigned Frequency: 157.425MHz, High Power, Modulation Type: FM, 30MHz-1GHz



Assigned Frequency: 157.425MHz, High Power, Modulation Type: FM, 1GHz-2GHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**10. Cabinet radiation and conducted spurious emissions other than those conveyed to the antenna**


Assigned Frequency:156.8MHz, High Power, Stand-by mode				
Frequency MHz	Polarity H/V	Emission Level dBm	Limit dBm	Over Limit dBm
383.72	H	-63.67	-57	-6.67
500.16	H	-73.23	-57	-16.23
820.16	H	-72.11	-57	-15.11
383.28	V	-65.63	-57	-8.63
1803.15	V	-69.1	-57	-12.1
2006.29	V	-66.47	-57	-9.47

Assigned Frequency:156.8MHz, High Power, Operation mode				
Frequency MHz	Polarity H/V	Emission Level dBm	Limit dBm	Over Limit dBm
649.35	H	-42.61	-36	-6.61
805.37	H	-49.61	-36	-13.61
1273.99	H	-50.99	-36	-14.99
649.42	V	-46.1	-36	-10.1
805.37	V	-52.43	-36	-16.43
1274.48	V	-52.6	-36	-16.6



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

11. Transmitter/Transient frequency behaviour of the transmitter



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**12. Transmitter/Residual modulation of the transmitter**

Test Frequency (MHz)	Residual modulation (dB)	Residual modulation limit (dB)	Verdict
156.8	-47	≤-40	Pass

**13. Transmitter/Frequency error (demodulated DSC signal)**

Test State	Temperature (°C)	Power Supplied (V Dc)	Measured Frequency (Hz)	Tolerance	Measured Result (Hz)	Verdict
Normal condition, Assigned Frequency:156.525MHz(Channel 70)						
B-state	Tnor=25	Vnor=7.4	2100	±10	2100.02	Pass
Y-state	Tnor=25	Vnor=7.4	1300	±10	1300.02	Pass
Extreme condition, Assigned Frequency:156.525MHz(Channel 70)						
B-state	Tmin=-20	Vmin=6.29	2100	±10	2100.02	Pass
	Tmin =-20	Vmax=8.51	2100	±10	2100.02	Pass
	Tmax=55	Vmin=6.29	2100	±10	2100.02	Pass
	Tmax =55	Vmax=8.51	2100	±10	2100.01	Pass
Y-state	Tmin=-20	Vmin=6.29	1300	±10	1300.03	Pass
	Tmin =-20	Vmax=8.51	1300	±10	1300.03	Pass
	Tmax=55	Vmin=6.29	1300	±10	1300.03	Pass
	Tmax =55	Vmax=8.51	1300	±10	1300.03	Pass

**14. Transmitter/Modulation index for DSC**

Test State	Temperature (°C)	Power Supplied (V Dc)	Measured Frequency (Hz)	Modulation index	Measured Result (Hz)	Verdict
Normal condition, Assigned Frequency:156.525MHz(Channel 70)						
B-state	Tnor=25	Vnor=7.4	2100	2±10%	4095	Pass
Y-state	Tnor=25	Vnor=7.4	1300	2±10%	2550	Pass


**15. Transmitter/Modulation rate for DSC**


Test Frequency (MHz)	Temperature (°C)	Power Supplied (V Dc)	Modulation Rate (bit/s)	Frequency Error (ppm)	Limit (ppm)	Verdict
156.525	Tnor=25	Vnor=7.4	1200	17	≤30	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

### 16. Transmitter/occupied Bandwidth(Testing of free channel transmission on DSC channel 70)





**17. Receiver/Harmonic distortion and rated audio-frequency output power**

Signal Level (dbuV)	Modulation Frequency (Hz)	AF Loudspeaker		Limit		Verdict
		Pout(W)	Dist.(%)	Output Power(W)	AF Distortion (%)	
Normal condition, Assigned Frequency:156.8MHz						
60	300	4.6	3.5	>2	≤10	Pass
	500	8.7	3.6	>2	≤10	Pass
	1000	8.9	3.6	>2	≤10	Pass

**18.Receiver/Audio Frequency Response for receiver**

Modulation Frequency (Hz)	Upper Limit (dB)	Lower Limit (dB)	Relative Audio Power			Max Level	Min Level	Verdict
			Fn(dB)	Fn (-1.5KHz)	Fn (+1.5KHz)			
Normal condition, Assigned Frequency:156.8MHz								
300	11.5	7.5	8.8	8.2	9.7	9.7	8.2	Pass
500	7	3	5.6	5.2	5.5	5.6	5.2	Pass
800	2.9	-1.1	1.4	1.4	1.1	1.4	1.1	Pass
1000	1	-3	0	0	0	0	0	Pass
1500	-1.5	-5.5	-3.2	-3.3	-3.8	-3.2	-3.8	Pass
2000	-5	-9	-5.7	-5.5	-6.7	-5.5	-6.7	Pass
3000	-8.5	-12.5	-9.6	-9.8	-10.3	-9.6	-10.3	Pass

**19. Receiver/Maximum useable sensitivity**

Test Freq. (MHz)	Temp. (°C)	Power Supplied (V Dc)	Receiver Sensitivity (dBuV)	Sensitivity Limit (dBuV)	Verdict
Normal condition					
156.8	Tnor=25	Vnor=7.4	-7	≤6	Pass
Extreme condition					
156.8	Tmin=-20	Vmin=6.29	-7	≤12	Pass
	Tmin =-20	Vmax=8.51	-7	≤12	Pass
	Tmax=55	Vmin=6.29	-7	≤12	Pass
	Tmax =55	Vmax=8.51	-7	≤12	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

**20. Receiver/Co-channel rejection**

Test Freq. (MHz)	Unwanted signal Frequency (MHz)	Rated AF output power (W)@4 ohms	Rejection Ratio (dB)	Upper Limit (dB)	Lower Limit (dB)	Verdict
Normal condition						
156.8	Fn + 3KHz	2	-7.4	0	-10	Pass
	Fn	2	-7.4	0	-10	Pass
	Fn - 3KHz	2	-7.4	0	-10	Pass

**21. Receiver/Adjacent channel selectivity**

Test Freq. (MHz)	Temperature (°C)	Power Supplied (V Dc)	Ratio of Unwanted to Wanted signal(dB)		Limit (dB)	Verdict
			Fn + 25KHz	Fn - 25KHz		
Normal condition						
156.8	Tnor=25	Vnor=7.4	71.7	73.4	≥70	Pass
Extreme condition						
156.8	Tmin=-20	Vmin=6.29	71.7	73.4	≥60	Pass
	Tmin =-20	Vmax=8.51	71.7	73.4	≥60	Pass
	Tmax=55	Vmin=6.29	71.7	73.4	≥60	Pass
	Tmax =55	Vmax=8.51	71.7	73.4	≥60	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)  
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

**22. Receiver/Spurious response rejection**

Test Freq. (MHz)	Defintion	Frequency of spurious Responses (MHz)	Rated AF output power (W) @ 4 ohms	Rejection ratio (dB)	Rejection ratio Limit (dB)	Verdict
Normal condition(Tnor=25, Vnor=7.4)						
156.8	1 <sup>st</sup> IF	21.7	2	107	≥70	Pass
	Image	113.4	2	107	≥70	Pass
	Half IF	135.1	2	107	≥70	Pass
	2 <sup>nd</sup> image	155.89	2	107	≥70	Pass

**23. Receiver/Intermodulation response**

Test Freq. (MHz)	Temperature (°C)	Power Supplied (V Dc)	Test Condition	Rejection ratio (dB)	Rejection ratio Limit (dB)	Verdict
Normal condition						
156.8	Tnor=25	Vnor=13.6	Upper Side	73.2	≥68	Pass
			Lower Side	72.7	≥68	Pass


**24. Receiver/Blocking or desensitisation**


Frequencies of the signal		Blocking Level (dBuV)	Block Limit (dBuV)	Verdict	
Wanted signal A (MHz)	Unwanted signal B (MHz)				
Normal condition(Tnor=25, Vnor=7.4)					
156.8	-10	146.8	102.4	≥90	Pass
	-5	151.8	101.6	≥90	Pass
	-2	154.8	101.1	≥90	Pass
	-1	155.8	102.5	≥90	Pass
	+1	157.8	102.7	≥90	Pass
	+2	158.8	102.2	≥90	Pass
	+5	161.8	102.2	≥90	Pass
	+10	166.8	102.4	≥90	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

### 25. Receiver/Spurious emissions





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**26.Receiver radiated spurious emissions**

Assigned Frequency:156.8MHz, receiver mode				
Frequency MHz	Polarity H/V	Emission Level dBm	Limit dBm	Over Limit dBm
384.17	H	-62.55	-57	-5.55
475.26	H	-71.74	-57	-14.74
823.44	H	-71.89	-57	-14.89
386.52	V	-66.58	-57	-9.58
1857.49	V	-70.52	-57	-13.52
2015.54	V	-67.54	-57	-10.54

**27.Receiver residual noise level**

Test Frequency (MHz)	Temperature (°C)	Power Supplied (V Dc)	Receiver residual noise level (dB)	Receiver residual noise Limit (dB)	Verdict
156.8	Tnor=25	Vnor=7.4	-42	≤-40	Pass

**28. Receiver/Squelch operation**

Relative Output Power(dB)	SINAD(dB)	Input Level (dBuV)	AF Output Power Limit(dB)	SINAD Limit(dB)	Input Level Limit (dBuV)	Verdict
Normal condition, Assigned Frequency:156.8MHz						
-46.6	24	5.1	≤-40	N/A	≤6	Pass

**29. Receiver/Squelch hysteresis**

Squelch Open(dBuV)	Squelch Closed(dBuV)	Difference (dB)	Upper Limit (dB)	Lower Limit (dB)	Verdict
Normal condition, Assigned Frequency:156.8MHz					
-8.2	-4.7	4.8	6	3	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
 Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

**30. Receiver/Multiple watch characteristic**

Temperature (°C)	Power Supplied (V Dc)	Scan Period (s)	Dwell Period (ms)	Dwell Time (s)	Limit			Verdict
					Scan Period (s)	Dwell Period (ms)	Dwell Time (s)	
Normal condition, Assigned Frequency:156.8MHz								
Tnor=25	Vnor=7.4	1.6	122	1.54	≤2	≤150	0.85 to 2	Pass
Extreme condition, Assigned Frequency:156.8MHz								
Tmin=-20	Vmin=6.29	1.6	122	1.54	≤2	≤150	0.85 to 2	Pass
Tmin =-20	Vmax=8.51	1.6	122	1.54	≤2	≤150		Pass
Tmax=55	Vmin=6.29	1.6	122	1.54	≤2	≤150		Pass
Tmax =55	Vmax=8.51	1.6	122	1.54	≤2	≤150		Pass

**31. DSC Receiver/Maximum useable sensitivity**

Test Freq. (MHz)	Temp. (°C)	Power Supplied (V Dc)	Carrier Freq. (KHz)	Input Level (dBuV)	BER (%)	BER limit (%)	Verdict
Normal condition							
156.525	Tnor=25	Vnor=7.4	Fn	0	0.02	≤1	Pass
			Fn+1.5	0	0.02	≤1	Pass
			Fn-1.5	0	0.02	≤1	Pass
Extreme condition							
156.525	Tmin=-20	Vmin=6.29	Fn	6	0.02	≤1	Pass
	Tmin =-20	Vmax=8.51	Fn	6	0.02	≤1	Pass
	Tmax=55	Vmin=6.29	Fn	6	0.02	≤1	Pass
	Tmax =55	Vmax=8.51	Fn	6	0.02	≤1	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**32. DSC Receiver/Co-channel rejection**

Test Freq. (MHz)	Unwanted signal Frequency (MHz)	Unwanted signal Level* (dBuV)	Wanted signal Level (dBuV)	BER (%)	BER Limit (%)	Verdict
Normal condition						
156.525	F <sub>n</sub> + 3KHz	-5	+3	0.05	≤1	Pass
	F <sub>n</sub>	-5	+3	0.05	≤1	Pass
	F <sub>n</sub> - 3KHz	-5	+3	0.05	≤1	Pass

\*:The unwanted signal shall be modulated by 400 Hz with a deviation of ±3 kHz

**33. DSC Receiver/Adjacent channel selectivity**

Temp. (°C)	Power Supplied (V Dc)	Unwanted signal Frequency (MHz)	Unwanted signal Level* (dBuV)	Wanted signal Level (dBuV)	BER (%)	BER Limit (%)	Verdict
Normal condition, Assigned Frequency:156.525MHz							
T <sub>nor</sub> =25	V <sub>nor</sub> =7.4	F <sub>n</sub> + 25KHz	73	3	0.01	≤1	Pass
		F <sub>n</sub>	73	3	0.01	≤1	Pass
		F <sub>n</sub> - 25KHz	73	3	0.01	≤1	Pass
Extreme condition, Assigned Frequency:156.525MHz							
T <sub>min</sub> =-20	V <sub>min</sub> =6.29	F <sub>n</sub> + 25KHz	63	6	0.01	≤1	Pass
		F <sub>n</sub>	63	6	0.01	≤1	Pass
		F <sub>n</sub> - 25KHz	63	6	0.01	≤1	Pass
T <sub>min</sub> = -20	V <sub>max</sub> =8.51	F <sub>n</sub> + 25KHz	63	6	0.01	≤1	Pass
		F <sub>n</sub>	63	6	0.02	≤1	Pass
		F <sub>n</sub> - 25KHz	63	6	0.02	≤1	Pass
T <sub>max</sub> =55	V <sub>min</sub> =6.29	F <sub>n</sub> + 25KHz	63	6	0.01	≤1	Pass
		F <sub>n</sub>	63	6	0.01	≤1	Pass
		F <sub>n</sub> - 25KHz	63	6	0.01	≤1	Pass
T <sub>max</sub> =55	V <sub>max</sub> =8.51	F <sub>n</sub> + 25KHz	63	6	0.01	≤1	Pass
		F <sub>n</sub>	63	6	0.02	≤1	Pass
		F <sub>n</sub> - 25KHz	63	6	0.02	≤1	Pass

\*:The unwanted signal shall be modulated by 400 Hz with a deviation of ±3 kHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**34. DSC Receiver/Spurious response and blocking immunity**

Test Freq.	Defintion	UnWanted Frequency (MHz)	Wanted signal Level (dBuV)	Unwanted signal Level (dBuV)	BER (%)	BER Limit (%)	Verdict
Normal condition(Tnor=25, Vnor=7.4)							
156.525	1 <sup>ST</sup> IF (Receiver A)	46.35	3	73	0.02	≤1	Pass
	1 <sup>ST</sup> LO-Freq. - IF	249.225	3	73	0.02	≤1	Pass
	2 x 1 <sup>ST</sup> LO-Freq. - IF	359.4	3	73	0.02	≤1	Pass
	2 x 1 <sup>ST</sup> LO-Freq. + IF	452.1	3	73	0.02	≤1	Pass
	3 x 1 <sup>ST</sup> LO-Freq. - IF	562.275	3	73	0.02	≤1	Pass
	3 x 1 <sup>ST</sup> LO-Freq. + IF	654.975	3	73	0.01	≤1	Pass

Test Freq.	Defintion	UnWanted Frequency (MHz)	Wanted signal Level (dBuV)	Unwanted signal Level (dBuV)	BER (%)	BER Limit (%)	Verdict
Normal condition(Tnor=25, Vnor=7.4)							
156.525	1 <sup>ST</sup> IF (Receiver B)	58.05	3	73	0	≤1	Pass
	1 <sup>ST</sup> LO-Freq. - IF	260.925	3	73	0	≤1	Pass
	2 x 1 <sup>ST</sup> LO-Freq. - IF	347.7	3	73	0	≤1	Pass
	2 x 1 <sup>ST</sup> LO-Freq. + IF	463.8	3	73	0	≤1	Pass
	3 x 1 <sup>ST</sup> LO-Freq. - IF	550.575	3	73	0	≤1	Pass
	3 x 1 <sup>ST</sup> LO-Freq. + IF	666.675	3	73	0	≤1	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Frequencies of the signal		Wanted signal Level A(dBuV)	Unwanted signal Level B(dBuV)	BER (%)	BER Limit (%)	Verdict	
Wanted signal A* (MHz)	Unwanted signal B (MHz)						
Normal condition(Tnor=25, Vnor=7.4)							
156.525	-10	146.525	3	93	0.02	≤1	Pass
	-5	151.525	3	93	0.02	≤1	Pass
	-2	154.525	3	93	0.02	≤1	Pass
	-1	155.525	3	93	0.02	≤1	Pass
	+1	157.525	3	93	0.02	≤1	Pass
	+2	158.525	3	93	0.02	≤1	Pass
	+5	161.525	3	93	0.01	≤1	Pass
	+10	166.525	3	93	0.01	≤1	Pass

**35. DSC Receiver/Intermodulation response**

Frequencies of the signal			Wanted signal Level A(dBuV)	Unwanted signal Level* B(dBuV)	Unwanted signal Level* C(dBuV)	BER (%)	BER Limit (%)	Verdict
Generator A	Generator B	Generator C						
Normal condition(Tnor=25, Vnor=7.4)								
156.525	156.475	156.425	3	68	68	0.03	≤1	Pass
	156.575	156.625	3	68	68	0.03	≤1	Pass

\*: Modulated with 400Hz/3KHz deviation

**36. DSC Receiver/Dynamic range**

Test Freq. (MHz)	Maximum Input Level (dBuV)	Minimum input Level (dBuV)	BER (%)	BER Limit (%)	Verdict
Normal condition(Tnor=25, Vnor=7.4)					
156.525	100	0	0.03	≤1	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**

**37. DSC Receiver/Simultaneous reception**


Test Freq. (MHz)	Input Freq. (MHz)	Input signal Level (dBuV)	Wanted signal Level (dBuV)	SINAD(dB)		BER (%)	SINAD Limit (dB)	BER Limit (%)	Verdict
				With Wanted signal	Without Wanted signal				
Normal condition(Tnor=25, Vnor=7.4)									
156.525	156.8	20	0	33.1	0	0.3	≥20	≤1	Pass




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 38. DSC Receiver/Spurious emissions





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**7.2 Appendix B---Test Requirement for Class D DSC Equipment.**

<b>DSC Signalling</b>			
<b>Item</b>	<b>Standard</b>	<b>Requirement</b>	<b>Satisfactory</b>
Dispaly	EN 301 025 clause 10.9.1	EN 300 338-3 clause 4.1	Yes
Watchkeeping receiver	EN 301 025 clause 10.9.2	EN 300 338-3 clause 5.1.1	Yes
Individual DSC calls	EN 301 025 clause 10.9.3	EN 300 338-3 clause 5.2.2	Yes
All ships calls	EN 301 025 clause 10.9.4	EN 300 338-3 clause 5.2.3	Yes
DSC call functionality	EN 301 025 clause 10.9.5	EN 300 338-3 clause 5.2.4	Yes
DSC message composition	EN 301 025 clause 10.9.6	EN 300 338-3 clause 6.2.1	Yes
Prioritized wait	EN 301 025 clause 10.9.7	EN 300 338-3 clause 6.2.2	Yes
Alarms	EN 301 025 clause 10.9.8	EN 300 338-3 clause 6.2.3	Yes
Standby	EN 301 025 clause 10.9.9	EN 300 338-3 clause 6.3	Yes
Sending distress automated requirements	EN 301 025 clause 10.9.10	EN 300 338-3 clause 6.4.2	Yes
Display-sending distress	EN 301 025 clause 10.9.11	EN 300 338-3 clause 6.4.3	Yes
Distress button sub procedure	EN 301 025 clause 10.9.12	EN 300 338-3 clause 6.4.4	Yes
Transmission of the alert attempt	EN 301 025 clause 10.9.13	EN 300 338-3 clause 6.4.5	Yes
Updating position	EN 301 025 clause 10.9.14	EN 300 338-3 clause 6.4.6	Yes
Handling received DSC messages - sending distress	EN 301 025 clause 10.9.15	EN 300 338-3 clause 6.4.7	Yes
Alarms - sending distress	EN 301 025 clause 10.9.16	EN 300 338-3 clause 6.4.8	Yes
Determining subsequent communications - sending distress	EN 301 025 clause 10.9.17	EN 300 338-3 clause 6.4.9	Yes
Automated tuning - sending distress	EN 301 025 clause 10.9.18	EN 300 338-3 clause 6.4.10	Yes
Cancelling the distress alert	EN 301 025 clause 10.9.19	EN 300 338-3 clause 6.4.11	Yes
Acknowledgements - sending distress	EN 301 025 clause 10.9.20	EN 300 338-3 clause 6.4.12	Yes
Termination - sending distress	EN 301 025 clause 10.9.21	EN 300 338-3 clause 6.4.13	Yes
Warnings - sending distress	EN 301 025 clause 10.9.22	EN 300 338-3 clause 6.4.14	Yes
Tasks - receiving distress	EN 301 025 clause 10.9.23	EN 300 338-3 clause 6.5.2	Yes
Display - receiving distress	EN 301 025 clause 10.9.24	EN 300 338-3 clause 6.5.3	Yes



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Handling received DSC messages - receiving distress	EN 301 025 clause 10.9.25	EN 300 338-3 clause 6.5.4	Yes
Alarms - receiving distress	EN 301 025 clause 10.9.26	EN 300 338-3 clause 6.5.5	Yes
Determining subsequent communications - receiving distress	EN 301 025 clause 10.9.27	EN 300 338-3 clause 6.5.6	Yes
Automated tuning - receiving distress	EN 301 025 clause 10.9.28	EN 300 338-3 clause 6.5.7	Yes
Acknowledgements - receiving distress	EN 301 025 clause 10.9.29	EN 300 338-3 clause 6.5.8	Yes
Termination - receiving distress	EN 301 025 clause 10.9.30	EN 300 338-3 clause 6.5.9	Yes
Warnings - receiving distress	EN 301 025 clause 10.9.31	EN 300 338-3 clause 6.5.10	Yes
Tasks - sending non distress	EN 301 025 clause 10.9.32	EN 300 338-3 clause 6.6.2	Yes
Display - sending non distress	EN 301 025 clause 10.9.33	EN 300 338-3 clause 6.6.3	Yes
Handling received DSC messages - sending non distress	EN 301 025 clause 10.9.34	EN 300 338-3 clause 6.6.4	Yes
Alarms - sending non distress	EN 301 025 clause 10.9.35	EN 300 338-3 clause 6.6.5	Yes
Automated tuning - sending non distress	EN 301 025 clause 10.9.36	EN 300 338-3 clause 6.6.6	Yes
Delayed acknowledgements - sending non distress	EN 301 025 clause 10.9.37	EN 300 338-3 clause 6.6.7	Yes
Termination - sending non distress	EN 301 025 clause 10.9.38	EN 300 338-3 clause 6.6.8	Yes
Warnings - sending non distress	EN 301 025 clause 10.9.39	EN 300 338-3 clause 6.6.9	Yes
Tasks - receiving non distress	EN 301 025 clause 10.9.40	EN 300 338-3 clause 6.7.2	Yes
Display - receiving non distress	EN 301 025 clause 10.9.41	EN 300 338-3 clause 6.7.3	Yes
Handling received DSC messages - receiving non distress	EN 301 025 clause 10.9.42	EN 300 338-3 clause 6.7.4	Yes
Alarms - receiving non distress	EN 301 025 clause 10.9.43	EN 300 338-3 clause 6.7.5	Yes
Automated tuning - receiving non distress	EN 301 025 clause 10.9.44	EN 300 338-3 clause 6.7.6	Yes
Acknowledgements - receiving non distress	EN 301 025 clause 10.9.45	EN 300 338-3 clause 6.7.7	Yes



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Termination - receiving non distress	EN 301 025 clause 10.9.46	EN 300 338-3 clause 6.7.8	Yes
Warnings - receiving non distress	EN 301 025 clause 10.9.47	EN 300 338-3 clause 6.7.9	Yes
Communication automated procedure	EN 301 025 clause 10.9.48	EN 300 338-3 clause 6.8.1	Yes
Tasks - communication	EN 301 025 clause 10.9.49	EN 300 338-3 clause 6.8.2	Yes
Display - communication	EN 301 025 clause 10.9.50	EN 300 338-3 clause 6.8.3	Yes
Handling received DSC messages - communication	EN 301 025 clause 10.9.51	EN 300 338-3 clause 6.8.4	Yes
Tuning of the receiver and transmitter - communication	EN 301 025 clause 10.9.52	EN 300 338-3 clause 6.8.5	Yes
Termination - communication	EN 301 025 clause 10.9.53	N/A	Yes
Tasks of handling incoming calls while engaged	EN 301 025 clause 10.9.54	EN 300 338-3 clause 6.9.2	Yes
Termination of automated procedures	EN 301 025 clause 10.9.55	EN 300 338-3 clause 6.9.2.3	Yes
Actions after termination of an automated procedure	EN 301 025 clause 10.9.56	EN 300 338-3 clause 6.9.2.4	Yes
Putting automated procedures on hold	EN 301 025 clause 10.9.57	EN 300 338-3 clause 6.9.2.5	Yes
Controlling non-terminated automated procedures on hold	EN 301 025 clause 10.9.58	EN 300 338-3 clause 6.9.2.6	Yes

- End of the Report -



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.