

Harman International Industries, Inc.

RF TEST REPORT

Report Type:

FCC Part 15.247 & ISED RSS-247 RF report

Model:

AP72598V

REPORT NUMBER:

240100930SHA-001

ISSUE DATE:

January 31, 2024

DOCUMENT CONTROL NUMBER:

TTRF15.247-01_V1 © 2018 Intertek



Applicant: Harman International Industries, Inc.
8500 Balboa Blvd, Northridge, CA 91329, USA

Manufacturer: Dalian Golden Hualu Digital Technology Co., Ltd.
No.1 Hua Road,Qixianling,High-Tech Industrial Zone,Dalian,Liaoning, China

Manufacturing site: Dalian Golden Hualu Digital Technology Co., Ltd.
No.1 Hua Road,Qixianling,High-Tech Industrial Zone,Dalian,Liaoning, China

Product Name: WiFi & BT Platform Module

Type/Model: AP72598V

FCC ID: APIAP72598V

IC: 6132A-AP72598V

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:


47CFR Part 15 (2021): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices


RSS-247 Issue 3 (August 2023): Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5 (February 2021) Amendment 2: General Requirements for Compliance of Radio Apparatus

| | |
|---------------------|---------------------|
| PREPARED BY: | REVIEWED BY: |
|---------------------|---------------------|



Project Engineer
Erick Liu



Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

| | |
|--|-----------|
| REVISION HISTORY | 5 |
| MEASUREMENT RESULT SUMMARY | 6 |
| 1 GENERAL INFORMATION | 7 |
| 1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) | 7 |
| 1.2 TECHNICAL SPECIFICATION | 7 |
| 1.3 FREQUENCY HOPPING SYSTEM REQUIREMENT | 8 |
| 1.4 DESCRIPTION OF TEST FACILITY | 10 |
| 2 TEST SPECIFICATIONS | 11 |
| 2.1 STANDARDS OR SPECIFICATION | 11 |
| 2.2 MODE OF OPERATION DURING THE TEST..... | 11 |
| 2.3 TEST SOFTWARE LIST | 12 |
| 2.4 TEST PERIPHERALS LIST | 12 |
| 2.5 TEST ENVIRONMENT CONDITION:..... | 12 |
| 2.6 INSTRUMENT LIST | 13 |
| 2.7 MEASUREMENT UNCERTAINTY | 15 |
| 3 20DB BANDWIDTH | 16 |
| 3.1 LIMIT | 16 |
| 3.2 MEASUREMENT PROCEDURE | 16 |
| 3.3 TEST CONFIGURATION | 17 |
| 3.4 TEST RESULTS OF 20dB BANDWIDTH..... | 17 |
| 4 CARRIER FREQUENCY SEPARATION | 18 |
| 4.1 LIMIT | 18 |
| 4.2 TEST CONFIGURATION | 18 |
| 4.3 TEST PROCEDURE AND TEST SETUP..... | 18 |
| 4.4 TEST RESULTS OF CARRIER FREQUENCY SEPARATION..... | 18 |
| 5 OUTPUT POWER | 19 |
| 5.1 LIMIT | 19 |
| 5.2 TEST CONFIGURATION | 19 |
| 5.3 MEASUREMENT PROCEDURE | 19 |
| 5.4 TEST RESULTS OF OUTPUT POWER..... | 19 |
| 6 RADIATED EMISSIONS | 20 |
| 6.1 LIMIT | 20 |
| 6.2 MEASUREMENT PROCEDURE | 20 |
| 6.3 TEST RESULTS OF RADIATED EMISSIONS | 22 |
| 7 CONDUCTED SPURIOUS EMISSIONS & BAND EDGE | 43 |
| 7.1 LIMIT | 43 |
| 7.2 TEST CONFIGURATION | 43 |
| 7.3 MEASUREMENT PROCEDURE | 43 |
| 7.4 TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS & BAND EDGE | 44 |
| 8 POWER LINE CONDUCTED EMISSION | 45 |
| 8.1 LIMIT | 45 |
| 8.2 TEST CONFIGURATION | 45 |
| 8.3 MEASUREMENT PROCEDURE | 46 |

TEST REPORT

| | | |
|--|---|-----------|
| 8.4 | TEST RESULTS OF POWER LINE CONDUCTED EMISSION..... | 47 |
| 9 | NUMBER OF HOPPING FREQUENCIES | 49 |
| 9.1 | LIMIT | 49 |
| 9.2 | TEST CONFIGURATION | 49 |
| 9.3 | TEST PROCEDURE AND TEST SETUP | 49 |
| 9.4 | TEST RESULTS OF NUMBER OF HOPPING FREQUENCIES | 49 |
| 10 | DWELL TIME | 50 |
| 10.1 | LIMIT | 50 |
| 10.2 | TEST CONFIGURATION | 50 |
| 10.3 | TEST PROCEDURE AND TEST SETUP | 50 |
| 10.4 | TEST RESULTS OF DWELL TIME | 51 |
| 11 | OCCUPIED BANDWIDTH | 52 |
| 11.1 | LIMIT | 52 |
| 11.2 | MEASUREMENT PROCEDURE | 52 |
| 11.3 | TEST CONFIGURATION | 52 |
| 11.4 | THE RESULTS OF OCCUPIED BANDWIDTH | 52 |
| 12 | ANTENNA REQUIREMENT..... | 53 |
| APPENDIX A: TEST RESULTS | | 54 |
| 20dB EMISSION BANDWIDTH..... | | 54 |
| | <i>Test Result.....</i> | <i>54</i> |
| | <i>Test Graphs.....</i> | <i>55</i> |
| OCCUPIED CHANNEL BANDWIDTH..... | | 58 |
| | <i>Test Result.....</i> | <i>58</i> |
| | <i>Test Graphs.....</i> | <i>59</i> |
| MAXIMUM CONDUCTED OUTPUT POWER..... | | 62 |
| | <i>Test Result Peak.....</i> | <i>62</i> |
| | <i>Test Graphs.....</i> | <i>63</i> |
| CARRIER FREQUENCY SEPARATION..... | | 66 |
| | <i>Test Result.....</i> | <i>66</i> |
| | <i>Test Graphs.....</i> | <i>67</i> |
| TIME OF OCCUPANCY | | 68 |
| | <i>Test Result.....</i> | <i>68</i> |
| | <i>Test Graphs.....</i> | <i>69</i> |
| NUMBER OF HOPPING CHANNELS | | 72 |
| | <i>Test Result.....</i> | <i>72</i> |
| | <i>Test Graphs.....</i> | <i>73</i> |
| BAND EDGE MEASUREMENTS..... | | 74 |
| | <i>Test Result.....</i> | <i>74</i> |
| | <i>Test Graphs.....</i> | <i>75</i> |
| CONDUCTED SPURIOUS EMISSION | | 79 |
| | <i>Test Result.....</i> | <i>79</i> |
| | <i>Test Graphs.....</i> | <i>80</i> |
| DUTY CYCLE..... | | 89 |
| | <i>Test Result.....</i> | <i>89</i> |
| | <i>Test Graphs.....</i> | <i>90</i> |

Revision History

| Report No. | Version | Description | Issued Date |
|------------------|---------|-------------------------|------------------|
| 240100930SHA-001 | Rev. 01 | Initial issue of report | January 31, 2024 |
| | | | |
| | | | |

Measurement result summary

| TEST ITEM | FCC REFERANCE | IC REFERANCE | RESULT |
|--|-------------------|------------------------------------|--------|
| 20 dB Bandwidth | 15.247(a)(1) | RSS-247 Issue 3 Clause 5.1 | Pass |
| Carrier Frequency Separation | 15.247(a)(1) | RSS-247 Issue 3 Clause 5.1 | Pass |
| Output power | 15.247(b)(1) | RSS-247 Issue 3 Clause 5.4 | Pass |
| Radiated Emissions | 15.205 & 15.209 | RSS-Gen Issue 5 Clause 8.9&8.10 | Pass |
| Conducted Spurious Emissions & Band Edge | 15.247(d) | RSS-247 Issue 3 Clause 5.5 | Pass |
| Power line conducted emission | 15.207 | RSS-Gen Issue 5 Clause 8.8 | Pass |
| Number of Hopping Frequencies | 15.247(a)(1)(iii) | RSS-247 Issue 3 Clause 5.1 | |
| Dwell time | 15.247(a)(1)(iii) | RSS-247 Issue 3 Clause 5.1 | |
| Occupied bandwidth | - | RSS-Gen Issue 5 Clause 6.6 | Tested |
| Antenna requirement | 15.203 | - | Pass |

Notes: 1: NA =Not Applicable

2: Determination of the test conclusion is based on IEC Guide 115 in consideration of measurement uncertainty.

3: Additions, Deviations and Exclusions from Standards: None.

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

| | |
|-------------------------------|---|
| Product name: | WiFi & BT Platform Module |
| Type/Model: | AP72598V |
| Description of EUT: | The EUT is wireless module with WiFi and Bluetooth function, it has only one model. |
| Rating: | 4.5-5.5V DC |
| Category of EUT: | Class B |
| EUT type: | <input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing |
| Software Version: | BCM4362A2_001.003.006.1012.1017_Decrease_BDR_EDR_LE_3dB_2022_0105_2 |
| Hardware Version: | / |
| Sample received date: | December 19, 2023 |
| Sample Identification Number: | A231219-47-001 |
| Date of test: | December 19, 2023 – January 19, 2024 |

1.2 Technical Specification

| | |
|-----------------------|---|
| Frequency Band: | 2400MHz ~ 2483.5MHz |
| Support Standards: | Bluetooth 5.1 (BR+EDR) |
| Modulation Technique: | Frequency Hopping Spread Spectrum(FHSS) |
| Type of Modulation: | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Channel Number: | 79 (0 - 78) |
| Data Rate: | Max 3 Mbps |
| Channel Separation: | 1 MHz |
| Antenna: | Antenna1: Pole antenna, 2.53dBi Antenna2: PCB antenna, 3.19dBi Antenna3: Chip antenna, 1.55dBi Antenna4: Pole antenna, 1.83dBi |

Note:

1. This information is supplied by the applicant. Any change on this value would result in different test data / conclusion.
2. After evaluation, we performed Radiated Emissions tests on the following three antennas:
Antenna1: Pole antenna, 2.53dBi
Antenna2: PCB antenna, 3.19dBi
Antenna3: Chip antenna, 1.55dBi

TEST REPORT

1.3 Frequency Hopping System Requirement

Test Requirement: Section 15.247 (a)(1), (g), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES;

i.e. the shift register is initialized with nine ones.


- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

TEST REPORT

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

1.4 Description of Test Facility

| | |
|------------|--|
| Name: | Intertek Testing Services Shanghai |
| Address: | Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China |
| Telephone: | 86 21 61278200 |
| Telefax: | 86 21 54262353 |

| | |
|---|---|
| The test facility is recognized, certified, or accredited by these organizations: | CNAS Accreditation Lab Registration No. CNAS L0139 |
| | FCC Accredited Lab Designation Number: CN0175 |
| | IC Registration Lab CAB identifier.: CN0014 |
| | VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252 |
| | A2LA Accreditation Lab Certificate Number: 3309.02 |

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2021)
 ANSI C63.10 (2020)
 RSS-247 Issue 3 (August 2023)
 RSS-Gen Issue 5 (February 2021) Amendment 2
 KDB 558074 D01 15.247 Meas Guidance v05r02

2.2 Mode of operation during the test

While testing the transmitter mode of the EUT, the internal modulation is applied.
 All the functions of the host device except the BT module were set on stand-by mode.

The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

The worst-case modulation configuration:

| Worst Modulation Used for Conformance Testing | | | |
|---|-----------|------------------|---|
| Bluetooth Mode | Data Rate | Packet Type | Worst Mode |
| GFSK | BR-1Mbps | DH1, DH3, DH5 | BR-1Mbps DH5 EDR-2Mbps 2DH5 EDR-3Mbps 3DH5 |
| $\pi/4$ DQPSK | EDR-2Mbps | 2DH1, 2DH3, 2DH5 | |
| 8DPSK | EDR-3Mbps | 3DH1, 3DH3, 3DH5 | |

Note: The BR-1Mbps DH5 mode was chosen for radiation emission as representative in this report.

The power setting parameter:

| The worst-case power setting parameter | | | |
|--|------------|---------|---------|
| Test software Version | Secure CRT | | |
| Modulation Mode | 2402MHz | 2441MHz | 2480MHz |
| BR-1Mbps | Default | Default | Default |
| EDR-2Mbps | Default | Default | Default |
| EDR-3Mbps | Default | Default | Default |

Radiated test mode: EUT transmitted signal with BT antenna;

Conducted test mode: EUT transmitted signal from BT RF port connected to SPA directly;

2.3 Test software list

| Test Items | Software | Manufacturer | Version |
|--------------------|----------|--------------|---------|
| Conducted emission | ESxS-K1 | R&S | V2.1.0 |
| Radiated emission | ES-K1 | R&S | V1.71 |

2.4 Test peripherals list

| Item No. | Name | Band and Model | Description |
|----------|-----------------|----------------|-------------|
| 1 | Laptop computer | HP | - |
| | | | |

2.5 Test environment condition:

| Test items | Temperature | Humidity |
|--|-------------|----------|
| 20 dB Bandwidth | 24°C | 52% RH |
| Output power | | |
| Carrier Frequency Separation | | |
| Number of Hopping Frequencies | | |
| Dwell time | | |
| Occupied bandwidth | | |
| Conducted Spurious Emissions & Band Edge | | |
| Power line conducted emission | 25°C | 55% RH |
| Radiated Emissions | 24°C | 52% RH |

2.6 Instrument list

| Conducted Emission/Disturbance Power/Tri-loop Test/CDN method | | | | | |
|---|-----------------------------|-------------------|------------------------|--------------|------------|
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | Test Receiver | R&S | ESR7 | EC 6194 | 2024-12-07 |
| <input checked="" type="checkbox"/> | Attenuator | Hua Xiang | Ts5-10db-6g | EC 6194-1 | 2024-12-07 |
| <input checked="" type="checkbox"/> | A.M.N. | R&S | ESH2-Z5 | EC 3119 | 2024-11-09 |
| Radiated Emission | | | | | |
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | Test Receiver | R&S | ESIB 26 | EC 3045 | 2024-09-11 |
| <input checked="" type="checkbox"/> | Bilog Antenna | TESEQ | CBL 6112D | EC 4206 | 2024-06-10 |
| <input checked="" type="checkbox"/> | Pre-amplifier | R&S | AFS42-00101800-25-S-42 | EC5262 | 2024-06-10 |
| <input type="checkbox"/> | Horn antenna | R&S | HF 906 | EC 3049 | 2024-11-16 |
| <input checked="" type="checkbox"/> | Horn antenna | ETS | 3117 | EC 4792-1 | 2024-03-14 |
| <input type="checkbox"/> | Horn antenna | TOYO | HAP18-26W | EC 4792-3 | 2024-07-09 |
| <input type="checkbox"/> | Active loop antenna | Schwarzbeck | FMZB1519 | EC 5345 | 2024-03-14 |
| RF test | | | | | |
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | PXA Signal Analyzer | Keysight | N9030A | EC 5338 | 2024-03-14 |
| <input type="checkbox"/> | Power sensor | Agilent | U2021XA | EC 5338-1 | 2024-03-14 |
| <input type="checkbox"/> | Vector Signal Generator | Agilent | N5182B | EC 5175 | 2024-03-14 |
| <input type="checkbox"/> | Spectrum analyzer | R&S | CMW500 | EC5944 | 2024-12-07 |
| <input type="checkbox"/> | MXG Analog Signal Generator | Agilent | N5181A | EC 5338-2 | 2024-03-14 |
| <input type="checkbox"/> | Mobile Test System | Litepoint | lqxel | EC 5176 | 2024-01-09 |
| <input type="checkbox"/> | Test Receiver | R&S | ESCI 7 | EC 4501 | 2024-09-11 |
| Tet Site | | | | | |
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |
| <input checked="" type="checkbox"/> | Shielded room | Zhongyu | - | EC 2838 | 2024-01-07 |
| <input checked="" type="checkbox"/> | Semi-anechoic chamber | Albatross project | - | EC 3048 | 2024-07-31 |
| Additional instrument | | | | | |
| Used | Equipment | Manufacturer | Type | Internal no. | Due date |

TEST REPORT

| | | | | | |
|-------------------------------------|-------------------|--------|----------|---------|------------|
| <input checked="" type="checkbox"/> | Therom-Hygrograph | ZJ1-2A | S.M.I.F. | EC 3783 | 2024-03-14 |
| <input checked="" type="checkbox"/> | Therom-Hygrograph | ZJ1-2A | S.M.I.F. | EC 5198 | 2024-01-18 |

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Test item | Measurement uncertainty |
|---|---------------------------|
| Maximum peak output power | ± 0.74dB |
| Power spectrum density | ± 0.74dB |
| Radiated Emissions in restricted frequency bands below 1GHz | ± 4.90dB |
| Radiated Emissions in restricted frequency bands above 1GHz | ± 5.02dB |
| Emission outside the frequency band | ± 2.89dB |
| Power line conducted emission | ± 3.19dB |
| Occupied bandwidth | ± 0.84 × 10 ⁻⁷ |
| Occupied bandwidth | ± 0.84 × 10 ⁻⁷ |

3 20dB bandwidth

Test result: Pass

3.1 Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.


Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

3.2 Measurement Procedure

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using [(reference value) - xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker

TEST REPORT

- amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

3.3 Test Configuration**3.4 Test Results of 20dB bandwidth**

Please refer to Appendix A.

4 Carrier Frequency Separation


Test result: Pass

4.1 Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

4.2 Test Configuration



4.3 Test Procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.

4.4 Test Results of Carrier Frequency Separation

Please refer to Appendix A.

5 Output power


Test result: Pass

5.1 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

5.2 Test Configuration



5.3 Measurement Procedure

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW \geq RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

5.4 Test Results of Output Power

Please refer to Appendix A.

6 Radiated Emissions

Test result: Pass

6.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490 | 2400/F(kHz) | 300 |
| 0.490 ~ 1.705 | 24000/F(kHz) | 30 |
| 1.705 ~ 30.0 | 30 | 30 |
| 30 ~ 88 | 100 | 3 |
| 88 ~ 216 | 150 | 3 |
| 216 ~ 960 | 200 | 3 |
| Above 960 | 500 | 3 |

6.2 Measurement Procedure

For Radiated emission below 30MHz:

- a) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) Both X and Y axes of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

TEST REPORT**For Radiated emission above 30MHz:**

- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or $3 \times \text{RBW}$ (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported

TEST REPORT



6.3 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

All modulation mode has been tested, and the worst data(GFSK) was listed in the report.

Test data below 1GHz

Antenna1: Pole antenna, 2402MHz





TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|-----------------|-----------------|-------------|-----------------|----------------|----------|-------|
| 1* | 375.029MHz | 46.0 | 37.2 | -8.8 | 20.3 | 16.9 | PK | Hor |
| 2* | 499.965MHz | 46.0 | 32.4 | -13.6 | 12.6 | 19.8 | PK | Hor |
| 3* | 624.998MHz | 46.0 | 30.2 | -15.8 | 7.7 | 22.5 | PK | Hor |
| 4* | 750.031MHz | 46.0 | 30.6 | -15.4 | 6.4 | 24.2 | PK | Hor |
| 5* | 875.064MHz | 46.0 | 35.3 | -10.7 | 9.4 | 25.9 | PK | Hor |
| 6* | 959.648MHz | 46.0 | 33.6 | -12.4 | 6.8 | 26.8 | PK | Hor |
| 7* | 33.201MHz | 40.0 | 25.3 | -14.7 | 12.7 | 12.6 | PK | Ver |
| 8* | 118.367MHz | 43.5 | 28.5 | -15.0 | 16.6 | 11.9 | PK | Ver |
| 9* | 166.576MHz | 43.5 | 32.2 | -11.3 | 18.1 | 14.1 | PK | Ver |
| 10* | 624.998MHz | 46.0 | 33.1 | -12.9 | 10.6 | 22.5 | PK | Ver |
| 11* | 869.147MHz | 46.0 | 32.5 | -13.5 | 6.7 | 25.8 | PK | Ver |
| 12* | 959.745MHz | 46.0 | 35.5 | -10.5 | 8.7 | 26.8 | PK | Ver |

TEST REPORT

Antenna1: Pole antenna, 2441MHz





TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|
| 1* | 166.576MHz | 43.5 | 32.2 | -11.3 | 18.1 | 14.1 | PK | Hor |
| 2* | 199.168MHz | 43.5 | 29.7 | -13.8 | 18.3 | 11.4 | PK | Hor |
| 3* | 375.029MHz | 46.0 | 37.1 | -8.9 | 20.2 | 16.9 | PK | Hor |
| 4* | 499.965MHz | 46.0 | 32.4 | -13.6 | 12.6 | 19.8 | PK | Hor |
| 5* | 875.064MHz | 46.0 | 36.0 | -10.0 | 10.1 | 25.9 | PK | Hor |
| 6* | 959.745MHz | 46.0 | 33.7 | -12.3 | 6.9 | 26.8 | PK | Hor |
| 7* | 31.067MHz | 40.0 | 27.7 | -12.3 | 15.5 | 12.2 | PK | Ver |
| 8* | 118.561MHz | 43.5 | 28.9 | -14.6 | 17.0 | 11.9 | PK | Ver |
| 9* | 166.576MHz | 43.5 | 30.7 | -12.8 | 16.6 | 14.1 | PK | Ver |
| 10* | 624.998MHz | 46.0 | 34.4 | -11.6 | 11.9 | 22.5 | PK | Ver |
| 11* | 869.147MHz | 46.0 | 33.7 | -12.3 | 7.9 | 25.8 | PK | Ver |
| 12* | 959.745MHz | 46.0 | 33.3 | -12.7 | 6.5 | 26.8 | PK | Ver |

TEST REPORT



Antenna1: Pole antenna, 2480MHz



TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|
| 1* | 199.168MHz | 43.5 | 29.3 | -14.2 | 17.9 | 11.4 | PK | Hor |
| 2* | 336.035MHz | 46.0 | 31.9 | -14.1 | 16.0 | 15.9 | PK | Hor |
| 3* | 375.029MHz | 46.0 | 36.9 | -9.1 | 20.0 | 16.9 | PK | Hor |
| 4* | 750.031MHz | 46.0 | 31.7 | -14.3 | 7.5 | 24.2 | PK | Hor |
| 5* | 875.064MHz | 46.0 | 36.2 | -9.8 | 10.3 | 25.9 | PK | Hor |
| 6* | 959.745MHz | 46.0 | 35.2 | -10.8 | 8.4 | 26.8 | PK | Hor |
| 7* | 30.388MHz | 40.0 | 26.0 | -14.0 | 13.9 | 12.1 | PK | Ver |
| 8* | 119.046MHz | 43.5 | 29.1 | -14.4 | 17.1 | 12.0 | PK | Ver |
| 9* | 165.994MHz | 43.5 | 30.7 | -12.8 | 16.6 | 14.1 | PK | Ver |
| 10* | 624.998MHz | 46.0 | 34.0 | -12.0 | 11.5 | 22.5 | PK | Ver |
| 11* | 875.064MHz | 46.0 | 32.0 | -14.0 | 6.1 | 25.9 | PK | Ver |
| 12* | 959.745MHz | 46.0 | 31.6 | -14.4 | 4.8 | 26.8 | PK | Ver |



Antenna2: PCB antenna, 2402MHz



TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|
| 1* | 199.847MHz | 43.5 | 26.9 | -16.6 | 15.6 | 11.3 | PK | Hor |
| 2* | 336.035MHz | 46.0 | 30.4 | -15.6 | 14.5 | 15.9 | PK | Hor |
| 3* | 375.029MHz | 46.0 | 43.3 | -2.7 | 26.4 | 16.9 | PK | Hor |
| 4* | 499.965MHz | 46.0 | 33.2 | -12.8 | 13.4 | 19.8 | PK | Hor |
| 5* | 869.244MHz | 46.0 | 30.4 | -15.6 | 4.6 | 25.8 | PK | Hor |
| 6* | 959.745MHz | 46.0 | 31.6 | -14.4 | 4.8 | 26.8 | PK | Hor |
| 7* | 121.277MHz | 43.5 | 29.7 | -13.8 | 17.5 | 12.2 | PK | Ver |
| 8* | 166.576MHz | 43.5 | 32.2 | -11.3 | 18.1 | 14.1 | PK | Ver |
| 9* | 375.029MHz | 46.0 | 34.4 | -11.6 | 17.5 | 16.9 | PK | Ver |
| 10* | 499.965MHz | 46.0 | 31.0 | -15.0 | 11.2 | 19.8 | PK | Ver |
| 11* | 869.147MHz | 46.0 | 32.8 | -13.2 | 7.0 | 25.8 | PK | Ver |
| 12* | 959.745MHz | 46.0 | 34.1 | -11.9 | 7.3 | 26.8 | PK | Ver |



Antenna2: PCB antenna, 2441MHz



TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|
| 1* | 165.994MHz | 43.5 | 29.4 | -14.1 | 15.3 | 14.1 | PK | Hor |
| 2* | 375.029MHz | 46.0 | 43.8 | -2.2 | 26.9 | 16.9 | PK | Hor |
| 3* | 499.965MHz | 46.0 | 33.3 | -12.7 | 13.5 | 19.8 | PK | Hor |
| 4* | 750.031MHz | 46.0 | 30.3 | -15.7 | 6.1 | 24.2 | PK | Hor |
| 5* | 874.967MHz | 46.0 | 32.6 | -13.4 | 6.7 | 25.9 | PK | Hor |
| 6* | 959.745MHz | 46.0 | 34.8 | -11.2 | 8.0 | 26.8 | PK | Hor |
| 7* | 124.963MHz | 43.5 | 30.3 | -13.2 | 17.7 | 12.6 | PK | Ver |
| 8* | 165.994MHz | 43.5 | 32.2 | -11.3 | 18.1 | 14.1 | PK | Ver |
| 9* | 375.029MHz | 46.0 | 34.5 | -11.5 | 17.6 | 16.9 | PK | Ver |
| 10* | 666.417MHz | 46.0 | 31.2 | -14.8 | 8.1 | 23.1 | PK | Ver |
| 11* | 869.147MHz | 46.0 | 32.3 | -13.7 | 6.5 | 25.8 | PK | Ver |
| 12* | 959.745MHz | 46.0 | 36.1 | -9.9 | 9.3 | 26.8 | PK | Ver |

Antenna2: PCB antenna, 2480MHz





TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|
| 1* | 165.994MHz | 43.5 | 30.0 | -13.5 | 15.9 | 14.1 | PK | Hor |
| 2* | 336.035MHz | 46.0 | 29.5 | -16.5 | 13.6 | 15.9 | PK | Hor |
| 3* | 375.029MHz | 46.0 | 42.8 | -3.2 | 25.9 | 16.9 | PK | Hor |
| 4* | 499.965MHz | 46.0 | 32.6 | -13.4 | 12.8 | 19.8 | PK | Hor |
| 5* | 874.967MHz | 46.0 | 32.6 | -13.4 | 6.7 | 25.9 | PK | Hor |
| 6* | 959.745MHz | 46.0 | 32.0 | -14.0 | 5.2 | 26.8 | PK | Hor |
| 7* | 124.963MHz | 43.5 | 30.5 | -13.0 | 17.9 | 12.6 | PK | Ver |
| 8* | 166.576MHz | 43.5 | 32.3 | -11.2 | 18.2 | 14.1 | PK | Ver |
| 9* | 375.029MHz | 46.0 | 34.6 | -11.4 | 17.7 | 16.9 | PK | Ver |
| 10* | 499.965MHz | 46.0 | 31.5 | -14.5 | 11.7 | 19.8 | PK | Ver |
| 11* | 869.826MHz | 46.0 | 33.6 | -12.4 | 7.8 | 25.8 | PK | Ver |
| 12* | 959.745MHz | 46.0 | 33.2 | -12.8 | 6.4 | 26.8 | PK | Ver |

TEST REPORT



Antenna3: Chip antenna, 2402MHz



TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|
| 1* | 336.035MHz | 46.0 | 32.5 | -13.5 | 16.6 | 15.9 | PK | Hor |
| 2* | 375.029MHz | 46.0 | 35.4 | -10.6 | 18.5 | 16.9 | PK | Hor |
| 3* | 499.965MHz | 46.0 | 34.1 | -11.9 | 14.3 | 19.8 | PK | Hor |
| 4* | 750.031MHz | 46.0 | 36.3 | -9.7 | 12.1 | 24.2 | PK | Hor |
| 5* | 875.064MHz | 46.0 | 35.8 | -10.2 | 9.9 | 25.9 | PK | Hor |
| 6* | 959.745MHz | 46.0 | 33.6 | -12.4 | 6.8 | 26.8 | PK | Hor |
| 7* | 31.067MHz | 40.0 | 26.4 | -13.6 | 14.2 | 12.2 | PK | Ver |
| 8* | 44.744MHz | 40.0 | 24.7 | -15.3 | 10.6 | 14.1 | PK | Ver |
| 9* | 124.769MHz | 43.5 | 29.1 | -14.4 | 16.5 | 12.6 | PK | Ver |
| 10* | 165.994MHz | 43.5 | 31.0 | -12.5 | 16.9 | 14.1 | PK | Ver |
| 11* | 869.147MHz | 46.0 | 30.0 | -16.0 | 4.2 | 25.8 | PK | Ver |
| 12* | 959.745MHz | 46.0 | 33.2 | -12.8 | 6.4 | 26.8 | PK | Ver |



Antenna3: Chip antenna, 2441MHz



TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|
| 1* | 336.035MHz | 46.0 | 32.2 | -13.8 | 16.3 | 15.9 | PK | Hor |
| 2* | 375.029MHz | 46.0 | 34.6 | -11.4 | 17.7 | 16.9 | PK | Hor |
| 3* | 499.965MHz | 46.0 | 34.1 | -11.9 | 14.3 | 19.8 | PK | Hor |
| 4* | 750.031MHz | 46.0 | 34.2 | -11.8 | 10.0 | 24.2 | PK | Hor |
| 5* | 875.064MHz | 46.0 | 35.2 | -10.8 | 9.3 | 25.9 | PK | Hor |
| 6* | 959.745MHz | 46.0 | 34.5 | -11.5 | 7.7 | 26.8 | PK | Hor |
| 7* | 30.291MHz | 40.0 | 25.5 | -14.5 | 13.5 | 12.0 | PK | Ver |
| 8* | 44.647MHz | 40.0 | 24.4 | -15.6 | 10.3 | 14.1 | PK | Ver |
| 9* | 119.434MHz | 43.5 | 29.2 | -14.3 | 17.2 | 12.0 | PK | Ver |
| 10* | 166.576MHz | 43.5 | 30.6 | -12.9 | 16.5 | 14.1 | PK | Ver |
| 11* | 869.147MHz | 46.0 | 32.0 | -14.0 | 6.2 | 25.8 | PK | Ver |
| 12* | 959.745MHz | 46.0 | 32.7 | -13.3 | 5.9 | 26.8 | PK | Ver |

Antenna3: Chip antenna, 2480MHz



TEST REPORT

| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|
| 1* | 336.035MHz | 46.0 | 32.4 | -13.6 | 16.5 | 15.9 | PK | Hor |
| 2* | 375.029MHz | 46.0 | 35.9 | -10.1 | 19.0 | 16.9 | PK | Hor |
| 3* | 499.965MHz | 46.0 | 33.8 | -12.2 | 14.0 | 19.8 | PK | Hor |
| 4* | 750.031MHz | 46.0 | 34.5 | -11.5 | 10.3 | 24.2 | PK | Hor |
| 5* | 875.064MHz | 46.0 | 35.7 | -10.3 | 9.8 | 25.9 | PK | Hor |
| 6* | 959.745MHz | 46.0 | 30.1 | -15.9 | 3.3 | 26.8 | PK | Hor |
| 7* | 30.291MHz | 40.0 | 25.8 | -14.2 | 13.8 | 12.0 | PK | Ver |
| 8* | 45.035MHz | 40.0 | 24.9 | -15.1 | 10.8 | 14.1 | PK | Ver |
| 9* | 119.531MHz | 43.5 | 29.0 | -14.5 | 17.0 | 12.0 | PK | Ver |
| 10* | 165.994MHz | 43.5 | 30.5 | -13.0 | 16.4 | 14.1 | PK | Ver |
| 11* | 499.965MHz | 46.0 | 30.7 | -15.3 | 10.9 | 19.8 | PK | Ver |
| 12* | 959.648MHz | 46.0 | 32.6 | -13.4 | 5.8 | 26.8 | PK | Ver |

Test result of 1GHz to 25GHz:

Antenna1: Pole antenna

| CH | Antenna | Frequency (MHz) | Corrected Reading (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|----|---------|-----------------|----------------------------|----------------|-------------|----------|
| L | H | 2390.00 | 44.60 | 74.00 | 29.40 | PK |
| | V | 2390.00 | 43.10 | 74.00 | 30.90 | PK |
| | H | 4804.00 | 43.60 | 74.00 | 30.40 | PK |
| | V | 4804.00 | 42.70 | 74.00 | 31.30 | PK |
| M | H | 4880.00 | 42.20 | 74.00 | 31.80 | PK |
| | V | 4880.00 | 41.80 | 74.00 | 32.20 | PK |
| H | H | 2483.50 | 50.94 | 74.00 | 23.06 | PK |
| | V | 2483.50 | 43.80 | 74.00 | 30.20 | PK |
| | H | 4960.00 | 42.30 | 74.00 | 31.70 | PK |
| | V | 4960.00 | 41.90 | 74.00 | 32.10 | PK |

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Corrected Reading
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
 Limit = 40.00dBuV/m.
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
 Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

TEST REPORT

Antenna2: PCB antenna

| CH | Antenna | Frequency (MHz) | Corrected Reading (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|----|---------|-----------------|----------------------------|----------------|-------------|----------|
| L | H | 2390.00 | 41.60 | 74.00 | 32.40 | PK |
| | V | 2390.00 | 42.10 | 74.00 | 31.90 | PK |
| | H | 4804.00 | 42.50 | 74.00 | 31.50 | PK |
| | V | 4804.00 | 42.60 | 74.00 | 31.40 | PK |
| M | H | 4880.00 | 42.30 | 74.00 | 31.70 | PK |
| | V | 4880.00 | 41.20 | 74.00 | 32.80 | PK |
| H | H | 2483.50 | 46.10 | 74.00 | 27.90 | PK |
| | V | 2483.50 | 52.20 | 74.00 | 21.80 | PK |
| | H | 4960.00 | 42.50 | 74.00 | 31.50 | PK |
| | V | 4960.00 | 43.10 | 74.00 | 30.90 | PK |

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Corrected Reading
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB, gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV, Limit = 40.00dBuV/m.
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
 Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.

TEST REPORT

Antenna3: Chip antenna

| CH | Antenna | Frequency (MHz) | Corrected Reading (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Detector |
|----|---------|-----------------|----------------------------|----------------|-------------|----------|
| L | H | 2390.00 | 42.60 | 74.00 | 31.40 | PK |
| | V | 2390.00 | 42.80 | 74.00 | 31.20 | PK |
| | H | 4804.00 | 41.50 | 74.00 | 32.50 | PK |
| | V | 4804.00 | 42.30 | 74.00 | 31.70 | PK |
| M | H | 4880.00 | 43.10 | 74.00 | 30.90 | PK |
| | V | 4880.00 | 42.90 | 74.00 | 31.10 | PK |
| H | H | 2483.50 | 50.20 | 74.00 | 23.80 | PK |
| | V | 2483.50 | 47.50 | 74.00 | 26.50 | PK |
| | H | 4960.00 | 43.20 | 74.00 | 30.80 | PK |
| | V | 4960.00 | 43.50 | 74.00 | 30.50 | PK |

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Corrected Reading
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
 Limit = 40.00dBuV/m.
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
 Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.


7 Conducted Spurious Emissions & Band Edge

Test result: Pass

7.1 Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.2 Test Configuration



7.3 Measurement Procedure

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e)
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3. of ANSI C63.10.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6 of ANSI C63.10, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100 kHz
 - 6) Video bandwidth: 300 kHz
 - 7) Detector: Peak
 - 8) Trace: Max hold
- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.

TEST REPORT

- g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- h) Repeat step c) through step e) for every applicable modulation.
- i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).
- j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

7.4 Test Results of Conducted Spurious Emissions & Band Edge

Please refer to Appendix A

8 Power line conducted emission


Test result: Pass

8.1 Limit

| Frequency of Emission (MHz) | Conducted Limit (dBuV) | |
|-----------------------------|------------------------|------------|
| | QP | AV |
| 0.15-0.5 | 66 to 56* | 56 to 46 * |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

* Decreases with the logarithm of the frequency.

8.2 Test Configuration





8.3 Measurement Procedure

Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

8.4 Test Results of Power line conducted emission



| No. | Frequency | Limit dBuV | Level dBuV | Delta dB | Reading dBuV | Factor dB | Detector | Phase |
|-----|------------|------------|------------|----------|--------------|-----------|----------|-------|
| 1 | 154.500kHz | 65.8 | 45.0 | -20.8 | 38.8 | 6.2 | QP | L1 |
| 2 | 181.500kHz | 64.4 | 40.4 | -24.0 | 34.2 | 6.2 | QP | L1 |
| 3 | 217.500kHz | 62.9 | 36.1 | -26.9 | 29.9 | 6.2 | QP | L1 |
| 4 | 244.500kHz | 61.9 | 31.4 | -30.5 | 25.2 | 6.2 | QP | L1 |
| 5 | 402.000kHz | 57.8 | 28.9 | -28.9 | 22.7 | 6.2 | QP | L1 |

TEST REPORT

| No. | Frequency | Limit dBuV | Level dBuV | Delta dB | Reading dBuV | Factor dB | Detector | Phase |
|-----|------------|------------|------------|----------|--------------|-----------|----------|-------|
| 6 | 19.424MHz | 60.0 | 27.0 | -33.0 | 19.8 | 7.2 | QP | L1 |
| 7 | 154.500kHz | 65.8 | 45.1 | -20.6 | 38.9 | 6.2 | QP | N |
| 8 | 186.000kHz | 64.2 | 40.2 | -24.0 | 34.1 | 6.1 | QP | N |
| 9 | 213.000kHz | 63.1 | 36.0 | -27.1 | 29.8 | 6.2 | QP | N |
| 10 | 249.000kHz | 61.8 | 31.5 | -30.3 | 25.3 | 6.2 | QP | N |
| 11 | 339.000kHz | 59.2 | 25.6 | -33.6 | 19.4 | 6.2 | QP | N |
| 12 | 402.000kHz | 57.8 | 30.0 | -27.8 | 23.8 | 6.2 | QP | N |
| 13 | 402.000kHz | 47.8 | 21.0 | -26.8 | 14.8 | 6.2 | CAV | L1 |
| 14 | 402.000kHz | 47.8 | 22.2 | -25.6 | 16.0 | 6.2 | CAV | N |

Remark: 1. Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Original Receiver Reading + Factor

3. Delta= Level - Limit

4. If the PK Level is lower than AV limit, the AV test can be elided.

Example: Assuming LISN Factor = 10.00dB, Cable Loss = 2.00dB,
Original Receiver Reading = 10.00dBuV, Limit = 66.00dBuV.

Then Factor = 10.00 + 2.00 = 12.00dB;

Level = 10dBuV + 12.00dB = 22.00dBuV;

Delta = 22.00dBuV - 66.00dBuV = -44.00dB.


9 Number of Hopping Frequencies

Test result: Pass

9.1 Limit

Number of Hopping Frequencies in the 2400-2483.5 MHz band shall use at least 15 channels.

9.2 Test Configuration



9.3 Test procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

9.4 Test Results of Number of Hopping Frequencies

Please refer to Appendix A


10 Dwell Time

Test result: Pass

10.1 Limit

The dwell time on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

10.2 Test Configuration



10.3 Test procedure and test setup

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\begin{aligned}
 & \text{(Number of hops in the period specified in the requirements)} = \text{(number of hops on spectrum analyzer)} \\
 & \times \text{(period specified in the requirements / analyzer sweep time)}
 \end{aligned}$$

TEST REPORT

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

10.4 Test Results of Dwell Time

Please refer to Appendix A

11 Occupied Bandwidth

Test result: Tested

11.1 Limit


None

11.2 Measurement Procedure

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

11.3 Test Configuration



11.4 The results of Occupied Bandwidth

Please refer to Appendix A

12 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

The EUT uses an internal IPEX antenna connector, the user cannot easily open the inside of the device, so it can comply with the provisions of this section.

TEST REPORT

Appendix A: Test results

**20dB Emission Bandwidth
Test Result**

| TestMode | Antenna | Frequency[MHz] | 20db EBW[MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|----------|---------|----------------|------------------|----------|----------|------------|---------|
| DH5 | Ant1 | 2402 | 0.909 | 2401.544 | 2402.453 | --- | --- |
| DH5 | Ant1 | 2441 | 1.029 | 2440.493 | 2441.522 | --- | --- |
| DH5 | Ant1 | 2480 | 0.996 | 2479.496 | 2480.492 | --- | --- |
| 2DH5 | Ant1 | 2402 | 1.356 | 2401.331 | 2402.687 | --- | --- |
| 2DH5 | Ant1 | 2441 | 1.332 | 2440.328 | 2441.660 | --- | --- |
| 2DH5 | Ant1 | 2480 | 1.344 | 2479.319 | 2480.663 | --- | --- |
| 3DH5 | Ant1 | 2402 | 1.290 | 2401.355 | 2402.645 | --- | --- |
| 3DH5 | Ant1 | 2441 | 1.332 | 2440.331 | 2441.663 | --- | --- |
| 3DH5 | Ant1 | 2480 | 1.317 | 2479.340 | 2480.657 | --- | --- |

Test Graphs





2DH5-Ant1-2402




2DH5-Ant1-2441



2DH5-Ant1-2480



3DH5-Ant1-2402



3DH5-Ant1-2441





3DH5-Ant1-2480

Occupied Channel Bandwidth Test Result


| TestMode | Antenna | Frequency[MHz] | OCB [MHz] | FL[MHz] | FH[MHz] | Limit[MHz] | Verdict |
|----------|---------|----------------|-----------|-----------|-----------|------------|---------|
| DH5 | Ant1 | 2402 | 0.91403 | 2401.5553 | 2402.4693 | --- | --- |
| DH5 | Ant1 | 2441 | 0.89904 | 2440.5542 | 2441.4532 | --- | --- |
| DH5 | Ant1 | 2480 | 0.89369 | 2479.5543 | 2480.4480 | --- | --- |
| 2DH5 | Ant1 | 2402 | 1.1983 | 2401.4075 | 2402.6058 | --- | --- |
| 2DH5 | Ant1 | 2441 | 1.2049 | 2440.3980 | 2441.6029 | --- | --- |
| 2DH5 | Ant1 | 2480 | 1.2050 | 2479.3893 | 2480.5943 | --- | --- |
| 3DH5 | Ant1 | 2402 | 1.2039 | 2401.4017 | 2402.6056 | --- | --- |
| 3DH5 | Ant1 | 2441 | 1.2084 | 2440.3924 | 2441.6008 | --- | --- |
| 3DH5 | Ant1 | 2480 | 1.2157 | 2479.3821 | 2480.5978 | --- | --- |

Test Graphs









2DH5-Ant1-2402



2DH5-Ant1-2441



2DH5-Ant1-2480





Maximum conducted output power Test Result Peak

| Test Mode | Antenna | Frequency[MHz] | Conducted Peak Power[dBm] | Conducted Limit[dBm] | Verdict |
|-----------|---------|----------------|---------------------------|----------------------|---------|
| DH5 | Ant1 | 2402 | 5.44 | ≤20.97 | PASS |
| DH5 | Ant1 | 2441 | 5.86 | ≤20.97 | PASS |
| DH5 | Ant1 | 2480 | 4.14 | ≤20.97 | PASS |
| 2DH5 | Ant1 | 2402 | 7.30 | ≤20.97 | PASS |
| 2DH5 | Ant1 | 2441 | 7.08 | ≤20.97 | PASS |
| 2DH5 | Ant1 | 2480 | 5.53 | ≤20.97 | PASS |
| 3DH5 | Ant1 | 2402 | 7.76 | ≤20.97 | PASS |
| 3DH5 | Ant1 | 2441 | 7.33 | ≤20.97 | PASS |
| 3DH5 | Ant1 | 2480 | 6.07 | ≤20.97 | PASS |


Max EIRP is $7.76\text{dBm} + 3.19\text{dBi} = 10.95\text{dBm} = 12.45\text{mW} < 4\text{W}$.

Test Graphs






2DH5-Ant1-2402




2DH5-Ant1-2441




2DH5-Ant1-2480



3DH5-Ant1-2402



3DH5-Ant1-2441




3DH5-Ant1-2480

TEST REPORT**Carrier frequency separation****Test Result**

| TestMode | Antenna | Frequency[MHz] | Result[MHz] | Limit[MHz] | Verdict |
|----------|---------|----------------|-------------|--------------|---------|
| DH5 | Ant1 | Hop | 1.176 | ≥ 1.029 | PASS |
| 2DH5 | Ant1 | Hop | 0.99 | ≥ 0.904 | PASS |
| 3DH5 | Ant1 | Hop | 0.974 | ≥ 0.888 | PASS |

Test Graphs




Time of occupancy Test Result


| TestMode | Antenna | Frequency[MHz] | BurstWidth [ms] | TotalHops [Num] | Result[s] | Limit[s] | Verdict |
|----------|---------|----------------|-----------------|-----------------|-----------|----------|---------|
| DH1 | Ant1 | Hop | 0.380 | 320 | 0.122 | ≤0.4 | PASS |
| DH3 | Ant1 | Hop | 1.637 | 160 | 0.262 | ≤0.4 | PASS |
| DH5 | Ant1 | Hop | 2.884 | 106.67 | 0.308 | ≤0.4 | PASS |
| 2DH1 | Ant1 | Hop | 0.386 | 320 | 0.124 | ≤0.4 | PASS |
| 2DH3 | Ant1 | Hop | 1.639 | 160 | 0.262 | ≤0.4 | PASS |
| 2DH5 | Ant1 | Hop | 2.887 | 106.67 | 0.308 | ≤0.4 | PASS |
| 3DH1 | Ant1 | Hop | 0.386 | 320 | 0.124 | ≤0.4 | PASS |
| 3DH3 | Ant1 | Hop | 1.639 | 160 | 0.262 | ≤0.4 | PASS |
| 3DH5 | Ant1 | Hop | 2.885 | 106.67 | 0.308 | ≤0.4 | PASS |

Test Graphs







2DH1-Ant1-Hop




2DH3-Ant1-Hop




2DH5-Ant1-Hop



3DH1-Ant1-Hop



3DH3-Ant1-Hop



3DH5-Ant1-Hop

Number of hopping channels**Test Result**

| TestMode | Antenna | Frequency[MHz] | Result[Num] | Limit[Num] | Verdict |
|----------|---------|----------------|-------------|------------|---------|
| DH5 | Ant1 | Hop | 79 | ≥15 | PASS |
| 2DH5 | Ant1 | Hop | 79 | ≥15 | PASS |
| 3DH5 | Ant1 | Hop | 79 | ≥15 | PASS |

Test Graphs




Band edge measurements


Test Result

| TestMode | Antenna | ChName | Frequency[MHz] | RefLevel [dBm] | Result [dBm] | Limit [dBm] | Verdict |
|----------|---------|--------|----------------|----------------|--------------|-------------|---------|
| DH5 | Ant1 | Low | 2402 | 5.11 | -48.47 | ≤-14.9 | PASS |
| DH5 | Ant1 | High | 2480 | 3.17 | -47.28 | ≤-16.84 | PASS |
| DH5 | Ant1 | Low | Hop_2402 | 3.95 | -49.1 | ≤-16.05 | PASS |
| DH5 | Ant1 | High | Hop_2480 | 2.93 | -48.88 | ≤-17.07 | PASS |
| 2DH5 | Ant1 | Low | 2402 | 3.15 | -48.57 | ≤-16.85 | PASS |
| 2DH5 | Ant1 | High | 2480 | 2.17 | -48.74 | ≤-17.83 | PASS |
| 2DH5 | Ant1 | Low | Hop_2402 | 1.04 | -49.61 | ≤-18.96 | PASS |
| 2DH5 | Ant1 | High | Hop_2480 | 2.59 | -48.46 | ≤-17.41 | PASS |
| 3DH5 | Ant1 | Low | 2402 | 3.68 | -48.79 | ≤-16.32 | PASS |
| 3DH5 | Ant1 | High | 2480 | 2.76 | -48.6 | ≤-17.24 | PASS |
| 3DH5 | Ant1 | Low | Hop_2402 | 0.82 | -49.1 | ≤-19.18 | PASS |
| 3DH5 | Ant1 | High | Hop_2480 | 1.82 | -48.75 | ≤-18.18 | PASS |


Test Graphs




DH5-Ant1-2402




DH5-Ant1-2480




DH5-Ant1-Hop_2402




DH5-Ant1-Hop_2480




2DH5-Ant1-2402




2DH5-Ant1-2480




2DH5-Ant1-Hop_2402




2DH5-Ant1-Hop_2480




3DH5-Ant1-2402



3DH5-Ant1-2480



3DH5-Ant1-Hop_2402




3DH5-Ant1-Hop_2480

Conducted Spurious Emission Test Result


| TestMode | Antenna | Frequency[MHz] | FreqRange [MHz] | RefLevel [dBm] | Result [dBm] | Limit [dBm] | Verdict |
|----------|---------|----------------|-----------------|----------------|--------------|-------------|---------|
| DH5 | Ant1 | 2402 | 0~Reference | 4.70 | 4.70 | --- | PASS |
| DH5 | Ant1 | 2402 | 30~1000 | 4.70 | -61.14 | ≤-15.3 | PASS |
| DH5 | Ant1 | 2402 | 1000~26500 | 4.70 | -52.57 | ≤-15.3 | PASS |
| DH5 | Ant1 | 2441 | 0~Reference | 4.74 | 4.74 | --- | PASS |
| DH5 | Ant1 | 2441 | 30~1000 | 4.74 | -60.29 | ≤-15.26 | PASS |
| DH5 | Ant1 | 2441 | 1000~26500 | 4.74 | -52.61 | ≤-15.26 | PASS |
| DH5 | Ant1 | 2480 | 0~Reference | 3.52 | 3.52 | --- | PASS |
| DH5 | Ant1 | 2480 | 30~1000 | 3.52 | -60.76 | ≤-16.48 | PASS |
| DH5 | Ant1 | 2480 | 1000~26500 | 3.52 | -52.65 | ≤-16.48 | PASS |
| 2DH5 | Ant1 | 2402 | 0~Reference | 2.13 | 2.13 | --- | PASS |
| 2DH5 | Ant1 | 2402 | 30~1000 | 2.13 | -60.99 | ≤-17.87 | PASS |
| 2DH5 | Ant1 | 2402 | 1000~26500 | 2.13 | -50.82 | ≤-17.87 | PASS |
| 2DH5 | Ant1 | 2441 | 0~Reference | 3.37 | 3.37 | --- | PASS |
| 2DH5 | Ant1 | 2441 | 30~1000 | 3.37 | -60.72 | ≤-16.63 | PASS |
| 2DH5 | Ant1 | 2441 | 1000~26500 | 3.37 | -53.16 | ≤-16.63 | PASS |
| 2DH5 | Ant1 | 2480 | 0~Reference | 2.14 | 2.14 | --- | PASS |
| 2DH5 | Ant1 | 2480 | 30~1000 | 2.14 | -61.03 | ≤-17.86 | PASS |
| 2DH5 | Ant1 | 2480 | 1000~26500 | 2.14 | -52.38 | ≤-17.86 | PASS |
| 3DH5 | Ant1 | 2402 | 0~Reference | 2.81 | 2.81 | --- | PASS |
| 3DH5 | Ant1 | 2402 | 30~1000 | 2.81 | -60.5 | ≤-17.19 | PASS |
| 3DH5 | Ant1 | 2402 | 1000~26500 | 2.81 | -52.13 | ≤-17.19 | PASS |
| 3DH5 | Ant1 | 2441 | 0~Reference | 3.31 | 3.31 | --- | PASS |
| 3DH5 | Ant1 | 2441 | 30~1000 | 3.31 | -61.25 | ≤-16.69 | PASS |
| 3DH5 | Ant1 | 2441 | 1000~26500 | 3.31 | -52.98 | ≤-16.69 | PASS |
| 3DH5 | Ant1 | 2480 | 0~Reference | 0.98 | 0.98 | --- | PASS |
| 3DH5 | Ant1 | 2480 | 30~1000 | 0.98 | -61.57 | ≤-19.02 | PASS |
| 3DH5 | Ant1 | 2480 | 1000~26500 | 0.98 | -52.36 | ≤-19.02 | PASS |

Test Graphs






DH5-Ant1-2441-0~Reference



DH5-Ant1-2441-30~1000



DH5-Ant1-2441-1000~26500