

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 1 of 13

RF EXPOSURE EVALUATION REPORT

Application No.:	SZCR2302000478AT
Applicant:	Harman International Industries, Inc.
Address of Applicant:	8500 Balboa Boulevard, Northridge, California, 91329, United States
Manufacturer:	Harman International Industries, Inc.
Address of Manufacturer:	8500 Balboa Boulevard, Northridge, California, 91329, United States
Equipment Under Test (EUT):
EUT Name:	Wireless Speaker
Model No.:	Authentics 300
Trade Mark:	JBL
FCC ID:	APIAUTH300
Standard(s) :	FCC Rules 47 CFR §2.1091
	KDB 447498 D04 interim General RF Exposure Guidance v01
Date of Receipt:	2023-02-24
Date of Evaluation:	2023-03-23 to 2023-05-04
Date of Issue:	2023-05-12
Evaluation Result:	Pass*

* In the configuration evaluated, the EUT complied with the standards specified above.

Keny. XN

Keny Xu EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions of Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-to-Terms-end-to-T

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 2 of 13

	Revision Record							
Version Chapter Date Modifier Rema								
01		2023-05-12		Original				

Authorized for issue by:		
	Charle Doi	
	Charlie Dai/Project Engineer	
	Eric Fu	
	Eric Fu/Reviewer	



 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China
 518057
 t
 (86–755) 26012053
 f
 g
 www.sgsgroup.com.cn

 中国 • 深圳• 科技國中区M-10栋一号厂房
 邮编: 518057
 t
 (86–755) 26012053
 f
 (86–755) 26012053
 g
 sgs.com



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 3 of 13

2 Contents

		Paç	je
1	Cove	er Page	. 1
2	Con	tents	. 3
3	Gen	eral Information	. 4
	3.1	General Description of E.U.T.	. 4
	3.2	Details of E.U.T.	. 4
	3.3	Separation Distance	
	3.4	Test Location	. 6
	3.5	Test Facility	. 6
	3.6	Deviation from Standards	
	3.7	Abnormalities from Standard Conditions	. 6
4	FCC	Radiofrequency radiation exposure limits	. 7
	4.1	Blanket 1 mW Blanket Exemption	. 7
	4.2	MPE-based Exemption	. 7
	4.3	SAR-based Exemption	. 8
5	Meas	surement and Calculation	11
	5.1	Maximum transmit power	11
	5.2	RF Exposure Calculation	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exoncrate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) is test dand such sample(s) is retained to 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN_Doccheck@sgs.com

中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com Member of the SGS Group (SGS SA)



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 4 of 13

3 General Information

3.1 General Description of E.U.T.

Product Type:	Portable device
	⊠ Mobile device
	Fixed device

3.2 Details of E.U.T.

3.2 Details of E.U.T.	
Power supply:	Lithium-ion rechargeable battery (DC 3.6V 4800mAh) which can be charged from AC port.
	AC 100-240V 50/60Hz
Cable(s):	AC cable 210cm unshielded without ferrite core
For BT:	
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.3 Dual mode
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Spectrum Spread Technology:	Frequency Hopping Spread Spectrum(FHSS)
Antenna Type:	FPC Antenna
Antenna Gain:	2.04dBi
For BLE:	
Operation Frequency:	2402MHz to 2480MHz
Bluetooth Version:	V5.3 Dual mode
Modulation Type:	GFSK
Data Rate:	1Mbps, 2Mbps
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.04dBi
For 2.4G WIFI	
Operation Frequency	802.11b/g/n(HT20)/ax(HEW20): 2412MHz to 2462MHz;
Operation Frequency:	802.11n(HT40)/ax(HEW40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK); 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK); 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Number of Channels:	802.11b/g/n(HT20)/ax(HEW20):11;
	802.11n(HT40)/ax(HEW40):7



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of fhis document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is subawin this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 5180 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 5180

邮编: 518057 t (86-755)26012053 f (86-755)26710594 sgs.china@sgs.com Member of the SGS Group (SGS SA)



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 5 of 13

Channel Spacing:	5MHz
Antenna Type:	FPC Antenna
Antenna Gain:	Antenna 1: 3.9dBi, Antenna 2: 2.94dBi
	Directional gain: 6.44dBi
For 5G WIFI	
Operation Frequency/Number of channels (20MHz):	U-NII-1: 5180-5240MHz (4 Channels); U-NII-2A: 5260-5320MHz (4 Channels); U-NII-2C: 5500-5700MHz (11 Channels); U-NII-3: 5745- 5825MHz (5 Channels)
Operation Frequency/Number of channels/(40MHz):	U-NII-1: 5190-5230MHz (2 Channels); U-NII-2A: 5270-5310MHz (2 Channels); U-NII-2C: 5510-5670MHz (5 Channels); U-NII-3: 5755-5795MHz (2 Channels)
Operation Frequency/Number of channels (80MHz):	U-NII-1: 5210MHz (1 Channel); U-NII-2A: 5290MHz (1 Channels); U-NII-2C: 5530-5610MHz (2 Channels); U-NII-3: 5775MHz (1 Channel)
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 64QAM, 256QAM); 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Channel Spacing:	802.11a/n(HT20)/ac(VHT20)/ax(HEW20): 20MHz; 802.11n(HT40)/ac(VHT40)/ax(HEW40): 40MHz;
	802.11ac(VHT80)/ax(HEW80): 80MHz
DFS Function:	Slave without Radar detection
TPC Function:	Support TPC function
Antenna Type:	FPC Antenna
Antenna Gain:	Antenna 1: 3.16dBi, Antenna 2: 3.78dBi Directional gain: 6.49dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

3.3 Separation Distance

•					
Minimum test separation distance:	20cm				
Remark: This minimum test separation distance is determined by the smallest distance from the antenna and					
radiating structures or outer surface of the device, according to the host form factor, exposure conditions and					
platform requirements, to any part of the	body or extremity of a user or bystander.				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excenerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheek@ass.com

 No.1 Workshop.M-10, Middle Section, Science & Technology Park, Shenzhen, China
 518057
 t
 (86-755) 26012053
 f
 g
 www.sgsgroup.com.cn

 中国 · 深圳 · 科技國中区M-10栋一号厂房
 邮编: 518057
 t
 (86-755) 26012053
 f
 (86-755) 26012053
 g
 sg.cc
 sg.cc
 sg.cc
 t
 (86-755) 26012053
 f
 sg.cc
 sg.cc



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 6 of 13

3.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594 No tests were sub-contracted.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC – Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

3.6 Deviation from Standards

None

3.7 Abnormalities from Standard Conditions None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-end-Cond

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 ·深圳 · 科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.com



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 7 of 13

4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

RF Source Frequency		Minimum Distance			Threshold ERP		
<i>f</i> ∟ MHz		<i>f</i> ⊦ MHz	λ∟ / 2π	λ _L / 2π λ _H / 2π		W	
0.3	_	1.34	159 m	-	35.6 m	1,920 R ²	
1.34	_	30	35.6 m	-	1.6 m	3,450 R²/f ²	
30	-	300	1.6 m	_	159 mm	3.83 R ²	
300	_	1,500	159 mm –		31.8 mm	0.0128 R ² f	
1,500 – 100,000 31.8 mm – 0.5 mm 19.2R							
Subscripts L and H are low and high; λ is wavelength.							

Table B.1—Thresholds For Single RF Sources	Subject to Routine Environmental Evaluation
Table D.I—Thesholds For Single RF Sources	

From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction form exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@gs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-/55) 26012053 t (86-/55) 26/10594 中国 • 深圳 • 科技园中区M-10栋一号厂房 邮编: 518057 t (86-/55) 26012053 f (86-/55) 26710594



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 8 of 13

based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of \$1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in \$1.1310 is necessary if the ERP of the device is greater than *ERP*_{20cm} in Formula (B.1) [repeated from \$2.1091(c)(1); also in \$1.1307(b)(1)(i)(B)].

$$P_{\rm th} (\rm mW) = ERP_{20 \rm \ cm} (\rm mW) = \begin{cases} 2040f & 0.3 \rm \ GHz \le f < 1.5 \rm \ GHz \\ 3060 & 1.5 \rm \ GHz \le f \le 6 \rm \ GHz \end{cases}$$
(B.1)

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation								
Frequency rangeFrequency(MHz) $R(\lambda/2\pi)(m)$ Threshold ERP(W)								
300~1500MHz	915	0.0522	0.032					
1500~100000MHz	2480	0.0193	0.007					

4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions?Terms-e-Document.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issued by the termin. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonert parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisfication of the content or appearance of this document is and offenders may be prosecuted to the fullest extent of the aw. Unless otherwise stated the results shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: <u>CN.Doccheck@sgs.com</u> No.! Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn 中国 · 深圳 · 科技图中区M-10核一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.com



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 9 of 13

The SAR-based exemption formula of (1.1307(b)(3)(i)(B)), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{\rm th} \,({\rm mW}) = \begin{cases} ERP_{20\,\rm cm} (d/20\,\rm cm)^x & d \le 20\,\rm cm \\ \\ ERP_{20\,\rm cm} & 20\,\rm cm < d \le 40\,\rm cm \end{cases}$$
(B.2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\operatorname{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP_{20cm} is per Formula (B.1).



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of tils intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not excore the reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forger or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ess.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国 · 深圳 · 科技园中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594 sgs.cohina@sgs.com



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 10 of 13

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)										
Frequency		Distance(mm)								
(MHz)	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Limit calculation				
Frequency range(GHz)	Frequency(GHz)	Х	Distance(cm)	Pth (mW)
0.3~1.5	0.915	1.474	0.5	8.133
1.5~6	2.48	1.905	0.5	2.717



 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China
 518057
 t
 (86–755) 26012053
 f
 g
 www.sgsgroup.com.cn

 中国 • 深圳• 科技國中区M-10栋一号厂房
 邮编: 518057
 t
 (86–755) 26012053
 f
 (86–755) 26012053
 g
 sgs.com



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 11 of 13

5 **Measurement and Calculation**

Maximum transmit power 5.1

For BT/BLE:

The Power Data is based on the RF Test Report SZCR230200047802 & SZCR230200047803.

Antenna Gain: 2.04dBi

Output Power Into Antenna & RF Exposure Evaluation Distance

Frequency	Maximum EIRP [dBm]	Maximum EIRP (mW)
2402	14.38	27.42

For 2.4G WIFI:

The Power Data is based on the RF Test Report SZCR230200047804.

Antenna Gain: Antenna 1: 3.9dBi, Antenna 2: 2.94dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency	Maximum EIRP [dBm]	Maximum EIRP (mW)
2462	22.51	178.24

For 5G WIFI:

The Power Data is based on the RF Test Report SZCR230200047805.

Antenna Gain: Antenna 1: 3.16dBi, Antenna 2: 3.78dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency	Maximum Conducted Power/EIRP [dBm]	Maximum Conducted Power/EIRP (mW)	
5180	21.49	140.93	

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.forms-enDocument.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or rappearance of this document is stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone; (86-755) 8307 1443. e: (86-755) 8307 1443

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn 中国・深圳・科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 12 of 13

5.2 RF Exposure Calculation

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

For BT/BLE:

The Max EIRP is 27.42mW. The best case gain of the antenna is 2.04dBi.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
\boxtimes	SAR-based Exemption(<i>P</i> th)	3060	Yes

For 2.4G WIFI:

The Max EIRP is 178.24mW. The best case gain of the antenna is Antenna 1: 3.9dBi, Antenna 2: 2.94dBi.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
\boxtimes	SAR-based Exemption(P_{th})	3060	Yes

For 5G WIFI:

The Max EIRP is 140.93mW. The best case gain of the antenna is Antenna 1: 3.16dBi, Antenna 2: 3.78dBi.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
\boxtimes	SAR-based Exemption(Pth)	3060	Yes

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content of the Content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) testing and use and sole accessing (sections context) and unterticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: <u>CN.Doccheck@ass.com</u> (Mol Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn

no.1 workshop, M-10, Modie Securit, Science & recimionogy Park, Science and Halizieri, Julia 518057 (66–755) 26012053 f (66–755) 26710594 中国・深圳・科技园中区M-10栋一号厂房 邮编: 518057 t (86–755) 26012053 f (86–755) 26710594

Member of the SGS Group (SGS SA)



SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230200047805 Page: 13 of 13

Exposure condition for simultaneous transmission operations

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluatedk term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^{a} \frac{P_i}{P_{\text{th},i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{\text{th},j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$
(C.1)

Remark:

a -number of fixed, mobile, or portable RF sources claiming exemption using the §1.1307(b)(3)(i)(B) formula for Pth, including existing exempt transmitters and those being added.

b -number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.

c -number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.

Pi -the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i -the exemption threshold power (Pth) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i.

ERPj -the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j. ERPth,j -exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$, according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.

 $Evaluated_k$ -the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation.

Exposure Limit_k -either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable

The Max. sum of the ratios = 27.42mW/3060mW + 178.24mW/3060mW = 0.0672< 1

中国·深圳·科技园中区M-10栋一号厂房

Therefore, the device is to qualify for simultaneous transmission SAR test exemption, the exemption report is in lieu of the SAR report.

--End of the Report--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is enterviewed of the Content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ass.com

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594

Member of the SGS Group (SGS SA)