

FCC AND ISED CERTIFICATION TEST REPORT

FOR

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Multi-Channel Soundbar with wireless subwoofer
Model No.	:	BAR 800
Trade Mark	:	JBL
FCC ID	:	APIBAR800
IC	:	6132A-BAR800
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	4
1.	Summary of Test Results.....	6
2.	General Test Information	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT.....	9
2.3.	Assistant equipment used for test.....	9
2.4.	Block diagram of EUT configuration for test	9
2.5.	Deviations of test standard.....	10
2.6.	Test environment conditions	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty.....	11
3.	Equipment Used During Test.....	12
4.	6dB Bandwidth and 99% Bandwidth.....	14
4.1.	Block diagram of test setup.....	14
4.2.	Limits	14
4.3.	Test procedure	14
4.4.	Test result.....	15
4.5.	Original test data	18
5.	Conducted Peak Output Power	65
5.1.	Block diagram of test setup.....	65
5.2.	Limits	65
5.3.	Test procedure	65
5.4.	Test result.....	65
6.	Power Spectral Density.....	70
6.1.	Block diagram of test setup.....	70
6.2.	Limits	70
6.3.	Test procedure	70
6.4.	Test result.....	70
6.5.	Original test data	74
7.	Band Edge Compliance (Conducted Method)	109
7.1.	Block diagram of test setup.....	109
7.2.	Limits	109
7.3.	Test procedure	109
7.4.	Test result.....	110
7.5.	Original test data	110
8.	Radiated Spurious Emissions.....	119
8.1.	Block diagram of test setup.....	119

8.2.	Limit	120
8.3.	Test procedure	122
8.4.	Test result.....	123
9.	RF Conducted Spurious Emissions	156
9.1.	Block diagram of test setup.....	156
9.2.	Limits	156
9.3.	Test procedure	156
9.4.	Test result.....	157
9.5.	Original test data	157
10.	Radiated Band Edge Compliance.....	194
10.1.	Block diagram of test setup.....	194
10.2.	Limit.....	194
10.3.	Test procedure	194
10.4.	Test result.....	194
11.	Power Line Conducted Emission	235
11.1.	Block diagram of test setup.....	235
11.2.	Power Line Conducted Emission Limits (Class B)	235
11.3.	Test procedure	235
11.4.	Test result.....	236
12.	Antenna Requirements	239
12.1.	Limit.....	239
12.2.	Result	239
13.	Test Setup Photograph	240
14.	Photos of the EUT	242

Test Report Declare

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Multi-Channel Soundbar with wireless subwoofer
Model No	:	BAR 800
Trade Mark	:	JBL
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

Test procedure used: ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018, 558074 D01 15.247 Meas Guidance v05r02, 662911 D01 Multiple Transmitter Output v02r01

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&ISED standards.

Report No:	DDT-R21123117-2E04		
Date of Receipt:	Feb. 18, 2022	Date of Test:	Feb. 18, 2022 ~ Jun. 23, 2022

Prepared By:

Johnny Wang

Johnny Wang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jun. 24, 2022	

1. Summary of Test Results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	Standard	Results
6dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2	Pass
Conducted Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2	Pass
Power Spectral Density	FCC Part 15:15.247 ANSI C63.10:2013 RSS-247 Issue 2	Pass
Band-edge and Spurious Emissions (Conducted)	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	Pass
Radiated Spurious Emissions	FCC Part 15: 15.247 ANSI C63.10:2013 RSS-247 Issue 2 RSS-Gen Issue 5	Pass
Radiated Band Edge Compliance	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 RSS-247 Issue 2 RSS-Gen Issue 5	Pass
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2013 RSS-Gen Issue 5	Pass
Antenna requirement	FCC Part 15: 15.203 RSS-Gen Issue 5	Pass
Note: This product has two audio power amplifier ICs (TAS5825M and TAS5825P). All items are tested on TAS5825M. According to the test results of TAS5825M, TAS5825P only the Radiation Emission (below 1 GHz) tested.		

2. General Test Information

2.1. Description of EUT

EUT* Name	: Multi-Channel Soundbar with wireless subwoofer
Model Number	: BAR 800
EUT function description	: Please reference user manual of this device
Power supply	: AC 100-240V-50/60Hz 70W
Radio Technology	: IEEE 802.11b/g/n/ax
Operation frequency	: IEEE 802.11b: 2412MHz-2462MHz IEEE 802.11g: 2412MHz-2462MHz IEEE 802.11n HT20: 2412MHz-2462MHz IEEE 802.11n HT40: 2422MHz-2452MHz IEEE 802.11ax HE20: 2412MHz-2462MHz IEEE 802.11ax HE40: 2422MHz-2452MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax HE20, HE40: OFDM (1024QAM, 64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: IEEE 802.11b: up to 11 Mbps IEEE 802.11g: up to 54 Mbps IEEE 802.11n HT20, HT40: up to 130 Mbps IEEE 802.11ax HE20, HE40: up to 573.5 Mbps
Antenna Type	: Antenna 1: FPC antenna, Maximum PK gain: 2.17 dBi Antenna 2: FPC antenna, Maximum PK gain: 2.64 dBi
Sample Type	: Series production
Sample Number	: S21123117-02 for conductive S21123117-03 for radiation

Note: EUT is the ab. of equipment under test.

Antenna information			
	Ant1 gain	Ant2 gain	MIMO
IEEE 802.11b	2.17	2.64	/
IEEE 802.11g	2.17	2.64	/
IEEE 802.11n HT20	2.17	2.64	5.42
IEEE 802.11n HT40	2.17	2.64	5.42
IEEE 802.11ax HE20	2.17	2.64	5.42
IEEE 802.11ax HE40	2.17	2.64	5.42

Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

IEEE 802.11ax(HE20)	Operating Mode	Resource Unit	26 Tone(2M)		
	Specific Resource Unit		0		
			1		
			2		
			3		
			4		
			5		
			6		
			7		
			8		
		9			
		Resource Unit	52 Tone(4M)		
	Specific Resource Unit		37		
			38		
			39		
			40		
	Resource Unit	106 Tone(8M)			
Specific Resource Unit		53			
		54			
	Resource Unit	242 Tone(20M)			
	Specific Resource Unit	61			
Operating Mode	Resource Unit	26 Tone(2M)			
IEEE 802.11ax(HE40)	Specific Resource Unit		0	9	
			1	10	
			2	11	
			3	12	
			4	13	
			5	14	
			6	15	
			7	16	
			8	17	
		Resource Unit	52 Tone(4M)		
	Specific Resource Unit		37	41	
			38	42	
			39	43	
			40	44	
		Resource Unit	106 Tone(8M)		
	Specific Resource Unit		53	55	
		54	56		
	Resource Unit	242 Tone(20M)			
	Specific Resource Unit	61	62		
	Resource Unit	484 Tone(40M)			
	Specific Resource Unit	65			

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Description	Other
AC cable	Harman	N/A	N/A	Length: 1.85m,
HDMI cable	Harman	N/A	N/A	Length: 1.17m, with two magnetic rings
Remote control	Harman	N/A	N/A	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
N/A	N/A	N/A	N/A	N/A

2.4. Block diagram of EUT configuration for test



The test software was used to control EUT work in Continuous Tx mode and select test channel, wireless mode as below table.

Test software: adb.exe

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, channel, and data rate information				
Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	12	1	LCH: CH1	2412
	12	1	MCH: CH6	2437
	12	1	HCH: CH11	2462
IEEE 802.11g	11	6	LCH: CH1	2412
	11	6	MCH: CH6	2437
	11	6	HCH: CH11	2462
IEEE 802.11n HT20	11	MCS 0	LCH: CH1	2412
	11	MCS 0	MCH: CH6	2437
	11	MCS 0	HCH: CH11	2462
IEEE 802.11n HT40	11	MCS 0	LCH: CH3	2422
	11	MCS 0	MCH: CH6	2437
	11	MCS 0	HCH: CH9	2452
IEEE 802.11ax HE20	SU:13 RU:15	MCS 0	LCH: CH1	2412
	SU:13 RU:15	MCS 0	MCH: CH6	2437
	SU:13 RU:15	MCS 0	HCH: CH11	2462
IEEE 802.11ax HE40	SU:13 RU:15	MCS 0	LCH: CH3	2422
	SU:13 RU:15	MCS 0	MCH: CH6	2437
	SU:13 RU:15	MCS 0	HCH: CH9	2452

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

2.5. Deviations of test standard

No Deviation

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 × 10 ⁻⁸ (Antenna couple method)
	5.5 × 10 ⁻⁸ (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.40 dB (3.6 GHz ≤ f < 8 GHz)
	1.66 dB (8 GHz ≤ f < 22 GHz)
Uncertainty for radio frequency (RBW < 20 kHz)	3 × 10 ⁻⁸
Temperature	0.4 °C
Humidity	2%
Uncertainty for Radiation Emission test (30 MHz-1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz-40 GHz)	4.10 dB (1-6 GHz)
	4.40 dB (6 GHz-18 GHz)
	3.54 dB (18 GHz-26 GHz)
	4.30 dB (26 GHz-40 GHz)
Uncertainty for Power line conduction emission test	3.32 dB (150 kHz-30 MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	


3. Equipment Used During Test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
☑RF Connected Test (Tonscend RF Measurement System 1#)					
Spectrum analyzer	R&S	FSU26	200071	Sep. 02, 2021	1 Year
Wideband Radio Communication tester	R&S	CMW500	120259	Sep. 02, 2021	1 Year
MXG Vector Signal Generator	Agilent	N5182B	MY59100192	Jun. 01, 2021	1 Year
MXG Vector Signal Generator	Agilent	N5182B	MY59100192	May 18, 2022	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Sep. 18, 2021	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 01, 2021	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	May 18, 2022	1 Year
RF Control Unit	Tonsend	JS0806-2	158060010	Jun. 01, 2021	1 Year
RF Control Unit	Tonsend	JS0806-2	158060010	May 18, 2022	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Jun. 01, 2021	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	May 26, 2022	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.6.77.0518	N/A	N/A
☑Radiation 3#chamber					
EMI Test Receiver	R&S	ESU	100472	Jun. 01, 2021	1 Year
EMI Test Receiver	R&S	ESU	100472	May 18, 2022	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 01, 2021	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	May 18, 2022	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Sep. 19, 2021	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	01429	Aug. 07, 2021	1 Year
Double Ridged Horn Antenna	Schwarzbeck	BBHA9120	02108	Jul. 17, 2021	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	May 08, 2021	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	May 06, 2022	1 Year
Pre-amplifier	COM-POWER	PAM-118A	18040084	Sep. 02, 2021	1 Year
Pre-amplifier	COM-POWER	PAM-840A	461369	Mar. 15, 2021	1 Year
Pre-amplifier	COM-POWER	PAM-840A	461369	Apr. 11, 2022	1 Year
Test software	Audix	E3	V 6.1.1.1	N/A	N/A
☑Power Line Conducted Emissions Test 1#					
Test Receiver	R&S	ESCI	100551	Sep. 02, 2021	1 Year
LISN 1	R&S	ENV216	101109	Sep. 02, 2021	1 Year
LISN 2	R&S	ESH2-Z5	100309	Sep. 02, 2021	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Sep. 02, 2021	1 Year

CE Cable 1	HUBSER	N/A	W10.01	Sep. 02, 2021	1 Year
LISN 3	SCHWARZBECK	NSLK 8163	00017	Sep. 02, 2021	1 Year

4. 6dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) 99% Bandwidth set the spectrum analyzer as follows:

RBW:	300 kHz
VBW:	1 MHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) 6dB Bandwidth set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(4) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.4. Test result

Test Mode	Test	Ant	6dB Bandwidth [MHz]	Limit [MHz]	Verdict
11B	2412	Ant1	8.08	0.5	Pass
11B	2412	Ant2	8.08	0.5	Pass
11B	2437	Ant1	8.08	0.5	Pass
11B	2437	Ant2	8.00	0.5	Pass
11B	2462	Ant1	7.12	0.5	Pass
11B	2462	Ant2	7.12	0.5	Pass
11G	2412	Ant1	15.12	0.5	Pass
11G	2412	Ant2	15.12	0.5	Pass
11G	2437	Ant1	15.48	0.5	Pass
11G	2437	Ant2	15.12	0.5	Pass
11G	2462	Ant1	15.84	0.5	Pass
11G	2462	Ant2	15.44	0.5	Pass
11N20MIMO	2412	Ant1	15.12	0.5	Pass
11N20MIMO	2412	Ant2	16.32	0.5	Pass
11N20MIMO	2437	Ant1	15.80	0.5	Pass
11N20MIMO	2437	Ant2	16.56	0.5	Pass
11N20MIMO	2462	Ant1	15.32	0.5	Pass
11N20MIMO	2462	Ant2	16.92	0.5	Pass
11N40MIMO	2422	Ant1	35.20	0.5	Pass
11N40MIMO	2422	Ant2	35.12	0.5	Pass
11N40MIMO	2437	Ant1	35.12	0.5	Pass
11N40MIMO	2437	Ant2	35.12	0.5	Pass
11N40MIMO	2452	Ant1	35.20	0.5	Pass
11N40MIMO	2452	Ant2	35.04	0.5	Pass
11AX20SU	2412	Ant1	17.80	0.5	Pass
11AX20SU	2412	Ant2	17.76	0.5	Pass
11AX20SU	2437	Ant1	18.44	0.5	Pass
11AX20SU	2437	Ant2	18.64	0.5	Pass
11AX20SU	2462	Ant1	18.68	0.5	Pass
11AX20SU	2462	Ant2	18.60	0.5	Pass
11AX40SU	2422	Ant1	36.08	0.5	Pass
11AX40SU	2422	Ant2	36.72	0.5	Pass
11AX40SU	2437	Ant1	35.76	0.5	Pass
11AX40SU	2437	Ant2	35.20	0.5	Pass
11AX40SU	2452	Ant1	37.28	0.5	Pass
11AX40SU	2452	Ant2	36.56	0.5	Pass

Test Mode	Antenna	Channel	Ru Size	Ru Index	DTS BW [MHz]	Limit [MHz]	Verdict
11AX20MIMO	Ant1	2412	26Tone	RU0	2.08	0.5	PASS
				RU4	2.64	0.5	PASS
				RU8	2.04	0.5	PASS
			52Tone	RU37	17.04	0.5	PASS
				RU38	13.80	0.5	PASS
				RU39	4.04	0.5	PASS
			106Tone	RU40	15.80	0.5	PASS
				RU53	17.12	0.5	PASS
				RU54	17.08	0.5	PASS
	Ant2	2412	26Tone	RU0	2.12	0.5	PASS
				RU4	2.64	0.5	PASS
				RU8	2.08	0.5	PASS
			52Tone	RU37	17.04	0.5	PASS
				RU38	15.04	0.5	PASS
				RU39	15.04	0.5	PASS
			106Tone	RU40	17.04	0.5	PASS
				RU53	17.12	0.5	PASS
				RU54	17.12	0.5	PASS
	Ant1	2437	26Tone	RU0	2.12	0.5	PASS
				RU4	2.64	0.5	PASS
				RU8	2.12	0.5	PASS
			52Tone	RU37	17.08	0.5	PASS
				RU38	11.28	0.5	PASS
				RU39	13.80	0.5	PASS
			106Tone	RU40	4.08	0.5	PASS
				RU53	17.12	0.5	PASS
				RU54	17.12	0.5	PASS
	Ant2	2437	26Tone	RU0	2.08	0.5	PASS
				RU4	2.64	0.5	PASS
				RU8	2.12	0.5	PASS
			52Tone	RU37	17.08	0.5	PASS
				RU38	13.80	0.5	PASS
				RU39	13.80	0.5	PASS
			106Tone	RU40	17.08	0.5	PASS
				RU53	17.12	0.5	PASS
				RU54	17.16	0.5	PASS
Ant1	2462	26Tone	RU0	2.08	0.5	PASS	
			RU4	2.68	0.5	PASS	
			RU8	2.08	0.5	PASS	
		52Tone	RU37	17.04	0.5	PASS	
			RU38	15.08	0.5	PASS	
			RU39	13.84	0.5	PASS	
		106Tone	RU40	15.84	0.5	PASS	
			RU53	17.12	0.5	PASS	
			RU54	17.12	0.5	PASS	
Ant2	2462	26Tone	RU0	2.08	0.5	PASS	
			RU4	2.68	0.5	PASS	
			RU8	2.08	0.5	PASS	

			52Tone	RU37	17.08	0.5	PASS	
				RU38	15.04	0.5	PASS	
				RU39	13.84	0.5	PASS	
				RU40	15.84	0.5	PASS	
	11AX40MIMO	Ant1	2422	242Tone	RU53	17.16	0.5	PASS
					RU54	17.16	0.5	PASS
		Ant2	2422	242Tone	RU61	18.80	0.5	PASS
					RU62	18.80	0.5	PASS
		Ant1	2437	242Tone	RU61	18.80	0.5	PASS
					RU62	18.80	0.5	PASS
Ant2	2437	242Tone	RU61	18.80	0.5	PASS		
			RU62	18.80	0.5	PASS		
Ant1	2452	242Tone	RU61	18.80	0.5	PASS		
			RU62	18.80	0.5	PASS		
Ant2	2452	242Tone	RU61	18.80	0.5	PASS		
			RU62	18.80	0.5	PASS		


Test Mode	Test	Ant	99% OBW [MHz]	Limit [MHz]	Verdict
11B	2412	Ant1	13.37	---	Pass
11B	2412	Ant2	13.22	---	Pass
11B	2437	Ant1	13.57	---	Pass
11B	2437	Ant2	13.40	---	Pass
11B	2462	Ant1	13.48	---	Pass
11B	2462	Ant2	13.46	---	Pass
11G	2412	Ant1	17.27	---	Pass
11G	2412	Ant2	17.27	---	Pass
11G	2437	Ant1	19.49	---	Pass
11G	2437	Ant2	19.52	---	Pass
11G	2462	Ant1	19.48	---	Pass
11G	2462	Ant2	19.52	---	Pass
11N20MIMO	2412	Ant1	18.01	---	Pass
11N20MIMO	2412	Ant2	17.62	---	Pass
11N20MIMO	2437	Ant1	20.09	---	Pass
11N20MIMO	2437	Ant2	18.41	---	Pass
11N20MIMO	2462	Ant1	20.12	---	Pass
11N20MIMO	2462	Ant2	18.42	---	Pass
11N40MIMO	2422	Ant1	37.13	---	Pass
11N40MIMO	2422	Ant2	37.11	---	Pass
11N40MIMO	2437	Ant1	36.92	---	Pass
11N40MIMO	2437	Ant2	37.06	---	Pass
11N40MIMO	2452	Ant1	37.07	---	Pass


11N40MIMO	2452	Ant2	37.00	---	Pass
11AX20SU	2412	Ant1	18.86	---	Pass
11AX20SU	2412	Ant2	18.87	---	Pass
11AX20SU	2437	Ant1	19.26	---	Pass
11AX20SU	2437	Ant2	19.24	---	Pass
11AX20SU	2462	Ant1	19.41	---	Pass
11AX20SU	2462	Ant2	19.29	---	Pass
11AX40SU	2422	Ant1	37.72	---	Pass
11AX40SU	2422	Ant2	37.74	---	Pass
11AX40SU	2437	Ant1	37.68	---	Pass
11AX40SU	2437	Ant2	37.71	---	Pass
11AX40SU	2452	Ant1	37.76	---	Pass
11AX40SU	2452	Ant2	37.69	---	Pass

Note: according exploratory explorer test, for 802.11ax Mode, Specific Resource Unit have no distinct influence on 99% OBW, so for 99% OBW, the final test was only performed with EUT working in 802.11ax SU mode.


4.5. Original test data

6 dB bandwidth:







11B_Ant1_2437




11B_Ant2_2437




11B_Ant1_2462




11B_Ant2_2462




11G_Ant1_2412




11G_Ant2_2412




11G_Ant1_2437




11G_Ant2_2437




11G_Ant1_2462




11G_Ant2_2462




11N20MIMO_Ant1_2412




11N20MIMO_Ant2_2412




11N20MIMO_Ant1_2437




11N20MIMO_Ant2_2437




11N20MIMO_Ant1_2462




11N20MIMO_Ant2_2462




11N40MIMO_Ant1_2422




11N40MIMO_Ant2_2422




11N40MIMO_Ant1_2437




11N40MIMO_Ant2_2437




11N40MIMO_Ant1_2452




11N40MIMO_Ant2_2452




11AX20MIMO_Ant1_2412




11AX20MIMO_Ant2_2412




11AX20MIMO_Ant1_2437




11AX20MIMO_Ant2_2437




11AX20MIMO_Ant1_2462




11AX20MIMO_Ant2_2462




11AX40MIMO_Ant1_2422




11AX40MIMO_Ant2_2422




11AX40MIMO_Ant1_2437




11AX40MIMO_Ant2_2437




11AX40MIMO_Ant1_2452




11AX40MIMO_Ant2_2452




11AX20MIMO_Ant1_2412_26Tone_RU0




11AX20MIMO_Ant1_2412_26Tone_RU4




11AX20MIMO_Ant1_2412_26Tone_RU8




11AX20MIMO_Ant1_2412_52Tone_RU37




11AX20MIMO_Ant1_2412_52Tone_RU38




11AX20MIMO_Ant1_2412_52Tone_RU39




11AX20MIMO_Ant1_2412_52Tone_RU40




11AX20MIMO_Ant1_2412_106Tone_RU53




11AX20MIMO_Ant1_2412_106Tone_RU54




11AX20MIMO_Ant2_2412_26Tone_RU0




11AX20MIMO_Ant2_2412_26Tone_RU4




11AX20MIMO_Ant2_2412_26Tone_RU8




11AX20MIMO_Ant2_2412_52Tone_RU37




11AX20MIMO_Ant2_2412_52Tone_RU38




11AX20MIMO_Ant2_2412_52Tone_RU39




11AX20MIMO_Ant2_2412_52Tone_RU40




11AX20MIMO_Ant2_2412_106Tone_RU53




11AX20MIMO_Ant2_2412_106Tone_RU54




11AX20MIMO_Ant1_2437_26Tone_RU0




11AX20MIMO_Ant1_2437_26Tone_RU4




11AX20MIMO_Ant1_2437_26Tone_RU8




11AX20MIMO_Ant1_2437_52Tone_RU37




11AX20MIMO_Ant1_2437_52Tone_RU38




11AX20MIMO_Ant1_2437_52Tone_RU39




11AX20MIMO_Ant1_2437_52Tone_RU40




11AX20MIMO_Ant1_2437_106Tone_RU53




11AX20MIMO_Ant1_2437_106Tone_RU54




11AX20MIMO_Ant2_2437_26Tone_RU0




11AX20MIMO_Ant2_2437_26Tone_RU4




11AX20MIMO_Ant2_2437_26Tone_RU8




11AX20MIMO_Ant2_2437_52Tone_RU37




11AX20MIMO_Ant2_2437_52Tone_RU38




11AX20MIMO_Ant2_2437_52Tone_RU39




11AX20MIMO_Ant2_2437_52Tone_RU40




11AX20MIMO_Ant2_2437_106Tone_RU53



11AX20MIMO_Ant2_2437_106Tone_RU54



11AX20MIMO_Ant1_2462_26Tone_RU0



11AX20MIMO_Ant1_2462_26Tone_RU4