



■ Report No.: DDT-R20112017-1E11

■ Issued Date: Mar. 09, 2021

RF EXPOSURE REPORT

FOR

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Bluetooth Speaker
Model No.	:	PARTYBOX110
Trade Mark	:	JBL
FCC ID	:	APIBOX110
IC	:	6132A-BOX110
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan
City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	3
1.	General information.....	5
1.1.	Description of Equipment	5
1.2.	Assess laboratory	5
2.	RF Exposure evaluation	5
2.1.	Requirement.....	5
2.2.	Calculation Method.....	6
2.3.	Estimation Result.....	6

Test Report Declare

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Bluetooth Speaker
Model No.	:	PARTYBOX110
Trade mark	:	JBL
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R20112017-1E11		
Date of Receipt:	Feb. 07, 2021	Date of Test:	Feb. 07, 2021 ~ Mar. 09, 2021

Prepared By:

Talent Zhang

Talent Zhang/Engineer



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Mar. 09, 2021	

1. General information

1.1. Description of Equipment

EUT* Name	: Bluetooth Speaker
Model Number	: PARTYBOX110
EUT Function Description	: Please reference user manual of this device
Power Supply	: AC 100-240V, 50/60Hz built-in battery
Radio Specification	: Bluetooth V5.1
Operation Frequency	: 2402 MHz - 2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	: 1 Mbps, 2 Mbps, 3 Mbps
Antenna Type	: FPC antenna, maximum PK gain: 2.56 dBi
Serial Number	: GG1056-BL0000110 for conductive GG1056-BL0000118 for radiation by ICA002GA GG1056-BL0000109 for radiation by ICA002GA

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Addr.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Registration No. CNAS L6451; A2LA Certificate Number: 3870.01;

FCC Designation Number: CN1182; FCC Test Firm Registration Number: 540522

Industry Canada Site Registration Number: 10288A-1

2. RF Exposure evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation Method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation Result

Manufacturing Tolerance

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	8	8	8
Tolerance ±(dB)	1	1	1
π/4DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	10	10	10
Tolerance ±(dB)	1	1	1
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	11	11	11
Tolerance ±(dB)	1	1	1

Estimation Result

Mode	F (GHz)	Distance (mm)	RF output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW /cm ²)	MPE limits (mW/cm ²)	MPE Test Exclusion
			dBm	mW					
BDR	2.441	20	9	7.94	2.56	1.80	0.0028	1	Yes
EDR	2.441	20	12	15.85	2.56	1.80	0.0056	1	Yes

Note: The estimation distance is 20cm

END OF REPORT