



■ Report No.: DDT-RQ17080805-03E13

■ Issued Date: Sep. 12, 2017

RF EXPOSURE REPORT

FOR

Applicant	:	Harman International Industries, Incorporated
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Wireless Speaker
Model No.	:	ALLURE
Trade Mark	:	Harman Kardon
FCC ID	:	APIHKALLURE
IC	:	6132A-HKALLURE
Manufacturer	:	Harman International Industries, Incorporated
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808

Tel: +86-0769-89201699 **E-mail:** ddt@dgddt.com <http://www.dgddt.com>

REPORT

TABLE OF CONTENTS

Test report declares.....	3
1. General information	4
1.1. Description of Equipment	4
1.2. Assess laboratory.....	4
2. RF Exposure evaluation	4
2.1. Requirement	4
2.2. Calculation Method.....	5
2.3. Estimation Result	5

TEST REPORT DECLARE

Applicant	:	Harman International Industries, Incorporated
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	Wireless Speaker
Model No.	:	ALLURE
Trade mark	:	Harman Kardon
Manufacturer	:	Harman International Industries, Incorporated
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Standard Used: KDB447498 D01 General RF Exposure Guidance v06.

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-RQ17080805-03E13		
Date of Receipt:	Aug. 10, 2017	Date of Test:	Aug. 10, 2017 ~ Sep. 10, 2017

Prepared By:

Damon Hu
Damon Hu/Engineer



Kevin Feng / EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

1. General information

1.1. Description of Equipment

EUT* Name	:	Wireless Speaker
Model Number	:	ALLURE
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 19V from adapter AC 120V/60Hz
Radio Specification	:	Bluetooth V4.2 (BDR/EDR/BLE)
Operation frequency	:	2402-2480MHz, 2412MHz-2462MHz, 5150MHz-5250MHz, 5250MHz-5350MHz, 5470MHz-5725MHz, 5725MHz-5850MHz
Modulation	:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK,BPSK) IEEE 802.11ac: HT20, HT40, HT80: OFDM (256QAM, 64QAM, 16QAM, QPSK,BPSK)
Data rate	:	IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g, 11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: up to 150 Mbps, HT40: up to 300Mbps IEEE 802.11ac VHT20: up to 150 Mbps, VHT40: up to 300 Mbps VHT80: up to 886.7 Mbps
Antenna Type	:	Integrated antenna 1: 2.4G band maximum PK gain 2.63dBi, 5G band maximum PK gain 4.80dBi Integrated antenna 2: 2.4G band maximum PK gain 2.90dBi, 5G band maximum PK gain 4.80dBi
Sample Type	:	Series production

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong

Province, China, 523808 Tel: +86-0769-89201699 <http://www.dgddt.com> Email: ddt@dgddt.com

2. RF Exposure evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation Method

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(mW/cm^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation Result

Standalone MPE

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
Bluetooth Max power	6	3.98	2.90	1.95	0.0015	1
2.4G WIFI Max power	26	398.11	2.63	1.83	0.1452	1
5G WIFI Max power	17	50.12	4.80	3.02	0.0301	1

Maximum Simultaneous transmission MPE Ratio for 2.4G WLAN and 5G WLAN

Maximum MPE ratio 2.4G WLAN	Maximum MPE ratio 5G WLAN	Σ MPE ratios	Limit	Results
0.1452	0.0301	0.1753	1.000	Pass

Maximum Simultaneous transmission MPE Ratio for 2.4G WLAN and Bluetooth

Maximum MPE ratio 2.4G WLAN	Maximum MPE ratio Bluetooth	Σ MPE ratios	Limit	Results
0.1452	0.0015	0.1467	1.000	Pass

Maximum Simultaneous transmission MPE Ratio for Bluetooth and 5G WLAN

Maximum MPE ratio Bluetooth	Maximum MPE ratio 5G WLAN	Σ MPE ratios	Limit	Results
0.0015	0.0301	0.0316	1.000	Pass

Note: The estimation distance is 20cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

END OF REPORT