



# FCC 47 CFR PART 15 SUBPART C

for

## 2.1 Soundbar with Wireless Subwoofer

Model: SB20 Subwoofer

Brand: Harman/ kardon

Test Report Number:

C170330Z08-RP1

Issued for

Harman International Industries, Inc  
8500 Balboa Blvd, Northridge, CA91329, UNITED STATES

Issued by:

Compliance Certification Services (Shenzhen) Inc.

No.10-1, Mingkeda Logistics Park, No.18 Huanguan South Rd.,  
Guan Lan Town, Baoan District, Shenzhen, China

TEL: 86-755-28055000

FAX: 86-755-28055221

E-Mail: service@ccssz.com

Issued Date: April 20, 2017



中国认可  
国际互认  
检测  
TESTING  
CNAS L4818



TESTING CERT #2861.01

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services (Shenzhen) Inc. This document may be altered or revised by Compliance Certification Services (Shenzhen) Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NVLAP, NIST, CNAS or any government agencies. The test results in the report only apply to the tested sample.



## Revision History

Rev.	Issue Data	Revisions	Effect Page	Revised By
00	April 20, 2017	Initial Issue	ALL	Sinphy Xie



## TABLE OF CONTENTS

<b>1 TEST CERTIFICATION.....</b>	<b>4</b>
<b>2 TEST RESULT SUMMARY.....</b>	<b>5</b>
<b>3 EUT DESCRIPTION .....</b>	<b>6</b>
<b>4 TEST METHODOLOGY .....</b>	<b>7</b>
4.1. DESCRIPTION OF TEST MODES .....	7
<b>5 SETUP OF EQUIPMENT UNDER TEST.....</b>	<b>8</b>
5.1. DESCRIPTION OF SUPPORT UNITS.....	8
5.2. CONFIGURATION OF SYSTEM UNDER TEST .....	8
<b>6 FACILITIES AND ACCREDITATIONS .....</b>	<b>9</b>
6.1. FACILITIES .....	9
6.2. ACCREDITATIONS .....	9
6.3. MEASUREMENT UNCERTAINTY .....	10
<b>7 FCC PART 15.247 REQUIREMENTS.....</b>	<b>11</b>
7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT.....	11
7.2. SPURIOUS EMISSIONS MEASUREMENT.....	16
7.3. 6dB BANDWIDTH MEASUREMENT .....	42
7.4. ANTENNA GAIN .....	48
7.5. PEAK OUTPUT POWER .....	50
7.6. BAND EDGES MEASUREMENT .....	52
7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT.....	62



## 1 TEST CERTIFICATION

<b>Product</b>	2.1 Soundbar with Wireless Subwoofer
<b>Model</b>	SB20 Subwoofer
<b>Brand</b>	Harman/ kardon
<b>Tested</b>	March 30~April 18, 2017
<b>Applicant</b>	<b>Harman International Industries, Inc</b> 8500 Balboa Blvd, Northridge, CA91329, UNITED STATES
<b>Manufacturer</b>	<b>Harman International Industries, Inc</b> 8500 Balboa Blvd, Northridge, CA91329, UNITED STATES

### APPLICABLE STANDARDS

Standard	Test Type	Standard	Test Type
15.207(a)	Power Line Conducted Emissions	15.247(d) 15.209(a)	● Spurious Emissions ● Conducted Measurement ● Radiated Emissions
15.247(a)(2)	6dB Bandwidth Measurement	15.247(b)(3) 15.247(b)(4)	Peak Power Measurement
15.247(d)	Band Edges Measurement	15.247(e)	Peak Power Spectral Density

### We hereby certify that:

The above equipment was tested by Compliance Certification Services (Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

*Approved by:*

*Reviewed by:*

---

**Sunday Hu**  
Supervisor of EMC Dept.  
Compliance Certification Service (Shenzhen)  
Inc.

**Ruby Zhang**  
Supervisor of Report Dept.  
Compliance Certification Service (Shenzhen)  
Inc.



## 2 TEST RESULT SUMMARY

APPLICABLE STANDARDS			
Standard	Test Type	Result	Remark
15.247(a)(2)	6dB Bandwidth Measurement	Pass	Meet the requirement of limit.
15.247(b)(3) 15.247(b)(4)	Peak Power Measurement	Pass	Meet the requirement of limit.
15.247(d)	Band Edges Measurement	Pass	Meet the requirement of limit.
15.247(e)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.247(d) 15.209(a)	● Spurious Emissions ● Conducted Measurement ● Radiated Emissions	Pass	Meet the requirement of limit.
15.207(a)	Power line Conducted Emissions	Pass	Meet the requirement of limit.

Note: 1. The statements of test result on the above are decided by the request of test standard only;  
the measurement uncertainties are not factored into this compliance determination.  
2. The information of measurement uncertainty is available upon the customer's request.



### 3 EUT DESCRIPTION

<b>Product</b>	2.1 Soundbar with Wireless Subwoofer
<b>Model</b>	SB20 Subwoofer
<b>Brand</b>	Harman/ kardon
<b>Model Discrepancy</b>	N/A
<b>Identify Number</b>	C170330Z08-RP1
<b>Received Date</b>	March 30,2017
<b>Power Supply</b>	AC120V/60Hz
<b>Frequency Range</b>	2403.35MHz ~2477.35MHz
<b>Transmit Power</b>	Antenna 0: 6.50dBm Antenna 1: 6.40dBm
<b>Modulation Technique</b>	QPSK
<b>Number of Channels</b>	37 Channels
<b>Antenna Specification</b>	Integrated antenna with 3.9dBi gain (Max)
<b>Temperature Range</b>	-10°C ~ +70°C
<b>Hardware Version</b>	SB20
<b>Software Version</b>	V26

**Note:** 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2. This submittal(s) (test report) is intended for FCC ID: APIHKS20S filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



## 4 TEST METHODOLOGY

### 4.1. DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Used the AV6210 software to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Test Item	Test mode	Worse mode
Conducted Emission	Mode 1: AUX IN	<input checked="" type="checkbox"/>
Radiated Emission	Mode 1: TX	<input checked="" type="checkbox"/>

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.



## 5 SETUP OF EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Equipment	Model No.	Serial No.	FCC ID	Brand	Data Cable	Power Cord
1	Notebook	B475	WB04861612	DoC	THINKPAD	Unshielded, 1.50m	Unshielded, 1.60m (AC Cable) Unshielded, 1.80m (DC Cable)
2	LG Monitor	42LA6200-CN	309NDFVIH179	N/A	LG	Shielded 1.00m (AUX cable)	Unshielded 1.50m (AC cable)
3	Disk	WDBACY320 3ABK-PESN	WXB1AOV4476	N/A	WD	Unshielded 0.50m (USB cable)	N/A
4	Mobile phone	HUAWEI MLA-AL10	MLA-AL10C00B 133	N/A	HUAWEI	N/A	N/A
5	2.1 Soundbar with Wireless Subwoofer	SB20 Center	N/A	N/A	HAMAN	N/A	N/A

**Note:**

Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

### 5.2. CONFIGURATION OF SYSTEM UNDER TEST

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.



## 6 FACILITIES AND ACCREDITATIONS

### 6.1. FACILITIES

All measurement facilities used to collect the measurement data are located at  
**No. 10-1, Mingkeda Logistics Park, No.18 Huanguan South RD. Guan Lan Town,  
Baoan District, Shenzhen China**

The sites are constructed in conformance with the requirements of ANSI C63.10, ANSI C63.7 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 6.2. ACCREDITATIONS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

<b>USA</b>	<b>A2LA</b>
<b>China</b>	<b>CNAS</b>

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>USA</b>	<b>FCC</b>
<b>Japan</b>	<b>VCCI(C-4815, R-4320, T-2317, G-10624)</b>
<b>Canada</b>	<b>INDUSTRY CANADA</b>

Copies of granted accreditation certificates are available for downloading from our web site,  
<http://www.cssz.com>



### 6.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Uncertainty
Radiated Emission, 30 to 200 MHz Test Site : 966(2)	+/-3.6880dB
Radiated Emission, 200 to 1000 MHz Test Site : 966(2)	+/-3.6695dB
Radiated Emission, 1 to 8 GHz	+/-5.1782dB
Radiated Emission, 8 to 18 GHz	+/-5.2173dB
Conducted Emissions	+/-3.6836dB
Band Width	178kHz
Peak Output Power MU	+/-1.906dB
Band Edge MU	+/-0.182dB
Channel Separation MU	416.178Hz
Duty Cycle MU	0.054ms
Frequency Stability MU	226Hz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

The measured result is above (below) the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance (non-compliance) is more probable than non-compliance) with the specification limit.



## 7 FCC PART 15.247 REQUIREMENTS

### 7.1. POWER LINE CONDUCTED EMISSIONS MEASUREMENT

#### 7.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

**NOTE:**

- (1) The lower limit shall apply at the transition frequencies.
- (2) The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
- (3) All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 7.1.2. TEST INSTRUMENTS

Conducted Emission Test Site					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/11/2017	02/10/2018
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	02/11/2017	02/10/2018
LISN	EMCO	3825/2	8901-1459	02/12/2017	02/11/2018
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	02/15/2017	02/14/2018
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


2. N.C.R = No Calibration Request.



### 7.1.3. TEST PROCEDURES (please refer to measurement standard)

- The EUT and Support equipment, if needed, was placed on a non-conducted table, which is 0.8m above the ground plane and 0.4m away from the conducted wall.
- The test equipment EUT installed received AC main power, through a Line Impedance Stabilization Network (LISN), which supplied power source and was grounded to the ground plane. All support equipment power received from a second LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.
- The frequency range from 150 kHz to 30 MHz was searched. The test data of the worst-case condition(s) was recorded. Emission levels under limit 20dB were not recorded.

#### 7.1.4. TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 7.1.5. DATA SAMPLE

Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark
X.XXXX	34.99	19.33	10.15	45.14	29.48	65.99	56.00	-20.85	-26.52	Pass


Factor = Insertion loss of LISN + Cable Loss  
Result = Quasi-peak Reading/ Average Reading + Factor  
Limit = Limit stated in standard  
Margin = Result (dBuV) – Limit (dBuV)



### 7.1.6. TEST RESULTS

#### Test Data

Model No.	SB20 Subwoofer	RBW,VBW	9 kHz
Environmental Conditions	22°C, 45% RH	Test Mode	Mode 1
Tested by	Sam Zeng	Line	L1
Test Date	April 7, 2017	Test Voltage	AC 120V/60Hz




Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark
0.1580	35.41	14.26	19.54	54.95	33.80	65.56	55.57	-10.61	-21.77	Pass
0.4020	15.25	9.61	19.63	34.88	29.24	57.81	47.81	-22.93	-18.57	Pass
3.6700	13.71	3.64	19.67	33.38	23.31	56.00	46.00	-22.62	-22.69	Pass
4.0020	18.33	10.01	19.66	37.99	29.67	56.00	46.00	-18.01	-16.33	Pass
7.4780	17.36	0.48	19.80	37.16	20.28	60.00	50.00	-22.84	-29.72	Pass
12.0900	16.37	0.69	20.05	36.42	20.74	60.00	50.00	-23.58	-29.26	Pass

**REMARKS:** L1 = Line One (Live Line)



<b>Model No.</b>	SB20 Subwoofer	<b>RBW,VBW</b>	9 kHz
<b>Environmental Conditions</b>	22°C, 45% RH	<b>Test Mode</b>	Mode 2
<b>Tested by</b>	Sam Zeng	<b>Line</b>	L2
<b>Test Date</b>	April 7, 2017	<b>Test Voltage</b>	AC 120V/60Hz



Frequency (MHz)	QuasiPeak Reading (dBuV)	Average Reading (dBuV)	Correction Factor (dB)	QuasiPeak Result (dBuV)	Average Result (dBuV)	QuasiPeak Limit (dBuV)	Average Limit (dBuV)	QuasiPeak Margin (dB)	Average Margin (dB)	Remark (Pass/Fail)
0.1500	32.64	9.36	19.72	52.36	29.08	65.99	56.00	-13.63	-26.92	Pass
0.1940	31.61	10.08	19.74	51.35	29.82	63.86	53.86	-12.51	-24.04	Pass
0.2540	23.57	4.67	19.72	43.29	24.39	61.62	51.63	-18.33	-27.24	Pass
0.3300	18.54	3.41	19.70	38.24	23.11	59.45	49.45	-21.21	-26.34	Pass
4.0020	17.20	8.85	19.73	36.93	28.58	56.00	46.00	-19.07	-17.42	Pass
12.1100	13.87	2.47	19.97	33.84	22.44	60.00	50.00	-26.16	-27.56	Pass

**REMARKS:** L2 = Line Two (Neutral Line)



## 7.2. SPURIOUS EMISSIONS MEASUREMENT

### 7.2.1. CONDUCTED EMISSIONS MEASUREMENT

#### 7.2.1.1. LIMITS OF CONDUCTED EMISSIONS MEASUREMENT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

#### 7.2.1.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Due Calibration
Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2017	02/20/2018

#### 7.2.1.3. TEST PROCEDURE (please refer to measurement standard)

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site. The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 9kHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels. No emission found between lowest internal used/generated frequency to 10MHz , it is only recorded 10MHz to 26GHz.




#### 7.2.1.4. TEST RESULTS


##### Test Plot



###### Antenna 0



###### CH Low (10MHz ~26.5GHz)







###### CH Low (2.31GHz ~2.41GHz)





**CH Mid (10MHz ~26.5GHz)****CH Mid**

**CH High (10MHz ~26.5GHz)****CH High( 2.475GHz ~2.5GHz)**

**Antenna 1****CH Low (10MHz ~26.5GHz)****CH Low (2.31GHz ~2.41GHz)**

**CH Mid (10MHz ~26.5GHz)****CH Mid**

**CH High (10MHz ~26.5GHz)****CH High( 2.475GHz ~2.5GHz)**



## 7.2.2. RADIATED EMISSIONS MEASUREMENT

### 7.2.2.1. LIMITS OF RADIATED EMISSIONS MEASUREMENT

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

**Remark:** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

1. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength ( $\mu$ V/m at 3-meter)	Field Strength (dB $\mu$ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

**NOTE:** (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dB $\mu$ V/m) = 20 log Emission level ( $\mu$ V/m).



### 7.2.2.2. TEST INSTRUMENTS

Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/21/2017	02/20/2018
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2017	02/20/2018
Amplifier	EMEC	EM330	060661	03/18/2017	03/17/2018
High Noise Amplifier	Agilent	8449B	3008A01838	02/21/2017	02/20/2018
Loop Antenna	COM-POWER	AL-130	121044	09/25/2016	09/24/2017
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2017	02/20/2018
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2017	02/27/2018
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2017	02/27/2018
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/21/2017	02/20/2018
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The FCC Site Registration number is 101879.  
3. N.C.R = No Calibration Required.



### 7.2.2.3. Measuring Instruments and Setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/AVG
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/AVG
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

### 7.2.2.4. TEST PROCEDURE (please refer to measurement standard)

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### Pre measurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the



maximum of all emissions

**Final measurement:**

--- Identified emissions during the pre measurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).

--- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.

--- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement and the limit will be stored.

**2) Sequence of testing 30 MHz to 1 GHz**

**Setup:**

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 3 meter.

--- The EUT was set into operation.

**Pre measurement:**

--- The turntable rotates from 0° to 315° using 45° steps.

--- The antenna is polarized vertical and horizontal.

--- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.



#### **Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

### **3) Sequence of testing 1 GHz to 18 GHz**

#### **Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### **Pre measurement:**

- The turntable rotates from  $0^\circ$  to  $315^\circ$  using  $45^\circ$  steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.



#### **Final measurement:**

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the pre measurement with marked maximum final measurements and the limit will be stored.

#### **4) Sequence of testing above 18 GHz**

##### **Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

##### **Pre measurement:**


- The antenna is moved spherical over the EUT in different polarisations of the antenna.

##### **Final measurement:**


- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


### 7.2.2.5. TEST SETUP

#### Below 30MHz



#### Below 1 GHz



**Above 1 GHz**

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

**7.2.2.6. DATA SAMPLE****Below 1GHz**

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXX.XXXX	53.41	-18.63	34.78	43.50	-8.72	V	QP

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading  
 Correct Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain  
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)  
 Q.P. = Quasi-peak Reading

**Above 1GHz**

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Pole (V/H)	Remark
XXXX.XXXX	62.09	-11.42	50.67	74.00	-23.33	V	Peak
XXXX.XXXX	49.78	-11.42	38.36	54.00	-15.64	V	AVG

Frequency (MHz) = Emission frequency in MHz  
 Reading (dBuV) = Uncorrected Analyzer / Receiver reading  
 Correction Factor (dB/m) = Antenna factor + Cable loss – Amplifier gain  
 Result (dBuV/m) = Reading (dBuV) + Corr. Factor (dB/m)  
 Limit (dBuV/m) = Limit stated in standard  
 Margin (dB) = Result (dBuV/m) – Limit (dBuV/m)  
 Peak = Peak Reading  
 AVG = Average Reading

**Calculation Formula**

$$\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{Limits (dBuV/m)}$$

$$\text{Result (dBuV/m)} = \text{Reading (dBuV)} + \text{Correction Factor}$$



### 7.2.2.7. TEST RESULTS

#### Below 1 GHz

#### Antenna 0

**Test Mode:** TX / QPSK(CH Low)

**Tested by:** Sam Zeng

**Ambient temperature:** 24°C **Relative humidity:** 52% RH

**Date:** April 14, 2017

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
53.2800	57.89	-22.18	35.71	40.00	-4.29	V	QP
103.7200	56.05	-22.99	33.06	43.50	-10.44	V	QP
141.5500	53.71	-21.33	32.38	43.50	-11.12	V	QP
191.9900	52.77	-22.83	29.94	43.50	-13.56	V	QP
344.2800	49.80	-17.94	31.86	46.00	-14.14	V	QP
442.2500	47.60	-15.63	31.97	46.00	-14.03	V	QP
<hr/>							
141.5500	60.71	-21.33	39.38	43.50	-4.12	H	QP
191.9900	56.81	-22.83	33.98	43.50	-9.52	H	QP
344.2800	57.09	-17.94	39.15	46.00	-6.85	H	QP
466.5000	48.03	-14.88	33.15	46.00	-12.85	H	QP
515.9700	41.86	-14.18	27.68	46.00	-18.32	H	QP
712.8800	39.63	-11.89	27.74	46.00	-18.26	H	QP

**\*\*Remark:** No emission found between lowest internal used/generated frequency to 30MHz.


Pre-scan all mode and recorded the worst case results in this report (QPSK (Low Channel)).

#### **Notes:**


1. Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
2. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.
4. Frequency (MHz).  
Reading (dB $\mu$ V/m)  
Correction Factor (dB)  
Limit (dB $\mu$ V/m)  
Margin (dB)  
Antenna Pole (H/V) = Emission frequency in MHz  
= Receiver reading  
= Antenna factor + Cable loss – Amplifier gain  
= Limit stated in standard  
= Measured (dB $\mu$ V/m) – Limits (dB $\mu$ V/m)  
= Current carrying line of reading



### Vertical



### Horizontal



**Antenna 1****Test Mode:** TX / QPSK(CH Low)**Tested by:** Sam Zeng**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** April 14, 2017

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
54.2500	57.14	-22.47	34.67	40.00	-5.33	V	QP
141.5500	53.44	-21.33	32.11	43.50	-11.39	V	QP
141.5500	53.44	-21.33	32.11	43.50	-11.39	V	QP
344.2800	47.36	-17.94	29.42	46.00	-16.58	V	QP
398.6000	45.63	-16.14	29.49	46.00	-16.51	V	QP
442.2500	46.05	-15.63	30.42	46.00	-15.58	V	QP
80.4400	57.08	-26.59	30.49	40.00	-9.51	H	QP
141.5500	61.07	-21.33	39.74	43.50	-3.76	H	QP
208.4800	54.26	-21.70	32.56	43.50	-10.94	H	QP
270.5600	52.11	-20.49	31.62	46.00	-14.38	H	QP
344.2800	56.73	-17.94	38.79	46.00	-7.21	H	QP
442.2500	50.59	-15.63	34.96	46.00	-11.04	H	QP

**\*\*Remark:** No emission found between lowest internal used/generated frequency to 30MHz.


Pre-scan all mode and recorded the worst case results in this report (QPSK (Low Channel)).

**Notes:**


1. Radiated emissions measured in frequency range from 9kHz to 1GHz were made with an instrument using Quasi-peak detector mode.
2. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
3. The IF bandwidth of Receiver between 30MHz to 1GHz was 120kHz.
4. Frequency (MHz). = Emission frequency in MHz  
Reading (dB $\mu$ V/m) = Receiver reading  
Correction Factor (dB) = Antenna factor + Cable loss – Amplifier gain  
Limit (dB $\mu$ V/m) = Limit stated in standard  
Margin (dB) = Measured (dB $\mu$ V/m) – Limits (dB $\mu$ V/m)  
Antenna Pole (H/V) = Current carrying line of reading



### Vertical



### Horizontal



**Above 1 GHz****Antenna 0****Test Mode:** QPSK (CH Low)**Tested by:** Sam Zeng**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** April 14, 2017

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1243.000	50.13	-7.63	42.50	74.00	-31.50	V	peak
1999.000	50.82	-5.01	45.81	74.00	-28.19	V	peak
2530.000	46.24	-2.21	44.03	74.00	-29.97	V	peak
3925.000	42.34	1.27	43.61	74.00	-30.39	V	peak
5077.000	41.02	5.12	46.14	74.00	-27.86	V	peak
6400.000	40.79	6.73	47.52	74.00	-26.48	V	peak
1999.000	51.56	-5.01	46.55	74.00	-27.45	H	peak
2548.000	45.93	-2.17	43.76	74.00	-30.24	H	peak
3214.000	43.35	-1.00	42.35	74.00	-31.65	H	peak
4159.000	40.88	2.15	43.03	74.00	-30.97	H	peak
5464.000	41.05	5.81	46.86	74.00	-27.14	H	peak
6373.000	41.31	6.68	47.99	74.00	-26.01	H	peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dB $\mu$ V/m) – Average limit (dB $\mu$ V/m).

**Test Mode:** QPSK (CH Mid)**Tested by:** Sam Zeng**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** April 14, 2017

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1990.000	53.59	-5.06	48.53	74.00	-25.47	V	peak
2539.000	46.02	-2.19	43.83	74.00	-30.17	V	peak
3664.000	44.02	0.17	44.19	74.00	-29.81	V	peak
4591.000	42.46	3.65	46.11	74.00	-27.89	V	peak
5383.000	41.87	5.66	47.53	74.00	-26.47	V	peak
6337.000	41.43	6.63	48.06	74.00	-25.94	V	peak
1765.000	50.15	-6.35	43.80	74.00	-30.20	H	peak
1999.000	49.28	-5.01	44.27	74.00	-29.73	H	peak
2521.000	46.50	-2.22	44.28	74.00	-29.72	H	peak
3772.000	43.66	0.63	44.29	74.00	-29.71	H	peak
4627.000	44.74	3.76	48.50	74.00	-25.50	H	peak
4870.000	43.38	4.56	47.94	74.00	-26.06	H	peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dB $\mu$ V/m) – Average limit (dB $\mu$ V/m).

**Test Mode:** QPSK (CH High)**Tested by:** Sam Zeng**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** April 14, 2017

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1990.000	51.18	-5.06	46.12	74.00	-27.88	V	peak
2836.000	43.73	-1.66	42.07	74.00	-31.93	V	peak
4042.000	41.43	1.74	43.17	74.00	-30.83	V	peak
5419.000	41.47	5.73	47.20	74.00	-26.80	V	peak
6517.000	41.31	6.92	48.23	74.00	-25.77	V	peak
7705.000	40.61	9.07	49.68	74.00	-24.32	V	peak
<hr/>							
1765.000	49.35	-6.35	43.00	74.00	-31.00	H	peak
2521.000	45.38	-2.22	43.16	74.00	-30.84	H	peak
3223.000	43.15	-0.99	42.16	74.00	-31.84	H	peak
4186.000	42.34	2.24	44.58	74.00	-29.42	H	peak
5410.000	41.45	5.71	47.16	74.00	-26.84	H	peak
6832.000	40.82	7.43	48.25	74.00	-25.75	H	peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dB $\mu$ V/m) – Average limit (dB $\mu$ V/m).

**Antenna 1****Test Mode:** QPSK (CH Low)**Tested by:** Sam Zeng**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** April 14, 2017

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1765.000	50.21	-6.35	43.86	74.00	-30.14	V	peak
1999.000	51.05	-5.01	46.04	74.00	-27.96	V	peak
2503.000	45.64	-2.25	43.39	74.00	-30.61	V	peak
3826.000	43.60	0.86	44.46	74.00	-29.54	V	peak
5059.000	42.35	5.09	47.44	74.00	-26.56	V	peak
6508.000	41.45	6.90	48.35	74.00	-25.65	V	peak
1747.000	50.15	-6.38	43.77	74.00	-30.23	H	peak
1999.000	48.89	-5.01	43.88	74.00	-30.12	H	peak
2503.000	45.66	-2.25	43.41	74.00	-30.59	H	peak
3349.000	42.13	-0.77	41.36	74.00	-32.64	H	peak
4303.000	43.11	2.66	45.77	74.00	-28.23	H	peak
5410.000	41.63	5.71	47.34	74.00	-26.66	H	peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dB $\mu$ V/m) – Average limit (dB $\mu$ V/m).

**Test Mode:** QPSK (CH Mid)**Tested by:** Sam Zeng**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** April 14, 2017

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1765.000	51.58	-6.35	45.23	74.00	-28.77	V	peak
2809.000	45.88	-1.70	44.18	74.00	-29.82	V	peak
3880.000	43.22	1.08	44.30	74.00	-29.70	V	peak
5149.000	41.45	5.25	46.70	74.00	-27.30	V	peak
5644.000	41.56	5.93	47.49	74.00	-26.51	V	peak
6958.000	42.12	7.63	49.75	74.00	-24.25	V	peak
<hr/>							
1765.000	49.08	-6.35	42.73	74.00	-31.27	H	peak
2512.000	46.14	-2.24	43.90	74.00	-30.10	H	peak
3700.000	42.93	0.32	43.25	74.00	-30.75	H	peak
4123.000	41.87	2.02	43.89	74.00	-30.11	H	peak
5410.000	41.59	5.71	47.30	74.00	-26.70	H	peak
6850.000	40.41	7.46	47.87	74.00	-26.13	H	peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “N/A” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dB $\mu$ V/m) – Average limit (dB $\mu$ V/m).

**Test Mode:** QPSK (CH High)**Tested by:** Sam Zeng**Ambient temperature:** 24°C **Relative humidity:** 52% RH**Date:** April 14, 2017

Frequency (MHz)	Reading (dB $\mu$ V)	Correction Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pole (V/H)	Remark
1495.000	49.54	-6.89	42.65	74.00	-31.35	V	peak
1999.000	49.45	-5.01	44.44	74.00	-29.56	V	peak
2818.000	45.43	-1.69	43.74	74.00	-30.26	V	peak
4069.000	42.32	1.83	44.15	74.00	-29.85	V	peak
5140.000	42.05	5.23	47.28	74.00	-26.72	V	peak
6553.000	40.01	6.98	46.99	74.00	-27.01	V	peak
<hr/>							
1747.000	50.53	-6.38	44.15	74.00	-29.85	H	peak
2503.000	46.63	-2.25	44.38	74.00	-29.62	H	peak
3880.000	42.85	1.08	43.93	74.00	-30.07	H	peak
4339.000	43.17	2.78	45.95	74.00	-28.05	H	peak
5968.000	41.38	6.07	47.45	74.00	-26.55	H	peak
7048.000	41.79	7.79	49.58	74.00	-24.42	H	peak

**REMARKS:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “---” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “N/A” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dB $\mu$ V/m) – Average limit (dB $\mu$ V/m).



### 7.3. 6dB BANDWIDTH MEASUREMENT

#### 7.3.1. LIMITS

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5MHz. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### 7.3.2. TEST INSTRUMENTS


Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2017	02/20/2018

#### 7.3.3. TEST PROCEDURES (please refer to measurement standard)

##### 8.2 Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e.,  $RBW = 100$  kHz,  $VBW \geq 3$  RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.

#### 7.3.4. TEST SETUP





### 7.3.5. TEST RESULTS

No non-compliance noted

#### Test Data

##### Antenna 0

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2403.35	1558.00	>500	PASS
Mid	2441.35	1560.00		PASS
High	2477.35	1560.00		PASS

##### Antenna 1


Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2403.35	1558.00	>500	PASS
Mid	2441.35	1558.00		PASS
High	2477.35	1560.00		PASS




## Test Plot


### Antenna 0

#### 6dB Bandwidth (CH Low)



#### 6dB Bandwidth (CH Mid)










## Antenna 1

### 6dB Bandwidth (CH Low)



### 6dB Bandwidth (CH Mid)







## 7.4. ANTENNA GAIN

### MEASUREMENT

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

### MEASUREMENT PARAMETERS

Measurement parameter	
Detector	Peak
Sweep time	Auto
Resolution bandwidth	3 MHz
Video bandwidth	3 MHz
Trace-Mode	Max hold

### LIMITS

FCC	IC
Antenna Gain	
6 dBi	

## TEST RESULTS

### Antenna 0

T <sub>nom</sub>	V <sub>nom</sub>	Lowest channel 2403.35MHz	Middle channel 2441.35MHz	Highest channel 2477.35MHz
Conducted power [dBm] Measured with QPSK modulation		3.90	3.50	2.71
Radiated power [dBm] Measured with QPSK modulation		5.34	5.01	4.68
Gain [dBi] Calculated		1.44	1.51	1.97
Measurement uncertainty		± 1.5 dB (cond.) / ± 3 dB (rad.)		



**Antenna 0**

<b>T<sub>nom</sub></b>	<b>V<sub>nom</sub></b>	<b>Lowest channel 2403.35MHz</b>	<b>Middle channel 2441.35MHz</b>	<b>Highest channel 2477.35MHz</b>
Conducted power [dBm] Measured with QPSK modulation		3.80	3.61	2.61
Radiated power [dBm] Measured with QPSK modulation		5.98	5.37	4.76
Gain [dBi] Calculated		2.18	1.76	2.15
Measurement uncertainty	$\pm 1.5$ dB (cond.) / $\pm 3$ dB (rad.)			



## 7.5. PEAK OUTPUT POWER

### 7.5.1. LIMITS

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 7.5.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Power Meter	Anritsu	ML2495A	1204003	02/21/2017	02/20/2018
Power Sensor	Anritsu	MA2411B	1126150	02/21/2017	02/20/2018

### 7.5.3. TEST PROCEDURES (please refer to measurement standard)

#### 9.1.1 RBW $\geq$ DTS bandwidth

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the *DTS bandwidth*.


- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq$  3 RBW.
- c) Set span  $\geq$  3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

#### 9.1.3 PKPM1 Peak power meter method

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.



#### 7.5.4. TEST SETUP



#### 7.5.5. TEST RESULTS

*No non-compliance noted*

##### Test Data

##### Antenna 0

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Peak /AVG	Result
Low	2403.35	6.50	0.00447	1	peak	PASS
Mid	2441.35	6.10	0.00407			PASS
High	2477.35	5.30	0.00339			PASS
Low	2403.35	4.20	0.00263	1	AVG	PASS
Mid	2441.35	3.90	0.00245			PASS
High	2477.35	3.10	0.00204			PASS

##### Antenna 1

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Peak /AVG	Result
Low	2403.35	6.40	0.00437	1	peak	PASS
Mid	2441.35	6.20	0.00417			PASS
High	2477.35	5.20	0.00331			PASS
Low	2403.35	4.40	0.00275	1	AVG	PASS
Mid	2441.35	4.10	0.00257			PASS
High	2477.35	3.40	0.00219			PASS



## 7.6. BAND EDGES MEASUREMENT

### 7.6.1. LIMITS

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

### 7.6.2. TEST INSTRUMENTS


Radiated Emission Test Site 966(2)					
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	02/21/2017	02/20/2018
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	02/21/2017	02/20/2018
Amplifier	EMEC	EM330	060661	03/18/2017	03/17/2018
High Noise Amplifier	Agilent	8449B	3008A01838	02/21/2017	02/20/2018
Loop Antenna	COM-POWER	AL-130	121044	09/25/2016	09/24/2017
Bilog Antenna	SCHAFFNER	CBL6143	5082	02/21/2017	02/20/2018
Horn Antenna	SCHWARZBECK	BBHA9120	D286	02/28/2017	02/27/2018
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	02/28/2017	02/27/2018
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/21/2017	02/20/2018
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The FCC Site Registration number is 101879.  
3. N.C.R = No Calibration Required.

### 7.6.3. TEST PROCEDURES (please refer to measurement standard)

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

### 7.6.4. TEST SETUP






### 7.6.5. TEST RESULTS


#### Test Plot

##### Antenna 0



##### Band Edges (CH Low)




No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	54.47	-2.86	51.61	74.00	-22.39	Peak	Vertical
2.	2403.500	89.76	-2.79	86.97	---	---	Peak	Vertical
3.	2390.000	42.90	-2.86	40.04	54.00	-13.96	Average	Vertical
4.	2403.300	86.32	-2.79	83.53	---	---	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	62.19	-2.86	59.33	74.00	-14.67	Peak	Horizontal
2.	2403.500	102.63	-2.79	99.84	---	---	Peak	Horizontal
3.	2390.000	46.43	-2.86	43.57	54.00	-10.43	Average	Horizontal
4.	2403.400	99.35	-2.79	96.56	---	---	Average	Horizontal

**Band Edges (CH-High)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**


No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2477.600	85.02	-2.38	82.64	---	---	Peak	Vertical
2.	2483.500	54.46	-2.35	52.11	74.00	-21.89	Peak	Vertical
3.	2477.325	81.60	-2.38	79.22	---	---	Average	Vertical
4.	2483.500	43.80	-2.35	41.45	54.00	-12.55	Average	Vertical




No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2477.575	100.86	-2.38	98.48	---	---	Peak	Horizontal
2.	2483.500	64.34	-2.35	61.99	74.00	-12.01	Peak	Horizontal
3.	2477.350	97.57	-2.38	95.19	---	---	Average	Horizontal
4.	2483.500	51.04	-2.35	48.69	54.00	-5.31	Average	Horizontal





**Antenna 1**  
**Band Edges (CH Low)**




No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	54.42	-2.86	51.56	74.00	-22.44	Peak	Vertical
2.	2403.100	92.44	-2.79	89.65	---	---	Peak	Vertical
3.	2390.000	43.20	-2.86	40.34	54.00	-13.66	Average	Vertical
4.	2403.300	89.20	-2.79	86.41	---	---	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2390.000	58.51	-2.86	55.65	74.00	-18.35	Peak	Horizontal
2.	2403.600	98.91	-2.79	96.12	---	---	Peak	Horizontal
3.	2390.000	45.06	-2.86	42.20	54.00	-11.80	Average	Horizontal
4.	2403.300	95.61	-2.79	92.82	---	---	Average	Horizontal

**Band Edges (CH-High)****Detector mode: Peak****Polarity: Vertical****Detector mode: Average****Polarity: Vertical**

No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2477.550	89.16	-2.38	86.78	---	---	Peak	Vertical
2.	2483.500	56.10	-2.35	53.75	74.00	-20.25	Peak	Vertical
3.	2477.325	85.35	-2.38	82.97	---	---	Average	Vertical
4.	2483.500	43.70	-2.35	41.35	54.00	-12.65	Average	Vertical



No.	Frequency (MHz)	Reading (dB)	Factor (dB/m)	Result (dB/m)	Limit (dB/m)	Margin (dB)	Remark	Antenna Polar
1.	2477.125	98.16	-2.39	95.77	---	---	Peak	Horizontal
2.	2483.500	60.74	-2.35	58.39	74.00	-15.61	Peak	Horizontal
3.	2477.325	94.83	-2.38	92.45	---	---	Average	Horizontal
4.	2483.500	49.08	-2.35	46.73	54.00	-7.27	Average	Horizontal



## 7.7. PEAK POWER SPECTRAL DENSITY MEASUREMENT

### 7.7.1. LIMITS

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.


### 7.7.2. TEST INSTRUMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Last Calibration	Calibration Due
Spectrum Analyzer	Agilent	N9010A	MY55370330	02/21/2017	02/20/2018

### 7.7.3. TEST PROCEDURES (please refer to measurement standard)

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \text{ RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 7.7.4. TEST SETUP





### 7.7.5. TEST RESULTS

*No non-compliance noted*

#### Test Data

##### Antenna 0


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2403.35	-12.069	8.00	PASS
Mid	2441.35	-12.933		PASS
High	2477.35	-12.791		PASS


##### Antenna 1

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Test Result
Low	2403.35	-11.958	8.00	PASS
Mid	2441.35	-12.907		PASS
High	2477.35	-12.771		PASS



### Test Plot








### Antenna 1

#### PPSD (CH Low)



#### PPSD (CH Mid)

