

Prüfbericht - Nr.: CN220 Test report no.:	0J2E 001	Seite 24 von 25 Page 24 of 25
6 Safety Human Exposure		
6.1 Radio Frequency Exposure Compliance		
6.1.1 Electromagnetic Field	ls	
RESULT:		Pass
Test Specification		
Test standard	: CFR47 FCC Part 2.1093	
	RSS-102 Issue 5 March 2019	
	FCC KDB Publication 447498 v06	
Limit	: CFR47 FCC Part 1.1310	

The measured maximum conducted output power of the EUT is  $3..6dBm \approx 2.29$  mW, which is below the SAR exclusion threshold level 9. 6mW (SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq 50$  mm), hence the EUT is excluded from SAR evaluation according to FCC KDB publication 447498 D01: Mobile and Portable RF Exposure. Guidance v06.

The measured maximum conducted output power of the EUT is  $3..6dBm \approx 2.29$  mW and the measured maximum specified e.i.r.p of the EUT is  $3..6dBm \approx 2.29$  mW, which is below the SAR exclusion threshold level 4mW, hence the EUT is excluded from SAR evaluation according to RSS-102 Issue 5 section 2.5.1.