

Appendix B

Highest Test Plots

Table of Contents

1. SRD Body-worn 0mm SAR..... 3

1. SRD Body-worn 0mm SAR

Date: 08.07.2024

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q24043024-1E

DUT: Portable Bluetooth Speaker; Model Number: FLIP6G Serial: S24043024-004

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2441 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used (interpolated): $f = 2441\text{ MHz}$; $\sigma = 1.772\text{ S/m}$; $\epsilon_r = 38.51$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ComF(7.95, 7.95, 7.95); Calibrated: 29.04.2024;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 29.04.2024
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP-1197
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/Top side SRD 2441/Area Scan (9x10x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 0.701 W/kg

Configuration/Top side SRD 2441/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 5.469 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 0.967 W/kg

SAR(1 g) = 0.470 W/kg; SAR(10 g) = 0.206 W/kg

Info: Interpolated medium parameters used for SAR evaluation.
Maximum value of SAR (measured) = 0.787 W/kg

