

FCC AND IC CERTIFICATION TEST REPORT

FOR

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	WIRELESS SPEAKER
Model No.	:	LINK PORTABLE
Trade Mark	:	JBL
FCC ID	:	APIJBLLINKPORT
IC	:	6132A-JBLLINKPORT
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	6
2.	General test information.....	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT	7
2.3.	Assistant equipment used for test.....	7
2.4.	Block diagram of EUT configuration for test.....	8
2.5.	Deviations of test standard	8
2.6.	Test environment conditions	8
2.7.	Test laboratory	9
2.8.	Measurement uncertainty	9
3.	Equipment used during test.....	10
4.	6dB Bandwidth and 99% Bandwidth	11
4.1.	Block diagram of test setup	11
4.2.	Limits	11
4.3.	Test Procedure.....	11
4.4.	Test Result	11
4.5.	original test data.....	13
5.	Conducted peak Output Power.....	30
5.1.	Block diagram of test setup	30
5.2.	Limits	30
5.3.	Test Procedure.....	30
5.4.	Test Result	30
5.5.	original test data.....	31
6.	Power Spectral Density.....	40
6.1.	Block diagram of test setup	40
6.2.	Limits	40
6.3.	Test Procedure.....	40
6.4.	Test Result	40
6.5.	original test data.....	41
7.	Band Edge and Spurious Emissions (Conducted).....	50
7.1.	Block diagram of test setup	50
7.2.	Limits	50
7.3.	Test Procedure.....	50
7.4.	Test Result	51
7.5.	original test data.....	51

8.	Radiated Spurious Emissions.....	81
8.1.	Block diagram of test setup	81
8.2.	Limit.....	82
8.3.	Test Procedure.....	83
8.4.	Test result.....	85
9.	Radiated Band Edge Compliance	89
9.1.	Block diagram of test setup	89
9.2.	Limit.....	89
9.3.	Test Procedure.....	89
9.4.	Test result.....	89
10.	Power Line Conducted Emission.....	106
10.1.	Block diagram of test setup	106
10.2.	Power Line Conducted Emission Limits (Class B).....	106
10.3.	Test Procedure.....	106
10.4.	Test Result	107
11.	Antenna Requirements.....	110
11.1.	Limit.....	110
11.2.	Result.....	110

TEST REPORT DECLARE

Applicant	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES
Equipment under Test	:	WIRELESS SPEAKER
Model No	:	LINK PORTABLE
Trade Mark	:	JBL
Manufacturer	:	Harman International Industries, Inc.
Address	:	8500 Balboa Boulevard, Northridge, CA 91329, UNITED STATES

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 2 February 2017.

Test procedure used: ANSI C63.10:2013, RSS-Gen Issue 5, Apr. 2018, 558074 D01 DTS Meas Guidance v04,

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC&IC standards.

Report No:	DDT-R19031903-1E6		
Date of Receipt:	Apr. 19, 2019	Date of Test:	Apr. 19, 2019 ~ Jun. 28, 2019

Prepared By:

Ella Gong

Ella Gong/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jun. 28, 2019	

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.

Description of Test Item	Standard	Results
6dB Bandwidth and 99% Bandwidth	FCC 15.247 (a) (2) RSS-247 Clause 5.2 (a)	PASS
Conducted Output Power	FCC 15.247 (b) (3) RSS-247 Clause 5.4 (d)	PASS
Power Spectral Density	FCC 15.247 (e) RSS-247 Clause 5.2 (b)	PASS
Band-edge and Spurious Emissions (Conducted)	FCC 15.247 (d) RSS-247 Clause 5.5	PASS
Radiated Spurious Emissions	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	PASS
Radiated Band Edge Compliance	FCC 15.247 (d) FCC 15.209 FCC 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	PASS
Power Line Conducted Emission	FCC 15.207 RSS-GEN Clause 8.8	PASS
Antenna requirement	FCC 15.203 RSS-GEN Clause 6.8	PASS

2. General test information

2.1. Description of EUT

EUT* Name	: WIRELESS SPEAKER
Model Number	: LINK PORTABLE
EUT function description	: Please reference user manual of this device
Power supply	: DC 5V from external AC Adapter DC 3.6V 4800mAh Polymer Li-ion built-in battery
Radio Technology	: IEEE 802.11b/g/n
FCC Operation frequency	: IEEE 802.11b: 2412MHz-2462MHz IEEE 802.11g: 2412MHz-2462MHz IEEE 802.11n HT20: 2412MHz-2462MHz IEEE 802.11n HT40: 2422MHz-2452MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM, QPSK, BPSK)
Transmitter rate	: IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: 6.5, 13, 19.5, 26, 39, 52, 58.5, 65 Mbps IEEE 802.11n HT40: 13.5, 27, 40.5, 54, 81, 108, 121.5, 135 Mbps
Antenna Type	: Antenna 1: External FPC antenna, maximum PK gain: 2.89 dBi Antenna 2: External FPC antenna, maximum PK gain: 2.34 dBi
Sample Type	: Series production

Note: EUT is the ab. of equipment under test.

Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/


2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Other
USB cable	Harman	N/A	Length: 1.2m, unshielded	N/A

2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	EMC Compliance	SN
Notebook	DELL	Latitude D610	FCC DOC	00045-534-136-300

2.4. Block diagram of EUT configuration for test



EUT was connected to control to provide by manufacturer which has a standard LAN PORT connector to connect to Notebook, and the Notebook will run a special test software “adb.EXE” provided by manufacturer to control EUT work in Continuous Tx mode (>98% duty cycle), and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information				
Mode	Setting Tx Power	data rate (Mbps) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	15	11	LCH: CH1	2412
	15	11	MCH: CH6	2437
	15	11	HCH: CH11	2462
IEEE 802.11g	15	54	LCH: CH1	2412
	15	54	MCH: CH6	2437
	15	54	HCH: CH11	2462
IEEE 802.11n HT20	15	MCS 7	LCH: CH1	2412
	15	MCS 7	MCH: CH6	2437
	15	MCS 7	HCH: CH11	2462
IEEE 802.11n HT40	15	MCS 7	LCH: CH3	2422
	15	MCS 7	MCH: CH6	2437
	15	MCS 7	HCH: CH9	2452

Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.

2.5. Deviations of test standard

No Deviation

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

Designation Number: CN1182; Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz); 1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz); 1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 × 10 ⁻⁸ (Antenna couple method) 5.5 × 10 ⁻⁸ (Conducted method)
Conducted spurious emissions	0.86dB (10 MHz ≤ f < 3.6 GHz); 1.40 dB (3.6 GHz ≤ f < 8 GHz) 1.66 dB (8 GHz ≤ f < 22 GHz)
Uncertainty for radio frequency (RBW<20 kHz)	3×10 ⁻⁸
Temperature	0.4°C
Humidity	2%
Uncertainty for Radiation Emission test (30 MHz-1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz-40 GHz)	4.10 dB (1-6 GHz) 4.40 dB (6 GHz-18 GHz) 3.54 dB (18 GHz-26 GHz) 4.30 dB (26 GHz-40 GHz)
Uncertainty for Power line conduction emission test	3.32 dB (150 kHz-30 MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test (Tonscend RF Measurement System)					
Spectrum analyzer	R&S	FSU26	200071	Oct. 12, 2018	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 29, 2018	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Oct. 12, 2018	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 29, 2018	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Oct. 21, 2018	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Oct. 23, 2018	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Aug. 18, 2018	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2018	1 Year
RF Cable	Micable	C10-01-01-1	100309	Oct. 21, 2018	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Oct. 21, 2018	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
Radiation 1#chamber					
EMI Test Receiver	R&S	ESU8	100316	Oct. 12, 2018	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 29, 2018	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 09, 2018	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 20, 2018	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Nov. 16, 2018	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Oct. 25, 2018	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 12, 2018	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Oct. 12, 2018	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Oct. 21, 2018	1 Year
RF Cable	N/A	SMAJ-SMA J-1M+ 11M	17070133+17070131	Nov. 08, 2018	1 Year
MI Cable	HUBSER	C10-01-01-1 M	1091629	Oct. 21, 2018	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
Power Line Conducted Emissions Test					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2018	1 Year
LISN 1	R&S	ENV216	101109	Oct. 21, 2018	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 21, 2018	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 21, 2018	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Oct. 21, 2018	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

4. 6dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

- (3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.4. Test Result


Test Mode	Test	Ant	6dB Bandwidth [MHz]	Limit [MHz]	Verdict
11B	2412	Ant1	7.640	0.5	PASS
11B	2412	Ant2	7.920	0.5	PASS
11B	2437	Ant1	8.600	0.5	PASS
11B	2437	Ant2	8.360	0.5	PASS
11B	2462	Ant1	8.800	0.5	PASS
11B	2462	Ant2	8.800	0.5	PASS
11G	2412	Ant1	15.160	0.5	PASS


11G	2412	Ant2	15.200	0.5	PASS
11G	2437	Ant1	15.200	0.5	PASS
11G	2437	Ant2	15.760	0.5	PASS
11G	2462	Ant1	15.160	0.5	PASS
11G	2462	Ant2	15.160	0.5	PASS
11N20	2412	Ant1	16.080	0.5	PASS
11N20	2412	Ant2	16.400	0.5	PASS
11N20	2437	Ant1	16.080	0.5	PASS
11N20	2437	Ant2	16.040	0.5	PASS
11N20	2462	Ant1	16.080	0.5	PASS
11N20	2462	Ant2	16.360	0.5	PASS
11N40	2422	Ant1	35.280	0.5	PASS
11N40	2422	Ant2	35.280	0.5	PASS
11N40	2437	Ant1	35.840	0.5	PASS
11N40	2437	Ant2	35.600	0.5	PASS
11N40	2452	Ant1	35.280	0.5	PASS
11N40	2452	Ant2	35.600	0.5	PASS

Test Mode	Test	Ant	99% OBW [MHz]	Limit [MHz]	Verdict
11B	2412	Ant1	13.32	---	PASS
11B	2412	Ant2	13.32	---	PASS
11B	2437	Ant1	13.32	---	PASS
11B	2437	Ant2	13.32	---	PASS
11B	2462	Ant1	13.40	---	PASS
11B	2462	Ant2	13.32	---	PASS
11G	2412	Ant1	16.60	---	PASS
11G	2412	Ant2	16.60	---	PASS
11G	2437	Ant1	16.60	---	PASS
11G	2437	Ant2	16.60	---	PASS
11G	2462	Ant1	16.64	---	PASS
11G	2462	Ant2	16.60	---	PASS
11N20	2412	Ant1	17.64	---	PASS
11N20	2412	Ant2	17.68	---	PASS
11N20	2437	Ant1	17.68	---	PASS
11N20	2437	Ant2	17.68	---	PASS
11N20	2462	Ant1	17.64	---	PASS
11N20	2462	Ant2	17.68	---	PASS
11N40	2422	Ant1	36.72	---	PASS
11N40	2422	Ant2	36.72	---	PASS


11N40	2437	Ant1	36.64	---	PASS
11N40	2437	Ant2	36.64	---	PASS
11N40	2452	Ant1	36.64	---	PASS
11N40	2452	Ant2	36.72	---	PASS

4.5. original test data







11B_ANT2_2437




11B_ANT1_2462




11B_ANT2_2462




11G_ANT1_2412




11G_ANT2_2412




11G_ANT1_2437




11G_ANT2_2437




11G_ANT1_2462




11G_ANT2_2462




11N20SISO_ANT1_2412




11N20SISO_ANT2_2412




11N20SISO_ANT1_2437




11N20SISO_ANT2_2437




11N20SISO_ANT1_2462




11N20SISO_ANT2_2462




11N40SISO_ANT1_2422




11N40SISO_ANT2_2422




11N40SISO_ANT1_2437




11N40SISO_ANT2_2437




11N40SISO_ANT1_2452




11N40SISO_ANT2_2452




11B_ANT1_2412




11B_ANT2_2412




11B_ANT1_2437




11B_ANT2_2437




11B_ANT1_2462




11B_ANT2_2462




11G_ANT1_2412




11G_ANT2_2412




11G_ANT1_2437




11G_ANT2_2437




11G_ANT1_2462




11G_ANT2_2462




11N20SISO_ANT1_2412




11N20SISO_ANT2_2412




11N20SISO_ANT1_2437




11N20SISO_ANT2_2437




11N20SISO_ANT1_2462




11N20SISO_ANT2_2462




11N40SISO_ANT1_2422




11N40SISO_ANT2_2422




11N40SISO_ANT1_2437




11N40SISO_ANT2_2437



11N40SISO_ANT1_2452



11N40SISO_ANT2_2452



5. Conducted peak Output Power

5.1. Block diagram of test setup

Same as section 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3. Test Procedure

Connect each EUT's antenna output to power sensor by RF cable and attenuator


Measure the PK output power of each antenna port by Spectrum Analyzer.


5.4. Test Result

Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
11B	2412	Ant1	21.47	30	PASS
11B	2412	Ant2	21.64	30	PASS
11B	2437	Ant1	21.34	30	PASS
11B	2437	Ant2	21.39	30	PASS
11B	2462	Ant1	22.07	30	PASS
11B	2462	Ant2	22.30	30	PASS
11G	2412	Ant1	22.91	30	PASS
11G	2412	Ant2	23.51	30	PASS
11G	2437	Ant1	23.38	30	PASS
11G	2437	Ant2	23.50	30	PASS
11G	2462	Ant1	24.00	30	PASS
11G	2462	Ant2	24.11	30	PASS
11N20	2412	Ant1	23.12	30	PASS
11N20	2412	Ant2	23.15	30	PASS
11N20	2437	Ant1	22.76	30	PASS
11N20	2437	Ant2	23.05	30	PASS
11N20	2462	Ant1	23.56	30	PASS
11N20	2462	Ant2	23.76	30	PASS
11N40	2422	Ant1	23.05	30	PASS
11N40	2422	Ant2	23.37	30	PASS
11N40	2437	Ant1	22.78	30	PASS


11N40	2437	Ant2	23.32	30	PASS
11N40	2452	Ant1	22.90	30	PASS
11N40	2452	Ant2	23.03	30	PASS

5.5. original test data







11B_ANT2_2437




11B_ANT1_2462




11B_ANT2_2462




11G_ANT1_2412




11G_ANT2_2412




11G_ANT1_2437




11G_ANT2_2437




11G_ANT1_2462




11G_ANT2_2462




11N20SISO_ANT1_2412




11N20SISO_ANT2_2412



11N20SISO_ANT1_2437




11N20SISO_ANT2_2437




11N20SISO_ANT1_2462




11N20SISO_ANT2_2462




11N40SISO_ANT1_2422




11N40SISO_ANT2_2422




11N40SISO_ANT1_2437




11N40SISO_ANT2_2437



11N40SISO_ANT1_2452



11N40SISO_ANT2_2452



6. Power Spectral Density

6.1. Block diagram of test setup

Same as section 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode	Max hold


- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- (4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


6.4. Test Result

Test Mode	Test Channel	Ant	PSD [dBm]	Limit[dBm/kHz]	Verdict
11B	2412	Ant1	-7.81	8.00	PASS
11B	2412	Ant2	-7.57	8.00	PASS
11B	2437	Ant1	-8.02	8.00	PASS
11B	2437	Ant2	-7.74	8.00	PASS
11B	2462	Ant1	-7.16	8.00	PASS
11B	2462	Ant2	-7.05	8.00	PASS
11G	2412	Ant1	-12.54	8.00	PASS
11G	2412	Ant2	-12.93	8.00	PASS
11G	2437	Ant1	-12.74	8.00	PASS
11G	2437	Ant2	-13.05	8.00	PASS
11G	2462	Ant1	-11.81	8.00	PASS
11G	2462	Ant2	-11.23	8.00	PASS


11N20	2412	Ant1	-13.54	8.00	PASS
11N20	2412	Ant2	-11.95	8.00	PASS
11N20	2437	Ant1	-12.84	8.00	PASS
11N20	2437	Ant2	-13.37	8.00	PASS
11N20	2462	Ant1	-12.30	8.00	PASS
11N20	2462	Ant2	-12.62	8.00	PASS
11N40	2422	Ant1	-16.48	8.00	PASS
11N40	2422	Ant2	-15.92	8.00	PASS
11N40	2437	Ant1	-16.12	8.00	PASS
11N40	2437	Ant2	-16.85	8.00	PASS
11N40	2452	Ant1	-16.37	8.00	PASS
11N40	2452	Ant2	-15.97	8.00	PASS

6.5. original test data







11G_ANT1_2412




11G_ANT2_2412




11G_ANT1_2437




11G_ANT2_2437




11G_ANT1_2462




11G_ANT2_2462




11N20SISO_ANT1_2412




11N20SISO_ANT2_2412




11N20SISO_ANT1_2437




11N20SISO_ANT2_2437




11N20SISO_ANT1_2462




11N20SISO_ANT2_2462




11N40SISO_ANT1_2422




11N40SISO_ANT2_2422




11N40SISO_ANT1_2437




11N40SISO_ANT2_2437



11N40SISO_ANT1_2452



11N40SISO_ANT2_2452



7. Band Edge and Spurious Emissions (Conducted)

7.1. Block diagram of test setup

Same as section 4.1

7.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100 kHz
VBW:	300 kHz
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span}/\text{RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


7.4. Test Result


EUT Set Mode	CH or Frequency	Ant1 Result (dBm)	EUT Set Mode	CH or Frequency	Ant1 Result (dBm)
11b	CH1	PASS	11n HT 20	CH1	PASS
	CH6	PASS		CH6	PASS
	CH11	PASS		CH11	PASS
11g	CH1	PASS	11n HT 40	CH3	PASS
	CH6	PASS		CH6	PASS
	CH11	PASS		CH9	PASS

EUT Set Mode	CH or Frequency	Ant2 Result (dBm)	EUT Set Mode	CH or Frequency	Ant2 Result (dBm)
11b	CH1	PASS	11n HT 20	CH1	PASS
	CH6	PASS		CH6	PASS
	CH11	PASS		CH11	PASS
11g	CH1	PASS	11n HT 40	CH3	PASS
	CH6	PASS		CH6	PASS
	CH11	PASS		CH9	PASS


7.5. original test data

Band Edge







11B_ANT1_High




11B_ANT2_High




11G_ANT1_Low




11G_ANT2_Low




11G_ANT1_High




11G_ANT2_High




11N20SISO_ANT1_Low




11N20SISO_ANT2_Low




11N20SISO_ANT1_High




11N20SISO_ANT2_High




11N40SISO_ANT1_Low




11N40SISO_ANT2_Low



11N40SISO_ANT1_High




11N40SISO_ANT2_High




Spurious Emissions


11B_ANT1_2412_Ref




11B_ANT1_2412_30~1000




11B_ANT1_2412_1000~26500




11B_ANT2_2412_Ref




11B_ANT2_2412_30~1000




11B_ANT2_2412_1000~26500




11B_ANT1_2437_Ref




11B_ANT1_2437_30~1000




11B_ANT1_2437_1000~26500




11B_ANT2_2437_Ref




11B_ANT2_2437_30~1000




11B_ANT2_2437_1000~26500




11B_ANT1_2462_Ref




11B_ANT1_2462_30~1000



11B_ANT1_2462_1000~26500




11B_ANT2_2462_Ref




Date: 5.MAY.2019 20:12:22

11B_ANT2_2462_30~1000




Date: 5.MAY.2019 20:12:30

11B_ANT2_2462_1000~26500




Date: 5.MAY.2019 20:12:42


11G_ANT1_2412_Ref




11G_ANT1_2412_30~1000




11G_ANT1_2412_1000~26500




11G_ANT2_2412_Ref




11G_ANT2_2412_30~1000




11G_ANT2_2412_1000~26500




11G_ANT1_2437_Ref




11G_ANT1_2437_30~1000




11G_ANT1_2437_1000~26500




11G_ANT2_2437_Ref




11G_ANT2_2437_30~1000




11G_ANT2_2437_1000~26500




11G_ANT1_2462_Ref




11G_ANT1_2462_30~1000




11G_ANT1_2462_1000~26500




11G_ANT2_2462_Ref




11G_ANT2_2462_30~1000



11G_ANT2_2462_1000~26500




11N20SISO_ANT1_2412_Ref




Date: 5.MAY.2019 19:41:19

11N20SISO_ANT1_2412_30~1000




Date: 5.MAY.2019 19:41:28

11N20SISO_ANT1_2412_1000~26500




Date: 5.MAY.2019 19:42:13


11N20SISO_ANT2_2412_Ref




11N20SISO_ANT2_2412_30~1000




11N20SISO_ANT2_2412_1000~26500




11N20SISO_ANT1_2437_Ref




11N20SISO_ANT1_2437_30~1000




11N20SISO_ANT1_2437_1000~26500




11N20SISO_ANT2_2437_Ref




11N20SISO_ANT2_2437_30~1000




11N20SISO_ANT2_2437_1000~26500




11N20SISO_ANT1_2462_Ref




11N20SISO_ANT1_2462_30~1000




11N20SISO_ANT1_2462_1000~26500




11N20SISO_ANT2_2462_Ref




11N20SISO_ANT2_2462_30~1000




11N20SISO_ANT2_2462_1000~26500




11N40SISO_ANT1_2422_Ref




11N40SISO_ANT1_2422_30~1000




11N40SISO_ANT1_2422_1000~26500




11N40SISO_ANT2_2422_Ref




11N40SISO_ANT2_2422_30~1000




11N40SISO_ANT2_2422_1000~26500




11N40SISO_ANT1_2437_Ref




11N40SISO_ANT1_2437_30~1000




11N40SISO_ANT1_2437_1000~26500




11N40SISO_ANT2_2437_Ref




11N40SISO_ANT2_2437_30~1000




11N40SISO_ANT2_2437_1000~26500




11N40SISO_ANT1_2452_Ref




11N40SISO_ANT1_2452_30~1000




11N40SISO_ANT1_2452_1000~26500




11N40SISO_ANT2_2452_Ref



11N40SISO_ANT2_2452_30~1000




11N40SISO_ANT2_2452_1000~26500




8. Radiated Spurious Emissions

8.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9 kHz-30 MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

8.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

8.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

8.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions or comply with 15.209 limits.

8.3. Test Procedure

(1) EUT height should be 0.8 m for below 1 GHz at a semi-anechoic chamber while EUT height should be 1.5 m for above 1 GHz at full chamber or semi-anechoic chamber ground with absorbers.

(2) The antenna used as below table.

Test frequency range	Test antenna used	Measuring distance
9 kHz-30 MHz	Active Loop antenna	3 m
30 MHz-1 GHz	Trilog Broadband Antenna	3 m
1 GHz-18 GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3 m
18 GHz-40 GHz	Horn Antenna(18GHz-40GHz)	1 m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also

be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30 MHz, the Trilog Broadband Antenna or Horn Antenna was located 3 m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9kHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9-90 kHz, 110-490 kHz, for emissions from 9 kHz-90 kHz, 110 kHz-490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9 kHz-150 kHz	200 Hz
150 kHz-30 MHz	9 kHz
30 MHz-1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; RMS detector RBW 1 MHz VBW 10 Hz for Average measure (according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).

8.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limit.

Note1: According exploratory test no any obvious emission was detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.


Note2: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in ANT1, 11g, Tx CH11 mode.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#	D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\FCC BELOW1G.EM6
Test Date : 2019-06-17	Tested By : Talent
EUT : WIRELESS SPEAKER	Model Number : LINK PORTABLE
Power Supply : Battery	Test Mode : TX mode
Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa	Antenna/Distance : 2018 VULB 9163 1#/3m/VERTICAL
Memo : 2.4G	

Data: 5



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	50.06	1.20	14.58	3.87	19.65	40.00	-20.35	QP	VERTICAL
2	105.64	1.95	11.76	4.23	17.94	43.50	-25.56	QP	VERTICAL
3	245.09	6.17	12.70	4.98	23.85	46.00	-22.15	QP	VERTICAL
4	378.58	3.69	15.29	5.44	24.42	46.00	-21.58	QP	VERTICAL
5	642.86	3.83	19.22	6.22	29.27	46.00	-16.73	QP	VERTICAL
6	801.79	3.26	20.72	6.61	30.59	46.00	-15.41	QP	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
 2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
 3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\FCC BELOW1G.EM6

Test Date : 2019-06-17

Tested By : Talent

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 VULB 9163 1#/3m/HORIZONTAL

Memo : 2.4G

Data: 6



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	49.88	1.25	14.59	3.87	19.71	40.00	-20.29	QP	HORIZONTAL
2	102.72	0.78	11.73	4.22	16.73	43.50	-26.77	QP	HORIZONTAL
3	250.30	1.10	12.84	5.00	18.94	46.00	-27.06	QP	HORIZONTAL
4	378.58	4.24	15.29	5.44	24.97	46.00	-21.03	QP	HORIZONTAL
5	699.31	2.35	20.09	6.38	28.82	46.00	-17.18	QP	HORIZONTAL
6	968.93	1.76	22.47	7.06	31.29	54.00	-22.71	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector type	Polarization
11g CH1									
5556.00	41.25	34.35	44.08	11.06	42.58	74.00	-31.42	Peak	HORIZONTAL
7477.00	39.74	35.89	43.31	13.14	45.46	74.00	-28.54	Peak	HORIZONTAL
8395.00	40.68	36.70	43.32	13.55	47.61	74.00	-26.39	Peak	HORIZONTAL
10690.00	42.17	37.62	43.90	15.85	51.74	74.00	-22.26	Peak	HORIZONTAL
12254.00	40.01	38.05	43.50	18.09	52.65	74.00	-21.35	Peak	HORIZONTAL
12832.00	39.51	38.23	43.36	18.69	53.07	74.00	-20.93	Peak	HORIZONTAL
5624.00	41.33	34.40	44.07	11.18	42.84	74.00	-31.16	Peak	VERTICAL
7358.00	39.46	35.82	43.36	12.91	44.83	74.00	-29.17	Peak	VERTICAL
8412.00	41.06	36.71	43.33	13.62	48.06	74.00	-25.94	Peak	VERTICAL
9891.00	40.66	37.34	44.05	15.17	49.12	74.00	-24.88	Peak	VERTICAL
11064.00	42.18	37.64	43.80	16.34	52.36	74.00	-21.64	Peak	VERTICAL
5624.00	41.33	34.40	44.07	11.18	42.84	74.00	-31.16	Peak	VERTICAL
11g CH6									
5607.00	41.37	34.39	44.07	11.18	42.87	74.00	-31.13	Peak	HORIZONTAL
7409.00	41.00	35.85	43.34	13.09	46.60	74.00	-27.40	Peak	HORIZONTAL
9024.00	39.55	36.82	43.64	14.37	47.10	74.00	-26.90	Peak	HORIZONTAL
10384.00	40.56	37.63	43.99	15.46	49.66	74.00	-24.34	Peak	HORIZONTAL
11625.00	38.88	38.45	43.65	17.23	50.91	74.00	-23.09	Peak	HORIZONTAL
12815.00	39.53	38.23	43.37	18.67	53.06	74.00	-20.94	Peak	HORIZONTAL
4808.00	41.87	33.79	44.24	11.23	42.65	74.00	-31.35	Peak	VERTICAL
6882.00	39.24	35.53	43.57	12.33	43.53	74.00	-30.47	Peak	VERTICAL
8412.00	41.33	36.71	43.33	13.62	48.33	74.00	-25.67	Peak	VERTICAL
9908.00	40.72	37.35	44.06	15.24	49.25	74.00	-24.75	Peak	VERTICAL
11302.00	41.79	38.17	43.74	16.72	52.94	74.00	-21.06	Peak	VERTICAL
12798.00	40.23	38.22	43.37	18.65	53.73	74.00	-20.27	Peak	VERTICAL
11g CH11									
4774.00	40.27	33.77	44.24	11.01	40.81	74.00	-33.19	Peak	HORIZONTAL
6236.00	39.88	34.99	43.88	12.12	43.11	74.00	-30.89	Peak	HORIZONTAL
7443.00	40.00	35.87	43.33	13.11	45.65	74.00	-28.35	Peak	HORIZONTAL
8446.00	40.25	36.75	43.34	13.79	47.45	74.00	-26.55	Peak	HORIZONTAL
9908.00	40.59	37.35	44.06	15.24	49.12	74.00	-24.88	Peak	HORIZONTAL
12713.00	40.40	38.19	43.39	18.56	53.76	74.00	-20.24	Peak	HORIZONTAL
5590.00	41.03	34.37	44.08	11.15	42.47	74.00	-31.53	Peak	VERTICAL
7443.00	40.59	35.87	43.33	13.11	46.24	74.00	-27.76	Peak	VERTICAL
8956.00	40.31	36.80	43.61	14.19	47.69	74.00	-26.31	Peak	VERTICAL
10401.00	40.87	37.64	43.98	15.48	50.01	74.00	-23.99	Peak	VERTICAL
11761.00	40.37	38.28	43.62	17.45	52.48	74.00	-21.52	Peak	VERTICAL
12866.00	39.91	38.25	43.35	18.72	53.53	74.00	-20.47	Peak	VERTICAL

Note: 1.30MHz~25GHz: (Scan with 11b mode ANT 1 and ANT 2, 11g mode ANT 1 and ANT 2, 11n HT20 mode ANT 1 and ANT 2, 11n HT40 mode ANT 1 and ANT 2, the worst case is 11g ANT 1 mode)


2. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

4. For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

9. Radiated Band Edge Compliance

9.1. Block diagram of test setup



9.2. Limit

All restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400 MHz to 2483.5 MHz shall be at least 20dB below the fundamental emissions or comply with RSS-Gen Issue 3 clause 7.2.5 (Same as FCC 15.209) limits.

9.3. Test Procedure

Same with clause 8.3 except change investigated frequency range from 2310 MHz to 2430 MHz and 2445 MHz to 2500 MHz, 2310 MHz to 2450 MHz and 2425 MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worst case is shown in report.

9.4. Test result

PASS. (See below detailed test result)

Note: 11b, 11g, n20, n40 mode ANT 1 and ANT 2 mode all have been tested, only Ant 1 mode is worse case and reported.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : 11b 2412MHz

Data: 26



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2351.76	56.39	29.03	44.16	4.58	45.84	74.00	-28.16	Peak	VERTICAL
2	2390.04	53.63	29.10	44.18	4.56	43.11	74.00	-30.89	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : 11b 2412MHz

Data: 27



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2385.12	55.70	29.09	44.17	4.57	45.19	74.00	-28.81	Peak	HORIZONTAL
2	2390.04	53.54	29.10	44.18	4.56	43.02	74.00	-30.98	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : 11b 2462MHz

Data: 28



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	52.97	29.27	44.21	4.89	42.92	74.00	-31.08	Peak	VERTICAL
2	2492.85	54.68	29.29	44.22	4.93	44.68	74.00	-29.32	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : 11b 2462MHz

Data: 29



Item (Mark)	Freq. (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	53.71	29.27	44.21	4.89	43.66	74.00	-30.34	Peak	HORIZONTAL
2	2499.51	56.32	29.30	44.22	4.96	46.36	74.00	-27.64	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : 11G 2412MHz

Data: 30



Item (Mark)	Freq. (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Detector	Polarization
1	2389.30	63.86	29.10	44.18	4.56	53.34	74.00	-20.66	Peak	HORIZONTAL
2	2390.00	64.08	29.10	44.18	4.56	53.56	74.00	-20.44	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : 11G 2412MHz

Data: 31



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2383.06	61.03	29.09	44.17	4.57	50.52	74.00	-23.48	Peak	VERTICAL
2	2390.00	64.07	29.10	44.18	4.56	53.55	74.00	-20.45	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : 11G 2462MHz

Data: 32



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.60	29.27	44.21	4.89	41.55	54.00	-12.45	Average	VERTICAL
2	2483.50	65.19	29.27	44.21	4.89	55.14	74.00	-18.86	Peak	VERTICAL
3	2484.05	50.22	29.27	44.21	4.90	40.18	54.00	-13.82	Average	VERTICAL
4	2484.05	65.89	29.27	44.21	4.90	55.85	74.00	-18.15	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : 11G 2462MHz

Data: 33



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	50.30	29.27	44.21	4.89	40.25	54.00	-13.75	Average	HORIZONTAL
2	2483.50	65.48	29.27	44.21	4.89	55.43	74.00	-18.57	Peak	HORIZONTAL
3	2484.05	49.86	29.27	44.21	4.90	39.82	54.00	-14.18	Average	HORIZONTAL
4	2484.05	66.12	29.27	44.21	4.90	56.08	74.00	-17.92	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : 11N20 2412MHz

Data: 34



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2388.39	49.12	29.10	44.18	4.56	38.60	54.00	-15.40	Average	VERTICAL
2	2388.39	66.92	29.10	44.18	4.56	56.40	74.00	-17.60	Peak	VERTICAL
3	2390.00	51.01	29.10	44.18	4.56	40.49	54.00	-13.51	Average	VERTICAL
4	2390.00	64.53	29.10	44.18	4.56	54.01	74.00	-19.99	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : 11N20 2412MHz

Data: 35



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2389.17	49.25	29.10	44.18	4.56	38.73	54.00	-15.27	Average	HORIZONTAL
2	2389.17	66.31	29.10	44.18	4.56	55.79	74.00	-18.21	Peak	HORIZONTAL
3	2390.00	50.69	29.10	44.18	4.56	40.17	54.00	-13.83	Average	HORIZONTAL
4	2390.00	67.29	29.10	44.18	4.56	56.77	74.00	-17.23	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : 11N20 2462MHz

Data: 36



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	50.64	29.27	44.21	4.89	40.59	54.00	-13.41	Average	HORIZONTAL
2	2483.50	65.17	29.27	44.21	4.89	55.12	74.00	-18.88	Peak	HORIZONTAL
3	2484.93	49.87	29.27	44.21	4.90	39.83	54.00	-14.17	Average	HORIZONTAL
4	2484.93	65.85	29.27	44.21	4.90	55.81	74.00	-18.19	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : 11N20 2462MHz

Data: 37



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	50.86	29.27	44.21	4.89	40.81	54.00	-13.19	Average	VERTICAL
2	2483.50	64.92	29.27	44.21	4.89	54.87	74.00	-19.13	Peak	VERTICAL
3	2484.27	49.23	29.27	44.21	4.90	39.19	54.00	-14.81	Average	VERTICAL
4	2484.27	65.90	29.27	44.21	4.90	55.86	74.00	-18.14	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : 11N40 2422MHz

Data: 38



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2387.98	54.00	29.09	44.17	4.56	43.48	54.00	-10.52	Average	VERTICAL
2	2387.98	77.95	29.09	44.17	4.56	67.43	74.00	-6.57	Peak	VERTICAL
3	2390.00	56.01	29.10	44.18	4.56	45.49	54.00	-8.51	Average	VERTICAL
4	2390.00	76.70	29.10	44.18	4.56	66.18	74.00	-7.82	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : 11N40 2422MHz

Data: 39



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2389.38	54.68	29.10	44.18	4.56	44.16	54.00	-9.84	Average	HORIZONTAL
2	2389.38	77.92	29.10	44.18	4.56	67.40	74.00	-6.60	Peak	HORIZONTAL
3	2390.00	55.85	29.10	44.18	4.56	45.33	54.00	-8.67	Average	HORIZONTAL
4	2390.00	74.09	29.10	44.18	4.56	63.57	74.00	-10.43	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/HORIZONTAL

Memo : 11N40 2452MHz

Data: 40



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	54.61	29.27	44.21	4.89	44.56	54.00	-9.44	Average	HORIZONTAL
2	2483.50	74.99	29.27	44.21	4.89	64.94	74.00	-9.06	Peak	HORIZONTAL
3	2494.45	63.51	29.29	44.22	4.94	53.52	74.00	-20.48	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber 1#

D:\2019 RE1# Report Data\Q19031903-1E LINK PORTABLE AGAIN\LINK PORTABLE AGAIN\RF.EM6

Test Date : 2019-06-16

Tested By : Sunny

EUT : WIRELESS SPEAKER

Model Number : LINK PORTABLE

Power Supply : Battery


Test Mode : TX mode

Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa

Antenna/Distance : 2018 HF 907/3m/VERTICAL

Memo : 11N40 2452MHz

Data: 41



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	54.82	29.27	44.21	4.89	44.77	54.00	-9.23	Average	VERTICAL
2	2483.50	74.81	29.27	44.21	4.89	64.76	74.00	-9.24	Peak	VERTICAL
3	2498.05	62.10	29.30	44.22	4.95	52.13	74.00	-21.87	Peak	VERTICAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

10. Power Line Conducted Emission

10.1. Block diagram of test setup



10.2. Power Line Conducted Emission Limits (Class B)

Frequency	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150 kHz ~ 500 kHz	66 ~ 56*	56 ~ 46*
500 kHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

10.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

10.4. Test Result

PASS. (See below detailed test result)


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: “----” means peak detection; “-----” means average detection

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/60Hz, recorded worse case.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room D:\2019 CE report data\Q19031903-1E\CE-1.EM6
Test Date : 2019-06-19 **Tested By** : Elosky
EUT : WIRELESS SPEAKER **Model Number** : LINK PORTABLE
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa **LISN** : 2018 ENV216/LINE
Memo :




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.21	18.81	9.63	0.02	9.86	38.32	63.32	-25.00	QP	LINE
2	0.21	10.63	9.63	0.02	9.86	30.14	53.32	-23.18	Average	LINE
3	0.35	17.20	9.63	0.02	9.86	36.71	59.00	-22.29	QP	LINE
4	0.35	5.13	9.63	0.02	9.86	24.64	49.00	-24.36	Average	LINE
5	0.63	23.05	9.64	0.03	9.86	42.58	56.00	-13.42	QP	LINE
6	0.63	8.89	9.64	0.03	9.86	28.42	46.00	-17.58	Average	LINE
7	0.76	18.37	9.64	0.04	9.86	37.91	56.00	-18.09	QP	LINE
8	0.76	3.01	9.64	0.04	9.86	22.55	46.00	-23.45	Average	LINE
9	1.18	14.91	9.64	0.09	9.87	34.51	56.00	-21.49	QP	LINE
10	1.18	1.27	9.64	0.09	9.87	20.87	46.00	-25.13	Average	LINE
11	1.63	13.41	9.65	0.07	9.87	33.00	56.00	-23.00	QP	LINE
12	1.63	1.69	9.65	0.07	9.87	21.28	46.00	-24.72	Average	LINE

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site : DDT 1# Shield Room D:\2019 CE report data\Q19031903-1E\CE-1.EM6
Test Date : 2019-06-19 **Tested By** : Elosky
EUT : WIRELESS SPEAKER **Model Number** : LINK PORTABLE
Power Supply : AC 120V/60Hz **Test Mode** : Tx mode
Condition : Temp:24.5°C,Humi:55%,Press:100.1kPa **LISN** : 2018 ENV216/NEUTRAL
Memo :



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.21	17.53	9.64	0.02	9.86	37.05	63.40	-26.35	QP	NEUTRAL
2	0.21	5.73	9.64	0.02	9.86	25.25	53.40	-28.15	Average	NEUTRAL
3	0.27	13.67	9.64	0.02	9.86	33.19	60.98	-27.79	QP	NEUTRAL
4	0.27	2.17	9.64	0.02	9.86	21.69	50.98	-29.29	Average	NEUTRAL
5	0.56	11.04	9.64	0.03	9.86	30.57	56.00	-25.43	QP	NEUTRAL
6	0.56	0.55	9.64	0.03	9.86	20.08	46.00	-25.92	Average	NEUTRAL
7	0.62	13.88	9.64	0.03	9.86	33.41	56.00	-22.59	QP	NEUTRAL
8	0.62	1.71	9.64	0.03	9.86	21.24	46.00	-24.76	Average	NEUTRAL
9	0.76	10.51	9.64	0.04	9.86	30.05	56.00	-25.95	QP	NEUTRAL
10	0.76	-1.39	9.64	0.04	9.86	18.15	46.00	-27.85	Average	NEUTRAL
11	1.20	6.82	9.65	0.09	9.87	26.43	56.00	-29.57	QP	NEUTRAL
12	1.20	-4.37	9.65	0.09	9.87	15.24	46.00	-30.76	Average	NEUTRAL

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto

11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The antennas used for this product are dedicated antennas and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 2.89 dBi.

END OF REPORT