

# TEST REPORT

**Application No.:** SZCR2305001403AT  
**Applicant:** Harman International Industries, Inc.  
**Address of Applicant:** 8500 Balboa Boulevard, Northridge, California, 91329, United States  
**Manufacturer:** Harman International Industries, Inc.  
**Address of Manufacturer:** 8500 Balboa Boulevard, Northridge, California, 91329, United States  
**Factory:**  
1. Cosonic Electroacoustic Technology Co., Ltd.  
2. COSONIC VIETNAM COMPANY LIMITED  
3. Jiangxi Cosonic Electroacoustic Technologies Co., Ltd.  
**Address of Factory:**  
1. No.151, Shipai Section, Dongyuan Avenue, Shipai Town, Dongguan City, Guangdong Province, P.R.China  
2. Lot C5-1, Ba Thien II Industrial Park, Thien Ke Ward, Binh Xuyen District, Vinh Phuc Province, Vietnam  
3. Shangli Industrial Park, Jinshan Town, Shangli County, Pingxiang, 337009 Jiangxi, P.R. China

### Equipment Under Test (EUT):

**EUT Name:** Bluetooth headset  
**Model No.:** LIVE670NC  
**Trade Mark:** JBL  
**FCC ID:** APILIVE670NC  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2023-05-10  
**Date of Test:** 2023-05-16 to 2023-05-18  
**Date of Issue:** 2023-05-24

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2023-05-24		Original

Authorized for issue by:			
		<i>Benson Wang</i>	
		_____	
		<b>Benson Wang/Project Engineer</b>	
		<i>Eric Fu</i>	
		_____	
		<b>Eric Fu/Reviewer</b>	



## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass



### 3 Contents

	Page
<b>1 Cover Page</b> .....	<b>1</b>
<b>2 Test Summary</b> .....	<b>3</b>
<b>3 Contents</b> .....	<b>4</b>
<b>4 General Information</b> .....	<b>6</b>
4.1 Details of E.U.T. ....	6
4.2 Description of Support Units .....	6
4.3 Measurement Uncertainty .....	6
4.4 Test Location.....	7
4.5 Test Facility .....	7
4.6 Deviation from Standards.....	7
4.7 Abnormalities from Standard Conditions .....	7
<b>5 Equipment List</b> .....	<b>8</b>
<b>6 Radio Spectrum Technical Requirement</b> .....	<b>11</b>
6.1 Antenna Requirement .....	11
6.1.1 Test Requirement: .....	11
6.1.2 Conclusion .....	11
<b>7 Radio Spectrum Matter Test Results</b> .....	<b>12</b>
7.1 Radiated Emissions which fall in the restricted bands .....	12
7.1.1 E.U.T. Operation .....	12
7.1.2 Test Mode Description .....	12
7.1.3 Test Setup Diagram .....	13
7.1.4 Measurement Procedure and Data.....	13
7.2 Radiated Spurious Emissions Below 1GHz .....	22
7.2.1 E.U.T. Operation .....	22
7.2.2 Test Mode Description .....	22
7.2.3 Test Setup Diagram .....	23
7.2.4 Measurement Procedure and Data.....	23
7.3 Radiated Spurious Emissions Above 1GHz.....	28
7.3.1 E.U.T. Operation .....	28
7.3.2 Test Mode Description .....	28
7.3.3 Test Setup Diagram .....	28
7.3.4 Measurement Procedure and Data.....	29
7.4 Conducted Peak Output Power.....	42
7.4.1 E.U.T. Operation .....	42
7.4.2 Test Mode Description .....	42
7.4.3 Test Setup Diagram .....	43
7.4.4 Measurement Procedure and Data.....	43
7.5 Minimum 6dB Bandwidth .....	44



7.5.1	E.U.T. Operation .....	44
7.5.2	Test Mode Description .....	44
7.5.3	Test Setup Diagram .....	44
7.5.4	Measurement Procedure and Data.....	44
7.6	Power Spectrum Density.....	45
7.6.1	E.U.T. Operation .....	45
7.6.2	Test Mode Description .....	45
7.6.3	Test Setup Diagram .....	45
7.6.4	Measurement Procedure and Data.....	45
7.7	Conducted Band Edges Measurement .....	46
7.7.1	E.U.T. Operation .....	46
7.7.2	Test Mode Description .....	46
7.7.3	Test Setup Diagram .....	47
7.7.4	Measurement Procedure and Data.....	47
7.8	Conducted Spurious Emissions .....	48
7.8.1	E.U.T. Operation .....	48
7.8.2	Test Mode Description .....	48
7.8.3	Test Setup Diagram .....	49
7.8.4	Measurement Procedure and Data.....	49
<b>8</b>	<b>Test Setup Photo .....</b>	<b>50</b>
<b>9</b>	<b>EUT Constructional Details (EUT Photos) .....</b>	<b>50</b>
<b>10</b>	<b>Appendix.....</b>	<b>51</b>



## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	Rechargeable battery: 3.7V 850mAh (Charged by USB port)
Cable(s):	USB cable: 27cm unshielded AUX in cable: 131cm unshielded
Operation Frequency:	2402MHz to 2480MHz (BLE 1M/bits) 2404MHz to 2478MHz (BLE 2M/bits)
Bluetooth Version:	V5.3 Dual mode
Data Rate:	Support 1M/2M bits
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	FPC Antenna
Antenna Gain:	2.83dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

### 4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 4.5\text{dB}$
Radiated Spurious Emissions Above 1GHz	$\pm 4.8\text{dB}$
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$

Remark:

The  $U_{\text{lab}}$  (lab Uncertainty) is less than  $U_{\text{CISPR/ETSI}}$  (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### • VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### • FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

#### • Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

### 4.6 Deviation from Standards

None

### 4.7 Abnormalities from Standard Conditions

None



## 5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2022-04-02	2025-04-01
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2023-03-20	2024-03-19
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2022-07-24	2024-07-23
Microwave system amplifier	Agilent	83017A	SEM005-25	2022-09-21	2023-09-20
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2022-07-08	2023-07-07
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2022-08-10	2024-08-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2023-03-20	2024-03-19

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2021-11-30	2023-11-29
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2020-07-19	2023-07-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2022-10-20	2023-10-19
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2021-09-17	2023-09-16
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2023-03-20	2024-03-19
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2022-07-08	2023-07-07

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2022-04-02	2025-04-01
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2023-03-20	2024-03-19
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2022-07-24	2024-07-23
Microwave system amplifier	Agilent	83017A	SEM005-25	2022-09-21	2023-09-20
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2022-07-08	2023-07-07



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



<b>Conducted Peak Output Power</b>					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2023-04-01	2024-03-31
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2023-03-21	2024-03-20
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30

<b>Minimum 6dB Bandwidth</b>					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30

<b>Power Spectrum Density</b>					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30

<b>Conducted Band Edges Measurement</b>					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/0 Aug01,2022

Report No.: SZCR230500140303

Page: 10 of 77

Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30
------------	--------------	---------------	-----------	------------	------------

## Conducted Spurious Emissions

Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2022-10-20	2023-10-19
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2023-03-21	2024-03-20
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2022-07-08	2023-07-07
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2023-03-31	2024-03-30

## General used equipment

Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2022-09-04	2023-09-03
Humidity/ Temperature Indicator	Anymetre	TH101B	SEM002-09	2022-09-04	2023-09-03
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2023-03-23	2024-03-22



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Testing Center EEC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.83dBi.

Antenna location: Refer to internal photos.



## 7 Radio Spectrum Matter Test Results

### 7.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

#### 7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 20.9 °C Humidity: 60.0 % RH Atmospheric Pressure: 1010 mbar

#### 7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



### 7.1.3 Test Setup Diagram



### 7.1.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2402 Band edge  
 Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2380.865	4.24	28.72	35.64	46.98	44.30	74.00	-29.70 peak
2	2390.000	4.25	28.76	35.64	45.37	42.74	74.00	-31.26 peak
3 q	2402.000	4.26	28.81	35.64	97.53	94.96	74.00	20.96 peak



Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2402 Band edge  
 Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2374.115	4.23	28.70	35.65	48.32	45.60	74.00	-28.40 peak
2	2390.000	4.25	28.76	35.64	45.20	42.57	74.00	-31.43 peak
3 q	2402.000	4.26	28.81	35.64	94.83	92.26	74.00	18.26 peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2480 Band edge  
 Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2480.000	4.34	29.28	35.61	96.17	94.18	74.00	20.18 peak
2	2483.500	4.34	29.30	35.61	44.98	43.01	74.00	-30.99 peak
3	2484.221	4.34	29.31	35.61	47.28	45.32	74.00	-28.68 peak





Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2480 Band edge  
 Note : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2480.000	4.34	29.28	35.61	94.67	92.68	74.00	18.68 peak
2	2483.500	4.34	29.30	35.61	45.47	43.50	74.00	-30.50 peak
3	2484.021	4.34	29.30	35.61	46.94	44.97	74.00	-29.03 peak



Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2404 Band edge  
 Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2380.461	4.24	28.72	35.64	46.98	44.30	74.00	-29.70	peak
2	2390.000	4.25	28.76	35.64	45.39	42.76	74.00	-31.24	peak
3 q	2404.000	4.26	28.81	35.64	97.12	94.55	74.00	20.55	peak



Test Mode: 03; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2404 Band edge  
 Note : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2351.983	4.21	28.61	35.65	46.44	43.61	74.00	-30.39	peak
2	2390.000	4.25	28.76	35.64	44.40	41.77	74.00	-32.23	peak
3 q	2404.000	4.26	28.81	35.64	94.26	91.69	74.00	17.69	peak



Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2478 Band edge  
 Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2478.000	4.34	29.28	35.61	96.07	94.08	74.00	20.08 peak
2	2483.500	4.34	29.30	35.61	45.45	43.48	74.00	-30.52 peak
3	2496.736	4.36	29.38	35.60	47.10	45.24	74.00	-28.76 peak



Test Mode: 03; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2478 Band edge  
 Note : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	q 2478.000	4.34	29.28	35.61	94.47	92.48	74.00	18.48 peak
2	2483.500	4.34	29.30	35.61	45.20	43.23	74.00	-30.77 peak
3	2499.698	4.36	29.40	35.60	46.70	44.86	74.00	-29.14 peak



**7.2 Radiated Spurious Emissions Below 1GHz**

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209  
 Test Method: ANSI C63.10 (2013) Section 6.4,6.5  
 Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

**7.2.1 E.U.T. Operation**

Operating Environment:


Temperature: 23.2 °C Humidity: 50.5 % RH Atmospheric Pressure: 1010 mbar

**7.2.2 Test Mode Description**

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



### 7.2.3 Test Setup Diagram



### 7.2.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 02; Polarity: Horizontal




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No. : 01403AT  
 Test Mode: 02  
 : 4#

	Ant	Cable	Preamp	Read	Limit	Over		
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	40.28	15.31	0.67	27.20	25.56	14.34	40.00	-25.66 QP
2	64.66	10.68	0.89	27.12	26.01	10.46	40.00	-29.54 QP
3	104.17	12.96	1.16	26.98	29.97	17.11	43.50	-26.39 QP
4	239.99	17.80	1.86	26.44	26.41	19.63	46.00	-26.37 QP
5	472.18	22.93	2.72	26.72	25.22	24.15	46.00	-21.85 QP
6 q	760.70	26.63	3.57	26.46	28.63	32.37	46.00	-13.63 QP





Test Mode: 02; Polarity: Vertical




Site : chamber  
 Condition: 3m VERTICAL  
 Job No. : 01403AT  
 Test Mode: 02  
 : 4#

	Ant	Cable	Preamp	Read	Limit	Over		
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	63.54	10.80	0.88	27.12	29.89	14.45	40.00	-25.55 QP
2	97.46	12.91	1.13	27.01	25.04	12.07	43.50	-31.43 QP
3	154.28	13.57	1.44	26.78	24.66	12.89	43.50	-30.61 QP
4	263.82	17.85	1.96	26.34	28.12	21.59	46.00	-24.41 QP
5	480.53	23.19	2.75	26.74	25.10	24.30	46.00	-21.70 QP
6 q	742.26	26.75	3.53	26.53	26.12	29.87	46.00	-16.13 QP



Test Mode: 03; Polarity: Horizontal




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No. : 01403AT  
 Test Mode: 03  
 : 4#

	Ant	Cable	Preamp	Read	Limit	Over		
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	33.33	19.32	0.64	27.22	24.25	16.99	40.00	-23.01 QP
2	54.64	11.94	0.82	27.15	24.46	10.07	40.00	-29.93 QP
3	104.17	12.96	1.16	26.98	27.85	14.99	43.50	-28.51 QP
4	261.06	17.87	1.95	26.36	24.74	18.20	46.00	-27.80 QP
5	406.09	21.38	2.50	26.52	25.73	23.09	46.00	-22.91 QP
6 q	760.70	26.63	3.57	26.46	29.19	32.93	46.00	-13.07 QP



Test Mode: 03; Polarity: Vertical



Site : chamber  
 Condition: 3m VERTICAL  
 Job No. : 01403AT  
 Test Mode: 03  
 : 4#

	Ant	Cable	Preamp	Read	Limit	Over		
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	64.21	10.72	0.89	27.12	28.64	13.13	40.00 -26.87	QP
2	101.29	13.00	1.15	26.99	25.22	12.38	43.50 -31.12	QP
3	197.89	14.35	1.68	26.61	25.06	14.48	43.50 -29.02	QP
4	260.14	17.87	1.95	26.36	27.88	21.34	46.00 -24.66	QP
5	537.59	24.32	2.93	26.91	26.14	26.48	46.00 -19.52	QP
6 q	766.06	26.65	3.58	26.44	28.76	32.55	46.00 -13.45	QP



### 7.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 20.9 °C


Humidity: 60.0 % RH

Atmospheric Pressure: 1010 mbar

#### 7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.3.3 Test Setup Diagram



Above 1GHz



**7.3.4 Measurement Procedure and Data**


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- 2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2402 TX RSE  
 : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.47	26.77	36.44	46.39	40.19	74.00	-33.81	peak
2	4206.011	6.49	33.42	34.48	46.10	51.53	74.00	-22.47	peak
3	4804.000	7.04	33.82	34.86	43.58	49.58	74.00	-24.42	peak
4	6195.508	8.19	35.20	35.22	44.80	52.97	74.00	-21.03	peak
5	7206.000	8.52	35.80	35.95	44.17	52.54	74.00	-21.46	peak
6 q	9608.000	10.39	37.10	35.55	41.35	53.29	74.00	-20.71	peak



Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2402 TX RSE  
 : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1672.779	3.46	26.75	36.46	46.10	39.85	74.00	-34.15	peak
2	4482.150	6.75	33.50	34.66	45.18	50.77	74.00	-23.23	peak
3	4804.000	7.04	33.82	34.86	44.52	50.52	74.00	-23.48	peak
4	6756.708	8.28	35.50	35.71	44.23	52.30	74.00	-21.70	peak
5	7206.000	8.52	35.80	35.95	44.51	52.88	74.00	-21.12	peak
6 q	9608.000	10.39	37.10	35.55	41.29	53.23	74.00	-20.77	peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2440 TX RSE  
 : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	3.44	26.72	36.50	46.52	40.18	74.00	-33.82	peak
2	4254.921	6.54	33.60	34.51	45.17	50.80	74.00	-23.20	peak
3	4880.000	7.11	34.06	34.91	42.95	49.21	74.00	-24.79	peak
4	6934.778	8.31	35.67	35.86	43.95	52.07	74.00	-21.93	peak
5	7320.000	8.62	35.90	35.97	44.75	53.30	74.00	-20.70	peak
6 q	9760.000	10.45	37.20	35.56	41.67	53.76	74.00	-20.24	peak





Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:middle




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2440 TX RSE  
 : BLE 1M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1658.337	3.44	26.72	36.50	47.11	40.77	74.00	-33.23 peak
2	4291.977	6.57	33.60	34.54	45.26	50.89	74.00	-23.11 peak
3	4880.000	7.11	34.06	34.91	42.91	49.17	74.00	-24.83 peak
4	6914.763	8.31	35.63	35.84	44.92	53.02	74.00	-20.98 peak
5	7320.000	8.62	35.90	35.97	44.42	52.97	74.00	-21.03 peak
6 q	9760.000	10.45	37.20	35.56	41.86	53.95	74.00	-20.05 peak



Test Mode: 02; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2480 TX RSE  
 : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1597.181	3.37	26.47	36.64	47.29	40.49	74.00	-33.51	peak
2	4304.400	6.59	33.60	34.54	45.03	50.68	74.00	-23.32	peak
3	4960.000	7.18	34.22	34.96	43.71	50.15	74.00	-23.85	peak
4	6914.763	8.31	35.63	35.84	44.27	52.37	74.00	-21.63	peak
5	7440.000	8.73	35.90	35.99	44.28	52.92	74.00	-21.08	peak
6 q	9920.000	10.52	37.30	35.57	41.05	53.30	74.00	-20.70	peak



Test Mode: 02; Polarity: Vertical; Modulation:GFSK; Channel:High




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2480 TX RSE  
 : BLE 1M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1677.621	3.46	26.76	36.45	47.23	41.00	74.00	-33.00	peak
2	4341.886	6.62	33.60	34.57	45.51	51.16	74.00	-22.84	peak
3	4960.000	7.18	34.22	34.96	43.88	50.32	74.00	-23.68	peak
4	6914.763	8.31	35.63	35.84	44.27	52.37	74.00	-21.63	peak
5	7440.000	8.73	35.90	35.99	44.67	53.31	74.00	-20.69	peak
6	9920.000	10.52	37.30	35.57	41.05	53.30	74.00	-20.70	peak



Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; Channel:Low




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2404 TX RSE  
 : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1653.550	3.43	26.71	36.51	46.78	40.41	74.00	-33.59	peak
2	4230.396	6.51	33.52	34.49	46.27	51.81	74.00	-22.19	peak
3	4808.000	7.05	33.83	34.87	43.97	49.98	74.00	-24.02	peak
4	6855.063	8.30	35.60	35.79	43.98	52.09	74.00	-21.91	peak
5	7212.000	8.52	35.80	35.95	44.71	53.08	74.00	-20.92	peak
6 q	9616.000	10.39	37.10	35.55	41.74	53.68	74.00	-20.32	peak



Test Mode: 03; Polarity: Vertical; Modulation:GFSK; Channel:Low




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2404 TX RSE  
 : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	3.49	26.80	36.40	46.35	40.24	74.00	-33.76	peak
2	4230.396	6.51	33.52	34.49	45.46	51.00	74.00	-23.00	peak
3	4808.000	7.05	33.83	34.87	44.45	50.46	74.00	-23.54	peak
4	6470.026	8.24	35.44	35.47	44.49	52.70	74.00	-21.30	peak
5	7212.000	8.52	35.80	35.95	44.24	52.61	74.00	-21.39	peak
6 q	9616.000	10.39	37.10	35.55	41.60	53.54	74.00	-20.46	peak



Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; Channel:middle




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2440 TX RSE  
 : BLE 2M

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1672.779	3.46	26.75	36.46	46.61	40.36	74.00	-33.64 peak
2	4443.453	6.72	33.50	34.64	45.72	51.30	74.00	-22.70 peak
3	4880.000	7.11	34.06	34.91	44.77	51.03	74.00	-22.97 peak
4	6934.778	8.31	35.67	35.86	44.37	52.49	74.00	-21.51 peak
5	7320.000	8.62	35.90	35.97	43.78	52.33	74.00	-21.67 peak
6 q	9760.000	10.45	37.20	35.56	41.84	53.93	74.00	-20.07 peak



Test Mode: 03; Polarity: Vertical; Modulation:GFSK; Channel:middle




Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2440 TX RSE  
 : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	3.44	26.72	36.50	46.83	40.49	74.00	-33.51	peak
2	4430.628	6.71	33.50	34.63	46.10	51.68	74.00	-22.32	peak
3	4880.000	7.11	34.06	34.91	43.70	49.96	74.00	-24.04	peak
4	6507.536	8.24	35.52	35.50	44.68	52.94	74.00	-21.06	peak
5	7320.000	8.62	35.90	35.97	44.64	53.19	74.00	-20.81	peak
6 q	9760.000	10.45	37.20	35.56	41.14	53.23	74.00	-20.77	peak



Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; Channel:High




Site : chamber  
 Condition: 3m HORIZONTAL  
 Job No : 01403AT/01404AT  
 Mode : 2478 TX RSE  
 : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.47	26.77	36.44	45.92	39.72	74.00	-34.28	peak
2	4027.554	6.31	32.81	34.35	46.14	50.91	74.00	-23.09	peak
3	4956.000	7.17	34.21	34.95	42.71	49.14	74.00	-24.86	peak
4	6717.762	8.28	35.56	35.68	44.77	52.93	74.00	-21.07	peak
5	7434.000	8.73	35.90	35.99	44.08	52.72	74.00	-21.28	peak
6 q	9912.000	10.51	37.30	35.57	40.83	53.07	74.00	-20.93	peak





Test Mode: 03; Polarity: Vertical; Modulation:GFSK; Channel:High



Site : chamber  
 Condition: 3m VERTICAL  
 Job No : 01403AT/01404AT  
 Mode : 2478 TX RSE  
 : BLE 2M

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	3.48	26.78	36.42	46.32	40.16	74.00	-33.84	peak
2	4230.396	6.51	33.52	34.49	45.70	51.24	74.00	-22.76	peak
3	4956.000	7.17	34.21	34.95	44.41	50.84	74.00	-23.16	peak
4	6934.778	8.31	35.67	35.86	44.53	52.65	74.00	-21.35	peak
5	7434.000	8.73	35.90	35.99	44.67	53.31	74.00	-20.69	peak
6	9912.000	10.51	37.30	35.57	40.80	53.04	74.00	-20.96	peak



**7.4 Conducted Peak Output Power**

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

**7.4.1 E.U.T. Operation**

Operating Environment:

Temperature: 27.2 °C

Humidity: 46.8 % RH


Atmospheric Pressure: 1015 mbar

**7.4.2 Test Mode Description**

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



### 7.4.3 Test Setup Diagram



### 7.4.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



### 7.5 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:

≥500 kHz

#### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 27.2 °C


Humidity: 46.8 % RH

Atmospheric Pressure: 1015 mbar

#### 7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.5.3 Test Setup Diagram



#### 7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



### 7.6 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

#### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 27.2 °C


Humidity: 46.8 % RH

Atmospheric Pressure: 1015 mbar

#### 7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.6.3 Test Setup Diagram



#### 7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



**7.7 Conducted Band Edges Measurement**

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
 Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**7.7.1 E.U.T. Operation**

Operating Environment:


Temperature: 27.2 °C Humidity: 46.8 % RH Atmospheric Pressure: 1015 mbar

**7.7.2 Test Mode Description**

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.



### 7.7.3 Test Setup Diagram



### 7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



**7.8 Conducted Spurious Emissions**

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**7.8.1 E.U.T. Operation**

Operating Environment:

Temperature: 27.2 °C Humidity: 46.8 % RH Atmospheric Pressure: 1015 mbar


**7.8.2 Test Mode Description**

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	03	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.





### 7.8.3 Test Setup Diagram



### 7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details



### 8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2305001403AT

### 9 EUT Constructional Details (EUT Photos)

Refer to Appendix – External and Internal Photos for SZCR2305001403AT.



## 10 Appendix

### 1. Duty Cycle


#### 1.1 Ant1


##### 1.1.1 Test Result


Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	0.431	0.625	68.96	1.61	0.02
		2440	0.431	0.625	68.96	1.61	0.06
		2480	0.431	0.625	68.96	1.61	0.00
2M	SISO	2404	0.247	0.625	39.52	4.03	0.02
		2440	0.247	0.625	39.52	4.03	0.00
		2478	0.247	0.625	39.52	4.03	0.00



### 1.1.2 Test Graph







## 2. Bandwidth


### 2.1 OBW

#### 2.1.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)	Verdict
				Result	
1M	SISO	2402	1	1.007	Pass
		2440	1	1.009	Pass
		2480	1	1.009	Pass
2M	SISO	2404	1	2.004	Pass
		2440	1	2.004	Pass
		2478	1	2.006	Pass




### 2.1.2 Test Graph










### 2.2 6dB BW


#### 2.2.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.661	>=0.5	Pass
		2440	1	0.663	>=0.5	Pass
		2480	1	0.663	>=0.5	Pass
2M	SISO	2404	1	1.149	>=0.5	Pass
		2440	1	1.149	>=0.5	Pass
		2478	1	1.151	>=0.5	Pass



### 2.2.2 Test Graph







### 3. Maximum Conducted Output Power

#### 3.1 Power

##### 3.1.1 Test Result

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	3.94	<=30	Pass
		2440	4.50	<=30	Pass
		2480	4.84	<=30	Pass
2M	SISO	2404	3.96	<=30	Pass
		2440	4.46	<=30	Pass
		2478	4.81	<=30	Pass



## 4. Maximum Power Spectral Density

### 4.1 PSD


#### 4.1.1 Test Result


Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)		Verdict
			ANT1	Limit	
1M	SISO	2402	-10.70	<=8	Pass
		2440	-10.23	<=8	Pass
		2480	-9.77	<=8	Pass
2M	SISO	2404	-11.48	<=8	Pass
		2440	-11.00	<=8	Pass
		2478	-10.60	<=8	Pass






### 4.1.2 Test Graph







## 5. Unwanted Emissions In Non-restricted Frequency Bands


### 5.1 Ref

#### 5.1.1 Test Result

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	3.90
		2440	1	4.45
		2480	1	4.80
2M	SISO	2404	1	3.97
		2440	1	4.47
		2478	1	4.80





### 5.1.2 Test Graph



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**





5.2 CSE


5.2.1 Test Result


Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	4.80	-15.20	Pass
		2440	1	4.80	-15.20	Pass
		2480	1	4.80	-15.20	Pass
2M	SISO	2404	1	4.80	-15.20	Pass
		2440	1	4.80	-15.20	Pass
		2478	1	4.80	-15.20	Pass









### 5.2.2 Test Graph











- End of the Report -

