

BLE 1M 0CH 0mm

Measurement Report for Device, BACK, ISM 2.4 GHz Band, UID 10032 CAA, Channel 0 (2402.0MHz)

### Device under Test Properties

Model, Manufacturer Device,	Dimensions [mm] 40.0 x 40.0 x 40.0	IMEI	DUT Type Phone
--------------------------------	---------------------------------------	------	-------------------

### Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, HSL	BACK, 0.00	ISM 2.4 GHz Band	Bluetooth, 10032-CAA	2402.0, 0	7.85	1.81	39.5

### Hardware Setup

Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
Twin-SAM V8.0 (30deg probe tilt) - xxxx	HSL600-10000 Charge: xxxx, 2023-Dec-19	EX3DV4 - SN7383, 2023-06-05	DAE3 Sn427, 2023-05-17

### Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	80.0 x 80.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	10.0 x 10.0	3.1 x 3.1 x 1.2
Sensor Surface [mm]	3.0	1.4
Graded Grid	Yes	Yes
Grading Ratio	1.5	1.2
MAIA	Y	Y
Surface Detection	VMS + 6p	VMS + 6p
Scan Method	Measured	Measured

### Measurement Results

	Area Scan	Zoom Scan
Date	2023-12-19, 18:44	2023-12-19, 19:06
psSAR1g [W/kg]	0.130	0.124
psSAR10g [W/kg]	0.056	0.047
Power Drift [dB]	0.01	0.01
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		76.4
Dist 3dB Peak [mm]		4.3

### Warning(s) / Error(s)

Details	Area Scan	Zoom Scan
Warning(s)		
Error(s)		

