




3DH5\_ANT1\_2441\_Ref




3DH5\_ANT1\_2441\_30~1000




3DH5\_ANT1\_2441\_1000~26500




3DH5\_ANT1\_2480\_Ref






3DH5\_ANT1\_2480\_30~1000




3DH5\_ANT1\_2480\_1000~26500




Right side:







DH5\_ANT1\_2441\_Ref




DH5\_ANT1\_2441\_30~1000




DH5\_ANT1\_2441\_1000~26500




DH5\_ANT1\_2480\_Ref




DH5\_ANT1\_2480\_30~1000




DH5\_ANT1\_2480\_1000~26500




### 2DH5\_ANT1\_2402\_Ref




### 2DH5\_ANT1\_2402\_30~1000




### 2DH5\_ANT1\_2402\_1000~26500




2DH5\_ANT1\_2441\_Ref




2DH5\_ANT1\_2441\_30~1000




2DH5\_ANT1\_2441\_1000~26500



2DH5\_ANT1\_2480\_Ref




2DH5\_ANT1\_2480\_30~1000




2DH5\_ANT1\_2480\_1000~26500







### 3DH5\_ANT1\_2402\_Ref




### 3DH5\_ANT1\_2402\_30~1000




### 3DH5\_ANT1\_2402\_1000~26500




3DH5\_ANT1\_2441\_Ref




3DH5\_ANT1\_2441\_30~1000




3DH5\_ANT1\_2441\_1000~26500




3DH5\_ANT1\_2480\_Ref



3DH5\_ANT1\_2480\_30~1000




3DH5\_ANT1\_2480\_1000~26500



## 12. Band Edge Compliance (radiated method)

### 12.1. Block diagram of test setup



### 12.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

### 12.3. Test Procedure

Same with clause 10.3 except change investigated frequency range from 2310 MHz to 2410 MHz and 2475 MHz to 2500 MHz.

Remark: All restriction band have been tested, and only the worst case is shown in report.


### 12.4. Test result

PASS. (See below detailed test result)

Remark: hopping on and hopping off mode all have been test, hopping off mode is worse and reported only. Scan with all side, the worst case is right side recorded in this report.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/HORIZONTAL  
**Memo** : DH5 2402




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2364.70	51.69	29.40	43.19	4.31	42.21	74.00	-31.79	Peak	HORIZONTAL
2	2390.00	50.95	29.46	43.21	4.34	41.54	74.00	-32.46	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/VERTICAL  
**Memo** : DH5 2402




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2361.80	57.46	29.39	43.19	4.31	47.97	74.00	-26.03	Peak	VERTICAL
2	2390.00	51.68	29.46	43.21	4.34	42.27	74.00	-31.73	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/VERTICAL  
**Memo** : DH5 2480



Item (Mark)	Freq. (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	55.18	29.66	43.25	4.43	46.02	74.00	-27.98	Peak	VERTICAL
2	2483.88	59.73	29.67	43.25	4.43	50.58	74.00	-23.42	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#

D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6

**Test Date** : 2020-03-17

**Tested By** : Jacky

**EUT** : BLUETOOTH HEADSET

**Model Number** : REFLECT FLOW


**Power Supply** : Battery

**Test Mode** : Tx mode

**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa

**Antenna/Distance** : 2019 HF 907/3m/HORIZONTAL

**Memo** : DH5 2480



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.75	29.66	43.25	4.43	42.59	74.00	-31.41	Peak	HORIZONTAL
2	2483.70	58.58	29.66	43.25	4.43	49.42	74.00	-24.58	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#

D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6

**Test Date** : 2020-03-17

**Tested By** : Jacky

**EUT** : BLUETOOTH HEADSET

**Model Number** : REFLECT FLOW


**Power Supply** : Battery

**Test Mode** : Tx mode

**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa

**Antenna/Distance** : 2019 HF 907/3m/VERTICAL

**Memo** : 2DH5 2402



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2323.00	59.09	29.31	43.17	4.27	49.50	74.00	-24.50	Peak	VERTICAL
2	2390.00	49.71	29.46	43.21	4.34	40.30	74.00	-33.70	Peak	VERTICAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/HORIZONTAL  
**Memo** : 2DH5 2402




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2366.80	51.92	29.41	43.19	4.32	42.46	74.00	-31.54	Peak	HORIZONTAL
2	2390.00	50.91	29.46	43.21	4.34	41.50	74.00	-32.50	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# **D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6**  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/HORIZONTAL  
**Memo** : 2DH5 2480




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	55.63	29.66	43.25	4.43	46.47	74.00	-27.53	Peak	HORIZONTAL
2	2484.05	59.03	29.67	43.25	4.43	49.88	74.00	-24.12	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/VERTICAL  
**Memo** : 2DH5 2480



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	51.82	29.66	43.25	4.43	42.66	74.00	-31.34	Peak	VERTICAL
2	2484.33	53.94	29.67	43.25	4.43	44.79	74.00	-29.21	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#

D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6

**Test Date** : 2020-03-17

**Tested By** : Jacky

**EUT** : BLUETOOTH HEADSET

**Model Number** : REFLECT FLOW


**Power Supply** : Battery

**Test Mode** : Tx mode

**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa

**Antenna/Distance** : 2019 HF 907/3m/HORIZONTAL

**Memo** : 3DH5 2402



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2337.80	54.39	29.34	43.18	4.28	44.83	74.00	-29.17	Peak	HORIZONTAL
2	2390.00	50.07	29.46	43.21	4.34	40.66	74.00	-33.34	Peak	HORIZONTAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/VERTICAL  
**Memo** : 3DH5 2402




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2372.00	56.71	29.42	43.20	4.32	47.25	74.00	-26.75	Peak	VERTICAL
2	2390.00	49.91	29.46	43.21	4.34	40.50	74.00	-33.50	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# **D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6**  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/VERTICAL  
**Memo** : 3DH5 2480



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	53.05	29.66	43.25	4.43	43.89	74.00	-30.11	Peak	VERTICAL
2	2483.95	53.46	29.67	43.25	4.43	44.31	74.00	-29.69	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# **D:\2020 RE 1# Report data\Q20022505-1E REFLECT FLOW\FCC ABOVE1G.EM6**  
**Test Date** : 2020-03-17 **Tested By** : Jacky  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : Battery **Test Mode** : Tx mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2019 HF 907/3m/HORIZONTAL  
**Memo** : 3DH5 2480




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	54.54	29.66	43.25	4.43	45.38	74.00	-28.62	Peak	HORIZONTAL
2	2483.80	61.58	29.67	43.25	4.43	52.43	74.00	-21.57	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 13. Power Line Conducted Emission

### 13.1. Block diagram of test setup



### 13.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150 kHz ~ 500 kHz	66 ~ 56*	56 ~ 46*
500 kHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

### 13.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

#### 13.4. Test Result

##### **PASS. (See below detailed test result)**


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "----" means Peak detection; "-----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worse case.

# TR-4-E-010 Conducted Emission Test Result

**Test Site** : DDT 1# Shield Room D:\2020 CE report data\Q20022505-1E\20200413 CE  
**Test Date** : 2020-04-13 **Tested By** : Lori  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode  
**Condition** : Temp:24.5°C, Humi:55.5%,  
**LISN** : 2019 ENV216 1#/NEUTRAL  
 Press:100.1kPa  
**Memo** :




Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.15	20.06	9.60	0.01	9.86	39.53	66.00	-26.47	QP	NEUTRAL
2	0.15	4.37	9.60	0.01	9.86	23.84	56.00	-32.16	Average	NEUTRAL
3	0.16	17.23	9.60	0.01	9.86	36.70	65.25	-28.55	QP	NEUTRAL
4	0.16	-1.04	9.60	0.01	9.86	18.43	55.25	-36.82	Average	NEUTRAL
5	0.18	15.92	9.60	0.02	9.86	35.40	64.55	-29.15	QP	NEUTRAL
6	0.18	-1.13	9.60	0.02	9.86	18.35	54.55	-36.20	Average	NEUTRAL
7	0.19	15.59	9.60	0.02	9.86	35.07	64.02	-28.95	QP	NEUTRAL
8	0.19	-0.45	9.60	0.02	9.86	19.03	54.02	-34.99	Average	NEUTRAL
9	0.21	16.64	9.60	0.02	9.86	36.12	63.40	-27.28	QP	NEUTRAL
10	0.21	1.35	9.60	0.02	9.86	20.83	53.40	-32.57	Average	NEUTRAL
11	0.60	6.65	9.60	0.03	9.86	26.14	56.00	-29.86	QP	NEUTRAL
12	0.60	-2.77	9.60	0.03	9.86	16.72	46.00	-29.28	Average	NEUTRAL

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

# TR-4-E-010 Conducted Emission Test Result

**Test Site** : DDT 1# Shield Room D:\2020 CE report data\Q20022505-1E\20200413 CE  
**Test Date** : 2020-04-13 **Tested By** : Lori  
**EUT** : BLUETOOTH HEADSET **Model Number** : REFLECT FLOW  
**Power Supply** : AC 120V/60Hz **Test Mode** : Tx Mode  
**Condition** : Temp:24.5°C, Humi:55.5%,  
**LISN** : 2019 ENV216 1#/LINE  
 Press:100.1kPa  
**Memo** :



Item	Freq.	Read Level	LISN Factor	Cable Loss	Pulse Limiter Factor	Result Level	Limit Line	Over Limit	Detector	Phase
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)		
1	0.15	19.70	9.60	0.01	9.86	39.17	65.87	-26.70	QP	LINE
2	0.15	4.93	9.60	0.01	9.86	24.40	55.87	-31.47	Average	LINE
3	0.17	17.36	9.60	0.01	9.86	36.83	65.08	-28.25	QP	LINE
4	0.17	3.89	9.60	0.01	9.86	23.36	55.08	-31.72	Average	LINE
5	0.18	17.00	9.60	0.02	9.86	36.48	64.50	-28.02	QP	LINE
6	0.18	4.72	9.60	0.02	9.86	24.20	54.50	-30.30	Average	LINE
7	0.19	15.75	9.60	0.02	9.86	35.23	63.98	-28.75	QP	LINE
8	0.19	3.47	9.60	0.02	9.86	22.95	53.98	-31.03	Average	LINE
9	0.22	16.10	9.60	0.02	9.86	35.58	62.92	-27.34	QP	LINE
10	0.22	2.37	9.60	0.02	9.86	21.85	52.92	-31.07	Average	LINE
11	0.62	8.89	9.60	0.03	9.86	28.38	56.00	-27.62	QP	LINE
12	0.62	-0.21	9.60	0.03	9.86	19.28	46.00	-26.72	Average	LINE

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

## 14. Antenna Requirements

### 14.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 14.2. Result

The antennas used for this product are LDS antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the left side transmit antenna is 0.71dBi and right side is -0.06dBi.

**END OF REPORT**