



WHAT'S IN THE BOX

POWER ON & CONNECT

POWER ON AND AUTOMATICALLY ENTER PAIRING MODE

CHOOSE "JBL TUNE750BT" TO CONNECT

MANUAL PAIRING

POWER OFF

MANUAL PAIRING MODE

CHOOSE "JBL TUNE750BT" TO CONNECT

BUTTON COMMAND

WIRED LISTENING

MULTI-POINT CONNECTION

1. HANG UP 2. DEVICES

ENTER PAIRING MODE WITH THE 2ND DEVICE

- TO SWITCH MUSIC SOURCE, PRESS THE MIDDLE ON THE CURRENT DEVICE AND BRACKET PLAY ON THE 2ND DEVICE.
- PHONE CALL WILL ALWAYS TAKE PRIORITY.
- IF ONE IS IN CALL AND YOU WANT TO ANSWER OR POWER OFF, YOU MAY NEED TO MANUALLY DISCONNECT THE CURRENT DEVICE.
- SELECT "POWER" THIS DEVICE OR FOR BLUETOOTH DEVICES TO DISCONNECT. HOLD TO POWER.

1ST BLUETOOTH DEVICE

CHOOSE "JBL TUNE750BT" TO CONNECT

2ND BLUETOOTH DEVICE

CHARGING

CHARGE

LED BEHAVIORS

- LOW BATTERY
- CHARGING
- FULLY CHARGED
- POWER OFF
- 1ST DEVICE CONNECTED
- 2ND DEVICE CONNECTED
- BT CONNECTING
- BT CONNECTED
- ANC ON

TECH SPEC

TRANSDUCER SIZE: 10MM
FREQUENCY RANGE: 20HZ-20KHZ
SENSITIVITY (ACTIVE MODE): 100MV/PA @ 1KHZ
SENSITIVITY (PASSIVE MODE): 33.3MV/PA @ 1KHZ
TRANSDUCER IMPEDANCE: 50 OHM
MAX. WGT. (PASSIVE MODE): 400MG
TRANSDUCER SENSITIVITY: -105DB/PA
RELATIVE TRANSMITTED POWER: P_{REF}
ELECTRIC TRANSMITTED POWER: 0.5W, 1W, 2W, 5W, 10W, 20W, 50W, 100W
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)
ELECTRIC PROFILE VERSION: 2.0 (IEC 60268-17:2003)



TEST ITEM	TEST METHOD	TEST RESULT
1.1
1.2
1.3
1.4
1.5
1.6
1.7
1.8
1.9
1.10
1.11
1.12
1.13
1.14
1.15
1.16
1.17
1.18
1.19
1.20

TEST ITEM	TEST METHOD	TEST RESULT
2.1
2.2
2.3
2.4
2.5
2.6
2.7
2.8
2.9
2.10
2.11
2.12
2.13
2.14
2.15
2.16
2.17
2.18
2.19
2.20

TEST ITEM	TEST METHOD	TEST RESULT
3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9
3.10
3.11
3.12
3.13
3.14
3.15
3.16
3.17
3.18
3.19
3.20

TEST ITEM	TEST METHOD	TEST RESULT
4.1
4.2
4.3
4.4
4.5
4.6
4.7
4.8
4.9
4.10
4.11
4.12
4.13
4.14
4.15
4.16
4.17
4.18
4.19
4.20

TEST ITEM	TEST METHOD	TEST RESULT
5.1
5.2
5.3
5.4
5.5
5.6
5.7
5.8
5.9
5.10
5.11
5.12
5.13
5.14
5.15
5.16
5.17
5.18
5.19
5.20

TEST ITEM	TEST METHOD	TEST RESULT
6.1
6.2
6.3
6.4
6.5
6.6
6.7
6.8
6.9
6.10
6.11
6.12
6.13
6.14
6.15
6.16
6.17
6.18
6.19
6.20

TEST ITEM	TEST METHOD	TEST RESULT
7.1
7.2
7.3
7.4
7.5
7.6
7.7
7.8
7.9
7.10
7.11
7.12
7.13
7.14
7.15
7.16
7.17
7.18
7.19
7.20

ANATEL
Bluetooth

FPO

CE