



Radio Frequency Exposure Evaluation Report

For:
CalAmp

Model Number:
LMU3030LABL, LMU3035LABL

Product Description:
GPS tracking device with OBD support

FCC ID: APV-3030LAB
IC ID: 5843C-3030LAB

Applied Rules and Standards:
CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091),
FCC KDB 447498 D01 General RF Exposure Guidance v06
Industry Canada RSS-102, Issue 5 of March 2015

Report number: EMC_CALAM-071-18001_MPE
DATE: 2018-12-17



A2LA Accredited

IC recognized #
3462B-1

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <http://www.cetecom.com>
CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

1. Assessment

This RF Exposure evaluation report provides information about compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091), and IC standard RSS-102, under given conditions (measured or rated RF output power, antenna gain, distance towards human body of more than 20cm and multiple transmitter information as presented by the applicant). In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device meets the limits as stipulated by the above given FCC rule parts based on available specifications.

Company Name	Product Description	Model #
CalAmp	GPS tracking device with OBD support	LMU3030LABL, LMU3035LABL

Responsible for Testing Laboratory:

2018-12-17	Compliance	Cindy Li (EMC Lab Manager)	
Date	Section	Name	Signature

Responsible for the Report:

2018-12-17	Compliance	Tri Nguyen (Associate EMC Engineer)	
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

Contents

1. Assessment	2
2. Administrative Data	4
2.1. Identification of the Testing Laboratory Issuing the Test Report	4
2.2. Identification of the Client	4
2.3. Identification of the Manufacturer	4
3. Equipment under Assessment	5
4. RF Exposure Limits and FCC	6
4.1. Power Density Limits acc. to FCC 1.1310(e)	6
4.2. Power Density Limits acc. To RSS-102	6
4.3. Routine Environmental Evaluation Categorical Exclusion Limits acc. to FCC 2.1091(c) ...	6
4.4. Exemption Limits for Routine Evaluation — RF Exposure Evaluation RSS-102	6
4.5. RF Exposure Estimation (MPE Estimation)	7
5. Evaluations	8
5.1. Routine Environmental Evaluation Applicability Stand Alone transmission	8
5.2. Compliance with MPE (Power Density) limits	8
6. Routine Environmental Evaluation Applicability Simultaneous Transmission	9
7. Revision History	10

2. Administrative Data

2.1. Identification of the Testing Laboratory Issuing the Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Compliance Manager:	Cindy Li
Responsible Project Leader:	Cathy Palacios

2.2. Identification of the Client

Applicant's Name:	CalAmp
Street Address:	2177 Salk Ave, Suite 200
City/Zip Code	Carlsbad, CA 90228
Country	USA

2.3. Identification of the Manufacturer

Manufacturer's Name:	Same as Applicant
Manufacturers Address:	-----
City/Zip Code	-----
Country	-----

3. Equipment under Assessment

Model No	LMU3030LABL, LMU3035LABL
HW Version	REV C
SW Version	7.6
FCC-ID	APV-3030LAB
IC-ID	5843C-3030LAB
Product Description	GPS tracking device with OBD support
Transceiver Technology / Type(s) of Modulation	LTE Module: Telit LE910B1-SA / QPSK/16QAM Bluetooth Low Energy / GFSK GPS
Frequency Range	LTE Band 2: 1850 – 1910 MHz LTE Band 4: 1710-1755 MHz LTE Band 12: 699 – 716 MHz Bluetooth LE: 2400-2483.5 MHz
Max. declared antenna gain	Cellular: Taoglas customized antenna for LMU3030, peak gain is 2.5dBi Bluetooth LE: WLA.01, 2.4G Peak gain 2.5dBi
Co-located Transmitters/ Antennas?	LTE / BTLE
Power Supply/ Rated Operating Voltage Range	Vmin: 9 VDC/ Vnom: 12 VDC / Vmax: 16 VDC
Operating Temperature Range	-30 °C to +75 °C
Sample Revision	<input type="checkbox"/> Prototype <input checked="" type="checkbox"/> Production <input type="checkbox"/> Pre-Production
Device Category	<input checked="" type="checkbox"/> Fixed Installation <input type="checkbox"/> Mobile <input type="checkbox"/> Portable
Exposure Category	<input type="checkbox"/> Occupational/ Controlled <input checked="" type="checkbox"/> General Population/ Uncontrolled

4. RF Exposure Limits and FCC

For the specific described radio apparatus the following basic limits and rules apply

4.1. Power Density Limits acc. to FCC 1.1310(e)

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	$f \text{ (MHz)} / 1500$	30
1500 – 100.000	1.0	30

4.2. Power Density Limits acc. To RSS-102

Frequency Range (MHz)	Power density (W/m ²)	Averaging time (minutes)
300 – 6000	$0.02619 f^{0.6834}$	6

4.3. Routine Environmental Evaluation Categorical Exclusion Limits acc. to FCC 2.1091(c)

Mobile devices that operate in the Commercial Mobile Radio Services pursuant to part 20 of this chapter; the Cellular Radiotelephone Service pursuant to part 22 of this chapter; the Personal Communications Services pursuant to part 24 of this chapter; the Satellite Communications Services pursuant to part 25 of this chapter; the Miscellaneous Wireless Communications Services pursuant to part 27 of this chapter; the Maritime Services (ship earth station devices only) pursuant to part 80 of this chapter; the Specialized Mobile Radio Service, and the 3650 MHz Wireless Broadband Service pursuant to part 90 of this chapter; and the Citizens Broadband Radio Service pursuant to part 96 of this chapter are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if:

- (i) They operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more, or
- (ii) They operate at frequencies above 1.5 GHz and their ERP is 3 watts or more.

4.4. Exemption Limits for Routine Evaluation — RF Exposure Evaluation RSS-102

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} \text{ W}$ (adjusted for tune-up tolerance), where f is in MHz;

4.5. RF Exposure Estimation (MPE Estimation)

Having available the source based average output power and peak antenna gain or the ERP/EIRP of the specified device and for a known minimum distance of its radiating structures from the body of persons according to its use cases (at least 20cm) the power density at that distance can be estimated by the following formula for plane-wave equivalent conditions (far-field conditions), when ground reflection is neglected.

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (mW/cm² or W/m²)

P = power input to the antenna (mW or W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna (cm or m)

5. Evaluations

5.1. Routine Environmental Evaluation Applicability Stand Alone transmission

Transmission Mode	EIRP dBm	Duty Cycle %	Limits for Routine Environmental Evaluation Applicability, EIRP dBm	Exempt from Routine evaluation (Yes/No)
LTE Band 2	26.135	100	<33.50	Yes
LTE Band 4	25.588	100	<33.27	Yes
LTE Band 12	26.930	100	<30.61	Yes
BTLE	1.370	100	<34.27	Yes

Note1: EIRP power calculation is based on the maximum conducted output power and antenna gain for each transmission band

5.2. Compliance with MPE (Power Density) limits

Power Density Calculation							
Band of Operation MHz	EIRP dBm	Maximum Duty Cycle %	Distance cm	Power Density mW/cm ²	FCC / IC Limit mW/cm ²	percentage of limit used up	Verdict
LTE Band 2	26.135	100	20	0.0817	1.00/0.45	18.26	Pass
LTE Band 4	25.588	100	20	0.0721	1.00/0.42	16.99	Pass
LTE Band 12	26.930	100	20	0.0982	0.47/0.23	42.65	Pass
BTLE	1.370	100	20	0.0003	1.00/0.53	0.05	Pass

6. Routine Environmental Evaluation Applicability Simultaneous Transmission

Possible worst case simultaneous transmissions:

- LTE Band 4 with BTLE

Transmission Mode	Percentage of Power Density to Applicable limit for Stand Alone Operation	Sum of the percentage for the Highest Possible Simultaneous Operation	Exempt from Routine evaluation
LTE Band12 + BTLE	42.65 + 0.05	42.7	Yes

Note: Power Density to Applicable limit for Stand Alone Operation are derived from table in section 5.2

Conclusion:

- The equipment meets the MPE requirements limits for simultaneous transmission for distance greater than 20cm

7. Revision History

Date	Report Name	Changes to report	Report prepared by
2018-12-17	EMC_CALAM-071-18001_MPE	Initial Version	Tri Nguyen