



Radio Frequency Exposure Evaluation Report

For:
CalAmp

Model Name:
LMU3640LAB

Product Description:

Vehicle tracking and telemetry device

FCC ID: APV-3640LAB

IC ID: 5843A-3640LAB

Per:

CFR Part Part 1 (1.1307 & 1.1310), Part 2 (2.1091),
FCC KDB 447498 D01 General RF Exposure Guidance v06

Report number: EMC_CALAM-063-17001_FCC_IC_MPE

DATE: 10/9/2017



CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

1 Assessment

This RF Exposure evaluation report provides evidence for compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 & 1.1310), Part 2 (2.1091) and IC standard RSS-102 issue 5 under worst case conditions (measured or rated RF output power, antenna gain, distance towards human body, multiple transmitter information as presented by the applicant).

In addition, maximum antenna gain or minimum distance towards the human body is calculated, respectively, where relevant.

The device meets the limits as stipulated by the above given FCC and IC rule parts based on available specifications for worst case conditions at 20cm distance to the body.

Company	Description	Model #
CalAmp	Vehicle tracking and telemetry device	LMU3640LAB

Report reviewed by: TCB Evaluator

Peter Nevermann

10/9/2017 Compliance (Director Radio Communications and EMC)

Date	Section	Name	Signature
------	---------	------	-----------

Responsible for the Report:

Issa Ghanma

10/9/2017 Compliance (EMC Engineer)

Date	Section	Name	Signature
------	---------	------	-----------

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Address:	411 Dixon Landing Road Milpitas, CA 95035 U.S.A.
Telephone:	+1 (408) 586 6200
Fax:	+1 (405) 586-6299
Project Manager:	Laith Saman
Project Engineer:	Issa Ghanma

2.2 Identification of the Client / Manufacturer

Applicant's Name:	Calamp
Street Address:	2177 Dalk Ave, Suits 200
City/Zip Code	Carlsbad, CA 90228
Country	USA

3 Equipment under Assessment

Model #:	LMU3640LAB
HW Version :	REV A
SW Version :	6.1
FCC-ID :	APV-3640LAB
IC ID:	5843A-3640LAB
HVIN:	LMU3640LAB
PMN:	LMU-3640
Product Description:	Vehicle tracking and telemetry device
Regulatory Band:	<p>Bluetooth EDR/BDR, Bluetooth LE Nominal band: 2400 – 2483.5 MHz</p> <p>Cellular: WCDMA/UMTS FDD BAND II : 1852.4MHz – 1907.6MHz WCDMA/UMTS FDD BAND V : 826.4MHz – 846.6MHz LTE BAND 2 : 1850.7MHz ~ 1909.3MHz LTE BAND 4 : 1710.7MHz ~ 1754.3MHz LTE BAND 5 : 824.7MHz ~ 848.3MHz LTE BAND 12 : 699.7MHz – 715.3MHz LTE BAND 13 : 779.5MHz – 784.5MHz</p>
Integrated Module Info:	<p>Bluetooth EDR/BDR, Bluetooth LE Chipset name: CC2564.</p> <p>Cellular: LE910-NA1, FCC ID: RI7LE910NAV2, IC ID: 5131A-LE910NAV2</p>
Antenna Type:	<p>Bluetooth EDR/BDR, Bluetooth LE Ethertronics M830320 BT Peak Gain 1.39dBi</p> <p>Cellular: EIRP measurements from OTA testing used because antenna gain is unknown.</p>

Maximum Conducted Output Power from modular grant:	Bluetooth EDR/BDR: 11.51dBm Bluetooth LE: 8.89dBm Cellular: WCDMA Band II: 23.66 dBm WCDMA Band V: 23.59 dBm LTE Band 2: 23.4 dBm LTE Band 4: 23.11 dBm LTE Band 5: 22.9 dBm LTE Band 12: 22.94 dBm LTE Band 13: 22.88 dBm
Power Supply:	No Power supply is part of the sales package.
Rated Operating Voltage Range:	8 VDC – 32 VDC
Operating Temperature Range:	-10 ⁰ to 60 ⁰ C
Sample Revision:	<input type="checkbox"/> Prototype Unit; <input checked="" type="checkbox"/> Production Unit; <input type="checkbox"/> Pre-Production

4 RF Exposure Limits and FCC and IC Basic Rules

For the specific described radio apparatus the following basic limits and rules apply for both, FCC and IC where not indicated differently.

4.1 Power Density Limits acc. to FCC 1.1310(e) / RSS-102 i5, cl. 4:

FCC

Frequency Range (MHz)	Power density (mW/cm ²)	Averaging time (minutes)
300 – 1500	f (MHz) /1500	30
1500 – 100.000	1.0	30

IC

300 – 6000	0.02619 x f (MHz) ^{0.6834}	6
------------	-------------------------------------	---

4.2 Routine Environmental Evaluation Categorical Exclusion Limits acc. to FCC 2.109(c) / RSS-102, cl. 2.5 (rounded to 1 decimal point):

FCC

operating frequency < 1.5GHz: excluded if ERP < 1.5W / 31.8dBm (EIRP: 33.9);
 operating frequency > 1.5GHz: excluded if ERP < 3.0W / 34.8dBm (EIRP: 36.9);

IC

300MHz <= operating frequency < 6 GHz: excluded if EIRP < 0.0131 x f (MHz)^{0.6834} W

4.3 RF Exposure Estimation (MPE Estimation)

Having available the source based average output power and peak antenna gain or the ERP/EIRP of the specified device and for a known minimum distance of its radiating structures from the body of persons according to its use cases (at least 20cm) the power density at that distance can be estimated by the following formula for plane-wave equivalent conditions (far-field conditions), when ground reflection is neglected.

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)

P = power input to the antenna (mW or W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm or m)

5 Evaluations

5.1 Analysis to Exclude Routine RF Exposure evaluation for Stand Alone Operation

band	lowest frequency [MHz]	FCC EIRP limit	IC EIRP limit in W	IC EIRP limit in dBm	EIRP in dBm	Verdict
UMTS II	1850.00	36.900	2.24	33.50	28.4	Exempt
UMTS V	824.00	33.900	1.29	31.11	25.6	Exempt
LTE 2	1850.00	36.900	2.24	33.50	27.4	Exempt
LTE 4	1710.00	36.900	2.12	33.27	26.6	Exempt
LTE 5	824.00	33.900	1.29	31.11	26.2	Exempt
LTE 12	699.7	33.900	1.16	30.65	22.94	Exempt
LTE 13	777	33.900	1.24	30.94	22.88	Exempt
BT-LE	2400	36.900	2.68	34.28	10.28	Exempt
BT EDR/BDR	2400	36.900	2.68	34.28	12.9	Exempt

The single radios are exempt from routine environmental evaluation.

5.2 Analysis of RF Exposure for simultaneous transmission

- Evaluations are based on worst case power density limits for Canada.
- Calculations are made for 20cm.
- Evaluations are based on EIRP measured or calculated from known gain and conducted output power.
- Cellular and BT can transmit simultaneously

Radio	freq MHz	EIRP in W	Canada W/m2	Actual W/m2	How much of limit is used up
Band II	1852.4	0.69	4.480	1.376	30.72%
Band V	826.4	0.36	2.581	0.722	27.99%
Band 2	1852.5	0.55	4.480	1.093	24.40%
Band 2	1860	0.55	4.493	1.093	24.33%
Band 4	1710.7	0.46	4.243	0.909	21.43%
Band 4	1717.5	0.46	4.255	0.909	21.37%
Band 5	825.5	0.42	2.579	0.829	32.16%
Band 12	709	0.20	2.324	0.391	16.84%
Band 13	779.5	0.19	2.480	0.386	15.57%
BT-LE	2402	0.011	5.351	0.021	0.40%
BT EDR/BDR	2402	0.019	5.351	0.039	0.72%

Conclusion:

- The worst case simultaneous transmission is Band 5 simultaneous with BT EDR/BDR which is using 33% of a limit of 100%. The equipment is passing RF exposure requirements for 20cm distance.

6 Revision History

Date	Report Name	Changes to report	Report prepared by
10/9/2017	EMC_CALAM-063-17001_FCC_IC_MPE_NA1	Initial Release	Issa Ghanma