

## FCC ISED RF Exposure Evaluation Report

<b>Test Report Number</b>	CMP-20061702-LC-FCC-IC-MPE
<b>FCC ID</b> APV-3641MB <b>ISED ID</b> 5843C-3641MB  <b>Applicant</b> CalAmp <b>Applicant Address</b> 2177 Salk Ave, Suite 200, Carlsbad, CA 92008 USA <b>Product Name</b> Fleet Management and Tracking Device <b>Model (s)</b> LMU3641MB <b>Date of Receipt</b> 04/20/2020 <b>Date of Test</b> 04/20/2020-05/08/2020 <b>Report Issue Date</b> 06/17/2020 <b>Test Standards</b> 47 CFR §1.1307(b), 47 CFR §1.1310 RSS-102 Issue 5: March 2015  <b>Test Result</b> <b>PASS</b>	
	<p>Issued by:</p> <p><b>Vista Compliance Laboratories</b> 1261 Puerta Del Sol, San Clemente, CA 92673 USA <a href="http://www.vista-compliance.com">www.vista-compliance.com</a></p>
 <hr/> <p><b>Daniel Bruno (Test Technician)</b></p>	 <hr/> <p><b>David Zhang (Technical Manager)</b></p>
<p>This report is for the exclusive use of the applicant. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. Note that the results contained in this report pertain only to the test samples identified herein, and the results relate only to the items tested and the results that were obtained in the period between the date of initial receipt of samples and the date of issue of the report. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested and the results thereof based upon the information provided to us. The applicant has 60 days from date of issuance of this report to notify us of any material error or omission. Failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies. This report is not to be reproduced by any means except in full and in any case not without the written approval of Vista Laboratories.</p>	

### REVISION HISTORY

Report Number	Version	Description	Issued Date
CMP-20061702-LC-FCC-IC-MPE	01	Initial report	06/17/2020

**TABLE OF CONTENTS**

**1 GENERAL INFORMATION.....4**

1.1 Applicant.....4

1.2 Product information.....4

1.3 Test standard and method .....5

**2 TEST SITE INFORMATION.....5**

**3 TEST RESULTS.....6**

3.1 FCC MPE CALCULATION .....6

3.2 ISED RF Exposure Evaluation.....7

## 1 General Information

### 1.1 Applicant

<b>Applicant</b>	CalAmp
<b>Applicant address</b>	2177 Salk Ave, Suite 200, Carlsbad, CA 92008 USA
<b>Manufacturer</b>	CalAmp
<b>Manufacturer Address</b>	2177 Salk Ave, Suite 200, Carlsbad, CA 92008 USA

### 1.2 Product information

<b>Product Name</b>	Fleet Management and Tracking Device
<b>Product Description</b>	Fleet Management and Tracking Device
<b>Model Number</b>	LMU3641MB
<b>Family Models</b>	N/A
<b>Serial Number</b>	18CF06601004-0B
<b>Frequency Band</b>	BLE: 2402-2480MHz GSM850: 824.2 - 848.8 MHz GSM1900: 1850.2 - 1909.8 MHz LTE CAT-M1 Band 2: 1850.7-1909.3MHz LTE CAT-M1 Band 4: 1710.7-1754.3MHz LTE CAT-M1 Band 5: 824.7-848.3MHz LTE CAT-M1 Band 12: 699.7-715.3MHz LTE CAT-M1 Band 13: 779.5-784.5 MHz LTE CAT-M1 Band 25: 1850.7 - 1914.3 MHz
<b>Type of modulation</b>	BLE: GFSK GSM: GMSK, 8PSK LTE CAT-M1: QPSK, 16QAM
<b>Equipment Class</b>	DTS, PCB
<b>Antenna Information</b>	Bluetooth ceramic antenna, peak Gain: 1.88dBi; P/N: 1001312 Cellular LPWA antenna: peak gain: 0.89dBi; P/N: MA220.LB.001
<b>Clock Frequencies</b>	N/A
<b>Input Power</b>	Vehicle Battery powered: 12-24VDC
<b>Power Adapter Manufacturer/Model</b>	N/A
<b>Power Adapter SN</b>	N/A
<b>Hardware version</b>	N/A
<b>Software version</b>	N/A
<b>Simultaneous Transmission</b>	BT and GSM/LTE can transmit simultaneously. GSM/LTE antenna is more than 20 cm away from BLE module/antenna. They're not co-located with each other.
<b>Additional Info</b>	EMC Emission Class B

### 1.3 Test standard and method

<b>Test standard</b>	47 CFR §1.1307(b), 47 CFR §1.1310 RSS-102 Issue 5: March 2015
<b>Test method</b>	47 CFR §1.1307(b), 47 CFR §1.1310 RSS-102 Issue 5: March 2015

## 2 Test Site Information

<b>Lab performing tests</b>	Vista Laboratories, Inc.
<b>Lab Address</b>	1261 Puerta Del Sol, San Clemente, CA 92673 USA
<b>Phone Number</b>	+1 (949) 393-1123
<b>Website</b>	www.vista-compliance.com

Test Condition	Temperature	Humidity	Atmospheric Pressure
RF Testing	23.5°C	58.2%	996 mbar
Radiated Emission Testing	23.5°C	58.2%	996 mbar

### 3 Test Results

#### 3.1 FCC MPE CALCULATION

RF Exposure Requirements: 47 CFR §1.1307(b)  
 RF Radiation Exposure Limits: 47 CFR §1.1310  
 RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65  
 EUT Frequency Band:

BLE: 2402-2480MHz  
 GSM850: 824.2 - 848.8 MHz  
 GSM1900: 1850.2 - 1909.8 MHz  
 LTE CAT-M1 Band 2: 1850.7-1909.3MHz  
 LTE CAT-M1 Band 4: 1710.7-1754.3MHz  
 LTE CAT-M1 Band 5: 824.7-848.3MHz  
 LTE CAT-M1 Band 12: 699.7-715.3MHz  
 LTE CAT-M1 Band 13: 779.5-784.5 MHz  
 LTE CAT-M1 Band 25: 1850.7 - 1914.3 MHz

Limits for General Population/Uncontrolled Exposure in the band of: 300 - 1500 MHz,  
 Power Density Limit: f/1500 mW/cm<sup>2</sup>

Limits for General Population/Uncontrolled Exposure in the band of: 1500 - 100,000 MHz  
 Power Density Limit: 1 mW / cm<sup>2</sup>

Equation:  $S = PG / 4\pi R^2$  or  $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

Prediction distance 20 cm

Radio	Frequency (MHz)	Max Conducted Output Power (dBm)	Antenna Gain (dBi)	Separation distance (cm)	Power Density (mW/ cm <sup>2</sup> )	MPE Limit (mW/ cm <sup>2</sup> )
BLE	2402-2480	5.43	1.88	20	0.001	1
GSM850	824.2-848.8	23.97	0.89	20	0.061	0.549
GSM1900	1850.2-1909.8	20.97	0.89	20	0.031	1
LTE Band2	1850.7-1909.3	24.00	0.89	20	0.061	1
LTE Band4	1710.7-1754.3	23.00	0.89	20	0.049	1
LTE Band5	824.7-848.3	24.00	0.89	20	0.061	0.550
LTE Band12	699.7-715.3	24.00	0.89	20	0.061	0.466
LTE Band13	779.5-784.5	24.00	0.89	20	0.061	0.520
LTE Band25	1850.7-1914.3	25.00	0.89	20	0.077	1

The above results show that the device complies with the MPE requirement.

### 3.2 ISED RF Exposure Evaluation

RF Exposure Requirements:

RF Radiation Exposure Limits:

RF Radiation Exposure Guidelines:

EUT Frequency Band:

RSS-102 Issue 5: March 2015

RSS-102 Issue 5: March 2015

RSS-102 Issue 5: March 2015

BLE: 2402-2480MHz

GSM850: 824.2 - 848.8 MHz

GSM1900: 1850.2 - 1909.8 MHz

LTE CAT-M1 Band 2: 1850.7-  
1909.3MHz

LTE CAT-M1 Band 4: 1710.7-  
1754.3MHz

LTE CAT-M1 Band 5: 824.7-848.3MHz

LTE CAT-M1 Band 12: 699.7-715.3MHz

LTE CAT-M1 Band 13: 779.5-784.5

MHz

LTE CAT-M1 Band 25: 1850.7 - 1914.3  
MHz

Limits for General Population/Uncontrolled Exposure in the band of:

300 - 6,000 MHz

Exemption limit for Routine Evaluation:

$1.31 \times 10^{-2} f_{0.6834} W$

Radio	Frequency (MHz)	Max Conducted Output Power (dBm)	Antenna Gain (dBi)	Max E.I.R.P (dBm)	Max E.I.R.P (W)	Evaluation Exemption limit (W)
BLE	2402-2480	5.43	1.88	7.31	0.005	2.676
GSM850	824.2-848.8	23.97	0.89	24.86	0.306	1.289
GSM1900	1850.2-1909.8	20.97	0.89	21.86	0.153	2.239
LTE Band2	1850.7-1909.3	24.00	0.89	24.89	0.308	2.240
LTE Band4	1710.7-1754.3	23.00	0.89	23.89	0.245	2.122
LTE Band5	824.7-848.3	24.00	0.89	24.89	0.308	1.289
LTE Band12	699.7-715.3	24.00	0.89	24.89	0.308	1.152
LTE Band13	779.5-784.5	24.00	0.89	24.89	0.308	1.240
LTE Band25	1850.7-1914.3	25.00	0.89	25.89	0.388	2.240

The above results show that the E.I.R.P of this device is below the exemption limit for Routine Evaluation.