




Test CH11: 2462MHz



6. BAND EDGE COMPLIANCE TEST

6.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3mChamber(Svswr)	AUDIX	N/A	N/A	Aug.09,22	3Year
2.	3mChamber(SE)	AUDIX	N/A	N/A	Sep.16,22	3Year
3.	Signal Analyzer	Rohde & Schwarz	FSV30	104050	Apr.01,23	1 Year
4.	Amplifier	EMCI	EMC0518A45SE	980965	Aug.25,23	1 Year
5.	RF Cable	Shanghaichaoyu	SFT205-NMSM-10.00M	689241	Aug.25,23	1 Year
6.	Test Software	AUDIX	e3	6.100913a	N/A	N/A
7.	Horn Antenna	ETC	MCTD 1209	DRH15F03006	Aug.23,23	1 Year

Note: N/A means Not applicable.

6.2. Limit


All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

6.3. Test Procedure

1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO

6.4. Test Results

Pass (The testing data was attached in the next pages.)



```


Site no.      : 3m Chamber                      Data no.   : 1
Dis. / Ant.   : 3m 2023 MCTD1209-3006         Ant. pol.  : VERTICAL
Limit        : FCC PART 15C PEAK
Env. / Ins.   : 23.2*C/52.5%                  Engineer   : nier
Test Mode    : 2.4G 11b 2412MHz TX
:
:

```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Emission Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	50.88	48.99	74.00	25.01	Peak
2	2410.97	27.64	4.87	34.36	101.98	100.13	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
2. The emission levels that are 20dB below the official limit are not reported.

Data: 2 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 2
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11b 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	47.76	45.87	74.00	28.13	Peak
2	2410.97	27.64	4.87	34.36	96.36	94.51	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.


Data: 3 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17



Site no. : 3m Chamber Data no. : 3
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11b 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	36.76	34.87	54.00	19.13	Average
2	2411.20	27.64	4.87	34.36	93.76	91.91	-----	-----	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.



```


Site no.      : 3m Chamber                      Data no.   : 4
Dis. / Ant.  : 3m 2023 MCTD1209-3006          Ant. pol.  : VERTICAL
Limit        : FCC PART 15C AV
Env. / Ins.  : 23.2*C/52.5%                    Engineer   : nier
Test Mode    : 2.4G 11b 2412MHz TX
:
:

```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Emission Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	38.17	36.28	54.00	17.72	Average
2	2411.20	27.64	4.87	34.36	97.04	95.19	-----	-----	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 5 File: F:\2023 Report\TPVA\1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 5
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11b 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.20	27.80	4.92	34.35	98.20	96.57	-----	-----	Peak
2	2483.50	27.80	4.94	34.35	48.86	47.25	74.00	26.75	Peak
3	2500.00	27.80	4.95	34.35	47.00	45.40	74.00	28.60	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 6 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 6
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11b 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.26	27.80	4.92	34.35	100.38	98.75	-----	-----	Peak
2	2483.50	27.80	4.94	34.35	50.01	48.40	74.00	25.60	Peak
3	2500.00	27.80	4.95	34.35	46.92	45.32	74.00	28.68	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 7 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 7
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11b 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2461.22	27.80	4.92	34.35	97.36	95.73	-----	-----	Average
2	2483.50	27.80	4.94	34.35	42.45	40.84	54.00	13.16	Average
3	2500.00	27.80	4.95	34.35	36.05	34.45	54.00	19.55	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 8 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 8
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11b 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2461.22	27.80	4.92	34.35	93.65	92.02	-----	-----	Average
2	2483.50	27.80	4.94	34.35	39.10	37.49	54.00	16.51	Average
3	2500.00	27.80	4.95	34.35	34.91	33.31	54.00	20.69	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 9 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 9
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11g 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	47.39	45.50	54.00	8.50	Average
2	2411.20	27.64	4.87	34.36	91.56	89.71	-----	-----	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 10 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 10
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11g 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	48.98	47.09	54.00	6.91	Average
2	2411.20	27.64	4.87	34.36	94.04	92.19	-----	-----	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 11 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 11
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11g 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	65.63	63.74	74.00	10.26	Peak
2	2410.97	27.64	4.87	34.36	103.76	101.91	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 12 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 12
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11g 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Emission Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	62.82	60.93	74.00	13.07	Peak
2	2412.35	27.65	4.87	34.36	99.77	97.93	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.


Data: 13 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17



Site no. : 3m Chamber Data no. : 13
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11g 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2463.26	27.80	4.92	34.35	103.34	101.71	-----	-----	Peak
2	2483.50	27.80	4.94	34.35	71.41	69.80	74.00	4.20	Peak
3	2500.00	27.80	4.95	34.35	55.32	53.72	74.00	20.28	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 14
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11g 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2463.50	27.80	4.92	34.35	103.51	101.88	-----	-----	Peak
2	2483.50	27.80	4.94	34.35	70.55	68.94	74.00	5.06	Peak
3	2500.00	27.80	4.95	34.35	57.26	55.66	74.00	18.34	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 15 File: F:\2023 Report\TPVA\1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17




Site no. : 3m Chamber Data no. : 15
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11g 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2461.22	27.80	4.92	34.35	94.20	92.57	-----	-----	Average
2	2483.50	27.80	4.94	34.35	52.06	50.45	54.00	3.55	Average
3	2500.00	27.80	4.95	34.35	38.72	37.12	54.00	16.88	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.


Data: 16 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-17



Site no. : 3m Chamber Data no. : 16
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11g 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2461.16	27.80	4.92	34.35	90.51	88.88	-----	-----	Average
2	2483.50	27.80	4.94	34.35	48.33	46.72	54.00	7.28	Average
3	2500.00	27.80	4.95	34.35	36.54	34.94	54.00	19.06	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.




```

Site no.      : 3m Chamber                      Data no.   : 17
Dis. / Ant.  : 3m 2023 MCTD1209-3006          Ant. pol.  : HORIZONTAL
Limit        : FCC PART 15C PEAK
Env. / Ins.  : 23.2*C/52.5%                   Engineer   : nier
Test Mode    : 2.4G 11n20 2412MHz TX
:
:
    
```

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Emission Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	66.04	64.15	74.00	9.85	Peak
2	2413.16	27.65	4.87	34.36	107.05	105.21	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 18 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-18




Site no. : 3m Chamber Data no. : 18
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11n20 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	68.40	66.51	74.00	7.49	Peak
2	2411.78	27.65	4.87	34.36	108.97	107.13	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.


Data: 19 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-18



Site no. : 3m Chamber Data no. : 19
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11n20 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	51.56	49.67	54.00	4.33	Average
2	2412.70	27.65	4.87	34.36	99.55	97.71	-----	-----	Average


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 20
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11n20 2412MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.62	4.85	34.36	48.36	46.47	54.00	7.53	Average
2	2411.09	27.64	4.87	34.36	95.75	93.90	-----	-----	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 21
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11n20 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.32	27.80	4.92	34.35	101.21	99.58	-----	-----	Peak
2	2483.50	27.80	4.94	34.35	64.31	62.70	74.00	11.30	Peak
3	2500.00	27.80	4.95	34.35	51.69	50.09	74.00	23.91	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 22 File: F:\2023 Report\TPVA1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-19




Site no. : 3m Chamber Data no. : 22
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11n20 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2463.02	27.80	4.92	34.35	90.47	88.84	-----	-----	Peak
2	2483.50	27.80	4.94	34.35	54.56	52.95	74.00	21.05	Peak
3	2500.00	27.80	4.95	34.35	47.05	45.45	74.00	28.55	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 23 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-19




Site no. : 3m Chamber Data no. : 23
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11n20 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2461.04	27.80	4.91	34.35	81.20	79.56	-----	-----	Average
2	2483.50	27.80	4.94	34.35	37.93	36.32	54.00	17.68	Average
3	2500.00	27.80	4.95	34.35	34.76	33.16	54.00	20.84	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Data: 24 File: F:\2023 Report\TPVA\A1Z2310026R1\EP-C131\A1Z2310026R1-2.4G.EM6 (78) Date: 2023-10-19



Site no. : 3m Chamber Data no. : 24
 Dis. / Ant. : 3m 2023 MCTD1209-3006 Ant. pol. : VERTICAL
 Limit : FCC PART 15C AV
 Env. / Ins. : 23.2°C/52.5% Engineer : nier
 Test Mode : 2.4G 11n20 2462MHz TX
 :
 :

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2462.78	27.80	4.92	34.35	89.85	88.22	-----	-----	Average
2	2483.50	27.80	4.94	34.35	44.07	42.46	54.00	11.54	Average
3	2500.00	27.80	4.95	34.35	36.30	34.70	54.00	19.30	Average

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

7. 6dB Bandwidth & 99% Bandwidth TEST

7.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Apr.01,23	1 Year
2.	RF Cable	HUBER+SUHNER	SUCOFLE X-106	505238/6	Apr.02,23	1 Year

7.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

7.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 300kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

7.4. Test Results

EUT: Electronic paper display		
M/N: EP-C131		
Test date: 2023-10-30	Pressure: 102.5±1.0 kpa	Humidity: 53.6±3.0%
Tested by: Jason	Test site: RF site	Temperature: 22.4±0.6 °C

-6 dB bandwidth:

Test Mode	CH	-6dB Bandwidth (MHz)	Limit (KHz)
11b	CH1	7.581	≥ 500
	CH6	7.610	
	CH11	7.566	
11g	CH1	15.54	≥ 500
	CH6	15.52	
	CH11	15.19	
11n HT20	CH1	15.19	≥ 500
	CH6	15.22	
	CH11	15.19	
Conclusion: Pass			



99% Occupied bandwidth:

Test Mode	CH	99% Bandwidth (MHz)	Limit (MHz)
11b	CH1	11.013	N/A
	CH6	10.982	
	CH11	11.006	
11g	CH1	16.337	N/A
	CH6	16.342	
	CH11	16.294	
11n HT20	CH1	17.536	N/A
	CH6	17.546	
	CH11	17.471	
Conclusion: Pass			

-6 dB bandwidth:


Test Mode: IEEE 802.11b
Test CH1: 2412MHz

Test Mode: IEEE 802.11g
Test CH1: 2412MHz




Test CH6: 2437MHz

Test CH6: 2437MHz



Test CH11: 2462MHz

Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT20



Test CH1: 2412MHz



Test CH11: 2462MHz





Test CH6: 2437MHz



99% Occupied bandwidth:


Test Mode: IEEE 802.11b
Test CH1: 2412MHz

Test Mode: IEEE 802.11g
Test CH1: 2412MHz




Test CH6: 2437MHz

Test CH6: 2437MHz




Test CH11: 2462MHz

Test CH11: 2462MHz



Test Mode: IEEE 802.11n HT20


Test CH1: 2412MHz



Test CH11: 2462MHz



Test CH6: 2437MHz



8. OUTPUT POWER TEST

8.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Apr.01,23	1 Year
2.	Power meter	Anritsu	ML2487A	6K00003262	Jun.26,23	1 Year
3.	Power sensor	Anritsu	MA2491A	0332516	Jun.26,23	1 Year
4.	RF Cable	HUBER+SUHNER	SUCOFLE X-106	505238/6	Apr.02,23	1 Year

8.2. Limit (FCC Part 15C 15.247 b(3))

For systems using digital modulation in the 2400—2483.5MHz, The Peak output Power shall not exceed 1W(30dBm), As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level.

8.3. Test Procedure

- 1, Connected the EUT's antenna port to measure device by 20dB attenuator.
- 2, Use the test method described in ANSI C63.10-2013 clause 11.9.2.2.2 Method AVGSA-1.
 - 1) Set span to at least 1.5 times the OBW.
 - 2) Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
 - 3) Set VBW $\geq [3 \times \text{RBW}]$.
 - 4) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
 - 5) Sweep time = auto.
 - 6) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
 - 7) If transmit duty cycle < 98%, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at the maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFF intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."
 - 8) Trace average at least 100 traces in power averaging (rms) mode.
 - 9) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.


8.4. Test Results

EUT: Electronic paper display		
M/N: EP-C131		
Test date: 2023-11-04	Pressure: 103.1±1.0 kpa	Humidity: 51.5±3.0%
Tested by: Jason	Test site: RF site	Temperature: 22.5±0.6 °C

Test Mode	CH	Power Setting	Duty factor(dB)	Output Power(dBm)	Limit (dBm)
11b	CH1	Default	0	13.61	30
	CH6	Default	0	14.09	
	CH11	Default	0	14.51	
11g	CH1	Default	0	13.51	30
	CH6	Default	0	14.34	
	CH11	Default	0	14.52	
11n HT20	CH1	Default	0	14.00	30
	CH6	Default	0	14.62	
	CH11	Default	0	15.06	
Conclusion: PASS					


Test Mode: IEEE 802.11b

Test CH1: 2412MHz




Test Mode: IEEE 802.11g


Test CH1: 2412MHz




Test CH6: 2437MHz




Test CH6: 2437MHz



Test CH11: 2462MHz




Test CH11: 2462MHz




Test Mode: IEEE 802.11n HT20



Test CH1: 2412MHz



Test CH11: 2462MHz



Test CH6: 2437MHz



9. POWER SPECTRAL DENSITY TEST

9.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Apr.01,23	1 Year
2.	RF Cable	HUBER+SUHNER	SUCOFLEX-106	505238/6	Apr.02,23	1 Year

9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

9.3. Test Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.

9.4. Test Results

EUT: Electronic paper display		
M/N: EP-C131		
Test date: 2023-11-07	Pressure: 102.5±1.0 kpa	Humidity: 53.6±3.0%
Tested by: Jason	Test site: RF site	Temperature: 22.4±0.6 °C


Test Mode	CH	Power Spectral Density (dBm/3KHz)	Limit (dBm/3KHz)
11b	CH1	-5.653	8
	CH6	-6.857	
	CH11	-6.977	
11g	CH1	-8.023	8
	CH6	-7.603	
	CH11	-7.103	
11n HT20	CH1	-8.078	8
	CH6	-7.027	
	CH11	-6.205	
Conclusion: PASS			

Test Mode: IEEE 802.11b

Test CH1: 2412MHz



Test Mode: IEEE 802.11g

Test CH1: 2412MHz




Test CH6: 2437MHz

Test CH6: 2437MHz



Test CH11: 2462MHz



Test CH11: 2462MHz





Test Mode: IEEE 802.11n HT20

Test CH1: 2412MHz

Test CH11: 2462MHz



Test CH6: 2437MHz



10. ANTENNA REQUIREMENT

10.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Antenna Connected Construction

The antennas used for this product is shrapnel Antenna, that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is DTS Band: 2.51dBi.

11. DEVIATION TO TEST SPECIFICATIONS

[NONE]

..... **THE END**