

ENGINEERING TEST RECORD
REPORT OF MEASUREMENTS (MICROWAVE OVEN TEST DATA SHEET)


FCC ID : APYDMR0125
Tested Product : Household Microwave Oven, VFA Chassis
Input Power Rating : 120 V ac, 60 Hz
Output Power Rating : 1200 W
Nominal Frequency : 2450 MHz
Magnetron Type No. : 2M226, mfd by LG Electronics
Test Date : March 2 - 7, 2000

Tested by;

Tested/Reviewed by;



T. Miyamoto
Microwave Oven Engineering Dept.
Kitchen Appliance Systems Div.
Sharp Corp. (Yao Factory)



Y. Honkawa
Microwave Oven Engineering Dept.
Kitchen Appliance Systems Div.
Sharp Corp. (Yao Factory)

DATA SUMMARY (FCC Measurement Procedure MP-5)

1. Frequency Measurements : See attached data sheet.
2. Radiated Field Strength : See attached data sheet.

Measurement Test Site : Sharp Corporation
Kitchen Appliance Systems Div.
Yao Factory, EMI Anechoic Chamber

Note: For further details of Test Site, refer to the attached "Description of Measurement Facilities".

Total Power Input to Oven : 1605 W
Power Developed in Dummy Load : 834.7 W
(by calorimetric method with 1500 ml water load,
well heated microwave oven.)
Supply Voltage : 120 V ac, 60 Hz

PERMISSIBLE : **32.3 uV/m at 300 m**

1. FREQUENCY MEASUREMENTS

FCC ID : APYDMR0125
Tested Unit : Microwave Oven, VFA Chassis
Magnetron Type No. : 2M226, mfd by LG Electronics
Tested : March 2 - 3, 2000

(1-1) Frequency VS Line Voltage Variation Test

Test Result (Room Temperature: 20 degC)
Load: 1500 cc water in the glass beaker

Line Voltage Variation (V)	Frequency	Allowed Tolerance for the ISM Band (2450 MHz)
96 (80%)	Lower: 2439 MHz Upper: 2483 MHz	Lower: 2400 MHz Upper: 2500 MHz
108 (90%)	Lower: 2422 MHz Upper: 2483 MHz	
120 (Nominal)	Lower: 2460 MHz Upper: 2480 MHz	
132 (110%)	Lower: 2464 MHz Upper: 2481 MHz	
150 (125%)	Lower: 2470 MHz Upper: 2483 MHz	

(1-2) Frequency VS Load Variation Test

Test Results (room temperature: 20 degC)
Initial Load: 1500 cc water in the glass beaker

Volume of Water (cc)	Frequency	Allowed Tolerance for the ISM Band (2450 MHz)
1500	Lower: 2460 MHz Upper: 2480 MHz	Lower: 2400 MHz Upper: 2500 MHz
1200	Lower: 2463 MHz Upper: 2480 MHz	
900	Lower: 2463 MHz Upper: 2483 MHz	
600	Lower: 2459 MHz Upper: 2482 MHz	
300	Lower: 2463 MHz Upper: 2479 MHz	

2. RADIATED FIELD STRENGTH

DATA SHEET (FCC Measurement Procedure MP-5)

FCC ID: APYDMR0125

Tested Model: VFA Chassis

Magnetron: 2M226, mfd by LG Electronics

Date: March 03 - 07, 2000

	Frequency (MHz)	Load (ml)	Place of the load	Antenna Factor (dB)	Cable Loss (dB)	Reading Data (dBuV @:3m)		Radiated Field Strength (uV/m @:300m)	
						Vertical	Horizen	Vertical	Horizen
Fundamental	2460	1500	Center	20.70	1.03	72	76	308.82	489.44
2nd Harmonic	4910	1050	Center	20.50	1.58	42	43	16.00	17.95
	4914	1050	R.F.Corner	20.50	1.58	37	35	9.00	7.15
	4909	450	Center	20.50	1.58	43	42	17.95	16.00
	4915	450	R.F.Corner	20.50	1.58	40	40	12.71	12.71
3rd Harmonic	7371	1050	Center	22.00	2.10	24	22	2.54	2.02
	7384	1050	R.F.Corner	22.00	2.10	21	28	1.80	4.03
	7361	450	Center	22.00	2.10	26	27	3.20	3.59
	7373	450	R.F.Corner	22.00	2.10	27	21	3.59	1.80
4th Harmonic	9858	1050	Center	20.00	2.62	Noise<15	21	Noise<0.76	1.52
Sprious : 1000<F<4575	2368	1050	Center	20.70	1.00	29	30	2.10	2.36
	2390	1050	Center	20.70	1.01	24	26	1.19	1.50
Sprious : 1000>F, 4575<F	14740	1050	Center	19.20	3.70	22	26	1.76	2.79
	-	-	Center	-	-	-	-	-	-
Emission Sideband	2400	1500	Center	20.70	1.01	30	31	2.39	2.68
	2415	1500	Center	20.70	1.02	28	27	1.91	1.70
	2485	1500	Center	20.70	1.03	7	7	0.18	0.18
	2500	1500	Center	20.80	1.04	7	7	0.18	0.18

Emission observed from 100 MHz through 18 GHz by spectrum analyzer. No significant emission was detected except for above data.

Microwave Leakage at 5 cm on fundamental : 0.1 mW/cm²

DESCRIPTION OF THE MEASUREMENT FACILITIES


SHARP CORPORATION, KITCHEN APPLIANCE SYSTEMS DIVISION
EMI ANECHOIC CHAMBER

PHOTOGRAPH OF TEST EQUIPMENT #1

Spectrum Analyzer
8566B

Field Strength Meter
NM-67

Horn Antenna



Turn Table Controller

PHOTOGRAPH OF TEST EQUIPMENT #2

Horn Antenna




Field Strength Meter
NM-67

PHOTOGRAPH OF TEST EQUIPMENT #3


Microwave Oven
Test Sample

Wooden Table




Transparent Turn Table

4. DIMENSIONS OF TEST SITE




Electric Magnetic Wave Absorber: Cat. No. AEP-12EM WP
Mfd by Advanced ElectroMagnetic, Inc.



(mm)

EMI Anechoic Chamber equipped by Akzo Kashima Ltd.

5. ARRANGEMENT OF INSTRUMENTATION



6. DESCRIPTION OF MEASUREMENT EQUIPMENTS

6-1. FIELD STRENGTH METER

- a) #UHR4000, Mfd by CHASE (100 MHz through 1.0 GHz)

BANDWIDTH	120 kHz
DETECTOR FUNCTION	Linear average value; AVERAGE 1: 1 ms averaging AVERAGE 2: 600 ms averaging
CALIBRATION DATE	July 21, 1999

- b) #NM-67, Mfd by EATON (1.0 GHz through 18 GHz)

BANDWIDTH	1 MHz
DETECTOR FUNCTION	Linear average value; Field Intensity
CALIBRATION DATE	October 20, 1999

6-2. RADIATED FREQUENCY OBSERVATION SUB-EQUIPMENT

SPECTRUM ANALYZER	#8566B, Mfd by HEWLETT. PACKARD
-------------------	---------------------------------

6-3. ANTENNA

<u>RANGE FOR FREQUENCY</u>	<u>ANTENNA</u>
From 100 MHz to 140 MHz	#DM-105A-T1, Mfd by SINGER
From 140 MHz to 400 MHz	#DM-105A-T2, Mfd by SINGER
From 400 MHz to 1.0 GHz	#DM-105A-T3, Mfd by SINGER
From 1.0 GHz to 2.0 GHz	#91888-2, Mfd by EATON
From 2.0 GHz to 3.6 GHz	#91889-2, Mfd by EATON
From 3.6 GHz to 7.3 GHz	#94613-1 with Reflector #91892-1 Mfd by EATON
From 7.3 GHz to 12.0 GHz	#91891-2 with Reflector #91892-1 Mfd by EATON
From 12.0 GHz to 18.0 GHz	#94614-1 with Reflector #91892-1 Mfd by EATON

6-4. CABLE

<u>RANGE FOR FREQUENCY</u>	<u>CABLE</u>
From 100 MHz to 1.0 GHz	#RG-55/U
From 1.0 GHz to 18.0 GHz	#94615-1

6.5. PERTINENT DETAILS

a) Calculation Formula	(See Attachment 1)
b) Antenna Correction Factor	(See Attachment 2)
c) Cable Loss	(See Attachment 3)
d) Calibration Curve	(See Attachment 4)

6-6. TEST CONDITION

a) Antenna height variation	From <u>1.1 m</u> to <u>2.1 m</u>
b) Antenna to test unit distance	<u>3 m</u>

CALCULATION OF RADIATED FIELD STRENGTH (uV/m)

$$E_f = 10^{\left(\frac{F_a + F_c + D}{20}\right)} * K$$

E_f : Radiated Field Strength at 300 m (uV/m)

F_a : Antenna Factor (dB)

F_c : Cable Factor (dB)

D : Reading Data of the Field Strength Meter (dBuV at 3 m)

K : Conversion Factor

$K = 0.0137 * \log F - 0.0401$ (if $F < 4575$ MHz)

$K = 0.01$ (if $F \geq 4574$ MHz)

F : Emission Frequency

Emission Frequency (MHz)	K
1830	0.0046
2745	0.0070
3660	0.0090
4575 and above	0.0100

In case of emission frequency less than 1.0 GHz, conversion factor $K=0.01$ is used for the measurement of 3 m distance.

ANTENNA FACTOR (dB)




Figure 5-3. Antenna Correction Factors, 1-18 GHz Horn Antennas




Figure 2-18. Antenna Factor Versus Frequency Characteristics, Models DM-105-T1, DM-105-T2 and DM-105-T3 Dipole Antennas




Figure 2-10. Attenuation Vs. Frequency for RG-55/U Coaxial Cable




Figure 5-1. Model 94615-1 RF Cable Loss Chart

CALIBRATION CURVE

For Model NM-67

