

EMI TEST REPORT

Test Report No. : 25AE0006-HO-2

Applicant : Sharp Corporation
Type of Equipment : GSM & WCDMA Cellular Phone
Model No. : 802SH
Test standard : FCC Part 15 Subpart C
Section 15.207, Section 15.247 : 2004
FCC ID : APYHRO00039
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Apex Co., Ltd.
2. The results in this report apply only to the sample tested.
3. This equipment is in compliance with above regulation. We hereby certify that the data contain a true representation of the EMC profile.
4. The test results in this report are traceable to the national or international standards.


Date of test:

August 31 to September 11, 2004

Tested by:




Naoki Sakamoto
EMC Service



Hiroka Umeyama
EMC Service

Approved by :



Hironobu Shimoji
Group Leader of
EMC Service

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

CONTENTS	PAGE
SECTION 1: Client information	3
SECTION 2: Equipment under test (E.U.T.)	3
SECTION 3: Test specification, procedures & results	4
SECTION 4: Operation of E.U.T. during testing	6
SECTION 5: Conducted Emission, Section 15.207	7
SECTION 6: Carrier Frequency Separation, Section15.247(a)(1)	7
SECTION 7: 20 dB Bandwidth, Section 15.247(a)(1)	7
SECTION 8: Number of Hopping Frequency, Section 15.247(a)(1)(iii)	8
SECTION 9: Dwell time, Section 15.247(a)(1)(iii)	8
SECTION 10: Maximum Peak Output Power, Section 15.247(b)(1)	8
SECTION 11: Spurious Emission / Band Edge Compliance 15.247(c)	9
APPENDIX 1: Photographs of test setup	10
Conducted Emission	10
Spurious Emission (Radiated)	11
Worst Case Position (Y-axis:Horizontal / Z-axis:Vertical)	12
APPENDIX 2: Test instruments	13
APPENDIX 3: Data of EMI test	14
Conducted Emission	14
Carrier Frequency Separation.....	19
20dB Bandwidth	21
Number of Hopping Frequency	23
Dwell time.....	25
Maximum Peak Output Power	28
Radiated Spurious Emission(30-1000MHz).....	30
Radiated Spurious Emission (1-25GHz) / Band Edge compliance.....	33
Conducted Spurious Emission(30MHz-25GHz).....	36
Conducted Spurious Emission / Band Edge compliance	39

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

SECTION 1: Client information

Company Name : Sharp Corporation
Brand or Trade name : SHARP
Address : 2-13-1 Iida Hachihonmatsu HigashiHiroshima-City, Hiroshima-ken,
739-0192 Japan
Telephone Number : +81-82-420-1592
Facsimile Number : +81-82-420-1852
Contact Person : Seiichi Ichikawa

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : GSM & WCDMA Cellular Phone
Model No. : 802SH
Serial No. : 350263/00/004031/1 and 350263/00/004039/4
(For the Radiated Spurious Emission)
350263/00/004079/0 (For Conducted tests)
Country of Manufacture : Japan
Receipt Date of Sample : August 27, 2004
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)

2.2 Product Description

Clock frequency	CPU:13MHz/ RTC:32.768kHz
Feature of EUT	802SH(referred to as the EUT in this report)is Tri-Band GSM &WCDMA Mobile Cellular Phone with AC CHARGER(XN-1QC93), DATA CABLE (XN-1DC30)

<Transmitter>

Equipment Type	Transceiver
Frequency of Operation	2402MHz to 2480MHz
Bandwidth & Channel spacing	1MHz & 1MHz
Type of Modulation	FHSS
Antenna Type	Internal Antenna
Antenna Connector Type	Soldering
Antenna Gain	0 dBi
Mode of Operation	Simplex
ITU code	F1D
Operating voltage (Inner)	2.9V
Operating temperature	-10 to +55 deg.C.

FCC 15.31 (e)

This EUT provides stable voltage(DC2.9V) constantly to RF Module regardless of input voltage. Therefore, this EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part15 Subpart C : 2004

Title : FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits : 2004
Section 15.247 Operation within the bands 902-928MHz,
2400-2483.5MHz, and 5725-5850MHz : 2004

3.2 Procedures and results

No.	Item	Test Procedure	Specification	Remarks	Deviation	Worst margin	Results
1	Conducted emission	ANSI C63.4:2003 7. AC powerline conducted emission measurements	Section 15.207	-	N/A	11.1dB 1.7064MHz N, QP	Complied
2	Carrier Frequency Separation	ANSI C63.4:2003 13. Measurement of intentional radiators	Section15.247(a)(1)	Conducted	N/A	*See data.	Complied
3	20dB Bandwidth	ANSI C63.4:2003 13. Measurement of intentional radiators	Section15.247(a)(1)	Conducted	N/A		Complied
4	Number of Hopping Frequency	ANSI C63.4:2003 13. Measurement of intentional radiators	Section15.247(a)(1)(iii)	Conducted	N/A		Complied
5	Dwell time	ANSI C63.4:2003 13.Measurement of intentional radiators	Section15.247(a)(1)(iii)	Conducted	N/A		Complied
6	Maximum Peak Output Power	ANSI C63.4:2003 13. Measurement of intentional radiators	Section15.247(b)(1)	Conducted	N/A		Complied
7	Spurious Emission /Band Edge Compliance	ANSI C63.4:2003 13. Measurement of intentional radiators	Section15.247(c)	Conducted/ Radiated	N/A		2.4dB, 1736.0MHz HOR (2480MHz)

Note: UL Apex's EMI Work Procedures No.QPM05.

Uncertainty

*In case of the margin below the EMC Head Office's uncertainty.
The data listed in this report meets the limits unless the uncertainty is taken into consideration.

Conducted Emission

The measurement uncertainty (with a 95% confidence level) for this test is ±1.3dB.

Spurious Emission (Radiated)

The measurement uncertainty (with a 95% confidence level) for this test using Biconical antenna is ±4.5dB(3m)/ ±4.7dB(10m).
The measurement uncertainty (with a 95% confidence level) for this test using Logperiodic antenna is ±5.2dB(3m)/ ±3.8dB(10m).
The measurement uncertainty (with a 95% confidence level) for this test using Horn antenna is ±6.6dB.

Other test except Conducted Emission and Spurious Emission (Radiated)

The measurement uncertainty (with a 95% confidence level) for this test is ±3.0dB.

*These tests were also referred to FCC Public Notice DA 00-705 "Guidance on Measurement for Frequency Hopping Spread Spectrum Systems".

*These tests were performed without any deviations from test procedure except for additions or exclusions.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

3.3 Addition to standards

No addition, deviation, nor exclusion has been made from standards.

3.4 Test Location

UL Apex Co., Ltd. Head Office EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124

	Listed date (for FCC)	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	February 01, 2002	313583	IC4247	19.2 x 11.2 x 7.7m	7.0 x 6.0m	Preparation room
No.2 semi-anechoic chamber	June 05, 2002	846015	IC4247-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 shielded room	-	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.4 measurement room	-	-	-	3.1 x 5.0 x 2.7m	N/A	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1 and No.2 semi-anechoic and No.3 shielded room.

3.5 Test set up, Test instruments and Data of EMI

Refer to APPENDIX 1 to 3.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124


MF060b(10.04.03)

SECTION 4: Operation of E.U.T. during testing

4.1 Operating Modes

The mode is used : [FHSS: Bluetooth]
Transmitting mode(Packet size DH5)
Low Channel :2402MHz
Mid Channel :2441MHz
High Channel :2480MHz
Inquiry

4.2 Configuration and peripherals



* Cabling was taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	FCC ID
A	GSM & WCDMA Cellular Phone	802SH	350263/00/004031/1 and 350263/00/004039/4 (For the Radiated Spurious Emission) 350263/00/004079/0 (For Conducted tests)	SHARP Corporation	APYHRO00039
B	AC Charger	XN-1QC08	N/A	HOSIDEN	N/A
C	Earphone	N/A	N/A	SHARP Corporation	N/A

List of cables used

No.	Name	Length (m)	Shield	Backshell Material
1	AC Charger Cable	1.5	N	Polyvinyl chloride
2	Earphone Cable	1.2	N	Polyvinyl chloride

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

SECTION 5: Conducted Emission, Section 15.207

Test Procedure and conditions

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT, including peripherals aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN)/ Artificial mains Network (AMN) and excess AC cable was bundled in center.

1) For the tests on EUT itself (as a stand alone equipment)

Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN/(AMN) to the input power source. All unused 50ohm connectors of the LISN(AMN) were resistively terminated in 50ohm when not connected to the measuring equipment.

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT in a Semi Anechoic Chamber or a Measurement Room.

The EUT was connected to a LISN (AMN).

An overview sweep with peak detection has been performed.

Detector : CISPR quasi-peak detector (IF BW 9 kHz)
Measurement range : 0.15-30MHz
Test data : APPENDIX 3
Test result : Pass

SECTION 6: Carrier Frequency Separation, Section15.247(a)(1)

Test Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 3
Test result : Pass

SECTION 7: 20 dB Bandwidth, Section 15.247(a)(1)

Test Procedure

The 20dB bandwidth was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 3
Test result : Pass

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

SECTION 8: Number of Hopping Frequency, Section 15.247(a)(1)(iii)

Test Procedure

The Number of Hopping Frequency was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 3
Test result : Pass

SECTION 9: Dwell time, Section 15.247(a)(1)(iii)

Test Procedure

The Dwell time was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 3
Test result : Pass

SECTION 10: Maximum Peak Output Power, Section 15.247(b)(1)

Test Procedure

The Maximum Peak Output Power was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 3
Test result : Pass

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

SECTION 11: Spurious Emission / Band Edge Compliance 15.247(c)

[Conducted]

Test Procedure

The Out of Band Emission was measured with a spectrum analyzer connected to the antenna port.

Test data : APPENDIX 3
Test result : Pass

[Radiated]

Test Procedure

EUT was placed on a platform of nominal size, 0.5m by 0.5m, raised 80cm above the conducting ground plane. The Radiated Electric Field Strength intensity has been measured in a Semi Anechoic Chamber with a ground plane and at a distance of 3m(Below 10GHz) and 1m(Upper 10GHz).

The height of the measuring varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver or the Spectrum Analyzer.

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.

Test data : APPENDIX 3
Test result : Pass

When not satisfying the requirement of Section 15.209, 20dBc was applied the restricted band of Section 15.205.

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver / Spectrum Analyzer	Spectrum Analyzer
Detector	QP: BW 120kHz(T/R)	PK: RBW:1MHz/VBW: 1MHz
IF Bandwidth	20dBc : RBW: 100kHz VBW: 300kHz (S/A)	AV: RBW:1MHz/VBW:10Hz 20dBc : RBW:100kHz/VBW:300kHz

- The carrier level and noise levels were measured at each position of all three axes X, Y and Z, and the position that has the maximum noise was determined.

With the position, the noise levels of all the frequencies was measured.

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

APPENDIX 1: Photographs of test setup

This page has been submitted for a separate exhibit.

This page has been submitted for a separate exhibit.

This page has been submitted for a separate exhibit.

APPENDIX 2: Test instruments

EMI test equipment

Control No.	Instrument	Manufacturer	Model No	Test Item	Calibration Date * Interval(month)
MAEC-02	Anechoic Chamber	TDK	Semi Anechoic Chamber 3m	RE / CE	2004/04/12 * 12
MTR-02	Test Receiver	Rohde & Schwarz	ESCS30	RE/CE	2004/02/03 * 12
MAT-07	Attenuator(6dB)	Weinschel Corp	2	RE	2003/12/16 * 12
MBA-02	Biconical Antenna	Schwarzbeck	BBA9106	RE	2003/10/15 * 12
MHA-02	Horn Antenna	EMCO	3160-09	RE	2004/01/10 * 12
MHA-05	Horn Antenna	Schwarzbeck	BBHA9120D	RE	2004/01/10 * 12
MLA-02	Logperiodic Antenna	Schwarzbeck	USLP9143	RE	2003/10/15 * 12
MPA-01	Pre Amplifier	Agilent	8449B	RE	2004/02/06 * 12
MPA-02	Pre Amplifier	Agilent	87405A	RE	2004/04/16 * 12
MOS-02	Digital Humidity Indicator	N.T	NT-1800	RE/CE	2003/11/27 * 12
MRENT-09	Spectrum Analyzer	Advantest	R3273	RE/CE	2004/02/18 * 12
MLS-06	LISN(AMN)	Schwarzbeck	NSLK8127	CE(EUT)	2004/02/17 * 12
MCC-12	Coaxial Cable	Fujikura/Agilent	-	RE	2004/02/24 * 12
MCC-13	Coaxial Cable	Fujikura/Agilent	-	CE	2004/02/24 * 12
MCC-04	Microwave Cable	Storm	421-011	RE	2004/01/06 * 12
MCC-24	Microwave Cable	Storm	-	RE	2004/05/01 * 12
MHF-02	High Pass Filter	Tokimec	TF323DCA	RE	2003/09/19 * 12
MBTR10	Spectrum Analyzer	Rohde & Schwarz	FSP30	AT	2003/11/12 * 12

All equipment is calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.

Test Item:

CE: AC Main Conducted Emission

RE: Radiated Spurious Emission

AT: Other test s

UL Apex Co., Ltd.

Head Office EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

APPENDIX 3: Data of EMI test

Conducted Emission

DATA OF CONDUCTED EMISSION TEST


UL Apex Co., Ltd. Head Office EMC Lab. No.2 Semi Anechoic Chamber
Date : 2004/09/03 13:26:05

Applicant : SHARP Corporation
Kind of EUT : GSM-WCDMA Cellular phone
Model No. : 902SH
Serial No. : 350263/00/004031/1

Report No. : 25AE0006-HO
Power : AC120V / 60Hz (AC Adapter)
Temp°C/Humi% : 23 deg. C / 62 %
Operator : Naoki Sakamoto

Mode / Remarks : 2402MHz

LIMIT : FCC15C § 15. 207 (QP)
FCC15C § 15. 207 (AV)



NO	FREQ [MHz]	READING		C. F [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dB μV]	AV [dB μV]		QP [dB μV]	AV [dB μV]	QP [dB μV]	AV [dB μV]	QP [dB]	AV [dB]	
1	0.1687	36.9	22.0	0.0	36.9	22.0	65.0	55.0	28.1	33.0	N
2	0.2505	32.4	18.9	0.0	32.4	18.9	61.7	51.7	29.3	32.8	N
3	0.3381	35.3	20.9	0.0	35.3	20.9	59.2	49.2	23.9	28.3	N
4	0.8436	36.4	19.1	0.0	36.4	19.1	56.0	46.0	19.6	26.9	N
5	1.7335	36.9	16.3	0.2	37.1	16.5	56.0	46.0	18.9	29.5	N
6	3.5046	18.2	6.2	0.3	18.5	6.5	56.0	46.0	37.5	39.5	N
7	0.1684	36.8	21.9	0.0	36.8	21.9	65.0	55.0	28.2	33.1	L
8	0.2580	33.1	17.4	0.0	33.1	17.4	61.5	51.5	28.4	34.1	L
9	0.3415	34.8	18.2	0.0	34.8	18.2	59.2	49.2	24.4	31.0	L
10	0.8487	33.6	14.6	0.0	33.6	14.6	56.0	46.0	22.4	31.4	L
11	1.7451	34.8	13.6	0.2	35.0	13.8	56.0	46.0	21.0	32.2	L
12	3.5059	23.3	12.2	0.3	23.6	12.5	56.0	46.0	32.4	33.5	L

CHART:WITH FACTOR,Peak hold data.Data is uncorrected. CALCURATION:RESULT=READING+C. F (L ISN LOSS+CABLE LOSS)
Except for the above table : adequate margin data below the limits.


DATA OF CONDUCTED EMISSION TEST

UL Apex Co., Ltd. Head Office EMC Lab. No.2 Semi Anechoic Chamber
 Date : 2004/09/03 13:20:05

Applicant : SHARP Corporation Kind of EUT : GSM-WCDMA Cellular phone Model No. : 802SH Serial No. : 350263/00/004031/1	Report No. : 25AE0006-HO Power : AC120V / 60Hz (AC Adapter) Temp°C/Humi% : 23 deg. C / 62 % Operator : Naoki Sakamoto
---------------------------------------------------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------

Mode / Remarks : 2441MHz

LIMIT : FCC15C §15.207 (QP)
 FCC15C §15.207 (AV)



NO	FREQ [MHz]	READING PEAK [dBµV]	C.F [dB]	RESULT [dBµV]	LIMIT		MARGIN		PHASE
					QP [dBµV]	AV [dBµV]	QP [dB]	AV [dB]	

CHART: WITH FACTOR, Peak hold data. Data is uncorrected. CALCURATION: RESULT=READING+C.F (LISN LOSS+CABLE LOSS)
 Except for the above table : adequate margin data below the limits.

DATA OF CONDUCTED EMISSION TEST


UL Apex Co., Ltd. Head Office EMC Lab. No. 2 Semi Anechoic Chamber
 Date : 2004/09/03 13:08:01

Applicant : SHARP Corporation
 Kind of EUT : GSM-WCDMA Cellular phone
 Model No. : 802SH
 Serial No. : 350263/00/004031/1

Report No. : 25AE0006-HO
 Power : AC120V / 60Hz (AC Adapter)
 Temp°C/Humi% : 23 deg. C / 62 %
 Operator : Naoki Sakamoto

Mode / Remarks : 2480MHz

LIMIT : FCC15C §15.207 (QP)
 FCC15C §15.207 (AV)



NO	FREQ [MHz]	READING PEAK [dBµV]	C. F [dB]	RESULT [dBµV]	LIMIT		MARGIN		PHASE
					QP [dBµV]	AV [dBµV]	QP [dB]	AV [dB]	

CHART: WITH FACTOR, Peak hold data. Data is uncorrected. CALCULATION: RESULT=READING+C.F (LISN LOSS+CABLE LOSS)
 Except for the above table : adequate margin data below the limits.

DATA OF CONDUCTED EMISSION TEST


UL Apex Co., Ltd. Head Office EMC Lab. No.2 Semi Anechoic Chamber
 Date : 2004/09/03 12:44:16

Applicant : SHARP Corporation
 Kind of EUT : GSM-WCDMA Cellular phone
 Model No. : 902SH
 Serial No. : 350263/00/004031/1

Report No. : 25AE0006-HO
 Power : AC120V / 60Hz (AC Adapter)
 Temp°C/Humi% : 23 deg. C / 62 %
 Operator : Naoki Sakamoto

Mode / Remarks : Inq

LIMIT : FCC15C § 15.207 (QP)
 FCC15C § 15.207 (AV)



NO	FREQ [MHz]	READING		C. F [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dB μV]	AV [dB μV]		QP [dB μV]	AV [dB μV]	QP [dB μV]	AV [dB μV]	QP [dB]	AV [dB]	
1	0.1500	35.6	20.7	0.0	35.6	20.7	66.0	56.0	30.4	35.3	N
2	0.2000	34.8	20.0	0.0	34.8	20.0	63.6	53.6	28.8	33.6	N
3	0.2400	34.0	12.1	0.0	34.0	12.1	62.1	52.1	28.1	40.0	N
4	0.4525	35.2	20.0	0.0	35.2	20.0	56.8	46.8	21.6	26.8	N
5	1.7064	44.7	26.6	0.2	44.9	26.8	56.0	46.0	11.1	19.2	N
6	3.5087	26.4	12.6	0.3	26.7	12.9	56.0	46.0	29.3	33.1	N
7	0.1500	35.5	21.2	0.0	35.5	21.2	66.0	56.0	30.5	34.8	L
8	0.2038	34.9	18.5	0.0	34.9	18.5	63.5	53.5	28.6	35.0	L
9	0.2321	32.6	9.6	0.0	32.6	9.6	62.4	52.4	29.8	42.8	L
10	0.4575	35.4	18.5	0.0	35.4	18.5	56.7	46.7	21.3	28.2	L
11	1.7438	43.4	24.4	0.2	43.6	24.6	56.0	46.0	12.4	21.4	L
12	3.5087	25.6	10.1	0.3	25.9	10.4	56.0	46.0	30.1	35.6	L

CHART: WITH FACTOR, Peak hold data. Data is uncorrected. CALCURATION: RESULT=READING+C. F (LISN LOSS+CABLE LOSS)
 Except for the above table : adequate margin data below the limits.

DATA OF CONDUCTED EMISSION TEST


UL Apex Co., Ltd. Head Office EMC Lab. No. 2 Semi Anechoic Chamber
 Date : 2004/09/03 13:02:21

Applicant : SHARP Corporation
 Kind of EUT : GSM-WCDMA Cellular phone
 Model No. : 802SH
 Serial No. : 350263/00/004031/1

Report No. : 25AE0006-HO
 Power : AC120V / 60Hz (AC Adapter)
 Temp°C/Humi% : 23 deg. C / 62 %
 Operator : Naoki Sakamoto

Mode / Remarks : Standby

LIMIT : FCC15C § 15.207 (QP)
 FCC15C § 15.207 (AV)



NO	FREQ [MHz]	READING PEAK [dBµV]	C. F [dB]	RESULT [dBµV]	LIMIT		MARGIN		PHASE
					QP [dBµV]	AV [dBµV]	QP [dB]	AV [dB]	

CHART: WITH FACTOR, Peak hold data. Data is uncorrected. CALCULATION: RESULT=READING+C. F (LISN LOSS+CABLE LOSS)
 Except for the above table : adequate margin data below the limits.


Carrier Frequency Separation

UL Apex Co., Ltd.
Head Office EMC Lab. No.3 Measurement Room

COMPANY	Sharp Corporation	REGULATION	Fcc Part15 Subpart C 15.247(a)(1)
EQUIPMENT	GSM & WCDMA Cellular Phone	TEST DISTANCE	-
MODEL	802SH	DATE	08/31/2004
S/ N	350262/00/004079/0	TEMPERATURE	25deg.C
POWER	DC4.0V	HUMIDITY	49%
MODE	Tx(Hopping on)/Inquiry	ENGINEER	Hiroka Umeyama

Ch	Freq. [MHz]	Channel separation [MHz]	Limit
Low	2402.0	1.002	>20dB Bandwidth and 25[kHz]
Mid	2441.0	1.008	>20dB Bandwidth and 25[kHz]
High	2480.0	1.014	>20dB Bandwidth and 25[kHz]
Inquiry	2441.0	2.010	>20dB Bandwidth and 25[kHz]

Carrier Frequency Separation




20dB Bandwidth

UL Apex Co., Ltd.
Head Office EMC Lab. No.3 Measurement Room

COMPANY	Sharp Corporation	REGULATION	Fcc Part15 Subpart C 15.247(a)(1)
EQUIPMENT	GSM & WCDMA Cellular Phone	TEST DISTANCE	-
MODEL	802SH	DATE	08/31/2004
S/ N	350263/00/004079/0	TEMPERATURE	25deg.C
POWER	DC4.0V	HUMIDITY	49%
MODE	Tx(Hopping OFF)/Inquiry	ENGINEER	Hiroka Umeyama

Ch	Freq. [MHz]	20dB Bandwidth [MHz]	Limit [MHz]
Low	2402.0	0.762	-
Mid	2441.0	0.816	-
High	2480.0	0.816	-
Inquiry	2441.0	0.666	-

20dB Bandwidth



Number of Hopping Frequency


UL Apex Co., Ltd.
Head Office EMC Lab. No.3 Measurement Room

COMPANY	Sharp Corporation	REGULATION	Fcc Part15 Subpart C 15.247(a)(1)(iii)
EQUIPMENT	GSM & WCDMA Cellular Phone	TEST DISTANCE	-
MODEL	802SH	DATE	08/31/2004
S/ N	350263/00/004079/0	TEMPERATURE	25deg.C
POWER	DC4.0V	HUMIDITY	49%
MODE	Tx(Hopping ON)/Inquiry	ENGINEER	Hiroka Umeyama

Mode	Number of channel [time]	Limit [time]
Tx(Hoppng on)	79	≥ 15

Mode	Number of channel [time]	Limit [time]
Inquiry	32	≥ 15

Number of Hopping Frequency




Dwell time

UL Apex Co., Ltd.
Head Office EMC Lab. No.3 Measurement Room


COMPANY	Sharp Corporation	REGULATION	Fcc Part15 Subpart C 15.247(a)(1)(iii)
EQUIPMENT	GSM & WCDMA Cellular Phone	TEST DISTANCE	-
MODEL	802SH	DATE	08/31/2004
S/ N	350263/00/004079/0	TEMPERATURE	25deg.C
POWER	DC4.0V	HUMIDITY	49%
MODE	Tx(Hopping ON)/Inquiry	ENGINEER	Hiroka Umeyama

Mode	Number of transmission in a 31.6(79 Hopping x 0.4) / 12.8(32 Hopping x 0.4)second period	Length of transmission time [msec]	Result [msec]	Limit [msec]
DH1	278times	0.456	127	400
DH3	149times	1.716	256	400
DH5	103times	2.996	309	400
Inquiry	100times / 1sec x 12.8sec = 1280	0.156	200	400

Dwell time



Dwell time



Maximum Peak Output Power

UL Apex Co., Ltd.
Head Office EMC Lab. No.3 Measurement Room

COMPANY	Sharp Corporation	REGULATION	Fcc Part15 Subpart C 15.247(b)(1)
EQUIPMENT	GSM & WCDMA Cellular Phone	TEST DISTANCE	-
MODEL	802SH	DATE	08/31/2004
S/ N	350263/00/004079/0	TEMPERATURE	25deg.C
POWER	DC4.0V	HUMIDITY	49%
MODE	Tx(Hopping OFF)/Inquiry	ENGINEER	Hiroka Umeyama

Ch	Freq. [MHz]	S/A Reading [dBm]	Cable Loss [dB]	Atten. [dB]	Result [dBm]	Limit (1W) [dBm]	Margin [dB]
Low	2402.0	-1.55	0.30	0.00	-1.25	30.00	31.25
Mid	2441.0	-1.28	0.30	0.00	-0.98	30.00	30.98
High	2480.0	-1.60	0.30	0.00	-1.30	30.00	31.30
Inquiry	2441.0	-1.60	0.30	0.00	-1.30	21.00	22.30

Sample Calculation:

Result = S/A Reading + Cable Loss (supplied by customer)+ Attenuator

* In the above table, factor 0.0dB represents no use of Atten. and/or Filter.

UL Apex Co., Ltd.

Head Office EMC Lab.


4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b(10.04.03)

Maximum Perik Output Power



Radiated Spurious Emission(30-1000MHz)


DATA OF RADIATED EMISSION TEST

UL Apex Co., Ltd. Head Office EMC Lab. No.2 Semi Anechoic Chamber
Date : 2004/09/01 21:32:20

Applicant : SHARP Corporation
Kind of EUT : GSM-WCDMA Cellular phone
Model No. : 802SH
Sample No. : 350263/00/004031/1
Report No. : 25AE0006-HO
Power : AC120V / 60Hz (DC4.0V)
Temp°C/Humi% : 25deg. C / 62%
Operator : Naoki Sakamoto

Mode / Remarks : Transmitting Mode 2402MHz Z Axis(MAX)

LIMIT : FCC15C §15.247(c) 3m, below1GHz:QP, above1GHz:PK
Except for the data below : adequate margin data below the limits.



No.	FREQ [MHz]	READING QP [dB μV]	ANT FACTOR [dB/m]	LOSS	GAIN	RESULT	LIMIT	MARGIN	ANTENNA	TABLE
				[dB]	[dB]	[dB μV/m]	[dB μV/m]	[dB]	[cm]	[DEG]
----- Horizontal -----										
1	38.932	21.5	14.3	6.6	27.8	14.6	40.0	25.4	100	0
2	45.961	21.5	11.4	6.6	27.8	11.7	40.0	28.3	100	360
3	56.987	22.1	8.8	6.8	27.7	10.0	40.0	30.0	100	0
4	60.754	21.3	8.0	6.8	27.8	8.3	40.0	31.7	100	360
5	78.200	21.5	6.4	7.1	27.6	7.4	40.0	32.6	100	0
6	131.685	21.7	13.6	7.4	27.4	15.3	43.5	28.2	100	360
----- Vertical -----										
7	40.001	22.2	13.7	6.6	27.8	14.7	40.0	25.3	100	360
8	45.896	25.9	11.4	6.6	27.8	16.1	40.0	23.9	100	0
9	57.438	26.1	8.7	6.8	27.7	13.9	40.0	26.1	100	360
10	60.001	28.8	8.1	6.8	27.8	15.9	40.0	24.1	100	0
11	80.002	26.7	6.3	7.1	27.6	12.5	40.0	27.5	100	360
12	132.247	27.0	13.7	7.4	27.4	20.7	43.5	22.8	100	360

CHART: WITH FACTOR ANT TYPE : -30MHz LOOP, 30-300MHz BICONICAL, 300MHz-1000MHz LOGPERIODIC, 1000MHz- HORN
CALCULATION : READING + ANT FACTOR + LOSS (CABLE+ATTEN.) - AMP. GAIN Page:


DATA OF RADIATED EMISSION TEST

UL Apex Co., Ltd. Head Office EMC Lab. No.2 Semi Anechoic Chamber
Date : 2004/09/01 20:33:57

Applicant : SHARP Corporation
Kind of EUT : GSM-WCDMA Cellular phone
Model No. : 802SH
Sample No. : 350263/00/004031/1
Report No. : 25AE0006-HO
Power : AC120V / 60Hz (DC4.0V)
Temp°C/Humi% : 25deg.C / 62%
Operator : Naoki Sakamoto

Mode / Remarks : Transmitting Mode 2441MHz Z Axis(MAX)

LIMIT : FCC15C §15.247(c) 3m, below1GHz:QP, above1GHz:PK
Except for the data below : adequate margin data below the limits.



No.	FREQ [MHz]	READING QP [dB μV]	ANT FACTOR [dB/m]	LOSS [dB]	GAIN [dB]	RESULT [dB μV/m]	LIMIT [dB μV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	46.767	21.4	11.1	6.6	27.8	11.3	40.0	28.7	100	360
2	60.002	23.6	8.1	6.8	27.8	10.7	40.0	29.3	100	360
3	78.286	21.4	6.4	7.1	27.6	7.3	40.0	32.7	100	0
4	132.486	23.7	13.7	7.4	27.4	17.4	43.5	26.1	205	360
5	140.003	24.0	14.1	7.5	27.4	18.2	43.5	25.3	175	0
6	546.411	21.4	18.9	9.6	28.2	21.7	46.0	24.3	100	360
----- Vertical -----										
7	45.884	26.0	11.4	6.6	27.8	16.2	40.0	23.8	100	0
8	60.002	29.0	8.1	6.8	27.8	16.1	40.0	23.9	100	360
9	80.001	26.9	6.3	7.1	27.6	12.7	40.0	27.3	100	0
10	132.250	26.0	13.7	7.4	27.4	19.7	43.5	23.8	100	360
11	140.002	24.0	14.1	7.5	27.4	18.2	43.5	25.3	100	0
12	543.652	21.3	18.9	9.5	28.2	21.5	46.0	24.5	100	360

CHART: WITH FACTOR ANT TYPE : -30MHz LOOP, 30-300MHz BICONICAL, 300MHz-1000MHz LOGPERIODIC, 1000MHz- HORN
CALCULATION : READING + ANT FACTOR + LOSS (CABLE+ATTEN.) - AMP. GAIN Page:


DATA OF RADIATED EMISSION TEST

UL Apex Co., Ltd. Head Office EMC Lab. No.2 Semi Anechoic Chamber
Date : 2004/09/01 22:13:03

Applicant : SHARP Corporation
Kind of EUT : GSM-WCDMA Cellular phone
Model No. : 802SH
Sample No. : 350263/00/004031/1
Report No. : 25AE0006-HO
Power : AC120V / 60Hz (DC4.0V)
Temp°C/Humi% : 25deg.C / 62%
Operator : Naoki Sakamoto

Mode / Remarks : Transmitting Mode 2480MHz Z Axis(MAX)

LIMIT : FCC15C §15.247(c) 3m, below1GHz:QP, above1GHz:PK
Except for the data below : adequate margin data below the limits.



No.	FREQ [MHz]	READING QP [dB μV]	ANT FACTOR [dB/m]	LOSS [dB]	GAIN [dB]	RESULT [dB μV/m]	LIMIT [dB μV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	45.374	21.4	11.5	6.6	27.8	11.7	40.0	28.3	100	360
2	57.795	22.3	8.6	6.8	27.8	9.9	40.0	30.1	100	0
3	60.002	23.3	8.1	6.8	27.8	10.4	40.0	29.6	100	360
4	79.649	21.5	6.3	7.1	27.6	7.3	40.0	32.7	100	0
5	132.344	24.2	13.7	7.4	27.4	17.9	43.5	25.6	189	360
6	441.383	21.3	18.3	9.2	27.9	20.9	46.0	25.1	100	0
----- Vertical -----										
7	45.878	25.7	11.4	6.6	27.8	15.9	40.0	24.1	100	0
8	57.123	25.9	8.7	6.8	27.7	13.7	40.0	26.3	100	360
9	60.002	29.0	8.1	6.8	27.8	16.1	40.0	23.9	100	360
10	80.003	26.7	6.3	7.1	27.6	12.5	40.0	27.5	100	0
11	132.348	26.2	13.7	7.4	27.4	19.9	43.5	23.6	100	120
12	439.334	21.3	18.3	9.2	27.9	20.9	46.0	25.1	100	0

CHART: WITH FACTOR ANT TYPE : -30MHz LOOP, 30-300MHz BICONICAL, 300MHz-1000MHz LOGPERIODIC, 1000MHz- HORN
CALCULATION : READING + ANT FACTOR + LOSS (CABLE+ATTEN.) - AMP. GAIN Page:

Radiated Spurious Emission (1-25GHz) / Band Edge compliance

UL Apex Co., Ltd.
Head Office EMC Lab. No.2 Semi Anechoic Chamber

COMPANY : Sharp Corporation
EQUIPMENT : GSM-WCDMA Cellular phone
MODEL : 802SH
S/N : 350263/00/004039/4
POWER : AC120V/60Hz (DC4.0V)
MODE : Tx (2402MHz)
AXIS : Hor: Y-axis , Ver: Z-axis

REGULATION : FCC Part 15 Subpart C 15.247(c)
TEST DISTANCE : 3 and 1m
DATE : September 3 and 11, 2004
TEMPERATURE : 25deg.C and 24deg.C
HUMIDITY : 62% and 60%
ENGINEER : Naoki Sakamoto and Hiroka Umeyama

PK DETECT (RBW: 1MHz, VBW:1MHz)

No.	Freq. [MHz]	Reading [dBuV]		Ant. Factor [dB/m]	Amp. Gain [dB]	Cable Loss [dB]	Atten. or Filter [dB]	Result [dBuV/m]		Limit PK [dBuV/m]	Margin	
		HOR	VER					HOR	VER		HOR	VER
Test distance 3meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter)												
1	2390.0	52.7	53.3	30.8	36.3	6.3	10.0	63.5	64.1	74.0	10.5	9.9
2	4804.0	45.4	46.3	35.3	36.1	9.3	1.0	54.9	55.8	74.0	19.1	18.2
3	7206.0	43.4	43.8	37.9	35.6	11.8	0.5	58.0	58.4	74.0	16.0	15.6
4	9608.0	44.3	44.1	37.6	36.3	13.9	0.5	60.0	59.8	74.0	14.0	14.2
Test distance 1meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter) - Dfac												
5	12010.0	41.7	42.4	41.0	35.7	15.5	0.0	53.0	53.7	74.0	21.0	20.3
6	14412.0	41.2	40.5	41.1	34.6	16.6	0.0	54.8	54.1	74.0	19.2	19.9
7	16814.0	43.0	44.0	45.9	35.6	18.6	0.0	62.4	63.4	74.0	11.6	10.6
8	19216.0	41.9	41.6	39.7	34.9	20.3	0.0	57.5	57.2	74.0	16.5	16.8
9	21618.0	43.8	43.2	40.8	35.4	22.1	0.0	61.8	61.2	74.0	12.2	12.8
10	24020.0	43.8	43.8	39.9	35.8	22.6	0.0	61.0	61.0	74.0	13.0	13.0

AV DETECT (RBW: 1MHz, VBW:10Hz)

No.	Freq. [MHz]	Reading [dBuV]		Ant. Factor [dB/m]	Amp. Gain [dB]	Cable Loss [dB]	Atten. or Filter [dB]	Result [dBuV/m]		Limit AV [dBuV/m]	Margin	
		HOR	VER					HOR	VER		HOR	VER
Test distance 3meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter)												
1	2390.0	33.7	34.0	30.8	36.3	6.3	10.0	44.5	44.8	54.0	9.5	9.2
2	4804.0	34.3	36.5	35.3	36.1	9.3	1.0	43.8	46.0	54.0	10.2	8.0
3	7206.0	30.3	30.4	37.9	35.6	11.8	0.5	44.9	45.0	54.0	9.1	9.0
4	9608.0	30.8	30.8	37.6	36.3	13.9	0.5	46.5	46.5	54.0	7.5	7.5
Test distance 1meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter) - Dfac												
5	12010.0	29.2	29.3	41.0	35.7	15.5	0.0	40.5	40.6	54.0	13.5	13.4
6	14412.0	28.2	28.1	41.1	34.6	16.6	0.0	41.8	41.7	54.0	12.2	12.3
7	16814.0	30.6	30.7	45.9	35.6	18.6	0.0	50.0	50.1	54.0	4.0	3.9
8	19216.0	29.6	29.4	39.7	34.9	20.3	0.0	45.2	45.0	54.0	8.8	9.0
9	21618.0	31.0	31.0	40.8	35.4	22.1	0.0	49.0	49.0	54.0	5.0	5.0
10	24020.0	31.2	31.2	39.9	35.8	22.6	0.0	48.4	48.4	54.0	5.6	5.6

20dBc(Fundamental 2402MHz) (RBW: 100kHz, VBW:300kHz)

No.	FREQ [MHz]	S/A READING [dBuV/m]		ANT Factor [dB/m]	AMP GAIN [dB]	CABLE LOSS [dB]	ATTEN. [dB]	RESULT [dBuV/m]		Limit 20dBc [dBuV/m]	MARGIN	
		HOR	VER					HOR	VER		HOR	VER
Test distance 3meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator												
1	2400.0	90.2	90.9	30.8	36.3	6.4	10.0	101.1	101.8	-	-	-
2	2400.0	49.2	50.6	30.8	36.3	6.4	10.0	60.1	61.5	Funda-20dB	21.0	20.3

Test Distance 1.0m : Distance Factor(Dfac) = 20log(3/1.0) =

9.5 dB

* Except for the above table : All other spurious emissions were less than 20dB for the limit.

* Atten. : 1 to 3.5GHz, Filter : 3.5 to 26GHz

* In the above table, factor 0.0dB represents no use of Atten. and/or Filter.

* The result is rounded off to the second decimal place. Therefore, there may be 0.1 difference for the result.

In the frequency over the fifth harmonic, the noise from the EUT was not seen. Its base noise implies the system noise floor.

Radiated Spurious Emission (1-25GHz) / Band Edge compliance

UL Apex Co., Ltd.
Head Office EMC Lab. No.2 Semi Anechoic Chamber

COMPANY : Sharp Corporation
EQUIPMENT : GSM-WCDMA Cellular phone
MODEL : 802SH
S/N : 350263/00/004039/4
POWER : AC120V/60Hz (DC4.0V)
MODE : Tx (2441MHz)
AXIS : Hor: Y-axis, Ver: Z-axis

REGULATION : FCC Part 15 Subpart C 15.247(c)
TEST DISTANCE : 3 and 1m
DATE : September 3 and 11, 2004
TEMPERATURE : 25deg C and 24deg.C
HUMIDITY : 62% and 60%
ENGINEER : Naoki Sakamoto and Hiroka Umeyama

PK DETECT (RBW: 1MHz, VBW:1MHz)

No.	Freq. [MHz]	Reading		Ant. Factor [dB/m]	Amp. Gain [dB]	Cable Loss [dB]	Atten. or Filter [dB]	Result		Limit PK [dBuV/m]	Margin	
		HOR	VER					HOR	VER		HOR	VER
Test distance 3meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter)												
1	4882.0	46.3	45.2	35.7	36.1	9.5	1.0	56.4	55.3	74.0	17.6	18.7
2	7323.0	43.5	43.7	38.2	35.7	12.0	0.5	58.5	58.7	74.0	15.5	15.3
3	9764.0	44.3	44.2	37.3	36.3	14.0	0.5	59.8	59.7	74.0	14.2	14.3
Test distance 1meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter) - Dfac												
4	12205.0	42.0	41.6	41.5	35.6	15.6	0.0	54.0	53.6	74.0	20.0	20.4
5	14646.0	40.0	40.5	41.6	34.8	16.8	0.0	54.1	54.6	74.0	19.9	19.4
6	17087.0	42.5	42.5	46.5	35.4	18.8	0.0	62.9	62.9	74.0	11.1	11.1
7	19528.0	42.3	43.5	39.3	35.0	20.6	0.0	57.7	58.9	74.0	16.3	15.1
8	21969.0	42.8	43.3	40.4	35.0	22.3	0.0	61.0	61.5	74.0	13.0	12.5
9	24410.0	44.5	44.5	40.1	36.6	22.7	0.0	61.2	61.2	74.0	12.8	12.8

AV DETECT (RBW: 1MHz, VBW:10Hz)

No.	Freq. [MHz]	Reading		Ant. Factor [dB/m]	Amp. Gain [dB]	Cable Loss [dB]	Atten. or Filter [dB]	Result		Limit AV [dBuV/m]	Margin	
		HOR	VER					HOR	VER		HOR	VER
Test distance 3meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter)												
1	4882.0	35.6	34.8	35.7	36.1	9.5	1.0	45.7	44.9	54.0	8.3	9.1
2	7323.0	30.5	30.5	38.2	35.7	12.0	0.5	45.5	45.5	54.0	8.5	8.5
3	9764.0	30.7	30.3	37.3	36.3	14.0	0.5	46.2	45.8	54.0	7.8	8.2
Test distance 1meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter) - Dfac												
4	12205.0	29.4	29.3	41.5	35.6	15.6	0.0	41.4	41.3	54.0	12.6	12.7
5	14646.0	28.0	28.1	41.6	34.8	16.8	0.0	42.1	42.2	54.0	11.9	11.8
6	17087.0	30.7	30.5	46.5	35.4	18.8	0.0	51.1	50.9	54.0	2.9	3.1
7	19528.0	29.8	29.9	39.3	35.0	20.6	0.0	45.2	45.3	54.0	8.8	8.7
8	21969.0	30.5	30.5	40.4	35.0	22.3	0.0	48.7	48.7	54.0	5.3	5.3
9	24410.0	31.4	31.5	40.1	36.6	22.7	0.0	48.1	48.2	54.0	5.9	5.8

Test Distance 1.0m : Distance Factor(Dfac) = 20log(3/1.0) = 9.5 dB

- * Except for the above table : All other spurious emissions were less than 20dB for the limit.
- * Atten. : 1 to 3.5GHz, Filter : 3.5 to 26GHz
- * In the above table, factor 0.0dB represents no use of Atten. and/or Filter.
- * The result is rounded off to the second decimal place. Therefore, there may be 0.1 difference for the result.
- * In the frequency over the fifth harmonic, the noise from the EUT was not seen. Its base noise implies the system noise floor.

Radiated Spurious Emission (1-25GHz) / Band Edge compliance

UL Apex Co., Ltd.
Head Office EMC Lab. No.2 Semi Anechoic Chamber

COMPANY : Sharp Corporation
EQUIPMENT : GSM-WCDMA Cellular phone
MODEL : 802SH
S/ N : 350263/00/004039/4
POWER : AC120V/60Hz (DC4.0V)
MODE : Tx (2480MHz)
AXIS : Hor: Y-axis , Ver: Z-axis

REGULATION : FCC Part 15 Subpart C 15.247(c)
TEST DISTANCE : 3 and 1m
DATE : September 3 and 11, 2004
TEMPERATURE : 25deg.C and 24deg.C
HUMIDITY : 62% and 60%
ENGINEER : Naoki Sakamoto and Hiroka Umeyama

PK DETECT (RBW: 1MHz , VBW:1MHz)

No.	Freq. [MHz]	Reading		Ant. Factor [dB/m]	Amp. Gain [dB]	Cable Loss [dB]	Atten. or Filter [dB]	Result		Limit PK [dBuV/m]	Margin	
		HOR	VER					HOR	VER		HOR	VER
Test distance 3meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter)												
1	2483.5	61.9	62.6	31.0	36.2	6.4	10.0	73.1	73.8	74.0	0.9	0.2
2	4960.0	45.5	45.3	36.1	36.1	9.5	1.0	56.0	55.8	74.0	18.0	18.2
3	7440.0	44.6	43.8	38.5	35.7	12.0	0.5	59.9	59.1	74.0	14.1	14.9
4	9920.0	44.1	44.0	37.0	36.3	14.1	0.5	59.4	59.3	74.0	14.6	14.7
Test distance 1meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter) - Dfac												
5	12400.0	41.6	42.1	41.9	35.5	15.7	0.0	54.2	54.7	74.0	19.8	19.3
6	14880.0	41.3	41.8	42.6	35.0	17.1	0.0	56.5	57.0	74.0	17.5	17.0
7	17360.0	42.6	42.3	46.9	35.2	19.0	0.0	63.8	63.5	74.0	10.2	10.5
8	19840.0	42.2	42.5	39.9	35.3	20.9	0.0	58.2	58.5	74.0	15.8	15.5
9	22320.0	42.9	42.6	40.7	35.1	22.4	0.0	61.4	61.1	74.0	12.6	12.9
10	24800.0	43.7	43.8	40.2	36.7	22.9	0.0	60.6	60.7	74.0	13.4	13.3

AV DETECT (RBW: 1MHz , VBW:10Hz)


No.	Freq. [MHz]	Reading		Ant. Factor [dB/m]	Amp. Gain [dB]	Cable Loss [dB]	Atten. or Filter [dB]	Result		Limit AV [dBuV/m]	Margin	
		HOR	VER					HOR	VER		HOR	VER
Test distance 3meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter)												
1	2483.5	31.5	31.5	31.0	36.2	6.4	10.0	42.7	42.7	54.0	11.3	11.3
2	4960.0	35.5	34.9	36.1	36.1	9.5	1.0	46.0	45.4	54.0	8.0	8.6
3	7440.0	30.6	30.6	38.5	35.7	12.0	0.5	45.9	45.9	54.0	8.1	8.1
4	9920.0	30.3	30.4	37.0	36.3	14.1	0.5	45.6	45.7	54.0	8.4	8.3
Test distance 1meters RESULT=Reading + ANT Factor - Amp Gain + CABLE LOSS + Attenuator (or Filter) - Dfac												
5	12400.0	29.8	29.5	41.9	35.5	15.7	0.0	42.4	42.1	54.0	11.6	11.9
6	14880.0	28.8	28.7	42.6	35.0	17.1	0.0	44.0	43.9	54.0	10.0	10.1
7	17360.0	30.4	30.1	46.9	35.2	19.0	0.0	51.6	51.3	54.0	2.4	2.7
8	19840.0	30.0	30.0	39.9	35.3	20.9	0.0	46.0	46.0	54.0	8.0	8.0
9	22320.0	30.5	30.5	40.7	35.1	22.4	0.0	49.0	49.0	54.0	5.0	5.0
10	24800.0	31.0	31.0	40.2	36.7	22.9	0.0	47.9	47.9	54.0	6.1	6.1

Test Distance 1.0m : Distance Factor(Dfac) = 20log(3/1.0) = 9.5 dB


- * Except for the above table : All other spurious emissions were less than 20dB for the limit.
 - * Atten. : 1 to 3.5GHz, Filter : 3.5 to 26GHz
 - * In the above table, factor 0.0dB represents no use of Atten. and/or Filter.
 - * The result is rounded off to the second decimal place. Therefore, there may be 0.1 difference for the result.
- In the frequency over the fifth harmonic, the noise from the EUT was not seen. Its base noise implies the system noise floor.

Conducted Spurious Emission(30MHz-25GHz)


Ch:Low



Conducted Spurious Emission(30MHz-25GHz)
Ch:Mid



Conducted Spurious Emission(30MHz-25GHz)
Ch:High



Conducted Spurious Emission / Band Edge compliance

