



EMI TEST REPORT

Test Report No. : 10529478H-B

Applicant : Sharp Corporation, Communication Systems Division
Type of Equipment : Smart Phone
Model No. : 402SH
FCC ID : APYHRO00213
Test standard : FCC Part 15 Subpart B 2014 Class B
Test Result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.
5. This test report must not be used by the customer product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Date of test: October 14, 2014

**Representative
test engineer:**

Ken Fujita

Ken Fujita
Engineer

Consumer Technology Division

Approved by :

T. Hataheda

Takahiro Hataheda

Leader

Consumer Technology Division



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.
*As for the range of Accreditation in NVLAP, you may refer to the WEB address,
<http://www.ul.com/japan/jpn/pages/services/emc/about/mark1/index.jsp#nvlap>

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

13-EM-F0429

CONTENTS	PAGE
SECTION 1: Customer information	4
SECTION 2: Equipment under test (E.U.T.)	4
SECTION 3: Test specification, procedures & results	5
SECTION 4: Operation of E.U.T. during testing	8
SECTION 5: Conducted Emission	10
SECTION 6: Radiated Emission	11
APPENDIX 1: Data of EMI test	12
Conducted Emission	12
Radiated Emission	14
APPENDIX 2: Test instruments	18
APPENDIX 3: Photographs of test setup.....	19
Conducted Emission	19
Radiated Emission	20
Worst Case Position (Horizontal: X-axis/ Vertical:X-axis)	22

SECTION 1: Customer information

Company Name : Sharp Corporation, Communication Systems Division
Address : 2-13-1 Iida Hachihonmatsu HigashiHiroshima-City, Hiroshima, 739-0192
Japan
Telephone Number : +81-82-420-1552
Facsimile Number : +81-82-420-1572
Contact Person : Hiroyuki Uwatoko

SECTION 2: Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Smart Phone
Model No. : 402SH
Serial No. : Refer to Section 4, Clause 4.2
Receipt Date of Sample : October 10, 2014
Country of Mass-production : China
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No Modification by the test lab

2.2 Product description

Feature of EUT : 402SH is AXGP, Tri-band FDD-LTE(Band 1 / 3 / SBM Specific), Dual-band WCDMA(FDD I / VIII) & Tri-band GSM(900 / 1800 / 1900) Multi-mode Smart Phone.
The EUT has the function that NFC, Bluetooth, ANT+ and Wireless-LAN technology interface for establishing contact and transmitting data with certain device.
Clock frequencies in the system : CPU: 2.2656GHz (max)
Source oscillation: 19.2MHz, 27.12MHz (NFC), 48.0MHz (WLAN/BT/ANT+), 27.0MHz (TV)

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 3: Test specification, procedures & results

3.1 Test specification

Test Specification : FCC Part 15 Subpart B: 2014, final revised on August 15, 2014 and effective October 14, 2014

Title : FCC 47CFR Part15 Radio Frequency Device
Subpart B Unintentional Radiators

3.2 Procedures and results

Item	Test Procedure	Limits	Deviation	Worst margin	Result
Conducted emission	ANSI C63.4: 2009 7. AC powerline conducted emission measurements	Class B	N/A	[QP] 12.7dB 0.17023MHz, L 0.16569MHz, L [AV] 9.5dB 0.17023MHz, L	Complied
Radiated emission	ANSI C63.4: 2009 8. Radiated emission measurements	Class B	N/A	8.8dB 60.301MHz, Horizontal, QP	Complied

*Note: UL Japan, Inc's EMI Work Procedure 13-EM-W0420.

3.3 Addition to standard

No addition, exclusion nor deviation has been made from the standard.

3.4 Uncertainty

EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room (semi-anechoic chamber)	Conducted emission (+dB)
	150kHz-30MHz
No.1	3.5dB
No.2	3.5dB
No.3	3.6dB
No.4	3.5dB

Test room (semi-anechoic chamber)	Radiated emission						
	(3m*)(+dB)				(1m*)(+dB)		(0.5m*)(+dB)
	9kHz -30MHz	30MHz -300MHz	300MHz -1GHz	1GHz -10GHz	10GHz -18GHz	18GHz -26.5GHz	26.5GHz -40GHz
No.1	4.0dB	5.1dB	5.0dB	5.1dB	6.0dB	4.9dB	4.3dB
No.2	3.9dB	5.2dB	5.0dB	4.9dB	5.9dB	4.7dB	4.2dB
No.3	4.3dB	5.1dB	5.2dB	5.2dB	6.0dB	4.8dB	4.2dB
No.4	4.6dB	5.2dB	5.0dB	5.2dB	6.0dB	5.7dB	4.2dB

*3m/1m/0.5m = Measurement distance

Conducted emission test

The data listed in this test report has enough margin, more than the site margin.

Radiated emission test(3m)

The data listed in this test report has enough margin, more than the site margin.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.5 Test Location

UL Japan, Inc. Ise EMC Lab. *NVLAP Lab. code: 200572-0
4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN
Telephone : +81 596 24 8999 Facsimile : +81 596 24 8124

	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	4.0 x 4.5 x 2.7m	4.0 x 4.5 m	-
No.6 measurement room	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	8.8 x 4.6 x 2.8m	2.4 x 2.4m	-
No.11 measurement room	-	6.2 x 4.7 x 3.0m	4.8 x 4.6m	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Test set up, Data of EMI, and Test instruments


Refer to APPENDIX.

SECTION 4: Operation of E.U.T. during testing

4.1 Operating modes

The mode(s) : 1) USB Data Com Mode
The USB data is communicated between EUT and Personal computer (Pair of EUT).
2) Standby Mode
Standby state for USB communication.

4.2 Configuration and peripherals



*Cabling and setup were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Smart Phone	402SH	004401/11/523942/4	Sharp Corporation	EUT
B	microSD Memory Card	SD-C16G	None	TOSHIBA	-
C	Personal Computer	PP11L	CN-0D4571-48643-55V-1651	Dell	-
D	Mouse	M-BE55	LZE21450232	Logitech	-
E	AC Adapter (PC)	PA-1650-05D2	CN-0F7970-71615-561-14A1	Dell	-
F	Printer	895Cxi	SG8BL1W16V	Hewlett Packard	-
G	AC Adapter (Printer)	C4557-60004	C8K28B	Hewlett Packard	-

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	USB Data Cable	0.80	Shielded	Shielded	-
2	Mouse Cable	0.72	Unshielded	Unshielded	-
3	AC Adaptor Cable (PC)	1.76	Unshielded	Unshielded	-
4	AC Power Cable (PC)	0.85	Unshielded	Unshielded	-
5	Parallel Cable	1.65	Shielded	Shielded	-
6	AC Adapter Cable (printer)	2.00	Unshielded	Unshielded	-
7	AC Power Cable (printer)	1.75	Unshielded	Unshielded	-

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 5: Conducted Emission

5.1 Operating environment

Test place : No. 1 semi anechoic chamber
Temperature : See data
Humidity : See data

5.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane.

The rear of tabletop was located 40cm to the vertical conducting plane. The rear of EUT and its peripherals was aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from the LISN/AMN. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane. Each EUT current-carrying power lead, except the ground (safety) lead, was individually connected through a LISN/AMN to the input power source. All unused 50 ohm connectors of the LISN/AMN were resistivity terminated in 50 ohm when not connected to the measuring equipment. Photographs of the set up are shown in Appendix 3.

5.3 Test procedure

The AC Mains Terminal Continuous disturbance Voltage has been measured with the EUT within a semi anechoic chamber. The EUT was connected to a Line Impedance Stabilization Network (LISN)/ Artificial Mains network (AMN). An overview sweep with peak detection has been performed. The measurements have been performed with a quasi-peak detector and if required, with an average detector.

The conducted emission measurements were made with the following detector function of the test receiver.

Detector Type : Quasi-Peak and CISPR AV
IF Bandwidth : 9 kHz

5.4 Test result

Summary of the test results: Pass

Date: October 14, 2014

Test engineer: Ken Fujita

SECTION 6: Radiated Emission

6.1 Operating environment

Test place : No. 1 semi anechoic chamber
Temperature : See data
Humidity : See data

6.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 0.8m above the conducting ground plane.

The EUT was set on the edge of the tabletop.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

Photographs of the set up are shown in Appendix 3.

6.3 Test conditions

Frequency range : 30MHz-300MHz (Biconical antenna) / 300MHz-1000MHz (Logperiodic antenna)
1000MHz-12000MHz (Horn antenna)
Test distance : 3m
EUT position : Table top
EUT operation mode : See Clause 4.1

6.4 Test procedure

The height of the measuring antenna varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver.

The radiated emission measurements were made with the following detector function of the Test Receiver.

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver	Test Receiver
IF Bandwidth	QP: BW 120kHz	PK: BW 1MHz, CISPR AV: BW 1MHz

- The noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at representative X-axis since no difference was found among each position.

6.5 Test result

Summary of the test results: Pass

Date: October 14, 2014

Test engineer: Ken Fujita

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Emission

DATA OF CONDUCTED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2014/10/14

Report No. : 10529478H

Temp./Humi. : 21deg. C / 52% RH
Engineer : Ken Fujita

Mode / Remarks : Standby Mode

LIMIT : FCC15.107(a) QP ClassB
FCC15.107(a) AV ClassB



Frequency [MHz]	Reading Level		Corr. Factor	Results		Limit		Margin		Phase	Comment
	QP [dBuV]	AV [dBuV]		QP [dBuV]	AV [dBuV]	QP [dBuV]	AV [dBuV]	QP [dB]	AV [dB]		
0.15349	35.2	9.8	13.2	48.4	23.0	65.8	55.8	17.4	32.8	N	
0.16744	38.7	30.9	13.2	51.9	44.1	65.1	55.1	13.2	11.0	N	
0.21974	31.7	23.2	13.3	45.0	36.5	62.8	52.8	17.8	16.3	N	
1.99787	19.7	15.6	13.6	33.3	29.2	56.0	46.0	22.7	16.8	N	
3.37927	26.1	13.6	13.9	40.0	27.5	56.0	46.0	16.0	18.5	N	
3.72462	27.9	17.1	14.0	41.9	31.1	56.0	46.0	14.1	14.9	N	
0.15349	35.7	10.5	13.2	48.9	23.7	65.8	55.8	16.9	32.1	L	
0.16569	39.3	30.7	13.2	52.5	43.9	65.2	55.2	12.7	11.3	L	
0.21974	32.3	23.3	13.3	45.6	36.6	62.8	52.8	17.2	16.2	L	
1.99787	19.5	14.8	13.6	33.1	28.4	56.0	46.0	22.9	17.6	L	
3.37927	23.0	11.2	13.9	36.9	25.1	56.0	46.0	19.1	20.9	L	
3.72462	25.1	14.1	14.0	39.1	28.1	56.0	46.0	16.9	17.9	L	

CHART : WITH FACTOR. Peak hold data. CALCULATION : RESULT = READING + C.F (LISN + ATTEN + CABLE)
Except for the above table : adequate margin data below the limits.

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission
(Below 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2014/10/14

Report No. : 10529478H

Temp./Humi. : 22deg. C / 54% RH
Engineer : Ken Fujita

Mode / Remarks : USB Data Com Mode (Worst axis Ver: X-axis, Hori: X-axis)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
Except for the data below : adequate margin data below the limits.



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
31.623	34.9	QP	17.2	-31.4	20.7	289	400	Hori.	40.0	19.3	
31.623	44.4	QP	17.2	-31.4	30.2	227	100	Vert.	40.0	9.8	
78.156	53.6	QP	6.5	-30.7	29.4	297	400	Hori.	40.0	10.6	
78.156	47.8	QP	6.5	-30.7	23.6	151	100	Vert.	40.0	16.4	
159.860	42.4	QP	15.3	-29.8	27.9	2	400	Hori.	43.5	15.6	
159.860	39.6	QP	15.3	-29.8	25.1	23	100	Vert.	43.5	18.4	
447.294	43.6	QP	17.6	-26.7	34.5	217	100	Hori.	46.0	11.5	
447.294	41.2	QP	17.6	-26.7	32.1	141	167	Vert.	46.0	13.9	
479.559	42.2	QP	17.9	-26.5	33.6	167	150	Hori.	46.0	12.4	
479.559	40.3	QP	17.9	-26.5	31.7	161	156	Vert.	46.0	14.3	
500.601	42.0	QP	18.1	-26.3	33.8	12	207	Hori.	46.0	12.2	
500.601	39.5	QP	18.1	-26.3	31.3	299	110	Vert.	46.0	14.7	

CHART:WITH FACTOR ANT TYPE: ~30MHz:LOOP 30~300MHz:BICONICAL 300MHz~1000MHz:LOGPERIODIC, 1000MHz~:HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE+ATTEN. - GAIN (AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission
(Below 1GHz)

DATA OF RADIATED EMISSION TEST


UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2014/10/14

Report No. : 10529478H

Temp./Humi. : 22deg. C / 54% RH
Engineer : Ken Fujita

Mode / Remarks : Standby Mode (Worst axis Ver: X-axis, Hori: X-axis)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
Except for the data below : adequate margin data below the limits.



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
31.623	35.9	QP	17.2	-31.4	21.7	157	400	Hori.	40.0	18.3	
31.623	44.8	QP	17.2	-31.4	30.6	232	100	Vert.	40.0	9.4	
60.301	54.4	QP	7.8	-31.0	31.2	280	400	Hori.	40.0	8.8	
60.301	45.6	QP	7.8	-31.0	22.4	181	100	Vert.	40.0	17.6	
78.156	53.9	QP	6.5	-30.7	29.7	234	400	Hori.	40.0	10.3	
78.156	47.2	QP	6.5	-30.7	23.0	216	100	Vert.	40.0	17.0	
159.860	43.5	QP	15.3	-29.8	29.0	2	400	Hori.	43.5	14.5	
159.860	42.4	QP	15.3	-29.8	27.9	256	100	Vert.	43.5	15.6	
447.294	41.4	QP	17.6	-26.7	32.3	48	100	Hori.	46.0	13.7	
447.294	40.2	QP	17.6	-26.7	31.1	139	102	Vert.	46.0	14.9	
607.216	40.9	QP	19.5	-25.6	34.8	124	118	Hori.	46.0	11.2	
607.216	36.4	QP	19.5	-25.6	30.3	132	217	Vert.	46.0	15.7	

CHART:WITH FACTOR ANT TYPE: ~30MHz:LOOP, 30~300MHz:BICONICAL, 300MHz~1000MHz:LOGPERIODIC, 1000MHz~:HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE+ATTEN. - GAIN(AMP))

*The limit is rounded down to one decimal place.

*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Above 1GHz)


DATA OF RADIATED EMISSION TEST

UL Japan, Inc. Ise EMC Lab. No.1 Semi Anechoic Chamber
Date : 2014/10/14

Report No. : 10529478H
Temp./Humi. : 22deg. C / 54% RH
Engineer : Ken Fujita

Mode / Remarks : USB Data Com Mode (Worst axis Ver: X-axis, Hori: X-axis)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
1599.183	57.8	PK	25.2	-34.7	48.3	284	148	Hori.	73.9	25.6	
1599.183	60.1	PK	25.2	-34.7	50.6	231	111	Vert.	73.9	23.3	
1599.183	36.1	AV	25.2	-34.7	26.6	231	111	Vert.	53.9	27.3	
1599.183	35.2	AV	25.2	-34.7	25.7	284	148	Hori.	53.9	28.2	

CHART:WITH FACTOR ANT TYPE: ~30MHz:LOOP, 30~300MHz:BICONICAL, 300MHz~1000MHz:LOGPERIODIC, 1000MHz~:HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE+ATTEN. - GAIN (AMP))

*The limit is rounded down to one decimal place.
*The test result is rounded off to one or two decimal places, so some differences might be observed.

Radiated Emission (Above 1GHz)


DATA OF RADIATED EMISSION TEST

UL Japan, Inc. Ise EMC Lab. No. 1 Semi Anechoic Chamber
Date : 2014/10/14

Report No. : 10529478H
Temp./Humi. : 22deg. C / 54% RH
Engineer : Ken Fujita

Mode / Remarks : Standby Mode (Worst axis Ver: X-axis, Hori: X-axis)

LIMIT : FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:PK
FCC15.109(a) 3m, below 1GHz:QP, above 1GHz:AV



Frequency	Reading	DET	Antenna Factor	Loss& Gain	Level	Angle	Height	Polar.	Limit	Margin	Comment
[MHz]	[dBuV]		[dB/m]	[dB]	[dBuV/m]	[Deg]	[cm]		[dBuV/m]	[dB]	
1601.199	59.3	PK	25.2	-34.7	49.8	281	210	Hori.	73.9	24.1	
1601.199	62.0	PK	25.2	-34.7	52.5	238	141	Vert.	73.9	21.4	
1601.199	36.0	AV	25.2	-34.7	26.5	238	141	Vert.	53.9	27.4	
1601.199	35.1	AV	25.2	-34.7	25.6	281	210	Hori.	53.9	28.3	

CHART:WITH FACTOR ANT TYPE: ~30MHz:LOOP, 30~300MHz:BICONICAL, 300MHz~1000MHz:LOGPERIODIC, 1000MHz~:HORN
CALCULATION: RESULT = READING + ANT FACTOR + LOSS & GAIN(CABLE+ATTEN. - GAIN (AMP))

*The limit is rounded down to one decimal place.
*The test result is rounded off to one or two decimal places, so some differences might be observed.

APPENDIX 2: Test instruments

EMI Test Instruments

Control No.	Instrument	Manufacturer	Model No	Serial No	Test Item	Calibration Date * Interval(month)
MAEC-01	Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 10m	DA-06881	RE/CE	2014/09/01 * 12
MOS-27	Thermo-Hygrometer	CUSTOM	CTH-201	A08Q26	RE/CE	2014/02/20 * 12
MJM-21	Measure	KOMELON	KMC-36	-	RE/CE	-
COTS-MEMI	EMI measurement program	TSJ	TEPTO-DV	-	RE/CE	-
MTR-09	EMI Test Receiver	Rohde & Schwarz	ESU26	100412	RE/CE	2014/06/06 * 12
KBA-05	Biconical Antenna	Schwarzbeck	BBA9106	2513	RE	2013/11/24 * 12
KLA-04	Logperiodic Antenna	Schwarzbeck	USLP9143	361	RE	2013/11/24 * 12
MAT-08	Attenuator(6dB)	Weinschel Corp	2	BK7971	RE	2013/11/26 * 12
MCC-02	Coaxial Cable	Suhner/storm/Agilent/TSJ	-	-	RE	2014/09/12 * 12
MPA-19	Pre Amplifier	MITEQ	MLA-10K01-B01-35	1237616	RE	2014/02/17 * 12
MHA-05	Horn Antenna 1-18GHz	Schwarzbeck	BBHA9120D	253	RE	2014/05/16 * 12
MPA-01	Pre Amplifier	Agilent	8449B	3008A01671	RE	2014/02/05 * 12
MCC-165	Microwave Cable	Junkosha	MWX221	1203S213(1m) / 1311S166(5m)	RE	2013/11/27 * 12
MLS-24	LISN(AMN)	Schwarzbeck	NSLK8127	8127-730	CE(EUT)	2014/07/10 * 12
MLS-26	LISN(AMN)	Schwarzbeck	NSLK8127	8127-732	CE(AE)	2014/07/09 * 12
MTA-12	Terminator	TME	Termination	-	CE	2014/09/09 * 12
MCC-03	Coaxial Cable	Fujikura/Suhner/TSJ	5D-2W(20m)/ 3D-2W(7.5m)/ RG400u(1.5m)/ RFM-E421(Switcher)	-/01068 (Switcher)	CE	2014/09/12 * 12
MAT-64	Attenuator(13dB)	JFW Industries, Inc.	50FP-013H2 N	-	CE	2014/01/29 * 12

The expiration date of the calibration is the end of the expired month.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

Test Item:

CE: Conducted Emissions

RE: Radiated Emissions

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124