



**ANNEX A – TEST PLOTS**

System check	750MHz
<p>Communication System: UID 0, CW (0) Frequency: 750 MHz; Duty cycle:1:1                      Medium parameters used: f = 750 MHz; <math>\sigma = 0.92</math> S/m; <math>\epsilon_r = 43.24</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(9.75, 9.75, 9.75); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>System Performance Check at Frequencies 750MHz/d=15mm, Pin=250mW, dist=3.0mm (ES-Probe)/Area Scan (8x15x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 2.14 W/kg</p> <p><b>System Performance Check at Frequencies 750MHz/d=15mm, Pin=250mW, dist=3.0mm (ES-Probe)/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 41.21 V/m; Power Drift = 0.11 dB                      Peak SAR (extrapolated) = 3.24 W/kg  <b>SAR(1 g) = 2.02 W/kg; SAR(10 g) = 1.41 W/kg</b>                      Maximum value of SAR (measured) = 2.44 W/kg</p> <div data-bbox="440 1337 1158 1794" data-label="Figure"> </div>	


SRTC performed system check by using 250mw at antenna port

System check	835MHz
<p>Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty cycle:1:1                      Medium parameters used (interpolated): f = 835 MHz; <math>\sigma = 0.93</math> S/m; <math>\epsilon_r = 41.34</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(9.39, 9.39, 9.39) ; Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>Configuration 835/835/Area Scan (8x15x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 2.77 W/kg</p> <p><b>Configuration 835/835/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 51.61 V/m; Power Drift = 0.05 dB                      Peak SAR (extrapolated) = 3.52 W/kg  <b>SAR(1 g) = 2.25 W/kg; SAR(10 g) = 1.62 W/kg</b>                      Maximum value of SAR (measured) = 2.77 W/kg</p> 	

SRTC performed system check by using 250mw at antenna port

System check	900MHz
<p>Communication System: UID 0, CW (0); Frequency: 900 MHz; Duty Cycle: 1:1                      Medium parameters used: <math>f = 900 \text{ MHz}</math>; <math>\sigma = 0.99 \text{ S/m}</math>; <math>\epsilon_r = 41.8</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(9.39, 9.39, 9.39) ; Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>D900/Dipole 900MHz/Area Scan (5x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 3.44 W/kg</p> <p><b>D900/Dipole 900MHz/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 62.08 V/m; Power Drift = 0.02 dB                      Peak SAR (extrapolated) = 3.99 W/kg  <b>SAR(1 g) = 2.84 W/kg; SAR(10 g) = 1.77 W/kg</b>                      Maximum value of SAR (measured) = 3.44 W/kg</p> 	


SRTC performed system check by using 250mw at antenna port

System check	1800MHz
<p>Communication System: UID 0, CW (0); Frequency: 1800 MHz; Duty cycle:1:1                      Medium parameters used: <math>f = 1800</math> MHz; <math>\sigma = 1.42</math> S/m; <math>\epsilon_r = 41.9</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(8.27, 8.27, 8.27) ; Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>Configuration 1800/1800/Area Scan (7x10x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 8.41 W/kg</p> <p><b>Configuration 1800/1800/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 76.44 V/m; Power Drift = 0.15 dB                      Peak SAR (extrapolated) = 17.8 W/kg  <b>SAR(1 g) = 9.98 W/kg; SAR(10 g) = 5.20 W/kg</b>                      Maximum value of SAR (measured) = 12.2 W/kg</p> 	


SRTC performed system check by using 250mw at antenna port

System check	2000MHz
<p>Communication System: UID 0, CW (0); Frequency: 2000 MHz; Duty cycle:1:1                      Medium parameters used: f = 2000 MHz; <math>\sigma = 1.35</math> S/m; <math>\epsilon_r = 38.72</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.94, 7.94, 7.94); Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>Configuration 2000/2000/Area Scan (7x10x1):</b> Measurement grid: dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 8.42 W/kg</p> <p><b>Configuration 2000/2000/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 76.47 V/m; Power Drift = 0.13 dB                      Peak SAR (extrapolated) = 18.5 W/kg  <b>SAR(1 g) = 10.31 W/kg; SAR(10 g) = 5.21 W/kg</b>                      Maximum value of SAR (measured) = 12.7 W/kg</p> <div data-bbox="344 1249 1257 1704" data-label="Figure"> </div>	


SRTC performed system check by using 250mw at antenna port

System check	2450MHz
<p>Communication System: UID 0, CW (0); Frequency: 2450 MHz; Duty cycle:1:1                      Medium parameters used: f = 2450 MHz; <math>\sigma = 1.84</math> S/m; <math>\epsilon_r = 38.09</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.48, 7.48, 7.48); Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>System Performance Check at Frequencies 2450 MHz/2450/Area Scan (8x11x1):</b> Measurement grid: dx=12mm, dy=12mm                      Maximum value of SAR (measured) = 21.3 W/kg</p> <p><b>System Performance Check at Frequencies 2450 MHz/2450/Zoom Scan (7x7x7) (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 108.6 V/m; Power Drift = 0.09 dB                      Peak SAR (extrapolated) = 28.5 W/kg  <b>SAR(1 g) = 13.91 W/kg; SAR(10 g) = 5.89 W/kg</b>                      Maximum value of SAR (measured) = 22.9 W/kg</p> 	

SRTC performed system check by using 250mw at antenna port

System check	2600MHz
<p>Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1                      Medium parameters used: <math>f = 2600</math> MHz; <math>\sigma = 1.89</math> S/m; <math>\epsilon_r = 40.21</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.37, 7.37, 7.37); Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>SYSTEM CHECK 2600/Area Scan (5x11x1):</b> Measurement grid: dx=12mm, dy=12mm                      Maximum value of SAR (measured) = 23.4 W/kg</p> <p><b>SYSTEM CHECK 2600/Zoom Scan (7x7x7)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=5mm                      Reference Value = 102.6 V/m; Power Drift = 0.15 dB                      Peak SAR (extrapolated) = 34.2 W/kg  <b>SAR(1 g) = 14.66 W/kg; SAR(10 g) = 6.53 W/kg</b>                      Maximum value of SAR (measured) = 26.8 W/kg</p> 	

SRTC performed system check by using 250mw at antenna port

System check	5200MHz
<p>Communication System: UID 0, CW (0); Frequency: 5200 MHz; Duty Cycle: 1:1                      Medium parameters used: <math>f = 5200 \text{ MHz}</math>; <math>\sigma = 4.7 \text{ S/m}</math>; <math>\epsilon_r = 35.25</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(5.57, 5.57, 5.57) ; Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>Configuration 4/SYSTEM CHECK 5200MHz/Area Scan (6x7x1):</b> Measurement grid: dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 1.87 W/kg</p> <p><b>Configuration 4/SYSTEM CHECK 5200MHz/Zoom Scan (7x7x12)/Cube 0:</b> Measurement grid: dx=4mm, dy=4mm, dz=2mm                      Reference Value = 11.23 V/m; Power Drift = 0.12 dB                      Peak SAR (extrapolated) = 3.47 W/kg  <b>SAR(1 g) = 0.775 W/kg; SAR(10 g) = 0.215 W/kg</b>                      Maximum value of SAR (measured) = 2.14 W/kg</p> 	

SRTC performed system check by using 10mw at antenna port




System check	5300MHz
<p>Communication System: UID 0, CW (0); Frequency: 5300 MHz; Duty Cycle: 1:1                      Medium parameters used: <math>f = 5300 \text{ MHz}</math>; <math>\sigma = 4.94 \text{ S/m}</math>; <math>\epsilon_r = 35.26</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(5.43, 5.43, 5.43) ; Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>Configuration 4/SYSTEM CHECK 5300MHz/Area Scan (6x7x1):</b> Measurement grid: dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 1.78 W/kg</p> <p><b>Configuration 4/SYSTEM CHECK 5300MHz/Zoom Scan (7x7x12)/Cube 0:</b> Measurement grid: dx=4mm, dy=4mm, dz=2mm                      Reference Value = 10.45 V/m; Power Drift = 0.13 dB                      Peak SAR (extrapolated) = 3.89 W/kg  <b>SAR(1 g) = 0.809 W/kg; SAR(10 g) = 0.21 W/kg</b>                      Maximum value of SAR (measured) = 2.17 W/kg</p> 	

SRTC performed system check by using 10mw at antenna port

System check	5600MHz
<p>Communication System: UID 0, CW (0); Frequency: 5600 MHz; Duty Cycle: 1:1                      Medium parameters used: <math>f = 5600 \text{ MHz}</math>; <math>\sigma = 4.93 \text{ S/m}</math>; <math>\epsilon_r = 35.72</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(4.95, 4.95, 4.95) ; Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>Configuration 4/SYSTEM CHECK 5600MHz /Area Scan (6x7x1):</b> Measurement grid: dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 1.75 W/kg</p> <p><b>Configuration 4/SYSTEM CHECK 5600MHz /Zoom Scan (7x7x12)/Cube 0:</b> Measurement grid: dx=4mm, dy=4mm, dz=2mm                      Reference Value = 12.22 V/m; Power Drift = 0.13 dB                      Peak SAR (extrapolated) = 3.89 W/kg  <b>SAR(1 g) = 0.797 W/kg; SAR(10 g) = 0.222 W/kg</b>                      Maximum value of SAR (measured) = 2.39 W/kg</p> 	

SRTC performed system check by using 10mw at antenna port


System check	5800MHz
<p>Communication System: UID 0, CW (0); Frequency: 5800 MHz; Duty Cycle: 1:1                      Medium parameters used: <math>f = 5800 \text{ MHz}</math>; <math>\sigma = 5.09 \text{ S/m}</math>; <math>\epsilon_r = 36.35</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(5.12, 5.12, 5.12); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>D5GV2 /D5800 SYSTEM CHECK 2/Area Scan (7x9x1):</b> Measurement grid:                      dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 1.82 W/kg</p> <p><b>D5GV2 /D5800 SYSTEM CHECK 2/Zoom Scan (7x7x12)/Cube 0:</b> Measurement grid:                      dx=4mm, dy=4mm, dz=2mm                      Reference Value = 14.28 V/m; Power Drift = 0.06 dB                      Peak SAR (extrapolated) = 3.47 W/kg  <b>SAR(1 g) = 0.759 W/kg; SAR(10 g) = 0.191 W/kg</b>                      Maximum value of SAR (measured) = 1.82 W/kg</p> 	

SRTC performed system check by using 10mw at antenna port


**GSM 850**

Hotspot	Back
<p>Communication System: UID 0, Generic GSM (0); Frequency: 836.6 MHz; Duty Cycle: 1:4                      Medium parameters used (interpolated): <math>f = 836.6</math> MHz; <math>\sigma = 0.905</math> S/m; <math>\epsilon_r = 41.528</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(9.39, 9.39, 9.39); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BACK/GSM 850/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.151 W/kg</p> <p><b>BACK/GSM 850/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 7.856 V/m; Power Drift = -0.11 dB                      Peak SAR (extrapolated) = 0.223 W/kg  <b>SAR(1 g) = 0.119 W/kg; SAR(10 g) = 0.066 W/kg</b>                      Maximum value of SAR (measured) = 0.172 W/kg</p>	
	


**GSM 1900**

Hotspot	Back
<p>Communication System: UID 0, Generic GSM (0); Frequency: 1880 MHz; Duty Cycle: 1:2                      Medium parameters used (interpolated): <math>f = 1880</math> MHz; <math>\sigma = 1.4</math> S/m; <math>\epsilon_r = 40</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(8.27, 8.27, 8.27); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BACK/GSM 1900/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.165 W/kg</p> <p><b>BACK/GSM 1900/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 5.702 V/m; Power Drift = 0.05 dB                      Peak SAR (extrapolated) = 0.214 W/kg  <b>SAR(1 g) = 0.120 W/kg; SAR(10 g) = 0.067 W/kg</b>                      Maximum value of SAR (measured) = 0.176 W/kg</p>	
	


**WCDMA Band II**

Hotspot	Bottom
<p>Communication System: UID 0, wcdma BANDII (0); Frequency: 1880 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 1880</math> MHz; <math>\sigma = 1.4</math> S/m; <math>\epsilon_r = 40</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(8.27, 8.27, 8.27); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BOTTOM/WCDMA B2/Area Scan (5x7x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.396 W/kg</p> <p><b>BOTTOM/WCDMA B2/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 16.91 V/m; Power Drift = 0.09 dB                      Peak SAR (extrapolated) = 0.517 W/kg  <b>SAR(1 g) = 0.288 W/kg; SAR(10 g) = 0.162 W/kg</b>                      Maximum value of SAR (measured) = 0.432 W/kg</p>	
	

**WCDMA Band IV**


Hotspot	Bottom
<p>Communication System: UID 0, wcdma bandIV (0); Frequency: 1732.4 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 1732.4</math> MHz; <math>\sigma = 1.375</math> S/m; <math>\epsilon_r = 40.07</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(8.27, 8.27, 8.27); Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BOTTOM/WCDMA B4/Area Scan (5x7x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.530 W/kg</p> <p><b>BOTTOM/WCDMA B4/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 19.47 V/m; Power Drift = 0.00 dB                      Peak SAR (extrapolated) = 0.704 W/kg  <b>SAR(1 g) = 0.393 W/kg; SAR(10 g) = 0.220 W/kg</b>                      Maximum value of SAR (measured) = 0.592 W/kg</p>	
	

**WCDMA Band V**


Hotspot	Back
<p>Communication System: UID 0, WCDMA 5 (0); Frequency: 836.6 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 836.6</math> MHz; <math>\sigma = 0.905</math> S/m; <math>\epsilon_r = 41.528</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(9.39, 9.39, 9.39) ; Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BACK/WCDMA B5/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.575 W/kg</p> <p><b>BACK/WCDMA B5/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 13.57 V/m; Power Drift = -0.15 dB                      Peak SAR (extrapolated) = 0.718 W/kg  <b>SAR(1 g) = 0.376 W/kg; SAR(10 g) = 0.215 W/kg</b>                      aximum value of SAR (measured) = 0.552 W/kg</p> 	



**LTE Band 2**

Hotspot	Back
<p>Communication System: UID 0, LTE BAND02 (0); Frequency: 1880 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 1880</math> MHz; <math>\sigma = 1.4</math> S/m; <math>\epsilon_r = 40</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(8.27, 8.27, 8.27); Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BACK/LTE B2/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.288 W/kg</p> <p><b>BACK/LTE B2/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 8.848 V/m; Power Drift = 0.13 dB                      Peak SAR (extrapolated) = 0.376 W/kg  <b>SAR(1 g) = 0.214 W/kg; SAR(10 g) = 0.122 W/kg</b>                      Maximum value of SAR (measured) = 0.306 W/kg</p>	
	


**LTE Band 4**

Hotspot	Bottom
<p>Communication System: UID 0, LTE BAND4 (0); Frequency: 1732.5 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 1732.5</math> MHz; <math>\sigma = 1.375</math> S/m; <math>\epsilon_r = 40.07</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(8.27, 8.27, 8.27); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BOTTOM/LTE B4/Area Scan (5x7x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.479 W/kg</p> <p><b>BOTTOM/LTE B4/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 18.39 V/m; Power Drift = 0.07 dB                      Peak SAR (extrapolated) = 0.597 W/kg  <b>SAR(1 g) = 0.328 W/kg; SAR(10 g) = 0.182 W/kg</b>                      Maximum value of SAR (measured) = 0.499 W/kg</p> 	


**LTE Band 5**

Hotspot	Back
<p>Communication System: UID 0, LTE BAND05 (0); Frequency: 836.5 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 836.5</math> MHz; <math>\sigma = 0.905</math> S/m; <math>\epsilon_r = 41.528</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(9.39, 9.39, 9.39); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BACK/LTE B5/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.193 W/kg</p> <p><b>BACK/LTE B5/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 9.412 V/m; Power Drift = 0.03 dB                      Peak SAR (extrapolated) = 0.250 W/kg  <b>SAR(1 g) = 0.140 W/kg; SAR(10 g) = 0.083 W/kg</b>                      Maximum value of SAR (measured) = 0.199 W/kg</p>	
	


**LTE Band 7**

Hotspot	Bottom
<p>Communication System: UID 0, LTE BAND07 (0); Frequency: 2535 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 2535</math> MHz; <math>\sigma = 1.888</math> S/m; <math>\epsilon_r = 39.084</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.37, 7.37, 7.37); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BOTTOM/LTE B7/Area Scan (5x7x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.817 W/kg</p> <p><b>BOTTOM/LTE B7/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 21.36 V/m; Power Drift = 0.05 dB                      Peak SAR (extrapolated) = 1.11 W/kg  <b>SAR(1 g) = 0.547 W/kg; SAR(10 g) = 0.262 W/kg</b>                      Maximum value of SAR (measured) = 0.905 W/kg</p>	
	


**LTE Band 12**

Hotspot	Right
<p>Communication System: UID 0, LTE BAND12 (0); Frequency: 707.5 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 707.5</math> MHz; <math>\sigma = 0.887</math> S/m; <math>\epsilon_r = 42.115</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(9.75, 9.75, 9.75); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>RIGHT/LTE B12/Area Scan (4x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.205 W/kg</p> <p><b>RIGHT/LTE B12/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 15.50 V/m; Power Drift = -0.19 dB                      Peak SAR (extrapolated) = 0.233 W/kg  <b>SAR(1 g) = 0.155 W/kg; SAR(10 g) = 0.105 W/kg</b>                      Maximum value of SAR (measured) = 0.204 W/kg</p> 	


**LTE Band 17**

Hotspot	Back
<p>Communication System: UID 0, LTE BAND17 (0); Frequency: 710 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 710 \text{ MHz}</math>; <math>\sigma = 0.887 \text{ S/m}</math>; <math>\epsilon_r = 42.102</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(9.75, 9.75, 9.75); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BACK/LTE B17/Area Scan (9x13x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.113 W/kg</p> <p><b>BACK/LTE B17/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 11.35 V/m; Power Drift = -0.05 dB                      Peak SAR (extrapolated) = 0.134 W/kg  <b>SAR(1 g) = 0.094 W/kg; SAR(10 g) = 0.071 W/kg</b>                      Maximum value of SAR (measured) = 0.120 W/kg</p>	
	

**LTE Band 38**


Hotspot	Bottom
<p>Communication System: UID 0, LTE BAND38 (0); Frequency: 2595 MHz; Duty Cycle: 1:1.579                      Medium parameters used (interpolated): <math>f = 2595</math> MHz; <math>\sigma = 1.954</math> S/m; <math>\epsilon_r = 39.006</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.37, 7.37, 7.37); Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BOTTOM/LTE B38/Area Scan (5x7x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.450 W/kg</p> <p><b>BOTTOM/LTE B38/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 15.80 V/m; Power Drift = -0.06 dB                      Peak SAR (extrapolated) = 0.646 W/kg  <b>SAR(1 g) = 0.305 W/kg; SAR(10 g) = 0.140 W/kg</b>                      Maximum value of SAR (measured) = 0.517 W/kg</p> 	

**LTE Band 41**


Hotspot	Bottom
<p>Communication System: UID 0, LTE BAND41 (0); Frequency: 2593 MHz; Duty Cycle: 1: 1.579</p> <p>Medium parameters used (interpolated): <math>f = 2593</math> MHz; <math>\sigma = 1.952</math> S/m; <math>\epsilon_r = 39.009</math>; <math>\rho = 1000</math> kg/m<sup>3</sup></p> <p>Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>Probe: EX3DV4 - SN3708; ConvF(7.37, 7.37, 7.37); Calibrated: 10/30/2020</li> <li>Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>BOTTOM/LTE B41/Area Scan (5x7x1):</b> Measurement grid: dx=15mm, dy=15mm                      Maximum value of SAR (measured) = 0.570 W/kg</p> <p><b>BOTTOM/LTE B41/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 17.67 V/m; Power Drift = 0.05 dB                      Peak SAR (extrapolated) = 0.829 W/kg  <b>SAR(1 g) = 0.395 W/kg; SAR(10 g) = 0.182 W/kg</b>                      Maximum value of SAR (measured) = 0.667 W/kg</p>	
	




**WIFI 2.4GHz**

Head	Right Tilt
<p>Communication System: UID 0, WIFI 2.4GHz (0); Frequency: 2437 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 2437 \text{ MHz}</math>; <math>\sigma = 1.788 \text{ S/m}</math>; <math>\epsilon_r = 39.219</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.48, 7.48, 7.48); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>RT/WIFI 2.4 2/Area Scan (9x8x1):</b> Measurement grid: dx=12mm, dy=12mm                      Maximum value of SAR (measured) = 0.322 W/kg</p> <p><b>RT/WIFI 2.4 2/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 12.04 V/m; Power Drift = -0.12 dB                      Peak SAR (extrapolated) = 0.528 W/kg  <b>SAR(1 g) = 0.269 W/kg; SAR(10 g) = 0.129 W/kg</b>                      Maximum value of SAR (measured) = 0.433 W/kg</p> 	

**WIFI 5GHz UNII-1**

Hotspot	Front
<p>Communication System: UID 0, WIFI 5.3G (0); Frequency: 5220 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 5220 \text{ MHz}</math>; <math>\sigma = 4.68 \text{ S/m}</math>; <math>\epsilon_r = 35.98</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(5.57, 5.57, 5.57); Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>FRONT/WIFI 5.2/Area Scan (11x18x1):</b> Measurement grid: <math>dx=10\text{mm}</math>, <math>dy=10\text{mm}</math>                      Maximum value of SAR (measured) = 0.0766 W/kg</p> <p><b>FRONT/WIFI 5.2/Zoom Scan (6x6x12)/Cube 0:</b> Measurement grid: <math>dx=5\text{mm}</math>, <math>dy=5\text{mm}</math>, <math>dz=2\text{mm}</math>                      Reference Value = 5.71 V/m; Power Drift = 0.10 dB                      Peak SAR (extrapolated) = 0.189 W/kg  <b>SAR(1 g) = 0.023 W/kg; SAR(10 g) = 0.00707 W/kg</b>                      Maximum value of SAR (measured) = 0.0734 W/kg</p> 	


**WIFI 5GHz UNII-2A**

Hotspot	Front
<p>Communication System: UID 0, WIFI 5.3G (0); Frequency: 5280 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 5280</math> MHz; <math>\sigma = 4.74</math> S/m; <math>\epsilon_r = 35.92</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(5.43, 5.43, 5.43) ; Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>FRONT/WIFI 5.3/Area Scan (11x18x1):</b> Measurement grid: dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 0.0514 W/kg</p> <p><b>FRONT/WIFI 5.3/Zoom Scan (6x6x12)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=2mm                      Reference Value = 5.17 V/m; Power Drift = 0.06 dB                      Peak SAR (extrapolated) = 0.182 W/kg  <b>SAR(1 g) = 0.017 W/kg; SAR(10 g) = 0.00533 W/kg</b>                      Maximum value of SAR (measured) = 0.0533 W/kg</p> 	

**WIFI 5GHz UNII-2C**

Hotspot	Front
<p>Communication System: UID 0, WIFI 5.6G (0); Frequency: 5580 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 5580</math> MHz; <math>\sigma = 5.049</math> S/m; <math>\epsilon_r = 35.526</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(4.95, 4.95, 4.95) ; Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>FRONT/WIFI 5.5/Area Scan (11x18x1):</b> Measurement grid: dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 0.0525 W/kg</p> <p><b>FRONT/WIFI 5.5/Zoom Scan (6x6x12)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=2mm                      Reference Value = 6.11 V/m; Power Drift = 0.09 dB                      Peak SAR (extrapolated) = 0.240 W/kg  <b>SAR(1 g) = 0.019 W/kg; SAR(10 g) = 0.00476 W/kg</b>                      Maximum value of SAR (measured) = 0.0559 W/kg</p>	
	

**WIFI 5GHz UNII-3**

Hotspot	Front
<p>Communication System: UID 0, WIFI 5.8G (0); Frequency: 5785 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 5785</math> MHz; <math>\sigma = 5.255</math> S/m; <math>\epsilon_r = 35.315</math>; <math>\rho = 1000</math> kg/m<sup>3</sup>                      Phantom section: Flat Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(5.12, 5.12, 5.12) ; Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>FRONT/WIFI 5.8/Area Scan (11x18x1):</b> Measurement grid: dx=10mm, dy=10mm                      Maximum value of SAR (measured) = 0.0882 W/kg</p> <p><b>FRONT/WIFI 5.8/Zoom Scan (6x6x12)/Cube 0:</b> Measurement grid: dx=5mm, dy=5mm, dz=2mm                      Reference Value = 6.43 V/m; Power Drift = 0.02 dB                      Peak SAR (extrapolated) = 0.253 W/kg  <b>SAR(1 g) = 0.028 W/kg; SAR(10 g) = 0.00812 W/kg</b>                      Maximum value of SAR (measured) = 0.0957 W/kg</p>	
	

**Bluetooth**

Head	Right Tilt
<p>Communication System: UID 0, BT (0); Frequency: 2441 MHz; Duty Cycle: 1:1                      Medium parameters used (interpolated): <math>f = 2441 \text{ MHz}</math>; <math>\sigma = 1.792 \text{ S/m}</math>; <math>\epsilon_r = 39.213</math>; <math>\rho = 1000 \text{ kg/m}^3</math>                      Phantom section: Right Section</p> <p>DASY5 Configuration:</p> <ul style="list-style-type: none"> <li>• Probe: EX3DV4 - SN3708; ConvF(7.48, 7.48, 7.48) ; Calibrated: 10/30/2020</li> <li>• Sensor-Surface: 1.4mm (Mechanical Surface Detection)</li> <li>• Electronics: DAE4 Sn720; Calibrated: 9/30/2020</li> <li>• Phantom: Twin-SAM 1559; Type: QD 000 P40 CD; Serial: xxxx</li> <li>• Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7483)</li> </ul> <p><b>RT/BT/Area Scan (9x9x1):</b> Measurement grid: dx=12mm, dy=12mm                      Maximum value of SAR (measured) = 0.0978 W/kg</p> <p><b>RT/BT/Zoom Scan (5x5x7)/Cube 0:</b> Measurement grid: dx=8mm, dy=8mm, dz=5mm                      Reference Value = 5.624 V/m; Power Drift = 0.18 dB                      Peak SAR (extrapolated) = 0.127 W/kg  <b>SAR(1 g) = 0.061 W/kg; SAR(10 g) = 0.027 W/kg</b>                      Maximum value of SAR (measured) = 0.100 W/kg</p>	
	